



BARGE "EBL-2998"
EMPTY BARGE LINE
INNAGE TABLE

2 PORT OR STAR

SHEET NO. 2119-1
SHULL NO. 1 OF 2

Table with columns for INNAGE (0 FT. to 15 FT.) and BARGE SHOULD BE DN EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN. Includes a note: CAPACITIES GIVEN IN BARRELS OF U.S. GALLONS

INSPECTORATE
ISO 9002 ACCREDITED

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

REFERENCE GAUGE HEIGHT:

CAPACITIES GIVEN IN BARRELS OF U.S. GALLONS



**3 PORT OR STAR
EMPTY BARGE LINE
INNAGE TABLE**

3 PORT OR STAR

SHEET NO. 2119-1
SHALL NO. 1 OF 2

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	16 FT.	17 FT.	18 FT.	19 FT.	20 FT.	21 FT.	22 FT.	23 FT.	24 FT.	25 FT.	26 FT.	27 FT.	28 FT.	29 FT.	30 FT.	31 FT.	32 FT.	33 FT.	34 FT.	35 FT.	36 FT.	37 FT.	38 FT.	39 FT.	40 FT.	41 FT.	42 FT.	43 FT.	44 FT.	45 FT.	46 FT.	47 FT.	48 FT.	49 FT.	50 FT.	51 FT.	52 FT.	53 FT.	54 FT.	55 FT.	56 FT.	57 FT.	58 FT.	59 FT.	60 FT.	61 FT.	62 FT.	63 FT.	64 FT.	65 FT.	66 FT.	67 FT.	68 FT.	69 FT.	70 FT.	71 FT.	72 FT.	73 FT.	74 FT.	75 FT.	76 FT.	77 FT.	78 FT.	79 FT.	80 FT.	81 FT.	82 FT.	83 FT.	84 FT.	85 FT.	86 FT.	87 FT.	88 FT.	89 FT.	90 FT.	91 FT.	92 FT.	93 FT.	94 FT.	95 FT.	96 FT.	97 FT.	98 FT.	99 FT.	100 FT.
IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	16 FT.	17 FT.	18 FT.	19 FT.	20 FT.	21 FT.	22 FT.	23 FT.	24 FT.	25 FT.	26 FT.	27 FT.	28 FT.	29 FT.	30 FT.	31 FT.	32 FT.	33 FT.	34 FT.	35 FT.	36 FT.	37 FT.	38 FT.	39 FT.	40 FT.	41 FT.	42 FT.	43 FT.	44 FT.	45 FT.	46 FT.	47 FT.	48 FT.	49 FT.	50 FT.	51 FT.	52 FT.	53 FT.	54 FT.	55 FT.	56 FT.	57 FT.	58 FT.	59 FT.	60 FT.	61 FT.	62 FT.	63 FT.	64 FT.	65 FT.	66 FT.	67 FT.	68 FT.	69 FT.	70 FT.	71 FT.	72 FT.	73 FT.	74 FT.	75 FT.	76 FT.	77 FT.	78 FT.	79 FT.	80 FT.	81 FT.	82 FT.	83 FT.	84 FT.	85 FT.	86 FT.	87 FT.	88 FT.	89 FT.	90 FT.	91 FT.	92 FT.	93 FT.	94 FT.	95 FT.	96 FT.	97 FT.	98 FT.	99 FT.	100 FT.
IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	16 FT.	17 FT.	18 FT.	19 FT.	20 FT.	21 FT.	22 FT.	23 FT.	24 FT.	25 FT.	26 FT.	27 FT.	28 FT.	29 FT.	30 FT.	31 FT.	32 FT.	33 FT.	34 FT.	35 FT.	36 FT.	37 FT.	38 FT.	39 FT.	40 FT.	41 FT.	42 FT.	43 FT.	44 FT.	45 FT.	46 FT.	47 FT.	48 FT.	49 FT.	50 FT.	51 FT.	52 FT.	53 FT.	54 FT.	55 FT.	56 FT.	57 FT.	58 FT.	59 FT.	60 FT.	61 FT.	62 FT.	63 FT.	64 FT.	65 FT.	66 FT.	67 FT.	68 FT.	69 FT.	70 FT.	71 FT.	72 FT.	73 FT.	74 FT.	75 FT.	76 FT.	77 FT.	78 FT.	79 FT.	80 FT.	81 FT.	82 FT.	83 FT.	84 FT.	85 FT.	86 FT.	87 FT.	88 FT.	89 FT.	90 FT.	91 FT.	92 FT.	93 FT.	94 FT.	95 FT.	96 FT.	97 FT.	98 FT.	99 FT.	100 FT.
IN	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.	15 FT.	16 FT.	17 FT.	18 FT.	19 FT.	20 FT.	21 FT.	22 FT.	23 FT.	24 FT.	25 FT.	26 FT.	27 FT.	28 FT.	29 FT.	30 FT.	31 FT.	32 FT.	33 FT.	34 FT.	35 FT.	36 FT.	37 FT.	38 FT.	39 FT.	40 FT.	41 FT.	42 FT.	43 FT.	44 FT.	45 FT.	46 FT.	47 FT.	48 FT.	49 FT.	50 FT.	51 FT.	52 FT.	53 FT.	54 FT.	55 FT.	56 FT.	57 FT.	58 FT.	59 FT.	60 FT.	61 FT.	62 FT.	63 FT.	64 FT.	65 FT.	66 FT.	67 FT.	68 FT.	69 FT.	70 FT.	71 FT.	72 FT.	73 FT.	74 FT.	75 FT.	76 FT.	77 FT.	78 FT.	79 FT.	80 FT.	81 FT.	82 FT.	83 FT.	84 FT.	85 FT.	86 FT.	87 FT.	88 FT.	89 FT.	90 FT.	91 FT.	92 FT.	93 FT.	94 FT.	95 FT.	96 FT.	97 FT.	98 FT.	99 FT.	100 FT.

STRAPPED: 5/22/03

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

INSPECTORATE AMERICA CORPORATION

PORT REFERENCE GAUGE HEIGHT: 15-3 3/4" RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT: 15-3 1/4" RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

* CAPACITY BELOW STRIKE POINT

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS



ISO 9002 ACCREDITED

BARGE "EBL-2998"
EMPTY BARGE LINE
INNAGE TABLE

3 PORT OR STAR

ROLL NO. 2119-1
SHEET NO. 2 OF 2

Table with 20 columns (IN 9 FT. to IN 17 FT.) and 20 rows (0 to 19). Contains innage measurements for various depths.

STRAPPED: 52203

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

PORT REFERENCE GAUGE HEIGHT: 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT: 15'-3 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

Signature

INSPECTORATE AMERICA CORPORATION

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS



BARGE "EBL-2998"
EMPTY BARGE LINE
INNAAGE TABLE

1 PORT OR STAR

HULL NO. 2119-1

SHEET NO. 1 OF 2

Table with columns for IN 0 FT., IN 1 FT., IN 2 FT., IN 3 FT., IN 4 FT., IN 5 FT., IN 6 FT., IN 7 FT., IN 8 FT., IN 9 FT. and rows for various capacities from 21.29 to 187.71. Includes a note: 'BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN'.

* CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT: 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)
STAR REFERENCE GAUGE HEIGHT: 15'-4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

Inspector's signature

INSPECTORATE AMERICA CORPORATION

STRAPPED: 52203



BARGE "EBL-2998"
EMPTY BARGE LINE
INNAGE TABLE

3 PORT OR STAR

HULL NO. 2119-1
SHEET NO. 1 OF 2

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for IN 0 FT. to IN 10 FT. and 8 FT. to 1 FT. Each cell contains a numerical value representing the measurement at that specific height.

CAPACITIES GIVEN IN BARRELS OF 41 U.S. GALLONS

• CAPACITY BELOW STRIKE POINT

PORT REFERENCE GAUGE HEIGHT : 15'-3 3/4" IRM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT : 15'-3 1/4" IRM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION

2,894.31

2,894.31

2,894.31

2,894.31



BARGE "EBL-2998"
EMPTY BARGE LINE
INNAGE TABLE

3 PORT OR STAR

HULL NO. 2119-1
SHEET NO. 2 OF 2

Table with columns for measurements from 9 FT. to 17 FT. and rows for various gauge heights. Includes text: 'BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN', 'PORT REFERENCE GAUGE HEIGHT: 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)', 'STAR REFERENCE GAUGE HEIGHT: 15'-3 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)'. Includes a signature 'B. B. B.' and 'INSPECTORATE AMERICA CORPORATION'.

STRAPPED: 522103

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE

PORT REFERENCE GAUGE HEIGHT: 15'-3 3/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

STAR REFERENCE GAUGE HEIGHT: 15'-3 1/4" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

INSPECTORATE AMERICA CORPORATION