



United States of America  
Department of Homeland Security  
United States Coast Guard

Certification Date: 10 Jun 2014  
Expiration Date: 10 Jun 2019  
IMO Number:

# Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name <b>HTCO 3067</b>		Official Number <b>1218831</b>	Call Sign	Service <b>Tank Barge</b>
Hailing Port <b>HOUSTON TX</b>		Hull Material <b>Steel</b>	Horsepower	Propulsion
Place Built <b>MADISONVILLE, LA UNITED STATES</b>		Delivery Date <b>29May2009</b>	Date Keel Laid <b>14Apr2009</b>	Gross Tons <b>R-1819</b>
				Net Tons <b>R-1819</b>
				DWT <b>+</b>
				Length <b>R-287.5</b>
Owner <b>HIGMAN BARGE LINES INC 1980 POST OAK BLVD - SUITE 1101 HOUSTON, TX 77056 UNITED STATES</b>		Operator <b>HIGMAN BARGE LINES INC 1980 POST OAK BLVD STE 1101 HOUSTON, TX 77056 UNITED STATES</b>		

This vessel must be manned with the following licensed and unlicensed personnel. Included in which there must be 0 certified lifeboatmen, 0 certified tankarmen, 0 HSC type rating, and 0 GMDSS Operators.

Master	Master & 1st Class pilot	Radio Officer(s)	Chief Engineer	QMED/Rating
Chief Mate	Mate & 1st Class Pilot	Able Seamen/ROANW	1st Asst. Engr/2nd Engr.	Oilers
2nd Mate/OIC/NW	Lic. Mate/OIC/NW	Ordinary Seamen	2nd Asst. Engr/3rd Engr.	
3rd Mate/OIC/NW	1st Class Pilot	Deckhands	3rd Asst. Engr	
			Lic. Engr.	

In addition, this vessel may carry 0 passengers, 0 other persons in crew, 0 persons in addition to crew, and no others. Total persons allowed: 0

Route Permitted and Conditions of Operation:

---Lakes, Bays, and Sounds---

Also Lake Michigan, in fair weather on voyages between Chicago, Illinois and Burns Harbor, Indiana not more than three (3) miles offshore.

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR Table 31.10 -21(a)(2); if this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at Texas City, TX, the Officer in Charge, Marine Inspection, Houston-Galveston certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Quarterly Reinspections				This certificate issued by:  RICARDO M. ALONSO, CDR, USCG, BY DIRECTION
Date	Zone	API/Q	Signature	
27 May 14	Cat 23	- A		Officer in Charge, Marine Inspection Houston-Galveston Inspection Zone
26 May 16	MSU PA	- A		
17 Aug 17	MSU PA	- P		

2014MAY14 20



United States of America  
Department of Homeland Security  
United States Coast Guard

Certification Date: 10 Jun 2014  
Expiration Date: 10 Jun 2019  
IMO Number:

# Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name <b>HTCO 3067</b>	Official Number <b>1218831</b>	Call Sign	Service <b>Tank Barge</b>			
Hailing Port <b>HOUSTON TX</b>	Hull Material <b>Steel</b>	Horsepower	Propulsion			
Place Built <b>MADISONVILLE, LA UNITED STATES</b>	Delivery Date <b>29May2009</b>	Date Keel Laid <b>14Apr2009</b>	Gross Tons <b>R-1616</b>	Net Tons <b>R-1618</b>	DWT	Length <b>R-207.5</b>
Owner <b>HIGMAN BARGE LINES INC 1980 POST OAK BLVD - SUITE 1101 HOUSTON, TX 77056 UNITED STATES</b>	Operator <b>HIGMAN BARGE LINES INC 1980 POST OAK BLVD STE 1101 HOUSTON, TX 77056 UNITED STATES</b>					

This vessel must be manned with the following licensed and unlicensed personnel. Included in which there must be 0 certified lifeboatmen, 0 certified tankermen, 0 HSC type rating, and 0 GMDSS Operators.

Master	Master & 1st Class pilot	Radio Officer(s)	Chief Engineer	QMED/Rating
Chief Mate	Mate & 1st Class Pilot	Able Seamen/ROANW	1st Asst. Engr/2nd Engr.	Oilers
2nd Mate/OICNW	Lic. Mate/OICNW	Ordinary Seamen	2nd Asst. Engr/3rd Engr.	
3rd Mate/OICNW	1st Class Pilot	Deckhands	3rd Asst. Engr	
			Lic. Engr.	

In addition, this vessel may carry 0 passengers, 0 other persons in crew, 0 persons in addition to crew, and no others. Total persons allowed: 0

Route Permitted and Conditions of Operation:

---Lakes, Bays, and Sounds---

Also Lake Michigan, in fair weather on voyages between Chicago, Illinois and Burns Harbor, Indiana not more than three (3) miles offshore.

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR Table 31.10 -21(a) (2); if this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at Texas City, TX, the Officer in Charge, Marine Inspection, Houston-Galveston certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Quarterly Reinspections				This certificate issued by:  RICARDO M. ALONSO, CDR, USCG, BY DIRECTION
Date	Zone	A/P/I/Q	Signature	
29 June 2014	CG 23	A		
29 June 2014	MSVPA	A		
-	-	-	-	
-	-	-	-	
Officer in Charge, Marine Inspection <b>Houston-Galveston</b>				Inspection Zone



# Certificate of Inspection

Certification Date:  
10Jun2014

HTCO 3067

**---Hull Exams---**

Exam Type	Next Exam	Last Exam	Prior Exam
Drydock	10Jun2024	10Jun2014	29May2009
Internal Structure	10Jun2019	10Jun2014	29May2009

**---Liquid/Gas/Solid Cargo Authority/Conditions---**

Authorization/ Grade "A" and Lower and Specified Hazardous Cargoes.  
 46CFR Subchapter D Authority: Highest Grade/A Capacity/28200 Units/Barrels  
 46CFR Subchapter O Authority: Part 151/Yes Part 153/No Part 154/No

**\*Loading Constraints - Structural\***

Tanks	Max Cargo Weight/Tank(Short Tons)	Max Density(LBS/Gal)
1 P/S	863	13.6
2 P/S	879	13.6
3 P/S	683	13.6

**\*Loading Constraints - Stability\***

Hull Type	Max Load (STons)	Max Draft (Ft/In)	Max Density (Lbs/Gal)	Route
II Limited Great Lakes	3747	10'0	13.6	Lakes, Bays, and Sounds plus
III Limited Great Lakes	4614	11'9	13.6	Lakes, Bays, and Sounds plus
II	3742	10'0	13.6	Rivers
III	4614	11'9	13.6	Rivers
	3726	9'11	13.6	Great Lakes

**\*Conditions of Carriage\***

Only Grade A and lower cargoes and specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #C2-0900830, dated March 19, 2009, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the Person in Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "COMPAT GROUP NO" column listed in the vessel's Cargo Authority Attachment.

The thermal fluid heater located in the hazardous location does not meet the requirements of 46 CFR 111.105-31(I), and may not be used when carrying cargoes above Grade E. Additionally, in accordance with 46 CFR 111.105-29(c), no cargo may be heated to within 15 degrees (c) of its flash point.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed.

Per 46 CFR 151.10-15 (c) (2) the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.



# Certificate of Inspection

Certification Date:  
10Jun2014

HTCO 3067

**\*Vapor Control System\***

In accordance with 46 CFR Part 39, excluding part 39.40, this vessel's vapor collection system has been inspected to the plans approved by Marine Safety Center letter Serial #C2-0900830, dated March 19, 2009, and has been found acceptable for the collection of bulk liquid cargo vapors annotated with "Yes" in the VCS column of the vessel's Cargo Authority Attachment.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 CFR part 197, Subpart C are applied.

Cargo tank maximum design working pressure: 3.00 psig

**---Inspection Status---**

**\*Cargo Tanks\***

TankID	Internal Exam			External Exam		
	Previous	Last	Next	Previous	Last	Next
1 P/S	29May2009	10Jun2014	10Jun2024	-	-	-
2 P/S	29May2009	10Jun2014	10Jun2024	-	-	-
3 P/S	29May2009	10Jun2014	10Jun2024	-	-	-

TankID	Safety Valves	Hydro Test		
		Previous	Last	Next
1 P/S	-	-	-	-
2 P/S	-	-	-	-
3 P/S	-	-	-	-

**---Conditional Portable Fire Extinguisher Requirements---**

Required Only During Transfer of Cargo or Operation of Barge Machinery.

**---Fire Fighting Equipment---**

Number of Fireman Outfits/ 0

\*Fire Extinguishers - Hand portable and semi-portable\*

Qty	Class Type
3	B-II

\*\*\*END\*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **HTCO-3067**

Official #: 1218831

Shipyard: **Trinity Madisonville**

Hull #: 2175-2

### 46 CFR 151 Tank Group Characteristics

Tank Group Information		Cargo Identification			Tanks			Cargo Transfer		Environmental Control		Fire Protection Provided	Special Requirements					
Tnk Grp	Tanks in Group	Density	Press.	Temp.	Hull Typ	Cargo Seg Tank	Type	Vent	Gauge	Pipe Class	Cont		Tanks	Handling Space	General	Materials of Construction	Elec Haz	Temp Cont
A	#1-3 P/S	13.6	Atmos.	Elev	II	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50-81(b),	55-1(b), (c), (e), (f), (h), (i), 56-1(a), (b), (c), (d), (e), (f), (g),	NA	Yes

- Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.  
 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.  
 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

### List of Authorized Cargoes

Cargo Identification							Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period	
							App'd (Y or N)	Category			

#### Authorized Subchapter O Cargoes

Alkyl(C7-C9) nitrates	AKN	34 <sup>2</sup>	O	NA	III	A	No	N/A	.50-81, .50-85	G
Aminoethylethanolamine	AEE	8	O	E	III	A	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G
Carbon tetrachloride	CBT	36	O	NA	III	A	No	N/A	No	G
Caustic potash solution	CPS	5 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(d)	G
Caustic soda solution	CSS	5 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(d)	G
Chloroform	CRF	36	O	NA	III	A	Yes	3	No	G
Creosote	CCW	21 <sup>2</sup>	O	E	III	A	Yes	1	No	G
Cresols (all isomers)	CRS	21	O	E	III	A	Yes	1	No	G
Cresylic acid tar	CRX		O	E	III	A	Yes	1	.55-1(f)	G
iso-Decyl acrylate	IAI	14	O	E	III	A	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 <sup>1,2</sup>	O	A	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 <sup>2</sup>	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
Diethanolamine	DEA	8	O	E	III	A	Yes	1	.55-1(c)	G
Diethylenetriamine	DET	7 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(c)	G
Diisopropanolamine	DIP	8	O	E	III	A	Yes	1	.55-1(c)	G
Dodecyl dimethylamine, Tetradecyldimethylamine mixture	DOT	7	O	E	III	A	No	N/A	.56-1(b)	G
Dodecyl diphenyl ether disulfonate solution	DOS	43	O	#	II	A	No	N/A	No	G
Ethylene cyanohydrin	ETC	20	O	E	III	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	O	E	III	A	No	N/A	No	G
Ethylene glycol propyl ether	EGP	40	O	E	III	A	Yes	1	No	G
Glutaraldehyde solution (50% or less)	GTA	19	O	NA	III	A	No	N/A	No	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Perchloroethylene	PER	36	O	NA	III	A	No	N/A	No	G
Polyethylene polyamines	PEB	7 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		O		III	A	No	N/A	.50-73, .55-1(d)	G
Sodium aluminate solution (45% or less)	SAU	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDD	0 <sup>1,2</sup>	O	NA	III	A	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b)	G
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 <sup>1,2</sup>	O	NA	III	A	Yes	1	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 <sup>1,2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 <sup>1,2</sup>	O	NA	II	A	No	N/A	.50-73, .55-1(b)	G

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HTCO-3067

Official #: 1218831

Page 2 of 6

Shipyard: Trinity Madisonville

Hull #: 2175-2

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
1,1,2,2-Tetrachloroethane	TEC	36	O	NA	III	A	No	N/A	Nil	G
Toluenediamine	TDA	9	O	E	II	A	No	N/A	.50-73, .56-1(a), (b), (c), (d)	G
Triphenylborane (10% or less), caustic soda solution	TPB	5	O	NA	III	A	No	N/A	.56-1(a), (b), (c)	G
Trisodium phosphate solution	TSP	5	O	NA	III	A	No	N/A	.60-73, .56-1(a), (c)	G
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (d)	G

### Subchapter D Cargoes Authorized for Vapor Control

Acetone	ACT	18 <sup>2</sup>	D	C		A	Yes	1	
Acetophenone	ACP	18	D	E		A	Yes	1	
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1	
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1	
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1	
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		A	Yes	1	
Benzyl alcohol	BAL	21	D	E		A	Yes	1	
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		A	Yes	1	
Butyl acetate (all isomers)	BAX	34	D	D		A	Yes	1	
Butyl alcohol (iso-)	IAL	20 <sup>2</sup>	D	D		A	Yes	1	
Butyl alcohol (n-)	BAN		D	D		A	Yes	1	
Butyl alcohol (sec-)	BAS		D	C		A	Yes	1	
Butyl alcohol (tert-)	BAT		D	C		A	Yes	1	
Butyl benzyl phthalate	BPH	34	D	E		A	Yes	1	
Butyl toluene	BUE	32	D	D		A	Yes	1	
Caprolactam solutions	CLS	22	D	E		A	Yes	1	
Cyclohexane	CHX	31	D	C		A	Yes	1	
Cyclohexanol	CHN	20	D	E		A	Yes	1	
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2	
p-Cymene	CMP	32	D	D		A	Yes	1	
iso-Decaldehyde	IDA	19	D	E		A	Yes	1	
n-Decaldehyde	DAL	19	D	E		A	Yes	1	
Decane	DCE	30	D	D		A	Yes	1	
Decyl alcohol (all isomers)	DAX	20 <sup>2</sup>	D	E		A	Yes	1	
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		A	Yes	1	
Diacetone alcohol	DAA	20 <sup>2</sup>	D	D		A	Yes	1	
ortho-Dibutyl phthalate	DPA	34	D	E		A	Yes	1	
Diethylbenzene	DEB	32	D	D		A	Yes	1	
Diethylene glycol	DEG	40 <sup>2</sup>	D	E		A	Yes	1	
Diisobutylene	DBL	30	D	C		A	Yes	1	
Diisobutyl ketone	DIK	18	D	D		A	Yes	1	
Diisopropylbenzene (all isomers)	DIX	32	D	E		A	Yes	1	
Dimethyl phthalate	DTL	34	D	E		A	Yes	1	
Diocyl phthalate	DOP	34	D	E		A	Yes	1	
Dipentene	DPN	30	D	D		A	Yes	1	
Diphenyl	DIL	32	D	D/E		A	Yes	1	
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		A	Yes	1	
Diphenyl ether	DPE	41	D	{E}		A	Yes	1	
Dipropylene glycol	DPG	40	D	E		A	Yes	1	
Distillates: Flashed feed stocks	DFP	33	D	E		A	Yes	1	
Distillates: Straight run	DSR	33	D	E		A	Yes	1	
Dodecene (all isomers)	DOZ	30	D	D		A	Yes	1	

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HTCO-3067

Official #: 1218831

Page 3 of 6

Shipyard: Trinity Madisonville

Hull #: 2175-2

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		A	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		A	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	E		A	Yes	1		
Ethyl acetate	ETA	34	D	C		A	Yes	1		
Ethyl acetoacetate	EAA	34	D	E		A	Yes	1		
Ethyl alcohol	EAL	20 <sup>2</sup>	D	C		A	Yes	1		
Ethylbenzene	ETB	32	D	C		A	Yes	1		
Ethyl butanol	EBT	20	D	D		A	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	C		A	Yes	1		
Ethyl butyrate	EBR	34	D	D		A	Yes	1		
Ethyl cyclohexane	ECY	31	D	D		A	Yes	1		
Ethylene glycol	EGL	20 <sup>2</sup>	D	E		A	Yes	1		
Ethylene glycol butyl ether acetate	EMA	34	D	E		A	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		A	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	E		A	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1		
2-Ethylhexanol	EHX	20	D	E		A	Yes	1		
Ethyl propionate	EPR	34	D	C		A	Yes	1		
Ethyl toluene	ETE	32	D	D		A	Yes	1		
Formamide	FAM	10	D	E		A	Yes	1		
Furfuryl alcohol	FAL	20 <sup>2</sup>	D	E		A	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		A	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		A	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	C		A	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	C		A	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		A	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		A	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		A	Yes	1		
Glycerine	GCR	20 <sup>2</sup>	D	E		A	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	C		A	Yes	1		
Heptanoic acid	HEP	4	D	E		A	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		A	Yes	1		
Heptene (all isomers)	HPX	30	D	C		A	Yes	2		
Heptyl acetate	HPE	34	D	E		A	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 <sup>2</sup>	D	B/C		A	Yes	1		
Hexanoic acid	HXO	4	D	E		A	Yes	1		
Hexanol	HXN	20	D	D		A	Yes	1		
Hexene (all isomers)	HEX	30	D	C		A	Yes	2		
Hexylene glycol	HXG	20	D	E		A	Yes	1		
Isophorone	IPH	18 <sup>2</sup>	D	E		A	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		A	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1		
Kerosene	KRS	33	D	D		A	Yes	1		
Methyl acetate	MTT	34	D	D		A	Yes	1		
Methyl alcohol	MAL	20 <sup>2</sup>	D	C		A	Yes	1		
Methylamyl acetate	MAC	34	D	D		A	Yes	1		
Methylamyl alcohol	MAA	20	D	D		A	Yes	1		
Methyl amyl ketone	MAK	18	D	D		A	Yes	1		
Methyl tert-butyl ether	MBE	41 <sup>2</sup>	D	C		A	Yes	1		

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HTCO-3067  
Official #: 1218831

Page 4 of 6

Shipyard: Trinity Madisonville  
Hull #: 2175-2

Cargo Identification							Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period	
							App'd (Y or N)	VCS Category			
Methyl butyl ketone	MBK	18	D	C		A	Yes	1			
Methyl butyrate	MBU	34	D	C		A	Yes	1			
Methyl ethyl ketone	MEK	18 <sup>2</sup>	D	C		A	Yes	1			
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1			
Methyl isobutyl ketone	MIK	18 <sup>2</sup>	D	C		A	Yes	1			
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1			
Mineral spirits	MNS	33	D	D		A	Yes	1			
Myrcene	MRE	30	D	D		A	Yes	1			
Naphtha: Heavy	NAG	33	D	#		A	Yes	1			
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1			
Naphtha: Solvent	NSV	33	D	D		A	Yes	1			
Naphtha: Stoddard solvent	NSS	33	D	D		A	Yes	1			
Naphtha: Varnish makers and painters (75%)	NVM	33	D	C		A	Yes	1			
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A	Yes	1			
Nonene (all isomers)	NON	30	D	D		A	Yes	2			
Nonyl alcohol (all isomers)	NNS	20 <sup>2</sup>	D	E		A	Yes	1			
Nonyl phenol	NNP	21	D	E		A	Yes	1			
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		A	Yes	1			
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	C		A	Yes	1			
Octanoic acid (all isomers)	OAY	4	D	E		A	Yes	1			
Octanol (all isomers)	OCX	20 <sup>2</sup>	D	E		A	Yes	1			
Octene (all isomers)	OTX	30	D	C		A	Yes	2			
Oil, fuel: No. 2	OTW	33	D	D/E		A	Yes	1			
Oil, fuel: No. 2-D	OTD	33	D	D		A	Yes	1			
Oil, fuel: No. 4	OFR	33	D	D/E		A	Yes	1			
Oil, fuel: No. 5	OFV	33	D	D/E		A	Yes	1			
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1			
Oil, misc: Crude	OIL	33	D	C/D		A	Yes	1			
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1			
Oil, misc: Gas, high pour	OGP	33	D	E		A	Yes	1			
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1			
Oil, misc: Residual	ORL	33	D	E		A	Yes	1			
Oil, misc: Turbine	OTB	33	D	E		A	Yes	1			
Pentene (all isomers)	PTX	30	D	A		A	Yes	5			
alpha-Pinene	PIO	30	D	D		A	Yes	1			
beta-Pinene	PIP	30	D	D		A	Yes	1			
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		A	Yes	1			
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A	Yes	1			
Polybutene	PLB	30	D	E		A	Yes	1			
Polypropylene glycol	PGC	40	D	E		A	Yes	1			
iso-Propyl acetate	IAC	34	D	C		A	Yes	1			
n-Propyl acetate	PAT	34	D	C		A	Yes	1			
iso-Propyl alcohol	IPA	20 <sup>2</sup>	D	C		A	Yes	1			
n-Propyl alcohol	PAL	20 <sup>2</sup>	D	C		A	Yes	1			
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1			
iso-Propylcyclohexane	IPX	31	D	D		A	Yes	1			
Propylene glycol	PPG	20 <sup>2</sup>	D	E		A	Yes	1			
Propylene glycol methyl ether acetate	PGN	34	D	D		A	Yes	1			
Propylene tetramer	PTT	30	D	D		A	Yes	1			
Sulfolane	SFL	39	D	E		A	Yes	1			

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*





# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HTCO-3067  
Official #: 1218831

Page 6 of 6

Shipyard: Trinity Madison  
Hull #: 2175-2

### Explanation of terms & symbols used in the Table:

#### Cargo Identification

Name	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.
Chem Code none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatibility Group No.	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-9PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425.
Note 2	See Appendix I to 46 CFR Part 150 - exceptions to the compatibility chart.
Subchapter Subchapter D Subchapter O Note 3	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1. Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2. Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "[ ]" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
A, B, C D, E Note 4	Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15. The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
NA #	Those subchapter O cargoes which are not classified as a flammable or combustible liquid. No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type I II III NA	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
VCS Category:	The specified cargo's provisional classification for vapor control systems.
Category 1	(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.
Category 2	(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.
Category 3	(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Category 4	(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.
Category 5	(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.
Category 6	(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5.
Category 7	(High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.
none	The cargo has not been evaluated/classified for use in vapor control systems.



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HTCO-3067

Shipyard: Trinity Madison

Official #: 1218831

Page 6 of 6

Hull #: 2175-2

### Explanation of terms & symbols used in the Table:

#### Cargo Identification

Name	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.
Chem Code none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatibilty Group No.	The cargo reactive group number assigned for compatibilty determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20563-0001. Telephone (202) 372-1425.
Note 2	See Appendix I to 46 CFR Part 150 - exceptions to the compatibilty chart.
Subchapter	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.
Subchapter D	Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Subchapter O	Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.
Note 3	Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-ocangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "[ ]" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
A, B, C	Flammable liquid cargoes, as defined in 46 CFR 30-10.22.
D, E	Combustible liquid cargoes, as defined in 46 CFR 30-10.15.
Note 4	The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
NA	Those subchapter O cargoes which are not classified as a flammable or combustible liquid.
#	No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.
I	Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).
II	Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).
III	Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).
NA	Not applicable to barges certificated under Subchapter D.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

#### VCS Category:

Category 1	The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-1) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.
Category 2	(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.
Category 3	(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Category 4	(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.
Category 5	(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.
Category 6	(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5.
Category 7	(High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.
none	The cargo has not been evaluated/classified for use in vapor control systems.