



United States of America
Department of Homeland Security
United States Coast Guard

Certification Date: 08 Jul 2014
Expiration Date: 08 Jul 2019
IMO Number:

Certificate of Inspection

For ships on International voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT

| | | | | | | |
|--|---|------------------------------------|------------------------------|---------------------------|-----|--------------------------|
| Vessel Name HTCO 3068 | Official Number 1218832 | Call Sign | Service Tank Barge | | | |
| Home Port HOUSTON TX | Hull Material Steel | Horsepower | Propulsion | | | |
| Place Built MADISONVILLE, LA UNITED STATES | Delivery Date 12Jun2009 | Date Keel Laid 24Apr2009 | Gross Tons R-1619 | Net Tons R-1619 | LWT | Length R-297.6 |
| Owner HIGMAN BARGE LINES INC 1980 POST OAK BLVD - SUITE 1101 HOUSTON, TX 77056 UNITED STATES | Operator HIGMAN BARGE LINES INC 1980 POST OAK BLVD STE 1101 HOUSTON, TX 77056 UNITED STATES | | | | | |

This vessel must be manned with the following licensed and unlicensed personnel. Included in which there must be 0 certified lifeboatmen, 0 certified tankermen, 0 HSC type rating, and 0 GMDSS Operators.

| | | | | |
|----------------|--------------------------|--------------------|--------------------------|-------------|
| Master | Master & 1st Class pilot | Radio Officer(s) | Chief Engineer | QMED/Relief |
| Chief Mate | Mate & 1st Class Pilot | Able Seamen/PO/ANW | 1st Asst. Engr/2nd Engr. | Oilers |
| 2nd Mate/OICNW | Lic. Mate/OICNW | Ordinary Seamen | 2nd Asst. Engr/3rd Engr. | |
| 3rd Mate/OICNW | 1st Class Pilot | Deckhands | 3rd Asst. Engr. | |
| | | | Lic. Engr. | |

In addition, this vessel may carry 0 passengers, 0 other persons in crew, 0 persons in addition to crew, and no others. Total persons allowed: 0

Route Permitted and Conditions of Operation:

---Lakes, Bays, and Sounds---

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR 31.10-21 (a) (2); if this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

---Hull Exams---

| | | | |
|--------------------|-------------|-------------|-------------|
| Exam Type | Next Exam | Last Exam | Prior Exam |
| Drydock | 08 Jul 2014 | 08 Jul 2014 | 12 Jun 2009 |
| Internal Structure | 08 Jul 2019 | 08 Jul 2014 | 12 Jun 2009 |

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Freeport, TX, the Officer in Charge, Marine Inspection, Houston-Galveston certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

| | | | |
|---|--------|-----------|---|
| Annual/Periodic/Quarterly Reinspections | | | This certificate issued by: <i>Ricardo M. Alonso</i> RICARDO M. ALONSO, CDR, USCG, BY DIRECTION |
| Date | Zone | Signature | |
| 2 AUG 13 | HOUMS | A | Office in Charge, Marine Inspection Houston-Galveston |
| 27 July | HO-KAL | A | |
| - | - | - | Inspector Zone |



Certificate of Inspection

HICO 3068

Certification Date:
08Jul2014

---Liquid/Gas/Solid Cargo Authority/Conditions---

Authorization/ Grade "A" and Lower and Specified Hazardous Cargoes.
46CFR Subchapter D Authority: Highest Grade/A Capacity/28200 Units/Barrels
46CFR Subchapter O Authority: Part 151/Yes Part 153/No Part 154/No

Loading Constraints - Structural

| Tanks | Max Cargo Weight/Tank (Short Tons) | Max Density (LBS/Gal) |
|-------|------------------------------------|-----------------------|
| 1 P/S | 862 | 13.6 |
| 2 P/S | 878 | 13.6 |
| 3 P/S | 682 | 13.6 |

Loading Constraints - Stability

| Hull Type | Max Load (STons) | Max Draft (Ft/In) | Max Density (Lbs/Gal) | Route |
|-----------|------------------|-------------------|-----------------------|-------------------------|
| II | 3747 | 10'0 | 13.6 | Lakes, Bays, and Sounds |
| III | 4619 | 11'9 | 13.6 | Lakes, Bays, and Sounds |
| II | 3747 | 10'0 | 13.6 | Rivers |
| III | 4619 | 11'9 | 13.6 | Rivers |

Conditions of Carriage

Only Grade A and lower cargoes and specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #C2-0900830, dated May 19, 2009, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the Person in Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "COMPAT GROUP NO" column listed in the vessel's Cargo Authority Attachment.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed.

Per 46 CFR 151.10-15 (c) (2) the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

Cargo tank maximum design working pressure: 3.00 psig



Certificate of Inspection

HICO 3068

Certification Date:
08Jul2014

Thermal Fluid Heater

Thermal fluid heater may only be operated when carrying grade "E" cargoes.

The vessel is inspected and approved for the carriage of grade "E" combustible liquids when transported in molten form at elevated temperatures.

The thermal fluid heater located in the hazardous location does not meet the requirements of 46 CFR 111.105-31(I), and may not be used when carrying cargoes above Grade E. Additionally, in accordance with 46 CFR 111.105-29(c), no cargo may be heated to within 15 degrees (c) of its flash point.

Vapor Control Authorization

In accordance with 46 CFR Part 39, excluding part 39.4000, this vessel's vapor collection system has been inspected to the plans approved by Marine Safety Center letter Serial #C2-0900830, dated March 19, 2009, and has been found acceptable for the collection of bulk liquid cargo vapors annotated with "Yes" in the VCS column of the vessel's Cargo Authority Attachment.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 CFR part 197, Subpart C are applied.

---Inspection Status---

Cargo Tanks

| TankID | Internal Exam | | | External Exam | | |
|--------|---------------|-----------|-----------|---------------|------|------|
| | Previous | Last | Next | Previous | Last | Next |
| 1 P/S | 12Jun2009 | 08Jul2014 | 08Jul2024 | - | - | - |
| 2 P/S | 12Jun2009 | 08Jul2014 | 08Jul2024 | - | - | - |
| 3 P/S | 12Jun2009 | 08Jul2014 | 08Jul2024 | - | - | - |

| TankID | Safety | Hydro Test | | |
|--------|--------|------------|------|------|
| | Valves | Previous | Last | Next |
| 1 P/S | - | - | - | - |
| 2 P/S | - | - | - | - |
| 3 P/S | - | - | - | - |

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery.

---Fire Fighting Equipment---

Number of Fireman Outfits/ 0

Fire Extinguishers - Hand portable and semi-portable

| Qty | Class Type |
|-----|------------|
| 3 | B-II |

END



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **HTCO-3068**
Official #: 1218832

Shipyard: **Trinity Madisonville**
Hull #: 2175-3

46 CFR 151 Tank Group Characteristics

| Tank Group Information | | Cargo Identification | | | Hull Type | Cargo Seg Tank | Tanks | | | Cargo Transfer | | Environmental Control | | Fire Protection Provided | Special Requirements | | | Elec Haz | Temp Cont |
|------------------------|----------------|----------------------|--------|-------|-----------|----------------|------------------|------|--------|----------------|------|-----------------------|----------------|--------------------------|--|---|----|----------|-----------|
| Tnk Grp | Tanks in Group | Density | Press. | Temp. | | | Type | Vent | Gauge | Pipe Class | Cont | Tanks | Handling Space | | General | Materials of Construction | | | |
| A | #1-3 P/S | 13.6 | Atmos. | Elev | II | 1I 2II | Integral Gravity | PV | Closed | II | G-1 | NR | NA | Portable | 40-1(f)(1), .50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50-81(b) | 55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g) | NA | Yes | |

- Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.
2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

| Cargo Identification | | | | | | | Conditions of Carriage | | | | | |
|----------------------|-----------|-----------------|-------------|-------|-----------|------------|------------------------|--------------|---|--------------|--|--|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Recovery | | Special Requirements in 46 CFR 151 General and Mat'l's of | Insp. Period | | |
| | | | | | | | App'd (Y or N) | VCS Category | | | | |

Authorized Subchapter O Cargoes

| | | | | | | | | | | |
|--|-----|------------------|---|----|-----|---|-----|-----|-------------------------------------|---|
| Alkyl(C7-C9) nitrates | AKN | 34 ² | O | NA | III | A | No | N/A | .50-81, .50-88 | G |
| Aminoethylethanolamine | AEE | 8 | O | E | III | A | Yes | 1 | .55-1(b) | G |
| Ammonium bisulfite solution (70% or less) | ABX | 43 ² | O | NA | III | A | No | N/A | .50-73, .56-1(a), (b), (c) | G |
| Carbon tetrachloride | CBT | 36 | O | NA | III | A | No | N/A | No | G |
| Caustic potash solution | CPS | 5 ² | O | NA | III | A | No | N/A | .50-73, .55-1(j) | G |
| Caustic soda solution | CSS | 5 ² | O | NA | III | A | No | N/A | .50-73, .55-1(j) | G |
| Chloroform | CRF | 36 | O | NA | III | A | Yes | 3 | No | G |
| Creosote | CCW | 21 ² | O | E | III | A | Yes | 1 | No | G |
| Cresols (all isomers) | CRS | 21 | O | E | III | A | Yes | 1 | No | G |
| Cresylic acid tar | CRX | | O | E | III | A | Yes | 1 | .55-1(f) | G |
| iso-Decyl acrylate | IAI | 14 | O | E | III | A | Yes | 2 | .50-70(a), .50-81(a), (b), .55-1(c) | G |
| 2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution | DDE | 43 | O | E | III | A | No | N/A | .56-1(a), (b), (c), (g) | G |
| 2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution | DAD | 0 ^{1,2} | O | A | III | A | No | N/A | .56-1(a), (b), (c), (g) | G |
| 2,4-Dichlorophenoxyacetic acid, trisopropanolamine salt solution | DTI | 43 ² | O | E | III | A | No | N/A | .56-1(a), (b), (c), (g) | G |
| Diethanolamine | DEA | 8 | O | E | III | A | Yes | 1 | .55-1(c) | G |
| Diethylenetriamine | DET | 7 ² | O | E | III | A | Yes | 1 | .55-1(c) | G |
| Diisopropanolamine | DIP | 8 | O | E | III | A | Yes | 1 | .55-1(c) | G |
| Dodecyldimethylamine, Tetradecyldimethylamine mixture | DOT | 7 | O | E | III | A | No | N/A | .56-1(b) | G |
| Dodecyl diphenyl ether disulfonate solution | DOS | 43 | O | # | II | A | No | N/A | No | G |
| Ethylene cyanohydrin | ETC | 20 | O | E | III | A | Yes | 1 | No | G |
| Ethylene glycol hexyl ether | EGH | 40 | O | E | III | A | No | N/A | No | G |
| Ethylene glycol propyl ether | EGP | 40 | O | E | III | A | Yes | 1 | No | G |
| Glutaraldehyde solution (50% or less) | GTA | 19 | O | NA | III | A | No | N/A | No | G |
| Kraft pulping liquors (free alkali content 3% or more)(Including: Black, Green, or White liquor) | KPL | 5 | O | NA | III | A | No | N/A | .50-73, .56-1(a), (c), (g) | G |
| Perchloroethylene | PER | 36 | O | NA | III | A | No | N/A | No | G |
| Polyethylene polyamines | PEB | 7 ² | O | E | III | A | Yes | 1 | .55-1(e) | G |
| Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide) | SAP | | O | | III | A | No | N/A | .50-73, .55-1(j) | G |
| Sodium aluminate solution (45% or less) | SAU | 5 | O | NA | III | A | No | N/A | .50-73, .56-1(a), (b), (c) | G |
| Sodium chlorate solution (50% or less) | SDD | 0 ^{1,2} | O | NA | III | A | No | N/A | .50-73 | G |
| Sodium hypochlorite solution (20% or less) | SHQ | 5 | O | NA | III | A | No | N/A | .50-73, .56-1(a), (b) | G |
| Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less) | SSH | 0 ^{1,2} | O | NA | III | A | Yes | 1 | .50-73, .55-1(c) | G |
| Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm) | SSI | 0 ^{1,2} | O | NA | III | A | No | N/A | .50-73, .55-1(b) | G |
| Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm) | SSJ | 0 ^{1,2} | O | NA | II | A | No | N/A | .50-73, .55-1(b) | G |

*** This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **HTCO-3068**

Official #: 1218832

Page 2 of 6

Shipyard: **Trinity Madisonville**

Hull #: 2175-3

| Cargo Identification | | | | | | Conditions of Carriage | | | | |
|--|-----------|-----------------|-------------|-------|-----------|------------------------|----------------|--------------|--|--------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Recovery | | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| | | | | | | | App'd (Y or N) | VCS Category | | |
| 1,1,2,2-Tetrachloroethane | TEC | 36 | O | NA | III | A | No | N/A | No | G |
| Toluenediamine | TDA | 9 | O | E | II | A | No | N/A | .50-73, .56-1(a), (b), (c), (g) | G |
| Triphenylborane (10% or less), caustic soda solution | TPB | 5 | O | NA | III | A | No | N/A | .56-1(a), (b), (c) | G |
| Trisodium phosphate solution | TSP | 5 | O | NA | III | A | No | N/A | .50-73, .56-1(a), (c) | G |
| Vanillin black liquor (free alkali content, 3% or more). | VBL | 5 | O | NA | III | A | No | N/A | .50-73, .56-1(a), (c), (g) | G |

Subchapter D Cargoes Authorized for Vapor Control

| | | | | | | | | | |
|---|-----|-----------------|---|-----|--|---|-----|---|--|
| Acetone | ACT | 18 ² | D | C | | A | Yes | 1 | |
| Acetophenone | ACP | 18 | D | E | | A | Yes | 1 | |
| Alcohol(C12-C16) poly(1-6)ethoxylates | APU | 20 | D | E | | A | Yes | 1 | |
| Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates | AEB | 20 | D | E | | A | Yes | 1 | |
| Amyl acetate (all isomers) | AEC | 34 | D | D | | A | Yes | 1 | |
| Amyl alcohol (iso-, n-, sec-, primary) | AAI | 20 | D | D | | A | Yes | 1 | |
| Benzyl alcohol | BAL | 21 | D | E | | A | Yes | 1 | |
| Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters) | BFX | 20 | D | E | | A | Yes | 1 | |
| Butyl acetate (all isomers) | BAX | 34 | D | D | | A | Yes | 1 | |
| Butyl alcohol (iso-) | BAL | 20 ² | D | D | | A | Yes | 1 | |
| Butyl alcohol (n-) | BAN | | D | D | | A | Yes | 1 | |
| Butyl alcohol (sec-) | BAS | | D | C | | A | Yes | 1 | |
| Butyl alcohol (ter-) | BAT | | D | C | | A | Yes | 1 | |
| Butyl benzyl phthalate | BPH | 34 | D | E | | A | Yes | 1 | |
| Butyl toluene | BUE | 32 | D | D | | A | Yes | 1 | |
| Caprolactam solutions | CLS | 22 | D | E | | A | Yes | 1 | |
| Cyclohexane | CHX | 31 | D | C | | A | Yes | 1 | |
| Cyclohexanol | CHN | 20 | D | E | | A | Yes | 1 | |
| 1,3-Cyclopentadiene dimer (molten) | CPD | 30 | D | D/E | | A | Yes | 2 | |
| p-Cymene | CMP | 32 | D | D | | A | Yes | 1 | |
| iso-Decaldehyde | IDA | 19 | D | E | | A | Yes | 1 | |
| n-Decaldehyde | DAL | 19 | D | E | | A | Yes | 1 | |
| Decene | DCE | 30 | D | D | | A | Yes | 1 | |
| Decyl alcohol (all isomers) | DAX | 20 ² | D | E | | A | Yes | 1 | |
| n-Decylbenzene, see Alkyl(C9+)benzenes | DBZ | 32 | D | E | | A | Yes | 1 | |
| Diacetone alcohol | DAA | 20 ² | D | D | | A | Yes | 1 | |
| ortho-Dibutyl phthalate | DPA | 34 | D | E | | A | Yes | 1 | |
| Diethylbenzene | DEB | 32 | D | D | | A | Yes | 1 | |
| Diethylene glycol | DEG | 40 ² | D | E | | A | Yes | 1 | |
| Dilsobutylene | DBL | 30 | D | C | | A | Yes | 1 | |
| Dilsobutyl ketone | DIK | 18 | D | D | | A | Yes | 1 | |
| Diisopropylbenzene (all isomers) | DIX | 32 | D | E | | A | Yes | 1 | |
| Dimethyl phthalate | DTL | 34 | D | E | | A | Yes | 1 | |
| Diocetyl phthalate | DOP | 34 | D | E | | A | Yes | 1 | |
| Dipentene | DPN | 30 | D | D | | A | Yes | 1 | |
| Diphenyl | DIL | 32 | D | D/E | | A | Yes | 1 | |
| Diphenyl, Diphenyl ether mixtures | DDO | 33 | D | E | | A | Yes | 1 | |
| Diphenyl ether | DPE | 41 | D | (E) | | A | Yes | 1 | |
| Dipropylene glycol | DPG | 40 | D | E | | A | Yes | 1 | |
| Distillates: Flashed feed stocks | DFF | 33 | D | E | | A | Yes | 1 | |
| Distillates: Straight run | DSR | 33 | D | E | | A | Yes | 1 | |
| Dodecene (all isomers) | DOZ | 30 | D | D | | A | Yes | 1 | |

*** This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: HTCO-3068

Shipyard: Trinity Madisonville

Official #: 1218832

Page 3 of 6

Hull #: 2175-3

| Cargo Identification | | | | | | Conditions of Carriage | | | | |
|---|-----------|-----------------|-------------|-------|-----------|------------------------|----------------|--------------|--|--------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Recovery | | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| | | | | | | | App'd (Y or N) | VCS Category | | |
| Dodecylbenzene, see Alkyl(C9+)benzenes | DDB | 32 | D | E | | A | Yes | 1 | | |
| 2-Ethoxyethyl acetate | EEA | 34 | D | D | | A | Yes | 1 | | |
| Ethoxy triglycol (crude) | ETG | 40 | D | E | | A | Yes | 1 | | |
| Ethyl acetate | ETA | 34 | D | C | | A | Yes | 1 | | |
| Ethyl acetoacetate | EAA | 34 | D | E | | A | Yes | 1 | | |
| Ethyl alcohol | EAL | 20 ² | D | C | | A | Yes | 1 | | |
| Ethylbenzene | ETB | 32 | D | C | | A | Yes | 1 | | |
| Ethyl butanol | EBT | 20 | D | D | | A | Yes | 1 | | |
| Ethyl tert-butyl ether | EBE | 41 | D | C | | A | Yes | 1 | | |
| Ethyl butyrate | EBR | 34 | D | D | | A | Yes | 1 | | |
| Ethyl cyclohexane | ECY | 31 | D | D | | A | Yes | 1 | | |
| Ethylene glycol | EGL | 20 ² | D | E | | A | Yes | 1 | | |
| Ethylene glycol butyl ether acetate | EMA | 34 | D | E | | A | Yes | 1 | | |
| Ethylene glycol diacetate | EGY | 34 | D | E | | A | Yes | 1 | | |
| Ethylene glycol phenyl ether | EPE | 40 | D | E | | A | Yes | 1 | | |
| Ethyl-3-ethoxypropionate | EEP | 34 | D | D | | A | Yes | 1 | | |
| 2-Ethylhexanol | EHX | 20 | D | E | | A | Yes | 1 | | |
| Ethyl propionate | EPR | 34 | D | C | | A | Yes | 1 | | |
| Ethyl toluene | ETE | 32 | D | D | | A | Yes | 1 | | |
| Formamide | FAM | 10 | D | E | | A | Yes | 1 | | |
| Furfuryl alcohol | FAL | 20 ² | D | E | | A | Yes | 1 | | |
| Gasoline blending stocks: Alkylates | GAK | 33 | D | A/C | | A | Yes | 1 | | |
| Gasoline blending stocks: Reformates | GRF | 33 | D | A/C | | A | Yes | 1 | | |
| Gasolines: Automotive (containing not over 4.23 grams lead per gallon) | GAT | 33 | D | C | | A | Yes | 1 | | |
| Gasolines: Aviation (containing not over 4.86 grams of lead per gallon) | GAV | 33 | D | C | | A | Yes | 1 | | |
| Gasolines: Casinghead (natural) | GCS | 33 | D | A/C | | A | Yes | 1 | | |
| Gasolines: Polymer | GPL | 33 | D | A/C | | A | Yes | 1 | | |
| Gasolines: Straight run | GSR | 33 | D | A/C | | A | Yes | 1 | | |
| Glycerine | GCR | 20 ² | D | E | | A | Yes | 1 | | |
| Heptane (all isomers), see Alkanes (C6-C9) (all isomers) | HMX | 31 | D | C | | A | Yes | 1 | | |
| Heptanoic acid | HEP | 4 | D | E | | A | Yes | 1 | | |
| Heptanol (all isomers) | HTX | 20 | D | D/E | | A | Yes | 1 | | |
| Heptene (all isomers) | HPX | 30 | D | C | | A | Yes | 2 | | |
| Heptyl acetate | HPE | 34 | D | E | | A | Yes | 1 | | |
| Hexane (all isomers), see Alkanes (C6-C9) | HXS | 31 ² | D | B/C | | A | Yes | 1 | | |
| Hexanoic acid | HXO | 4 | D | E | | A | Yes | 1 | | |
| Hexanol | HXN | 20 | D | D | | A | Yes | 1 | | |
| Hexene (all isomers) | HEX | 30 | D | C | | A | Yes | 2 | | |
| Hexylene glycol | HXG | 20 | D | E | | A | Yes | 1 | | |
| Isophorone | IPH | 18 ² | D | E | | A | Yes | 1 | | |
| Jet fuel: JP-4 | JPF | 33 | D | E | | A | Yes | 1 | | |
| Jet fuel: JP-5 (kerosene, heavy) | JPV | 33 | D | D | | A | Yes | 1 | | |
| Kerosene | KRS | 33 | D | D | | A | Yes | 1 | | |
| Methyl acetate | MTT | 34 | D | D | | A | Yes | 1 | | |
| Methyl alcohol | MAL | 20 ² | D | C | | A | Yes | 1 | | |
| Methylamyl acetate | MAC | 34 | D | D | | A | Yes | 1 | | |
| Methylamyl alcohol | MAA | 20 | D | D | | A | Yes | 1 | | |
| Methyl amyl ketone | MAK | 18 | D | D | | A | Yes | 1 | | |
| Methyl tert-butyl ether | MBE | 41 ² | D | C | | A | Yes | 1 | | |

*** This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: HTCO-3068

Official #: 1218832

Page 4 of 6

Shipyard: Trinity Madisonville

Hull #: 2175-3

| Cargo Identification | | | | | | Conditions of Carriage | | | | |
|---|-----------|-----------------|-------------|-------|-----------|------------------------|----------------|--------------|--|--------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Recovery | | Special Requirements in 48 CFR 151 General and Mat'ls of | Insp. Period |
| | | | | | | | App'd (Y or N) | VCS Category | | |
| Methyl butyl ketone | MBK | 18 | D | C | | A | Yes | 1 | | |
| Methyl butyrate | MBU | 34 | D | C | | A | Yes | 1 | | |
| Methyl ethyl ketone | MEK | 18 ² | D | C | | A | Yes | 1 | | |
| Methyl heptyl ketone | MHK | 18 | D | D | | A | Yes | 1 | | |
| Methyl isobutyl ketone | MIK | 18 ² | D | C | | A | Yes | 1 | | |
| Methyl naphthalene (molten) | MNA | 32 | D | E | | A | Yes | 1 | | |
| Mineral spirits | MNS | 33 | D | D | | A | Yes | 1 | | |
| Myrcene | MRE | 30 | D | D | | A | Yes | 1 | | |
| Naphtha: Heavy | NAG | 33 | D | # | | A | Yes | 1 | | |
| Naphtha: Petroleum | PTN | 33 | D | # | | A | Yes | 1 | | |
| Naphtha: Solvent | NSV | 33 | D | D | | A | Yes | 1 | | |
| Naphtha: Stoddard solvent | NSS | 33 | D | D | | A | Yes | 1 | | |
| Naphtha: Varnish makers and painters (75%) | NVM | 33 | D | C | | A | Yes | 1 | | |
| Nonane (all isomers), see Alkanes (C6-C9) | NAX | 31 | D | D | | A | Yes | 1 | | |
| Nonene (all isomers) | NON | 30 | D | D | | A | Yes | 2 | | |
| Nonyl alcohol (all isomers) | NNS | 20 ² | D | E | | A | Yes | 1 | | |
| Nonyl phenol | NNP | 21 | D | E | | A | Yes | 1 | | |
| Nonyl phenol poly(4+)ethoxylates | NPE | 40 | D | E | | A | Yes | 1 | | |
| Octane (all isomers), see Alkanes (C6-C9) | OAX | 31 | D | C | | A | Yes | 1 | | |
| Octanoic acid (all isomers) | OAY | 4 | D | E | | A | Yes | 1 | | |
| Octanol (all isomers) | OCX | 20 ² | D | E | | A | Yes | 1 | | |
| Octene (all isomers) | OTX | 30 | D | C | | A | Yes | 2 | | |
| Oil, fuel: No. 2 | OTW | 33 | D | D/E | | A | Yes | 1 | | |
| Oil, fuel: No. 2-D | OTD | 33 | D | D | | A | Yes | 1 | | |
| Oil, fuel: No. 4 | OFR | 33 | D | D/E | | A | Yes | 1 | | |
| Oil, fuel: No. 5 | OFV | 33 | D | D/E | | A | Yes | 1 | | |
| Oil, fuel: No. 6 | OSX | 33 | D | E | | A | Yes | 1 | | |
| Oil, misc: Crude | OIL | 33 | D | C/D | | A | Yes | 1 | | |
| Oil, misc: Diesel | ODS | 33 | D | D/E | | A | Yes | 1 | | |
| Oil, misc: Gas, high pour | OGP | 33 | D | E | | A | Yes | 1 | | |
| Oil, misc: Lubricating | OLB | 33 | D | E | | A | Yes | 1 | | |
| Oil, misc: Residual | ORL | 33 | D | E | | A | Yes | 1 | | |
| Oil, misc: Turbine | OTB | 33 | D | E | | A | Yes | 1 | | |
| Pentene (all isomers) | PTX | 30 | D | A | | A | Yes | 5 | | |
| alpha-Pinene | PIO | 30 | D | D | | A | Yes | 1 | | |
| beta-Pinene | PIP | 30 | D | D | | A | Yes | 1 | | |
| Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether | PAG | 40 | D | E | | A | Yes | 1 | | |
| Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate | PAF | 34 | D | E | | A | Yes | 1 | | |
| Polybutene | PLB | 30 | D | E | | A | Yes | 1 | | |
| Polypropylene glycol | PGC | 40 | D | E | | A | Yes | 1 | | |
| iso-Propyl acetate | IAC | 34 | D | C | | A | Yes | 1 | | |
| n-Propyl acetate | PAT | 34 | D | C | | A | Yes | 1 | | |
| iso-Propyl alcohol | IPA | 20 ² | D | C | | A | Yes | 1 | | |
| n-Propyl alcohol | PAL | 20 ² | D | C | | A | Yes | 1 | | |
| Propylbenzene (all isomers) | PBY | 32 | D | D | | A | Yes | 1 | | |
| iso-Propylcyclohexane | IPX | 31 | D | D | | A | Yes | 1 | | |
| Propylene glycol | PPG | 20 ² | D | E | | A | Yes | 1 | | |
| Propylene glycol methyl ether acetate | PGN | 34 | D | D | | A | Yes | 1 | | |
| Propylene tetramer | PTT | 30 | D | D | | A | Yes | 1 | | |
| Sulfolane | SFL | 39 | D | E | | A | Yes | 1 | | |



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **HTCO-3068**

Shipyard: **Trinity Madisonville**

Official #: 1218832

Page 5 of 6

Hull #: 2175-3

| Cargo Identification | | | | | | Conditions of Carriage | | | | |
|--|-----------|-----------------|-------------|-------|-----------|------------------------|----------------|--------------|--|--------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Recovery | | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| | | | | | | | App'd (Y or N) | VCS Category | | |
| Tetraethylene glycol | TTG | 40 | D | E | | A | Yes | 1 | | |
| Tetrahydronaphthalene | THN | 32 | D | E | | A | Yes | 1 | | |
| Toluene | TOL | 32 | D | C | | A | Yes | 1 | | |
| Tricresyl phosphate (less than 1% of the ortho isomer) | TCP | 34 | D | E | | A | Yes | 1 | | |
| Triethylbenzene | TEB | 32 | D | E | | A | Yes | 1 | | |
| Triethylene glycol | TEG | 40 | D | E | | A | Yes | 1 | | |
| Triethyl phosphate | TPS | 34 | D | E | | A | Yes | 1 | | |
| Trimethylbenzene (all isomers) | TRE | 32 | D | {D} | | A | Yes | 1 | | |
| Trixylenyl phosphate | TRP | 34 | D | E | | A | Yes | 1 | | |
| Undecene | UDC | 30 | D | D/E | | A | Yes | 1 | | |
| 1-Undecyl alcohol | UND | 20 | D | E | | A | Yes | 1 | | |
| Xylenes (ortho-, meta-, para-) | XLX | 32 | D | D | | A | Yes | 1 | | |



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **HTCO-3068**

Official #: 1218832

Page 6 of 6

Shipyard: **Trinity Madison**

Hull #: 2175-3

Explanation of terms & symbols used in the Table:

Cargo Identification

| | |
|--|--|
| Name | The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2. |
| Chem Code none | The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned. |
| Compatibility Group No. | The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number. |
| Note 1 | Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425. |
| Note 2 | See Appendix I to 46 CFR Part 150 - exceptions to the compatibility chart. |
| Subchapter Subchapter D Subchapter O Note 3 | The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1. Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2. Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges. |
| Grade | The cargo classification assigned to each flammable or combustible liquid. Grades inside of "[]" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. |
| A, B, C | Flammable liquid cargoes, as defined in 46 CFR 30-10.22. |
| D, E | Combustible liquid cargoes, as defined in 46 CFR 30-10.15. |
| Note 4 | The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. |
| NA # | Those subchapter O cargoes which are not classified as a flammable or combustible liquid. No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available. |
| Hull Type I II III NA | The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D. |

Conditions of Carriage

| | |
|-------------------------------------|--|
| Tank Group | The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo. |
| Vapor Recovery Approved (Y or N) | Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. |

Conditions of Carriage

| | |
|-------------------------------------|--|
| Tank Group | The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo. |
| Vapor Recovery Approved (Y or N) | Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. |

| | |
|---------------|--|
| VCS Category: | The specified cargo's provisional classification for vapor control systems. |
| Category 1 | (No additional VCS requirements above those for benzene, gasoline and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. |
| Category 2 | (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester. |
| Category 3 | (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. |
| Category 4 | (Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3. |
| Category 5 | (High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1. |
| Category 6 | (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. |
| Category 7 | (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5. |
| none | The cargo has not been evaluated/classified for use in vapor control systems. |