

2380 Fifth Street  
Mandeville, LA 70471  
Phone (985) 629-2082 Fax (985) 629-2120

Florida Marine  
Transporters Inc.

MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER  
OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3009 OFFICIAL NUMBER: 1094956  
TESTING LOCATION: Bolivar Terminal Fleet MAXIMUM LOADING RATE (BPH) 5,000  
TANK(S) TESTED: All PRESSURE INDICATOR: MANOMETER  
VESSEL OWNER AND ADDRESS: FLORIDA MARINE 2360 FIFTH ST MANDEVILLE, LA

TEST RESULTS

TEST DATE: 2-11-26  
BEGINNING PRESSURE: 28" OF H<sub>2</sub>O BEGINNING TIME: 1330  
ENDING PRESSURE: 28" OF H<sub>2</sub>O ENDING TIME: 1400  
TOTAL PRESSURE LOSS: 0 ALLOWABLE PRESSURE LOSS: 2.2" OF H<sub>2</sub>O

NOTE: VESSEL IS CONSIDERED VAPOR TIGHT IF "TOTAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"

THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS  
CONSIDERED VAPOR TIGHT.

TESTER: HOSS STRIPP (PRINT) WITNESS: MATT BRAZZEL (PRINT)  
TESTER: [Signature] (SIGN) WITNESS: [Signature] (SIGN)  
FMT  
AFFILIATION OF WITNESS

CALCULATION OF ALLOWABLE PRESSURE LOSS:

$$0.861 \times \frac{15.7}{(TP)} \times \left( \frac{5,000}{(L)} \div \frac{30,706}{(V)} \right) = \frac{2.2}{(APL)}$$

TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI (1psi = 16 ounces)  
L = MAXIMUM LOADING RATE IN BARRELS PER HOUR  
V = VOLUME OF TANK(S) IN BARRELS  
APL = ALLOWABLE PRESSURE LOSS IN INCHES OF WATER

NOTES: 14.70psi = 406.8 inches of H<sub>2</sub>O  
1psi = 27.67 inches of H<sub>2</sub>O  
1 inch = 25.40 mm  
1 inch = 2.54 cm  
1 oz. = 1.729 inches OF H<sub>2</sub>O