Florida Marine Transporters Inc.

## MARINE VESSELS VAPOR TIGHTNESS DOCUMENTATION

REQUIRED SUBPART BB-NATIONAL EMISSION STANDARDS FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS SECTION 61.00-61.306

VESSEL: FMT 3178	OFFICIAL NUMBER: 1177880
TESTING LOCATION: CUMMINIC FLT	MAXIMUM LOADING RATE (BPH) 5,000
TANK(S) TESTED: ALL	PRESSURE INDICATOR: MANOMETER
VESSEL OWNER AND ADDRESS: PMT 236	O FIFTH ST. MANDEVILLE
	T RESULTS
BEGINNING PRESSURE: 28" OF H20	BEGINNING TIME: 1100
ENDING PRESSURE: 28'0F H20	ENDING TIME: 1130
TOTAL PRESSURE LOSS:	ALLOWABLE PRESSURE LOSS: 2.2" of H20
	TAL PRESSURE LOSS" IS LESS THAN "ALLOWABLE PRESSURE LOSS"
THIS VESSEL HAS BEEN TESTED IN ACCORDANCE WITH SECTION 61.304F, AND IS CONSIDERED VAPOR TIGHT.	
TESTER: DAVID MCNEMAR (PRINT) TESTER: (SIGN)	WITNESS: ROBERT MENEMAR (PRINT) WITNESS: (SIGN)  AFFILIATION OF WITNESS
CALCULATION OF ALLOWABLE PRESSURE LOSS:	APPLIATION OF WITHESS
0.861 x 15.7 x ( 5,000 ) 30,	$(X) = \frac{Z \cdot Z}{(APL)}$
TP = 14.7 PLUS THE BARGE TEST PRESSURE IN PSI ( L = MAXIMUM LOADING RATE IN BARRELS PER F V = VOLUME OF TANK(S) IN BARRELS APL = ALLOWABLE PRESSURE LOSS IN INCHES OF  NOTES: 14.70psi = 406.8 inches of H2O 1 psi = 27.67 inches of H2O 1 inch = 25.40 mm 1 inch = 2.54 cm 1 oz. = 1.729 inches OF H2O	HOUR