

### **United States of America Department of Homeland Security United States Coast Guard**

10 Aug 2020 Certification Date: **Expiration Date:** 10 Aug 2021

Marine Safety Unit Port Arthur

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

tion is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the

The temporary of	receipt on board sa	id vessel of the	original certificate of ins	pection, this certifi	cate in no case to be w	alid after one year from	the date of inspection	n.	
Vessel Name			Official Number	MO	Number	Call Sign	Service		
HFL 208		-	1225343				Tank Ba	arge	
							•		
Hailing Port				<del></del>		Propulsion			
NASHVILLE	TN		Hull Material	•	Horsepower	Propulsion			
·			Steel					•	
UNITED STA	TES					-			
				•					
Place Built		_	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length	
BELLE CHA	SSE, LA		08Jul2010	05May201	10 R-735	R-735		R-200.0	
			VOJUIZUTU	USINIAYZU	10  -	F		1-0	
UNITED STA	ATES					·			
									-
Owner					perator	MADINE ID			
HFS MARINE	ELLC ORO PIKE STE	- 202DA E	20V 450900		IRBY INLAND 8350 MARKET				
NASHVILLE,		202PO E	OV 190009		HANNELVIEW				
UNITED STA					NITED STATE		-		
This vessel m	ust be manned	with the fo	ollowing licensed	and unlicer	nsed Personnel	l. Included in w	hich there mu	st be	
0 Certified Lif	eboatmen, 0 Ce	ertified Tar	nkermen, 0 HSC	Type Ratir	ng, and 0 GMD	SS Operators.			
0 Masters	0	Licensed M	ates 0 Chief	<b>Engineers</b>	00	ilers			
0 Chief Mater	3 0	First Class	Pilots 0 First	Assistant Eng	ineers				
0 Second Ma	tes 0	Radio Offic	ers 0 Seco	nd Assistant E	Engineers				
0 Third Mates	. 0	Able Seam	en 0 Third	Assistant Eng	gineers				
0 Master Firs	t Class Pilot 0	Ordinary Se	eamen 0 Licen	sed Engineers	3				
0 Mate First (		Deckhands		fied Member E				o Othoro, To	tal
In addition, the Persons allow	is vessel may ca ved: 0	arry 0 Pas	sengers, 0 Othe	r Persons ir	n crew, 0 Perso 	ns in addition t	o crew, and in	o Others. 10	tai
Route Perm	itted And Cond	ditions Of	Operation:						
Lakes.	Bays, and S	ounds	plus Limited	d Coastw	vise				
نے ۔		. not mo	re than twelve	. (12) mile	s from shore	between St. 1	Marks and Ca	rrabelle,	
Florida.									
This vessel	has been gran	ted a fre	sh water servi	ce examina	tion interval	per 46 CFR	31.10-21(a)(	2). If thi	.s ısina
vessel is or	erated in sal	t water m 46 CFR 31	ore than 6 mon. .10-21(a)(1) a	iths in any and the coo	nizant OCMI r	notified in w	riting as so	on as this	
change in st	atus occurs.			_	•			,	
This tank ba	rge is partic	ipating i	n the Eighth C	oast Guard	l District's 7	Tank Barge St	reamlined In	spection Pr	ogram:
			NAL CERTIFIC				·		
With this Insp	ection for Certifi	cation hav	ing been compl	eted at Port	Arthur, TX, UN	NITED STATES	S, the Officer i	in Charge, M	larine
inspection, Ma	arine Safety Uni	t Port Arth	our certified the varied the varied the certified the cert	<i>r</i> essel, in all er	respects, is in	conformity with	ı me applicabl	io vessei iiist	7 <b>5</b> 0110[1
iaws and the	rules and regula Annual/Perio			<del>3</del> 1.	This certificat	e issued by	Makren	C.D	
Deta	Zone	A/P/R	Signatu	100		ANDREW, CD	R/USCG BV	direction	
Date	20116	17171	Gignatu		Officer in Charge, Me			1	
								1	



### **United States of America Department of Homeland Security United States Coast Guard**

Certification Date: 10 Aug 2020 10 Aug 2021 **Expiration Date:** 

### Temporary Certificate of Inspection

Vessel Name: HFL 208

(TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

### ---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

31Jul2030

10Aug2020

08Jul2010

Internal Structure

31Jul2025

10Aug2020

20Jul2015

### --- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

Grade "A" and Lower and Specified Hazardous Cargo.

**Total Capacity** 

Highest Grade Type Part151 Regulated Part153 Regulated

Part154 Regulated

11430

Barrels

Yes

No

No

### \*Hazardous Bulk Solids Authority\*

Not Authorized

### \*Loading Constraints - Structural\*

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1C	649	12.8
2 C	757	12.8
3 C	673	12.8

### \*Loading Constraints - Stability\*

ĺ	Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
I	1	1422	8ft 9in	15	R, LBS
	II	1511	9ft 2in	15	R, LBS
	LIA .	1727	10ft 1in	15	R, LBS
	101	1799	10ft 5in	13.5	R, LBS
	111	1817	10ft 6in	12.8	R, LBS
	114	1907	11ft Oin	15.0	R
	111	1961	11ft 3in	13.5	R
	131	1980	11ft 3in	12.8	R

### \*Conditions Of Carriage\*

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial # C1-1000198, dated 24-Mar-10, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compatible Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR Part 197, subpart C are applied.



## United States of America Department of Homeland Security United States Coast Guard

Certification Date: 10 Aug 2020 Expiration Date: 10 Aug 2021

### Temporary Certificate of Inspection

Vessel Name: HFL 208

Per 46 CFR, Part 39, excluding Part 39.40, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letter serial # C1-0801180, dated 4/16/2008, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Per 46 CFR 151.10(c)(2) the maximum tank weights listed above reflect uniform(within 5%) loading at the deepest draft allowed. When carrying subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.745 lbs/gal.

### --- Inspection Status ---

### \*Cargo Tanks\*

	Internal Exar	n		External Exa	m	
Tank Id	Previous	Last	Next	Previous	Last	Next
1C	08Jul2010	10Aug2020	31Jul2030	-	-	-
2 C	08Jul2010	10Aug2020	31Jul2030	-	-	•
3 C	08Jul2010	10Aug2020	31Jul2030	-	-	-
	•	•	Hydro Test			
Tank id	Safety Valve	s	Previous	Last	Next	-
1C	-		-	08Jul2010	• .	
2 C	-			08Jul2010	-	
3 C	-		-	08Jul2010	-	

### ---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

### --- Fire Fighting Equipment ---

Number of Fireman Outfits - 0

### \*Fire Extinguishers - Hand portable and semi-portable\*

Quantity

Class Type

2

40-B

\*\*\*END\*\*\*



Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HFL 208

Shipyard: C&C MARINE AND

Dated:

Serial #: C1-1000198

24-Mar-10

REPAIR CO.

Hull #: 137

Official #: 1225343

Tank Group Information	Cargo Identification			Cargo	Tanks		Cargo Transfer		Environmental Control		Fire	Special Requirements					
Tnk Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	full Seg	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction		Temp Cont
A #1,#2,#3	15	Atmos.	Amb.	1	1ii 2ii	Integral Gravity	PV	Closed	11	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50-73,	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

**List of Authorized Cargoes** 

Cargo Identificatio	n					Conditions of Carriage					
							Vapor Re	ecovery			
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period	
Authorized Subchapter O Cargoes											
Acetonitrile	ATN	37	0	С	Ш	Α	Yes	3	No	G	
Acrylonitrile	ACN	15 <sup>2</sup>	0	С	II	Α	Yes	4	.50-70(a), .55-1(e)	G	
Adiponitrile	ADN	37	0	Е	Ш	Α	Yes	1	No	G	
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	Ш	Α	No	N/A	.50-81, .50-86	G	
Aminoethylethanolamine	AEE	8	0	E	III	Α	Yes	1	.55-1(b)	G	
Ammonium bisulfite solution (70% or less)	ABX	43 <sup>2</sup>	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G	
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	Ш	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G	
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	Ш	Α	No	N/A	No	G	
Benzene	BNZ	32	0	С	Ш	Α	Yes	1	.50-60	G	
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	ВНВ	32 2	0	С	III	Α	Yes	1	.50-60	G	
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	322	0	С	Ш	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G	
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	Ш	Α	Yes	1	.50-60	G	
Butyl acrylate (all isomers)	BAR	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
Butyl methacrylate	ВМН	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
Butyraldehyde (all isomers)	BAE	19	0	С	Ш	Α	Yes	1	.55-1(h)	G	
Camphor oil (light)	CPO	18	0	D	П	Α	No	N/A	No	G	
Carbon tetrachloride	CBT	36	0	NA	Ш	Α	No	N/A	No	G	
Caustic potash solution	CPS	5 <sup>2</sup>	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G	
Caustic soda solution	CSS	5 <sup>2</sup>	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G	
Chemical Oil (refined, containing phenolics)	COD	21	0	Е	II	Α	No	N/A	.50-73	G	
Chlorobenzene	CRB	36	0	D	III	Α	Yes	1	No	G	
Chloroform	CRF	36	0	NA	Ш	Α	Yes	3	No	G	
Coal tar naphtha solvent	NCT	33	0	D	Ш	Α	Yes	1	.50-73	G	
Creosote	CCW	/ 21 <sup>2</sup>	0	E	Ш	Α	Yes	1	No	G	
Cresols (all isomers)	CRS	21	0	Е	Ш	Α	Yes	1	No	G	
Cresylate spent caustic	CSC	5	0	NA	III	Α	No	N/A	.50-73, .55-1(b)	G	
Cresylic acid tar	CRX		0	E	III	Α	Yes	1	.55-1(f)	G	
Crotonaldehyde	CTA	19 <sup>2</sup>	0	С	11	Α	Yes	4	.55-1(h)	G	
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	Ш	Α	No	N/A	No	G	
Cyclohexanone	ССН	18	0	D	111	Α	Yes	1	.56-1(a), (b)	G	
Cyclohexanone, Cyclohexanol mixture	CYX	18 <sup>2</sup>	0	Е	III	Α	Yes	1	.56-1 (b)	G	
Cyclohexylamine	CHA	7	0	D	Ш	Α	Yes	1	.56-1(a), (b), (c), (g)	G	
Cyclopentadiene, Styrene, Benzene mixture			_	_				-	EO CO EC 1/L)	G	
Cycloperitadiene, Ctyrene, Benzene mixtare	CSB	30	0	D	Ш	Α	Yes	1	.50-60, .56-1(b) .50-70(a), .50-81(a), (b), .55-1(c)		



Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **HFL 208**Official #: 1225343

Shipyard: C&C MARINE AND

Serial #: C1-1000198

24-Mar-10

Dated:

REPAIR CO.

Page 2 of 7

Hull #: 137

Cargo Identification	1					Conditions of Carriage						
								ecovery				
Name Dichlorobenzene (all isomers)	Chem Code DBX	Group No 36	Sub Chapter O	Grade E	Hull Type III	Tank Group A	App'd (Y or N) Yes	VCS Category 3	Special Requirements in 46 CFR 151 General and Mat'ls of .56-1(a), (b)	Insp. Period G		
1,1-Dichloroethane	DCH	36	0	С	III	Α	Yes	1	No	G		
2,2'-Dichloroethyl ether	DEE	41	0	D	II	Α	Yes	1	.55-1(f)	G		
Dichloromethane	DCM	36	0	NA	III	A	Yes	5	No	G		
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	 III	A	No	N/A	.56-1(a), (b), (c), (g)	G		
2,4-Dichlorophenoxyacetic acid, direthylamine salt solution	DAD	0 1,2		A	111	A	No	N/A	.56-1(a), (b), (c), (g)	G		
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 2	0		111	A	No	N/A	.56-1(a), (b), (c), (g)	G		
	DPB	36	0	C	III	A	Yes	3	No	G		
1,1-Dichloropropane	DPP	36	0	C		A	Yes	3	No	G		
1,2-Dichloropropane			0	C				3	No	G		
1,3-Dichloropropane	DPC	36				A	Yes		No	G		
1,3-Dichloropropene	DPU	15	0	D		A	Yes	4	No	G		
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	<u>II</u>	A	Yes	1	.55-1(c)	G		
Diethanolamine	DEA	8	0	E	III	Α .	Yes	1				
Diethylamine	DEN	7	0	C	III	A	Yes	3	.55-1(c)	G		
Diethylenetriamine	DET	72	0	E	III	Α	Yes	1	.55-1(c)	G		
Diisobutylamine	DBU	7	0	D	III	Α	Yes	3	.55-1(c)	G		
Diisopropanolamine	DIP	8	0	E	III	Α	Yes	1	.55-1(c)	G		
Diisopropylamine	DIA	7	0	С	- 11	Α	Yes	3	.55-1(c)	G		
N,N-Dimethylacetamide	DAC	10	0	E	III	Α	Yes	3	.56-1(b)	G		
Dimethylethanolamine	DMB	8	0	D	III	Α	Yes	1	.56-1(b), (c)	G		
Dimethylformamide	DMF	10	0	D	Ш	Α	Yes	1	.55-1(e)	G		
Di-n-propylamine	DNA	7	0	С	П	Α	Yes	3	.55-1(c)	G		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	III	Α	No	N/A	.56-1(b)	G		
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	II	Α	No	N/A	No	G		
EE Glycol Ether Mixture	EEG	40	0	D	Ш	Α	No	N/A	No	G		
Ethanolamine	MEA	8	0	Е	Ш	Α	Yes	1	.55-1(c)	G		
Ethyl acrylate	EAC	14	0	С	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Ethylamine solution (72% or less)	EAN	7	0	Α	II	Α	No	N/A	.55-1(b)	G		
N-Ethylbutylamine	EBA	7	0	D	III	Α	Yes	3	.55-1(b)	G		
N-Ethylcyclohexylamine	ECC	7	0	D	III	Α	Yes	1	.55-1(b)	G		
Ethylene cyanohydrin	ETC	20	0	Е	III	Α	Yes	1	No	G		
Ethylenediamine	EDA	72	0	D	III	Α	Yes	1	.55-1(c)	G		
Ethylene dichloride	EDC	36 <sup>2</sup>	0	С	III	A	Yes	1	No	G		
Ethylene glycol hexyl ether	EGH	40	0	E	Ш	Α	No	N/A	No	G		
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	III	Α	Yes	1	No	G		
Ethylene glycol propyl ether	EGP	40	0	E	III	A	Yes	1	No	G		
2-Ethylhexyl acrylate	EAI	14	0	E	 	A	Yes	2	.50-70(a), .50-81(a), (b)	G		
Ethyl methacrylate	ETM	14	0	D/E	 III	A	Yes	2	.50-70(a)	G		
2-Ethyl-3-propylacrolein	EPA	192	0	E			Yes	1	No	G		
Formaldehyde solution (37% to 50%)	FMS	19 2	0	D/E	111			1	.55-1(h)	G		
Furfural	FFA	19	0	D	111	A	Yes	1	.55-1(h)	G		
Glutaraldehyde solution (50% or less)	GTA	19	0	NA NA		A	Yes			G		
						A	No	N/A	.55-1(c)	G		
Hexamethylenediamine solution	HMC	7	0	E	- 111	A	Yes	1				
Hexamethyleneimine	HMI	7	0	С	- 11	A	Yes	1	.56-1(b), (c)	G		
Hydrocarbon 5-9	HFN	00	0	C		A	Yes	1	.50-70(a), .50-81(a), (b)	G		
Isoprene	IPR	30	0	Α		A	No	N/A	.50-70(a), .50-81(a), (b)	G		
Isoprene, Pentadiene mixture  Kraft pulping liquors (free alkali content 3% or more)(including: Black,	IPN KPL	5	0	B NA	111	A A	No No	N/A N/A	.50-70(a), .55-1(c) .50-73, .56-1(a), (c), (g)	G G		
Green, or White liquor)												
Mesityl oxide	MSO	18 <sup>2</sup>	0	D	Ш	Α	Yes	1	No	G		
Methyl acrylate	MAM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		



Serial #: C1-1000198 Dated:

24-Mar-10

# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HFL 208

Shipyard: C&C MARINE AND

REPAIR CO.

Official #: 1225343

Amyl acetate (all isomers)

Page 3 of 7

Cargo Identification		Conditions of Carriage								
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Ro App'd (Y or N)	ecovery VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp
Methylcyclopentadiene dimer	MCK	30	0	С	Ш	Α	Yes	1	No	G
Methyl diethanolamine	MDE	8	0	E	111	Α	Yes	1	.56-1(b), (c)	G
P-Methyl-5-ethylpyridine	MEP	9	0	Ε	Ш	Α	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	0	D	Ш	Α	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	72	0	D	III	Α	Yes	1	.55-1(c)	G
- or 2-Nitropropane	NPM	42	0	D	III	Α	Yes	1	.50-81	G
Pentachloroethane	PCE	36	0	NA	III	Α	No	N/A	No	G
,3-Pentadiene	PDE	30	0	Α	III	Α	No	N/A	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	III	Α	No	N/A	No	G
Polyethylene polyamines	PEB	72	0	Е	III	Α	Yes	1	.55-1(e)	G
so-Propanolamine	MPA	8	0	Е	III	Α	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	0	E	Ш	Α	Yes	1	.56-1(b), (c)	G
so-Propylamine	IPP	7	0	Α	Ш	Α	Yes	5	.55-1(c)	G
Pyridine	PRD	9	0	С	Ш	Α	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxic	de) SAP		0		III	Α	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
odium chlorate solution (50% or less)	SDD	0 1,2	2 0	NA	III	Α	No	N/A	.50-73	G
odium hypochlorite solution (20% or less)	SHQ	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b)	G
odium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2	2 0	NA	III	Α	Yes	1	.50-73, .55-1(b)	G
odium sulfide, hydrosulfide solution (H2S greater than 15 ppm but iss than 200 ppm)	SSI	0 1,2	2 0	NA	Ш	Α	No	N/A	.50-73, .55-1(b)	G
odium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	2 0	NA	Ш	Α	No	N/A	.50-73, .55-1(b)	G
styrene (crude)	STX		0	D	Ш	Α	Yes	2	No	G
Styrene monomer	STY	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
,1,2,2-Tetrachloroethane	TEC	36	0	NA	III	Α	No	N/A	No	G
etraethylenepentamine	TTP	7	0	E	III	Α	Yes	1	.55-1(c)	G
etrahydrofuran	THF	41	0	С	III	Α	Yes	1	.50-70(b)	G
Oluenediamine	TDA	9	0	Е	II	Α	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
,2,4-Trichlorobenzene	TCB	36	0	Е	III	Α	Yes	1	No	G
,1,2-Trichloroethane	TCM	36	0	NA	III	Α	Yes	1	.50-73, .56-1(a)	G
richloroethylene	TCL	36 <sup>2</sup>	0	NA	III	Α	Yes	1	No	G
,2,3-Trichloropropane	TCN	36	0	Е	II	Α	Yes	3	.50-73, .56-1(a)	G
riethanolamine	TEA	82	0	E	III	Α	Yes	1	.55-1(b)	G
riethylamine	TEN	7	0	С	II	Α	Yes	3	.55-1(e)	G
riethylenetetramine	TET	72	0	E	111	Α	Yes	1	.55-1(b)	G
riphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	III	Α	No	N/A	.56-1(a), (b), (c)	G
risodium phosphate solution	TSP	5	0	NA	III	Α	No	N/A		G
Irea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	III	Α	No	N/A		G
/anillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	III	Α	No	N/A		G
rinyl acetate	VAM	13	0	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
/invl neodecanate	VND	13	0	E	III	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
/inyltoluene	VNT	13	0		III	A	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (	G
ubchapter D Cargoes Authorized for Vapor Contr										
Acetone	ACT	18 <sup>2</sup>	D	С		Α	Yes	1		
acetophenone	ACP	18	D	E		Α	Yes	1		
klcohol(C12-C16) poly(1-6)ethoxylates	APU	20		E		A	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1		
And the fall face and a fall f	AEC	3/				^	Yes	1		

D

AEC



Serial #: C1-1000198 Dated: 24-Mar-10

Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: HFL 208

Ethylene glycol

Shipyard: C&C MARINE AND REPAIR CO.

Hull #: 137

Official #: 1225343

Page 4 of 7 Cargo Identification Conditions of Carriage Vapor Recovery VCS Chem Compat Sub Hull Tank App'd Special Requirements in 46 CFR Grade 151 General and Mat'ls of Group No hapte Groun Amyl alcohol (iso-, n-, sec-, primary) AAI 20 D D Α Yes BAI 21 D A Yes Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) BFX 20 D F Α Yes glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters) Butyl acetate (all isomers) 34 D Α Yes Butyl alcohol (iso-) IAL D D Α Yes Butyl alcohol (n-) BAN D D A Yes BAS D С Α Butyl alcohol (sec-) Yes BAT D C Α Yes Butyl alcohol (tert-) Butyl benzyl phthalate **BPH** 34 D F Α Yes BUE Butyl toluene 32 D D Α Yes Caprolactam solutions CLS 22 D F Α Yes CHX 31 D C Α Cyclohexane Yes D Cyclohexanol CHN 20 E Α Yes 1,3-Cyclopentadiene dimer (molten) CPD 30 D D/E 2 Α Yes p-Cymene CMP 32 D D Α Yes iso-Decaldehyde IDA 19 D Е Α Yes n-Decaldehyde DAL 19 D Е Α Yes D D Α Yes D Decyl alcohol (all isomers) Ε n-Decylbenzene, see Alkyl(C9+)benzenes DBZ D Ε Α DAA 202 D D Α ortho-Dibutyl phthalate DPA D F Α Diethylbenzene DFB D D Yes Diethylene glycol DEG 402 D F Α Diisobutylene DBL 30 D C A Yes Diisobutyl ketone DIK 18 D D Α Yes Diisopropylbenzene (all isomers) DIX 32 D Ε Α Yes Dimethyl phthalate DTL D Ε Yes Α Dioctyl phthalate D E Α Yes D Dipentene D Α Yes Diphenyl DIL D D/E Α Yes Diphenyl, Diphenyl ether mixtures DDO 33 D Е Α Diphenyl ether DPE 41 D {E} Α Yes DPG Dipropylene glycol 40 D F Α Yes Distillates: Flashed feed stocks DFF 33 D F Α Yes Distillates: Straight run DSR 33 D E Α Yes Dodecene (all isomers) DOZ 30 D D A Yes Dodecylbenzene, see Alkyl(C9+)benzenes DDB 32 D Е Α Yes 1 2-Ethoxyethyl acetate EEA 34 D D A Yes Ethoxy triglycol (crude) ETG D Е Α Yes Ethyl acetate ETA D Α Yes Ethyl acetoacetate EAA D E Yes Ethyl alcohol EAL 202 D C Ethylbenzene FTB 32 D C Ethyl butanol **EBT** 20 D D A Yes Ethyl tert-butyl ether EBE С 41 D Yes Ethyl butyrate **EBR** 34 D D A Yes Ethyl cyclohexane D Α Yes

D

Α

Yes

**EGL** 



Dated:

Serial #: C1-1000198 24-Mar-10

# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: HFL 208

Official #: 1225343

Page 5 of 7

Shipyard: C&C MARINE AND REPAIR CO.

Hull #: 137

Cargo Identification	on					Conditions of Carriage						
							-	Recovery				
Name Ethylene glycol butyl ether acetate	Chem Code EMA	Compat Group No 34	Sub Chapter D	Grade E	Hull Type	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1				
Ethylene glycol phenyl ether	EPE	40	D	Е		Α	Yes	1				
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1				
2-Ethylhexanol	EHX	20	D	Е		Α	Yes	1				
Ethyl propionate	EPR	34	D	С		Α	Yes	1				
Ethyl toluene	ETE	32	D	D		Α	Yes	1				
Formamide	FAM	10	D	E		Α	Yes	1				
Furfuryl alcohol	FAL	20 <sup>2</sup>	D	E		Α	Yes	1				
Gasoline blending stocks: Alkylates	GAK	33		A/C		Α	Yes	1				
Gasoline blending stocks: Reformates	GRF	33		A/C		A	Yes	<u>·</u> 1				
Gasolines: Automotive (containing not over 4.23 grams lead per	GAT	33	D	С		A	Yes	1				
gallon) Gasolines: Aviation (containing not over 4.86 grams of lead per	GAV	33	D	С		Α	Yes	1				
gallon)												
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α .	Yes	1				
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1				
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1				
Glycerine	GCR	20 <sup>2</sup>	D	E		Α	Yes	1				
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1				
Heptanoic acid	HEP	4	D	E		Α	Yes	1				
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1				
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2				
Heptyl acetate	HPE	34	D	E		Α	Yes	1				
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 <sup>2</sup>	D	B/C		Α	Yes	1				
Hexanoic acid	НХО	4	D	Е		Α	Yes	1				
Hexanol	HXN	20	D	D		Α	Yes	1				
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2				
Hexylene glycol	HXG	20	D	E		Α	Yes	1				
Isophorone	IPH	18 <sup>2</sup>	D	E		Α	Yes	1				
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1				
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		Α	Yes	1				
Kerosene	KRS	33	D	D		A	Yes	1				
Methyl acetate	MTT	34	D	D		A	Yes	1				
Methyl alcohol	MAL	20 2	D	С		A	Yes	1				
	MAC	34	D	D		A	Yes	1				
Methylamyl acetate	MAA	20	D	D		A	Yes	1				
Methylamyl alcohol			D	D		A	Yes	1				
Methyl amyl ketone	MAK MBE	18 41 <sup>2</sup>	D	С				1				
Methyl tert-butyl ether						A	Yes					
Methyl butyl ketone	MBK	18	D	<u>C</u>		A		1				
Methyl butyrate	MBU	34	D	C		Α	Yes	1				
Methyl ethyl ketone	MEK	18 2	D	С		A	Yes	1				
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1				
Methyl isobutyl ketone	MIK	18 <sup>2</sup>	D	С		Α	Yes	1				
Methyl naphthalene (molten)	MNA	32	D	E		Α	Yes	1				
Mineral spirits	MNS	33	D	D		Α	Yes	1				
Myrcene	MRE	30	D	D		Α	Yes	1				
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1				
Naphtha: Petroleum	PTN	33	D	#		Α	Yes	1				
Naphtha: Solvent	NSV	33	D	D		Α	Yes	1				
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1				



Serial #: C1-1000198 Dated:

24-Mar-10

# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: HFL 208

Shipyard: C&C MARINE AND REPAIR CO.

Hull #: 137

Official #: 1225343

Page 6 of 7

Cargo Identification **Conditions of Carriage** Vapor Recovery Chem Compat Sub Hull Tank VCS Special Requirements in 46 CFR App'd Insp. or N) Group No 33 Chapte Grade Category 151 General and Mat'ls of NVM Naphtha: Varnish makers and painters (75%) C Yes Nonane (all isomers), see Alkanes (C6-C9) NAX 31 D D Α Yes Nonene (all isomers) NON 30 D D Α Yes Е Nonyl alcohol (all isomers) D Yes Nonyl phenol NNP 21 D E Α Yes Nonyl phenol poly(4+)ethoxylates NPE 40 D Е Α Octane (all isomers), see Alkanes (C6-C9) OAX 31 D C Α Yes Octanoic acid (all isomers) OAY D F Α Yes 202 Octanol (all isomers) OCX D E Α Yes Octene (all isomers) OTX 30 D C Α Yes 2 Oil. fuel: No. 2 OTW 33 D D/E Α Yes Oil, fuel: No. 2-D D OTD 33 D Α Yes Oil, fuel: No. 4 OFR 33 D D/E Α Yes Oil, fuel: No. 5 33 D D/E Α Yes Oil, fuel: No. 6 osx 33 D Α Yes Oil, misc: Crude D C/D A Yes ODS D Oil, misc: Diesel D/E Yes OGP D Oil, misc: Gas, high pour E Oil, misc: Lubricating OLB D Е Oil. misc: Residual ORL D Е Oil, misc: Turbine OTB D F Yes PTX Pentene (all isomers) 30 D Yes PIO alpha-Pinene 30 D D A Yes beta-Pinene PIP 30 D D Yes Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether PAG 40 D Е Α Yes Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate PAF 34 D Ε Α Yes PLB 30 Е Α Yes Polypropylene glycol PGC D 40 E Yes iso-Propyl acetate IAC 34 D C Α Yes n-Propyl acetate PAT 34 D C Α Yes IPA iso-Propyl alcohol 202 D C Α Yes PAL n-Propyl alcohol 202 D C Α Yes 1 Propylbenzene (all isomers) PBY 32 D D Α Yes 1 iso-Propylcyclohexane **IPX** 31 D Α D Yes Propylene glycol PPG 20<sup>2</sup> D E A Yes Propylene glycol methyl ether acetate PGN 34 D D Α Yes Propylene tetramer PTT 30 D D Α Yes Sulfolane D Ε Α Yes Tetraethylene glyco Е Α Yes Tetrahydronaphthalene THN D E Α Yes TOL 32 D С Tricresyl phosphate (less than 1% of the ortho isomer) TCP 34 D Ε Α Triethylbenzene TEB 32 D F A Triethylene glycol TEG 40 D E Α Triethyl phosphate TPS 34 D E Α Yes Trimethylbenzene (all isomers) 32 D {D} Α Yes Trixylenyl phosphate TRP 34 Е Α Yes Undecene UDC 30 D D/E A Yes 1-Undecyl alcohol UND 20 D Е Α 1 Xylenes (ortho-, meta-, para-) D D Α 1



### Department of Homeland Security **United States Coast Guard**

Serial #: C1-1000198

24-Mar-10

# Certificate of Inspection

Cargo Authority Attachment

Vessel Name: HFL 208

Official #: 1225343

Page 7 of 7

Shipyard: C&C MARINE

Hull #: 137

#### Explanation of terms & symbols used in the Table:

Cargo Identification

Chem Code

Note 1 Note 2

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual Certain mixtures of cargoes may not have a CHRIS Code assigned

Compatability Group No.

(202) 372-1425. See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchanter

Subchapter D Subchapter O

Grade

A. B. C Note 4

Hull Type

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility art. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo

Flammable liquid cargoes, as defined in 46 CFR 30-10.22 Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4)

Not applicable to barges certificated under Subchapter D.

### **Conditions of Carriage**

Tank Group Vapor Recove Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

### **Conditions of Carriage**

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo,

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category: Category 1

The specified cargo's provisional classification for vapor control systems.

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9 This requirement is in addition to the requirements of Category 1.

Category 4

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7 (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.

The cargo has not been evaluated/classified for use in vapor control systems