



BARGE "KIRBY 10073"

ULLAGE TRIM TABLE

| | 1 FT. | | 2 FT. | | 3 FT. | | 4 FT. | | 5 FT. | | 6 FT. | |
|----------|------------|--------------|------------|--------------|------------|--------------|------------|--------------|------------|--------------|------------|--------------|
| | <u>BOW</u> | <u>STERN</u> | <u>BOW</u> | <u>STERN</u> | <u>BOW</u> | <u>STERN</u> | <u>BOW</u> | <u>STERN</u> | <u>BOW</u> | <u>STERN</u> | <u>BOW</u> | <u>STERN</u> |
| 1 CENTER | - 00-3/8 | 00-3/8 | - 00-3/4 | 00-3/4 | - 01-1/8 | 01-1/8 | - 01-1/2 | 01-1/2 | - 01-7/8 | 01-7/8 | - 02-1/8 | 02-1/8 |
| 2 CENTER | - 00-1/8 | 00-1/8 | - 00-1/8 | 00-1/8 | - 00-1/4 | 00-1/4 | - 00-1/4 | 00-1/4 | - 00-3/8 | 00-3/8 | - 00-3/8 | 00-3/8 |
| 3 CENTER | - 00-3/8 | 00-3/8 | - 00-5/8 | 00-5/8 | - 01-0/8 | 01-0/8 | - 01-3/8 | 01-3/8 | - 01-5/8 | 01-5/8 | - 02-0/8 | 02-0/8 |

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 CENTER IS 00-3/4"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 1 CENTER, THE TRIM CORRECTED ULLAGE IS 4'-00 3/4"

LENGTH BETWEEN DRAFT MARKS: 155'-09"

May 6, 2024

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "KIRBY 10073"

3 CENTER
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 15'-10"

Table with columns for gauge height (0 to 19 FT) and rows for capacity increments (0, 1/4, 1/2, 3/4) for each foot. Values represent capacity in barrels.

STRAPPED: 12/10/2008 CL - SW
CALCULATED: 12/10/2008 CL
VERIFIED: 05/06/2024 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 05/2024

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
http://www.pmacorp.net

