

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 24 May 2024 24 May 2025 Expiration Date:

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the ere of inspection is issued under the provision of three 40 officed states 600d, Section 335, it had by the regular certificate of inspection, and shall trace to be valid after one year from the date of inspection, this certificate in no case to be valid after one year from the date of inspection.

IMO Number Official Number Vessel Name Tank Barge 1209535 **KIRBY 10205** Hailing Port Propulsion Horsepower Hull Material WILMINGTON, DE Steel UNITED STATES DWT Length Gross Tons Net Tons Keel Laid Date Place Built Delivery Date R-200.0 R-735 R-735 GALVESTON, TX 03Mar2009 11Dec2008 1-0 **UNITED STATES** Operator Owner KIRBY INLAND MARINE, LP KIRBY INLAND MARINE LP 18350 MARKET ST. 55 WAUGH DR STE 1000 CHANNELVIEW, TX 77530 HOUSTON, TX 77007 **UNITED STATES UNITED STATES** This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators. 0 Oilers 0 Chief Engineers 0 Licensed Mates 0 Masters 0 First Class Pilots 0 First Assistant Engineers 0 Chief Mates 0 Second Assistant Engineers 0 Radio Officers 0 Second Mates 0 Third Assistant Engineers 0 Able Seamen 0 Third Mates 0 Licensed Engineers 0 Ordinary Seamen 0 Master First Class Pilot 0 Qualified Member Engineer 0 Deckhands

0 Mate First Class Pilots In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted fresh water service examination interval in accordance with 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than six months in any twelve month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

OLL NEXT TROE : GIVE	2.01
With this Inspection for Certification having been comp	leted at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine
Inspection, Sector New Orleans certified the vessel, in	all respects, is in conformity with the applicable vessel inspection laws and
the rules and regulations prescribed thereunder.	This sestificate issued by:

te Zone A/P/R Signature J. E. FOTHERGI	HITCH INTO THE REST RECTION
Officer in Charge, Marine Inspection	Ctor New Orleans
Inspection Zone	



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 24 May 2024 Expiration Date: 24 May 2025

Temporary Certificate of Inspection

Vessel Name: KIRBY 10205

Tank Barge Action Plan. Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

31Mar2029

11Jun2019

03Mar2009

Internal Structure

08May2029

08May2024

11Jun2019

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

Flammable/Combustible Liquids and Specified Hazardous Cargoes

Total Capacity

Units

Highest Grade Type

Part151 Regulated

Part153 Regulated Part154 Regulated

11098

Barrels

Yes

Nο

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1	576	13.6
2	672	13.6
3	601	13.6

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
.1	1383	8ft 9in	13.6	R, LBS
II	1383	8ft 9in	13.6	LBS
n	1544	9ft 6in	13.6	R
111	1761	10ft 6in	13.6	R, LBS

Conditions Of Carriage

Only those cargoes named in the barge's Cargo Authority Attachment (CAA) Serial No. C1-0803114 dated 28 October 2008, may be carried and then only in the tanks indicated.

Per 46 CFR 150.130, the Person In Charge of the vessel is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "Compat Group No" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Vapor Control Authorization

In accordance with 46 CFR 39, excluding part 39.40, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter Serial C1-0802337 dated 29 July 2008, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the VCS column of the vessel's CAA.

Stability and Trim

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 24 May 2024 Expiration Date: 24 May 2025

Temporary Certificate of Inspection

Vessel Name: KIRBY 10205

cargo in each tank may exceedn the uniformly loaded tank cargo weight by at most 5 percent.

The maximum design density of cargo which may be filled to the tank top is 8.7 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

١	Cargo ruinto				Estamal Even		
١		Internal Exam			External Exam		
	Tank ld	Previous	Last	Next	Previous	Last	Next
	1	03Mar2009	11Jun2019	11Jun2029	2	-	-
	2	03Mar2009	11Jun2019	11Jun2029	=	¥	
	3	03Mar2009	11Jun2019	11Jun2029	=	at .	7 <u>2</u> 5
				Hydro Test			
	Tank Id	Safety Valves		Previous	Last	Next	
	1	<u>1€</u>			•	6 0	
	2			<u>u</u>	(<u>*</u>		
	3	_		-	% **	#2	

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

40-B

END



Serial #: C1-0803114

28-Oct-08

Dated:

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: Kirby 10205 Official #: 1209535

Shipyard: Southwest Shipyard

Hull #: 9567

46 CFR 151 Tank	Group (Chara	cteris	tics													
Tank Group Information	Cargo I	dentificati	ion		Cargo	1	Tanks		Carg		Environ	mental	Fire	Special Require	ements		
Tnk Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Seg	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp Cont
A #1, #2, #3	13.6	Atmos.	Amb.	1	1ii 2ii	Integral Gravity	PV	Closed	Ш	G-1	NR	NA	Portable	.50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50-	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

 NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identificatio		Conditions of Carriage								
							Vapor Re			2
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	insp. Period
Authorized Subchapter O Cargoes										
Acetonitrile	ATN	37	0	С	Ш	Α	Yes	3	No	G
Acrylonitrile	ACN	15 ²	0	С	11	Α	Yes	4	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	0	E	II	Α	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	Ш	Α	No	N/A	.50-81, .50-86	G
Aminoethylethanolamine	AEE	8	0	Е	Ш	Α	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	III	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	II	Α	No	N/A	No	G
Benzene	BNZ	32	0	С	Ш	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 ²	0	С	111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 ²	0	С	Ш	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	III	Α	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyl methacrylate	ВМН	14	0	D	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	0	С	III	Α	Yes	1	.55-1(h)	G
Camphor oil (light)	СРО	18	0	D	11	Α	No	N/A	No	G
Carbon tetrachloride	CBT	36	0	NA	III	Α	No	N/A	No	G
Caustic potash solution	CPS	5 ²	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G
Caustic soda solution	CSS	5 ²	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G
Chemical Oil (refined, containing phenolics)	COD	21	0	E	11	Α	No	N/A	.50-73	G
Chlorobenzene	CRB	36	0	D	111	Α	Yes	1	No	G
Chloroform	CRF	36	0	NA	III	A	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	0	D	III	A	Yes	1	.50-73	G
Creosote	CCW	21 ²	0	E	III	Α	Yes	1	No	G
Cresols (all isomers)	CRS	21	0	E	III	A	Yes	1	No	G
Cresylate spent caustic	CSC	5	0	NA	III	A	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CRX		0	E	III	A	Yes	1	.55-1(f)	G
Crotonaldehyde	СТА	19 ²	0	С	II	A	Yes	4	.55-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	III	Α	No	N/A	No	G
Cyclohexanone	ССН	18	0	D	III	Α	Yes	1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	0	E	111	A	Yes	1	.56-1 (b)	G
Cyclohexylamine	СНА	7	0	D	III	Α	Yes	1	.56-1(a), (b), (c), (g)	G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	III	A	Yes	1	.50-60, .56-1(b)	G
iso-Decyl acrylate	IAI	14	0	E	III	A	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **Kirby 10205** Official #: 1209535

Page 2 of 7

Shipyard: Southwest Shipyard

Serial #:

Dated:

C1-0803114

28-Oct-08

Cargo Identification							(Condit	tions of Carriage	
							Vapor R	ecovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Dichlorobenzene (all isomers)	DBX	36	0	E	111	Α	Yes	3	.56-1(a), (b)	G
1,1-Dichloroethane	DCH	36	0	С	Ш	Α	Yes	1	No	G
2,2'-Dichloroethyl ether	DEE	41	0	D	П	Α	Yes	1	.55-1(f)	G
Dichloromethane	DCM	36	0	NA	Ш	Α	No	N/A	No	G
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	111	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2	0	Α	III	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 ²	0	Е	Ш	Α	No	N/A	.56-1(a), (b), (c), (g)	G
1,1-Dichloropropane	DPB	36	0	С	Ш	Α	Yes	3	No	G
1,2-Dichloropropane	DPP	36	0	С	III	Α	Yes	3	No	G
1,3-Dichloropropane	DPC	36	0	С	III	Α	Yes	3	No	G
1,3-Dichloropropene	DPU	15	0	D	II	Α	Yes	4	No	G
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	II	Α	Yes	1	No	G
Diethanolamine	DEA	8	0	E	111	Α	Yes	1	.55-1(c)	G
Diethylamine	DEN	7	0	С	Ш	Α	Yes	3	.55-1(c)	G
Diethylenetriamine	DET	72	0	E	III	Α	Yes	1	.55-1(c)	G
Diisobutylamine	DBU	7	0	D	Ш	Α	Yes	3	.55-1(c)	G
Diisopropanolamine	DIP	8	0	E	111	Α	Yes	1	.55-1(c)	G
Diisopropylamine	DIA	7	0	С	11	Α	Yes	3	.55-1(c)	G
N,N-Dimethylacetamide	DAC	10	0	Е	111	Α	Yes	3	.56-1(b)	G
Dimethylethanolamine	DMB	8	0	D	111	Α	Yes	1	.56-1(b), (c)	G
Dimethylformamide	DMF	10	0	D	111	Α	Yes	1	.55-1(e)	G
Di-n-propylamine	DNA	7	0	С	- II	Α	Yes	3	.55-1(c)	G
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	111	Α	No	N/A	.56-1(b)	G
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	11	Α	No	N/A	No	G
Dodecyl phenol	DOL	21	0	Е		Α	No	N/A	.50-73	2
EE Glycol Ether Mixture	EEG	40	0	D	111	Α	No	N/A	No	G
Ethanolamine	MEA	8	0	E	III	Α	Yes	1	.55-1(c)	G
Ethyl acrylate	EAC	14	0	С	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethylamine solution (72% or less)	EAN	7	0	A	11	A	No	N/A	.55-1(b)	G
N-Ethylbutylamine	EBA	7	0	D	III	A	Yes	3	.55-1(b)	G
N-Ethylcyclohexylamine	ECC	7	0	D	III	A	Yes	1	.55-1(b)	G
Ethylene cyanohydrin	ETC	20	0	E	III	Α	Yes	1	No	G
Ethylenediamine	EDA	72	0		111	A	Yes	<u>.</u>	.55-1(c)	G
Ethylene dichloride	EDC	36 ²	0	C	III	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	0	E		A	No	N/A	No	G
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	III	A	Yes	1	No	G
Ethylene glycol propyl ether	EGP	40	0	E	111	A	Yes	<u>·</u>	No	G
2-Ethylhexyl acrylate	EAI	14	0	 E		A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethyl methacrylate	ETM	14	0	D/E	 	A	Yes	2	.50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 ²	0	E	111	A	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E	 	A	Yes	1	.55-1(h)	G
Furfural	FFA	19	0	D	 III	A	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	111	A	No	N/A	No	G
Hexamethylenediamine solution	HMC	7	0	E	111	A	Yes	1	.55-1(c)	G
Hexamethyleneimine	HMI	7	0	C	11	A	Yes	1	.56-1(b), (c)	G
Hydrocarbon 5-9	HFN		0	c	111	A	Yes	1	.50-70(a), .50-81(a), (b)	G
Isoprene	IPR	30	-0	A	111	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Isoprene, Pentadiene mixture	IPN	- 50	-	В	111	A	No	N/A	.50-70(a), .55-1(c)	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 ²	0	D	III	Α	Yes	1	No	G
MOSICYT OXIGE	14100	10 -			- 111		163			



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **Kirby 10205** Official #: 1209535

Page 3 of 7

Shipyard: Southwest Shipyard

C1-0803114

28-Oct-08

Cargo Identificatio	n							Condi	tions of Carriage			
						Vapor Recovery						
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Methyl acrylate	MAM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Methylcyclopentadiene dimer	MCK	30	0	С	111	Α	Yes	1	No	G		
Methyl diethanolamine	MDE	8	0	E	111	Α	Yes	1	.56-1(b), (c)	G		
2-Methyl-5-ethylpyridine	MEP	9	0	E	111	Α	Yes	1	.55-1(e)	G		
Methyl methacrylate	MMM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
2-Methylpyridine	MPR	9	0	D	111	Α	Yes	3	.55-1(c)	G		
alpha-Methylstyrene	MSR	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Morpholine	MPL	72	0	D	III	Α	Yes	1	.55-1(c)	G		
1- or 2-Nitropropane	NPM	42	0	D	111	Α	Yes	1	.50-81	G		
1,3-Pentadiene	PDE	30	0	Α	III	Α	No	N/A	.50-70(a), .50-81	G		
Perchloroethylene	PER	36	0	NA	III	Α	No	N/A	No	G		
Polyethylene polyamines	PEB	72	0	Е	111	Α	Yes	1	.55-1(e)	G		
iso-Propanolamine	MPA	8	0	E	111	Α	Yes	1	.55-1(c)	G		
Propanolamine (iso-, n-)	PAX	8	0	E	111	Α	Yes	1	.56-1(b), (c)	G		
iso-Propylamine	IPP	7	0	Α	11	A	No	N/A	.55-1(c)	G		
Pyridine	PRD	9	0	С	III	A	Yes	1	.55-1(e)	G		
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxi			0		III	Α	No	N/A	.50-73, .55-1(j)	G		
Sodium aluminate solution (45% or less)	SAU	5	0	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G		
Sodium chlorate solution (50% or less)	SDD	0 1,2		NA		A	No	N/A	.50-73	G		
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (b)	G		
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2		NA	111		Yes	1	.50-73, .55-1(b)	G		
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,2		NA	III	A	No	N/A	.50-73, .55-1(b)	G		
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	0	NA	II	Α	No	N/A	.50-73, .55-1(b)	G		
Styrene (crude)	STX		0	D	III	Α	Yes	2	No	G		
Styrene monomer	STY	30	0	D	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	Α	No	N/A	No	G		
Tetraethylenepentamine	TTP	7	0	E	111	Α	Yes	1	.55-1(c)	G		
Tetrahydrofuran	THF	41	0	С	III	Α	Yes	1	.50-70(b)	G		
Toluenediamine	TDA	9	0	E	II	A	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G		
1,2,4-Trichlorobenzene	TCB	36	0	E	III	A	Yes	1	No	G		
1,1,2-Trichloroethane	TCM	36	0	NA	III	A	Yes	1	.50-73, .56-1(a)	G		
Trichloroethylene	TCL	36 ²	0	NA	III	Α	Yes	1	No	G		
1,2,3-Trichloropropane	TCN	36	0	E	II	Ä	Yes	3	.50-73, .56-1(a)	G		
Triethanolamine	TEA	82	0	 E	<u></u> -	A	Yes	1	.55-1(b)	G		
Triethylamine	TEN	7	0		 	A	Yes	3	.55-1(e)	G		
Triethylenetetramine	TET	72	0	E	 	Α	Yes	1	.55-1(b)	G		
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA		A	No	N/A	.56-1(a), (b), (c)	G		
Trisodium phosphate solution	TSP	5	0	NA			No	N/A	.50-73, .56-1(a), (c).	G		
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	 	$\frac{\Delta}{A}$	No	N/A	.56-1(b)	G		
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA		A	No	N/A	.50-73, .56-1(a), (c), (g)	G		
Vinyl acetate	VAM	13	-0	C			Yes	2	.50-70(a), .50-81(a), (b)	G		
Vinyl neodecanate	VND	13	0	E	- 111	A A	No	N/A	.50-70(a), .50-81(a), (b)	G		
Vinyltoluene	VNT	13	0			A	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (G		
		13			- 111		168		(-), (-), (-), (-), (-), (-), (-), (-),			
Subchapter D Cargoes Authorized for Vapor Control												
Acetone	ACT	18 ²	D	С		A	Yes	1				
Acetophenone	ACP	18	D	E		Α	Yes	1				
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		Α	Yes	1				
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1				
Amyl acetate (all isomers)	AEC	34	D	D		Α	Yes	1				



Serial #: C1-0803114

Dated: 28-Oct-08

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **Kirby 10205** Official #: 1209535

Page 4 of 7

Shipyard: Southwest Shipyard

Cargo Identification	Cargo Identification												
					20			Recovery					
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period			
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		Α	Yes	1					
Benzyl alcohol	BAL	21	D	E		Α	Yes	1					
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	Е		Α	Yes	1					
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1					
Butyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1					
Butyl alcohol (n-)	BAN		D	D		Α	Yes	1					
Butyl alcohol (sec-)	BAS		D	С		Α	Yes	1					
Butyl alcohol (tert-)	BAT		D	С		Α	Yes	1					
Butyl benzyl phthalate	BPH	34	D	E		Α	Yes	1					
Butyl toluene	BUE	32	D	D		Α	Yes	1					
Caprolactam solutions	CLS	22	D	E		Α	Yes	1					
Cyclohexane	CHX	31	D	С		Α	Yes	1					
Cyclohexanol	CHN	20	D	E		Α	Yes	1					
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		Α	Yes	2					
p-Cymene	CMP	32	D	D		Α	Yes	1					
iso-Decaldehyde	IDA	19	D	E		Α	Yes	1					
n-Decaldehyde	DAL	19	D	E		A	Yes	1					
Decene	DCE	30	D	D		A	Yes	1					
Decyl alcohol (all isomers)	DAX	20 ²	D	E		Α	Yes	1					
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		Α	Yes	1					
Diacetone alcohol	DAA	20 ²				A	Yes	1					
ortho-Dibutyl phthalate	DPA	34		E		A	Yes	1					
Diethylbenzene	DEB	32				A	Yes	1					
Diethylene glycol	DEG	40 ²	D	E		A	Yes	1					
Diisobutylene	DBL	30	D	C		A	Yes	1					
Diisobutyl ketone	DIK	18		D		A	Yes	1					
Diisopropylbenzene (all isomers)	DIX	32		E		A	Yes	1					
Dimethyl phthalate	DTL	34		E		A	Yes	1					
Dioctyl phthalate	DOP	34		Ē		A	Yes	1					
	DPN	30		D		A	Yes	1					
Dipentene	DIL	32	D	D/E		A	Yes	1					
Diphenyl Diphenyl Albert History	DDO	33	D	E		A	Yes	1					
Diphenyl, Diphenyl ether mixtures	DPE												
Diphenyl ether		41	D D	{E}		Α	Yes	1					
Dipropylene glycol	DPG	40		E		Α	Yes	1					
Distillates: Flashed feed stocks	DFF	33	D	E		A .	Yes	1					
Distillates: Straight run	DSR	33	D	E		Α	Yes	1					
Dodecene (all isomers)	DOZ	30	D	D		_ A	Yes	1					
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		A	Yes	1					
2-Ethoxyethyl acetate	EEA	34	D	D		A	Yes	1					
Ethoxy triglycol (crude)	ETG	40	D	E		Α	Yes	1					
Ethyl acetate	ETA	34	D	С		Α	Yes	1					
Ethyl acetoacetate	EAA	34	D	E		Α	Yes	1					
Ethyl alcohol	EAL	20 ²	D	С		Α	Yes	1					
Ethylbenzene	ETB	32		С		A	Yes	1					
Ethyl butanol	EBT	20	D	D		A	Yes	1					
Ethyl tert-butyl ether	EBE	41	D	С		A	Yes	1					
Ethyl butyrate	EBR	34	D	D		Α	Yes	1					
Ethyl cyclohexane	ECY	31	D	D		A	Yes	. 1					
Ethylene glycol	EGL	20 ²	D	E		Α	Yes	1					



Certificate of Inspection Cargo Authority Attachment

Vessel Name: Kirby 10205 Official #: 1209535

Page 5 of 7

Shipyard: Southwest Shipyard

Serial #: C1-0803114

28-Oct-08

Dated:

Cargo Identification	on				- 1			Condi	tions of Carriage	
								Recovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd	VCS	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Ethylene glycol butyl ether acetate	EMA	34	D	E		Α	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	Е		Α	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1		
2-Ethylhexanol	EHX	20	D	E		Α	Yes	1		-
Ethyl propionate	EPR	34	D	С	-	Α	Yes	1		
Ethyl toluene	ETE	32	D	D		Α	Yes	1	,	
Formamide	FAM	10	D	E		Α	Yes	1		
Furfuryl alcohol	FAL	20 ²	D	E		Α	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		Α	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		A	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1		
Glycerine	GCR	20 ²	D	E		Α	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1		
Heptanoic acid	HEP	4	D	E		Α	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1		
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2		
Heptyl acetate	HPE	34	D	E		Α	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1		
Hexanoic acid	НХО	4	D	E	54	Α	Yes	1		
Hexanol	HXN	20	D	D		Α	Yes	1		
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2		
Hexylene glycol	HXG	20	D	E		A	Yes	1		
Isophorone	IPH	18 ²	D	E		Α	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		A	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1		
Kerosene	KRS	33		D		A	Yes	1		
Methyl acetate	MTT	34	D	D		A	Yes	1		
Methyl alcohol	MAL	20 ²	D	C		Α	Yes	1		
Methylamyl acetate	MAC	34	 D	D		A	Yes	1		
Methylamyl alcohol	MAA	20		D		A	Yes	1		
Methyl amyl ketone	MAK	18	D	D	-	A	Yes	1		
Methyl tert-butyl ether	MBE	412		C		A	Yes	1		
Methyl butyl ketone	MBK	18		C		A	Yes	1		
Methyl butyrate	MBU	34		c		A	Yes	1		
Methyl ethyl ketone	MEK	18 ²	D	C		A	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1		
Methyl isobutyl ketone	MIK	18 ²		C		A	Yes	1		
Methyl naphthalene (molten)	MNA	32		E		A	Yes	1		
Mineral spirits	MNS	33	D	D		A	Yes	1		
Myrcene	MRE	30	D	D			Yes	1		
Naphtha: Heavy	NAG	33	D	#		Ā	Yes	1		
Naphtha: Petroleum	PTN	33	D	#		Ā	Yes	. 1		
Naphtha: Solvent	NSV	33		<i>#</i>			Yes	1		
Naphtha: Stoddard solvent	NSS	33		D		A	Yes	1		
riaphina. Stoudard Solvent	NOO	JJ	U	ט		^	1 62	1		



Serial #: C1-0803114

28-Oct-08

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: Kirby 10205 Official #: 1209535

Page 6 of 7

Shipyard: Southwest Shipyard

Cargo Identification			Condi	tions of Carriage						
A 9 4								Recovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Naphtha: Varnish makers and painters (75%)	NVM	33	D	С		Α	Yes	1		
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1		
Nonene (all isomers)	NON	30	D	D		Α	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		Α	Yes	1		
Nonyl phenol	NNP	21	D	Е		Α	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		Α	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		Α	Yes	1		
Octanoic acid (all isomers)	OAY	4	D	E		Α	Yes	1		
Octanol (all isomers)	OCX	20 ²	D	Е		Α	Yes	1		
Octene (all isomers)	OTX	30	D	С		Α	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		Α	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 6	DSX	33	D	E		Α	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		A	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1		
Oil, misc: Residual	ORL	33				A	Yes	1		
Oil, misc: Turbine	ОТВ	33	D	E		A	Yes	1		
alpha-Pinene	PIO	30		D		A	Yes	1		
beta-Pinene	PIP	30	D	D		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A	Yes	1		
Polybutene	PLB	30	D	E			Yes	1		
Polypropylene glycol	PGC	40	D	E		A	Yes	1		
iso-Propyl acetate	IAC	34		C		A	Yes	1		
	PAT	34	D	C		A	Yes	1		
n-Propyl acetate	IPA	20 ²	D	C		A	Yes	1		
iso-Propyl alcohol	PAL	20 2	D	С		A	Yes	1		
n-Propyl alcohol	PBY	32	D	D						
Propylbenzene (all isomers)	IPX	31	D	D		A	Yes	1		
iso-Propylcyclohexane						Α	Yes	1		
Propylene glycol	PPG	20 2	D	E		A	Yes	1		
Propylene glycol methyl ether acetate	PGN	34		D		A	Yes	1		
Propylene tetramer	PTT	30		D		Α	Yes	1		
Sulfolane	SFL	39	D	E		A	Yes	1		
Tetraethylene glycol	TTG	40	D	E		A	Yes	11		
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1		
Toluene	TOL	32	D	С		Α	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		A	Yes	1		
Triethylbenzene	TEB	32	D	E		Α	Yes	1		
Triethylene glycol	TEG	40	D	E		Α	Yes	1		
Triethyl phosphate	TPS	34	D	E		A	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		A	Yes	1		
Trixylenyl phosphate	TRP	34		E		Α	Yes	1		
Undecene	UDC	30	D	D/E		Α	Yes	1		
1-Undecyl alcohol	UND	20	D	E		Α	Yes	1		
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	11		



Serial #: C1-0803114

28-Oct-08

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: Kirby 10205 Official #: 1209535

Page 7 of 7

Shipyard: Southwest Ship Hull #: 9567

Explanation of terms & symbols used in the Table:

Cargo Identification

Subchapter O Note 3

Grade

Hull Type

NA

Name The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

Chem Code The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual.

Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No. The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables,

Note 1

and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone Note 2

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Subchapter D

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1. Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of A. B. C Flammable liquid cargoes, as defined in 46 CFR 30-10.22

Combustible liquid cargoes, as defined in 46 CFR 30-10.15. The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Note 4

NA Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo Vapor Recover

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified carg Approved (Y or N)

No. The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Tank Group The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Vapor Recovery Approved (Y or N) Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category: The specified cargo's provisional classification for vapor control systems.

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 Category 1

and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine

Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester. Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.

Category 4 (Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3,

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air Category 5

mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. Category 6

(High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5. Category 7

The cargo has not been evaluated/classified for use in vapor control systems.