



BARGE "KIRBY 10206"

ULLAGE TRIM TABLE

FORMERLY "HFL 212"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 CENTER	- 00-1/8	00-1/8	- 00-1/4	00-1/4	- 00-1/4	00-1/4	- 00-3/8	00-3/8	- 00-1/2	00-1/2	- 00-5/8	00-5/8
2 CENTER	00-2/8	- 00-2/8	00-3/8	- 00-3/8	00-5/8	- 00-5/8	00-3/4	- 00-3/4	01-0/8	- 01-0/8	01-1/8	- 01-1/8
3 CENTER	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 CENTER IS 00-1/4"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 1 CENTER, THE TRIM CORRECTED INNAGE IS 4'-00 1/4"

LENGTH BETWEEN DRAFT MARKS: 160'-06"

May 28, 2024

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "KIRBY 10206"

1 CENTER
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FORMERLY "HFL 212"

GAUGE HEIGHT 15'-06 1/4"

Table with columns for gauge height (0 to 19 FT.) and rows for barge height (0 to 11 FT.). Each cell contains capacity values for 1/4, 1/2, and 3/4 increments.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 02/19/2009 CL - SW
CALCULATED: 02/19/2009 CL
VERIFIED: 05/28/2024 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 05/2024

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
http://www.pmacorp.net



