

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 28 Sep 2020 **Expiration Date:** 28 Sep 2021

Length

R-200.0

Temporary Certificate of Inspection

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the

receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection. Vessel Name Official Number IMO Number Call Sign KIRBY 10213 1226073 Tank Barge Hailing Port Hull Material Horsepower WILMINGTON, DE Propulsion Steel **UNITED STATES** Place Built Delivery Date Keel Laid Date Gross Tons Net Tons DWT ASHLAND CITY, TN R-705 R-705 19Aug2010 22Jul2010 **UNITED STATES** Operator KIRBY INLAND MARINE LP KIRBY INLAND MARINE, LP 55 WAUGH DR STE 1000 18350 MARKET ST. HOUSTON, TX 77007 CHANNELVIEW, TX 77530 UNITED STATES UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Chief Mates

0 First Class Pilots

0 First Assistant Engineers

0 Second Mates

0 Radio Officers

0 Second Assistant Engineers

0 Third Mates

0 Able Seamen

0 Third Assistant Engineers

0 Master First Class Pilot

0 Ordinary Seamen

0 Licensed Engineers

0 Mate First Class Pilots

0 Deckhands

0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, coastwise, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR Table 31.10-21(b); if this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine Inspection, Sector New Orleans certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	Annual/Peri	iodic/Re-Inspe	ction	This certificate is used by:
Date	Zone	A/P/R	Signature	M.N. COPHRAN COMMANDER, by direction
				Officer in charge, Marite Inspection Sector New Orleans
				Inspection Zone



United States of America **Department of Homeland Security United States Coast Guard**

Certification Date: 28 Sep 2020 **Expiration Date:** 28 Sep 2021

Temporary Certificate of Inspection

Vessel Name: KIRBY 10213

Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-

---Hull Exams---

Exam Type Next Exam Last Exam Prior Exam DryDock 15Sep2025 15Sep2015 3 19Aug2010 Internal Structure 30Sep2025 18Sep2020 15Sep2015

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

GRADE "A" AND LOWER, SPECIFIED HAZARDOUS CARGOES.

Total Capacity Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

10300

Barrels

No

No

Hazardous Bulk Solids Authority

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1	585	13.57
2	538	13.57
3	535	13.57

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
II .	1471	9ft 0in	10.83	R, LBS, LC 0-12
11	1417	8ft 9in	11.74	R, LBS, LC 0-12
II	1364	8ft 6in	12.41	R, LBS, LC 0-12
11	1310	8ft 3in	12.99	R, LBS, LC 0-12
11	1256	8ft 0in	13.57	R, LBS, LC 0-12
Ш	1579	9ft 6in	10.41	R, LBS, LC 0-12
111	1525	9ft 3in	11.87	R, LBS, LC 0-12
III	1471	9ft 0in	12.70	R, LBS, LC 0-12
Ш	1417	8ft 9in	13.57	R, LBS, LC 0-12

Conditions Of Carriage

Only those cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial C1-1104465, dated 07-Dec-2011 may be carried, and then only in the tanks indicated.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR part 197, subpart C are applied.

Per 46 CFR 150.130, the Person in Charge of the vessel is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables and appendices of 46 CFR 150 in conjunction with the compatibility group numbers from the "COMPAT GRP" column listed in the vessel's CAA.

^{*}Conditions of Carriage*



United States of America Department of Homeland Security **United States Coast Guard**

Certification Date: 28 Sep 2020 **Expiration Date:** 28 Sep 2021

Temporary Certificate of Inspection

Vessel Name: KIRBY 10213

Vapor Control Authorization

In accordance with 46 CFR part 39, excluding part 39.40, this vessel's vapor control system has been inspected to the plans approved by marine safety center letter serial #C1-1104465, dated 07-Dec-2011 and found acceptable for collection of bulk liquid cargo vapors annotated with "yes" in the CAA's VCS column.

Stability and Trim

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of cargo in each tank may exceed the uniformly loaded tank cargo weight by at most 5 percent.

The maximum design density of cargo which may be filled to the tank top is 10.00 lbs/gal. Cargoes with higher densities, up to 13.57 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

Per D8 (dp) policy letter 01-2007 dated March 5, 2007, this tank barge is participating in the Eighth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to Sector Houston-Galveston OCMI.

--- Inspection Status ---

Fuel Tanks

Internal	Examinations
internai	Examinations

Tank ID Previous Last Next Forward main deck 19Aug2010 15Sep2015

Cargo Tanks

	l.						
	Tarakalı	Internal Exam			External Exan	1	
I	Tank Id	Previous	Last	Next	Previous	Last	Next
	1	19Aug2010	15Sep2015	15Sep2025	·	·	:70
	2	19Aug2010	15Sep2015	15Sep2025		5 7 8	-
	3	19Aug2010	15Sep2015	15Sep2025	*]* \$40	9
				Hydro Test			
	Tank ld	Safety Valves		Previous	Last	Next	
	1	ě		(4)	19Aug2010	=	
	2	ie.		30	19Aug2010	e.	
	3	2		*	19Aug2010	1.75	

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity Class Type 2 B-II

END



C1-1104465

07-Dec-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Shipyard: Trinity Ashland City

Hull #: 4732

46 CFR 151 Tank	Group (Charac	teris	ics													
Tank Group Information	Cargo l	dentificati	on		Cargo		Tanks		Carg Tran		Enviror Control	nmental	Fire	Special Requires	ments		
Trik Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Sec	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp Cont
A #1C, #2C, #3C	13.6	Atmos.	Elev	u	1fi 2fi	integral Gravity	PV	Closed	11	G-1	NR	NA	Portable	.50-70(a), .50-	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	Yes

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identificatio	n						Conditions of Carriage					
							Vapor Re	<u>-</u>				
Name	Chem Code	Compat Group No	Sub Chapter	Grada	Hull Type	Tank Group	(Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Authorized Subchapter O Cargoes												
Acetonitrile	ATN	37	0	Ç	III	Α	Yes	3	No	G		
Acrylonitrile	ACN	15 ²	0	С	n	A	Yes	4	.\$0-70(a), .55-1(e)	G		
Adiponitrile	ADN	37	0	E	l)	Α	Yes	1	No	G		
Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	UI	Α	No	N/A	.50-81, .50-86	G		
Aminoethylethanolamine	AEE	8	0	E	111	Α	Yes	1	.55-1(b)	G		
Ammonium bisulfite solution (70% or less)	ABX	43 2	0	NA	131	Α	No	N/A	.50-73, .58-1(a), (b), (c)	G		
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	IE	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G		
Anthracene oil (Coal tar fraction)	AHO	33	Q	NA	II	Α	No	N/A	No	G		
Benzene	BNZ	32	0	С	fΠ	A	Yes	1	.50-60	G		
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 ²	0	С	tii	Α	Yes	1	.50-60	G		
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 ²	0	С	(II)	Α	Yes	1	.50-80, .58-1(b), (d), (f), (g)	G		
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	втх	32	0	B/C	Ш	Α	Yes	1	.50-80	G		
Butyl acrylate (all isomers)	BAR	14	0	D	101	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Butyl methacrylate	BMH	14	0	D	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Butyraldehyde (all isomers)	BAE	19	0	С		Α	Yes	1	.55-1(h)	G		
Camphor oil (light)	CPO	18	0	D	П	Α	No	N/A	No	G		
Carbon tetrachloride	CBT	36	0	NA	Ш	A	No	N/A	No	G		
Caustic potash solution	CPS	5 ²	0	NA	#11	Α	No	N/A	.50-73, .55-1@	G		
Caustic soda solution	CSS	5 ²	0	NA	111	Α	No	N/A	.50-73, .55-1 ()	G		
Chemical Oil (refined, containing phenolics)	COD	21	0	E	[]	A	No	N/A	.50-73	G		
Chlorobenzene	CRB	36	0	D	111	A	Yes	1	No	G		
Chloroform	CRF	36	0	NA	III	A	Yes	3	No	G		
Coal tar naphtha solvent	NCT	33	0	D	III	Α	Yes	1	.50-73	G		
Coal tar pitch (molten)	CTP	33	0	E	111	A	No	N/A	.50-73	G		
Creosote	CCW	21 ²	0	E	EED	Α	Yes	1	No	G		
Cresols (all isomers)	CRS	21	0	E	111	Α	Yes	1	No	G		
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)	G		
Cresylic acid tar	CRX		0	E	III	Α	Yes	1	.55-1(f)	G		
Crotonaldehyde	CTA	19 ²	0	С	Ħ	A	Yes	4	.55-1(h)	G		
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrotein)	CHG		o	С	III	A	No	N/A	Ng	G		
Cyclohexanone	CCH	18	0	D	III	Α	Yes	1	.56-1(a), (b)	G		
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	0	Е	Ш	A	Yes	1	.58-1 (b)	G		



Serial #: C1-1104465 Dated: 07-Dec-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Page 2 of 8

Shipyard: Trinity Ashland City

Cargo Identificatio	n					Conditions of Carriage						
		T*************************************				Vapor Recovery						
Name	Chem Code	Compat Group No	Sub Chepter	Grade	Huli Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	insp. Period		
Cyclohexylamine	CHA	7	0	D	I))	Α	Yes	1	.58-1(a), (b), (c), (g)	G		
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	III	A	Yes	1	.50-60, .56-1(b)	G		
iso-Decyl acrylate	JAI	14	0	E	DF	Α	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G		
Dichlorobenzene (all isomers)	DBX	36	0	E	Ш	Α	Yes	3	.56-1 (a), (b)	G		
1,1-Dichloroethane	DCH	36	0	С	Ш	Α	Yes	1	No	G		
2,2'-Dichloroethyl ether	DEE	41	0	D	ll l	Α	Yes	1	.55-1(f)	G		
Dichloromethane	DCM	36	0	NA	11)	Α	Yes	5	No	G		
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	111	Α	No	N/A	.56-1(a), (b), (c), (g)	G		
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2	0	Α	Ш	Α	No	N/A	.58-1(a), (b), (c), (g)	G		
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 ²	0	E	111	Α	No	N/A	.58-1(a), (b), (c), (g)	G		
1,1-Dichloropropane	DPB	36	0	C	Ш	Α	Yes	3	No	G		
1,2-Dichloropropane	DPP	36	0	С	Jil	Α	Yes	3	No	G		
1,3-Dichloropropane	DPC	36	0	С	Ш	Α	Yes	3	No	G		
1,3-Dichloropropene	DPU	15	0	D	H	Α	Yes	4	No	G		
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	H	Α	Yes	1	No	G		
Diethanolamine	DEA	8	0	E	III	A	Yes	1	.55-1(c)	G		
Diethylamine	DEN	7	0	С	DI.	A	Yes	3	.55-1(c)	G		
Diethylenetriamine	DET	72	0	E	III	Α	Yes	1	.55-1(c)	G		
Diisobutylamine	DBU	7	0		111	Ä	Yes	3	.55-1(c)	G		
Diisopropanolamine	DIP	8	0	E	ill .	Α	Yes	1	.55-1(c)	G		
Diisopropylamine	DIA	- 7	0	c	il.	A	Yes	3	.55-1(c)	G		
N,N-Dimethylacetamide	DAC	10	-	E		 A	Yes	3	.58-1(b)	G		
Dimethylethanolamine	DMB		0			A	Yes	1	.\$8-1(b), (c)	G		
Dimethylformamide	DMF	10	0	D	111		Yes	1	.55-1(e)	G		
Di-n-propylamine	DNA	7	0	C	<u> </u>	A	Yes	3	.55-1(c)	G		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	<u></u>	A	No	N/A	.58-1(b)	G		
Dodecyldinhearlylatistic, retradecyldinhearlylatistic mixture Dodecyl diphenyl ether disulfonate solution	DOS	43	-	#	<u></u>		No	N/A	No	G		
	EEG	40	-	<u>"</u>	 HI	A	No	N/A	No	G		
EE Glycol Ether Mixture Ethanolamine	MEA	8	-	E	111	A	Yes	1	.55-1(c)			
	EAC	14	0	c	111	A	Yes	2	.50-70(a), .50-81(a), (b)	G		
Ethyl acrylate	EAN	7		Ā	<u>'''</u>		Yes	- 6	.55-1(b)			
Ethylamine solution (72% or less)	EBA	7	0	D	111	Ā	Yes	3	.\$5-1(b)	G		
N-Ethylbutylamine	ECC	7	- 0	<u> </u>			Yes	1	.55-1(b)	G		
N-Ethylcyclohexylamine	ETC	20	- 0	E	111	A	Yes	<u>'</u>	No	G		
Ethylene cyanohydrin	EDA	72	0	D	111	- A	Yes	1	.55-1(c)	G		
Ethylenediamine		36 ²	0	C	111		Yes	1	No	G		
Ethylene dichloride	EDC							N/A	No			
Ethylene glycol hexyl ether	EGH		0	E	(tt	A	No		No	G		
Ethylene glycol monoalkyl ethers	EGC		0	D/E		A	Yes	1	No	G		
Ethylene glycol propyl ether	EGP	40	0	<u>E</u>	<u> </u>	A	Yes	1	.50-70(a), .50-81(a), (b)	G		
2-Ethylhexyl acrylate	EAI	14	0	E		A	Yes	2	50-70(a)	<u> </u>		
Ethyl methacrylate	ETM		0	D/E	111	A	Yes	2				
2-Ethyl-3-propylacrolein	EPA	19 2		E	116	<u> </u>	Yes	1	No.			
Formaldehyde solution (37% to 50%)	FMS			D/E	- 111	<u>A</u>	Yes		.\$5-1(h)	G		
Furfural	FFA	19	0	D	111	<u> </u>	Yes	1	.55-1(h)	G		
Glutaraldehyde solution (50% or less)	GTA		0	NA	111	Α	No	N/A		G		
Hexamethylenediamine solution	HMC		0	E	18	A	Yes		.55-1(c)	G		
Hexamethyleneimine	HMI	7_	0	C	11	Α	Yes		.58-1(b), (c)	G.		
Hydrocarbon 5-9	HFN		0	С	III	A	Yes	1	.50-70(a), .50-81(a), (b)	G		



Certificate of Inspection


Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Page 3 of 8

Shipyard: Trinity Ashland City

Cargo Identification	1							Condi	tions of Carriage	
			[Vapor F	Recovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Huli Type	Tank Group	App'd (Y or N)	VCS Calegory	Special Requirements in 46 CFR 151 General and Mat's of	Insp. Perk
soprene	IPR	30	0	Α	HI	Α	Yes	7	.50-70(a), .50-81(a), (b)	G
soprene, Pentadiene mixture	IPN		0	В	- III	Α	No	N/A	.50-70(a), .55-1(c)	G
Kraft pulping liquors (free alkati content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	III	Α	No	N/A	.50-73, .58-1(a), (c), (g)	G
Mesityl oxide	MSO	18 2	0	D	111	Α	Yes	1	No	G
Methyl acrylate	MAM	14	0	С	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Methylcyclopentadiene dimer	MCK	30	0	C	111	Α	Yes	1	No	G
Methyl diethanolamine	MDE	8	0	E	- 111	Α	Yes	1	.58-1 (b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	0	Е	till	Α	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	0	С	H	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	0	D	III	Α	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	7 2	0	Đ	Ħ	Α	Yes	1	.55-1(c)	G
Vitroethane	NTE	42	0	D)1	Α	No	N/A	, 50-81 , .58-1(b)	G
I- or 2-Nitropropane	NPM	42	0	D	10	Α	Yes	1	.50-81	G
1,3-Pentadiene	PDE	30	0	Α	10	Α	Yes	7	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	111	Α	No	N/A	No	G
Phthalic anhydride (molten)	PAN	11	0	Ε	101	Α	Yes	1	No	G
Polyethylene polyamines	PEB	7 ²	0	E	101	Α	Yes	1	.55-1(e)	G
so-Propanolamine	MPA	8	0	E	111	Α	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	0	E	111	Α	Yes	1	.58-1(b), (c)	G
so-Propylamine	IPP	. 7	0	Α	¥I	Α	Yes	5	.55-1 (c)	G
Pyridine	PRD	9	0	С	811	Α	Yes	1	,SS-1(o)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide	e) SAP		0		(1)	Α	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	0	NA	())	Α	No	N/A	.50-73, .58-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDĐ	0 1,2	0	NA	IH	Α	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	111	Α	No	N/A	.50-73, .58-1(a), (b)	G
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2	0	NA	H	Α	Yes	1	.50-73, .55-1(b)	G
Sodium suffide, hydrosulfide solution (H2S greater than 15 ppm but ess than 200 ppm)	SSI	0 1,2	0	NA	IA	Α	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	0	NA	lì	Α	No	N/A	.50-73, .55-1(b)	G
Styrene (crude)	STX		0	D	111	Α	Yes	2	No	G
Styrene monomer	STY	30	0	D	111	Α	Yes	2	,50-70(a), ,50-81(a), (b)	G
i,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	Α	No	N/A	No	G
l'etraethylenepentamine	TTP	7	0	Ę	113	Α	Yes	1	.55-1(c)	G
l'etrahydrofuran	THF	41	0	C		Α	Yes	1	,50-70(b)	G
folvenediamine	TDA	9	0	E	11	Α	No	N/A	.50-73, .58-1(a), (b), (c), (g)	G
1,2,4-Trichlorobenzene	TCB	36	0	Ε	111	Α	Yes	1	No	G
,1,2-Trichloroethane	TCM	36	0	NA	111	Α	Yes	1	.50-73, .58-1(a)	G
Frichloroethylene	TCL	36 ²	0	NA	III	Α	Yes	1	No	G
1,2,3-Trichloropropane	TCN	36	0	Ę	l1	Α	Yes	3	.50-73, .58-1(e)	G
Friethanolamine	TEA	g 2	0	E	111	Α	Yes	1	.55-1(b)	G
Friethylamine	TEN	7	0	С	I1	Α	Yes	3	,53-1(e)	G
riethylenetetramine	TET	72	0	E	111	Α	Yes	1	.55-1(b)	G
riphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	HI	Α	No	N/A	.59-1(a), (b), (c)	G
Frisodium phosphate solution	TSP	5	0	NA	Ш	Α	No	N/A	.50-73, .56-1(e), (c).	G
Jrea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	111	Α	No	N/A	.58-1(b)	G
rea, Announce made solution (Containing more than 270 Mas)										
/anillin black liquor (free alkali content, 3% or more).	VBL.	5	0	NA	111	Α	No	N/A	.50-73, .56-1(s), (c), (g)	G







Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Page 4 of 8

Shipyard: Trinity Ashland City

Cargo Identification	n							Condi	tions of Carriage	
	\		0.1		14.41	Tank		ecovery	Sansial Sansianments in 46 CED	
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Vinyl neodecanate	VND	13	0	E	[]]	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	0	D	IJŧ	Α	Yes	2	.50-70(a), .50-81, .58-1(a), (b), (c), (G
Subchapter D Cargoes Authorized for Vapor Contro	ol									
Acetone	ACT	18 ²	Đ	С		Α	Yes	1		
Acetophenone	ACP	18	Đ	E		Α	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		Α	Yes	1		
Alcohol(C8-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	11		
Amyl acetate (all isomers)	AEC	34	D	D		Α	Yes	11	<u> </u>	
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		Α	Yes	1		
Benzyl alcohol	BAL	21	D	<u>E</u>		Α	Yes	11		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E,		Α	Yes	1		
Butyl acetate (all isomers)	BAX	34	Đ	D		Α	Yes	1		
Bulyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1		
Butyl alcohol (n-)	BAN	20 ²	D	D		Α	Yes	1		
Butyl alcohot (sec-)	BAS	20 ²	D	С		Α	Yes	1		
Butyl alcohof (tert-)	BAT		D	С		Α	Yes	1		
Butyl benzyl phthalate	BPH	34	D	Ε		Α	Yes	1		
Butyl toluene	BUE	32	D	D		Α	Yes	1		
Caprolactam solutions	CLS	22	D	E		Α	Yes	1		
Cyclohexane	CHX	31	D	С		A	Yes	1		
Cyclohexanol	CHN	20	D	E		Α	Yes	1		
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		Α	Yes	2		
p-Cymene	CMP	32	D	D		Α	Yes	1		
iso-Decaldehyde	IDA	19	D	Ē		Α	Yes	1		
n-Decaldehyde	DAL	19	D	E		Α	Yes	1		
Decene	DCE	30	D	D		Α	Yes	1		
Decyl alcohol (all isomers)	DAX	20 ²	D	E		Α	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		Α	Yes	1		
Diacetone alcohol	DAA	20 ²	D	D		Α	Yes	1		
ortho-Dibutyl phthalate	DPA	34	D	E		Α	Yes	1		
Diethylbenzene	DEB	32	D	D		Α	Yes	1		
Diethylene glycol	DEG	40 ²	D	E		Α	Yes	1		
Diisobutylene	DBL	30	D	Ç		Α	Yes	1		
Diisobutyl ketone	DIK	18	D	D		Α	Yes	1		
Diisopropylbenzene (all isomers)	DIX	32	D	E		Α	Yes	1		
Dimethyl phthalate	DTL	34	D	E		Α	Yes	1		
Dioctyl phthalate	DOP	34	D	Ε		Α	Yes	1		
Dipentene	DPN	30	D	ם		Α	Yes	1		
Diphenyl	DIL	32	D	D/E		Α	Yes	1		
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		Α	Yes	1		
Diphenyl ether	DPE	41	D	{E}		Α	Yes	1		
Dipropylene glycol	DPG	40	Ď	E		Α	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		Α	Yes	1		_
Distillates: Straight run	DSR	33	D	E		Α	Yes	1		
Dodecene (all isomers)	DOZ	30	D	D		Α	Yes	1		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D.	E		A	Yes	1		



07-Dec-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Page 5 of 8

Shipyard: Trinity Ashland City

Huil #: 4732

Cargo Identification	Cargo Identification										
		T						Recovery	tions of Carriage	\top	
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Huli Type	Tank Group	App'd (Y or N)	VCS Calegory	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period	
2-Ethoxyethyl acetate	EEA	34	D	D		Α	Yes	1			
Ethoxy triglycol (crude)	ETG	40	D	E		Α	Yes	1			
Ethyl acetate	ETA	34	D	С		Α	Yes	1			
Ethyl acetoacetate	EAA	34	D	E		Α	Yes	1			
Ethyl alcohol	EAL	20 ²	D	С		Α	Yes	1			
Ethylbenzene	ETB	32	D	C		Α	Yes	1			
Ethyl butanol	EBT	20	D	D		Α	Yes	1			
Ethyl tert-butyl ether	EBE	41	D	C		Α	Yes	1			
Ethyl butyrate	EBR	34	D	D		Α	Yes	1			
Ethyl cyclohexane	ECY	31	D	D		Α	Yes	1			
Ethylene glycol	EGL	20 ²	D	E		Α	Yes	1			
Ethylene glycol butyl ether acetate	EMA	34	D	E		Α	Yes	1			
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1	,		
Ethylene glycol phenyl ether	EPE	40	D	Ε		Α	Yes	1	·		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1			
2-Ethylhexanol	EHX	20	D	E		Α	Yes	1			
Ethyl propionale	EPR	34	D	C		A	Yes	1			
Ethyl toluene	ETE	32	D	D		Α	Yes	1			
Formamide	FAM	10	D	Ε		Α	Yes	1	**		
Furfuryl alcohol	FAL	20 ²	D	E		Α	Yes	1			
Gasoline blending stocks: Alkylates	GAK	33	Đ	A/C		Α	Yes	1			
Gasoline blending stocks: Reformates	GRF	33	Đ	A/C		Α	Yes	1	N-2.		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1			
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1	- 100		
Gasolines: Casinghead (natural)	GCS	33	D	A/C	·	Α	Yes	1			
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1			
Gasolines: Straight run	GSR	33	D	A/C		A	Yes	1			
Glycerine	GCR	20 ²	D	E		Α	Yes	1			
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1			
Heptanoic acid	HEP	4	D	E		Α	Yes	1			
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1			
Heptene (all isomers)	HPX	30	Đ	С		Α	Yes	2			
Heptyl acetate	HPE	34	D	Ε		Α	Yes	1			
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1			
Hexanoic acid	HXO	4	D	E		Α	Yes	1			
Hexanol	HXN	20	D	D		Α	Yes	1			
Hexene (all isomers)	HEX	30	D	Ç		Α	Yes	2			
Hexylene glycol	HXG	20	Ð	E		Α	Yes	1			
Isophorone	IPH	18 ²	D	E		Α	Yes	1			
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1			
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	Ð		Α	Yes	1			
Kerosene	KRS	33	D	D		Α	Yes	1			
Methyl acetate	MTT	34	D	D		A	Yes	1			
Methyl alcohol	MAL	20 ²	D	С		Α	Yes	1		·····	
Methylamyl acetate	MAC	34	D	D	•	Α	Yes	1			
Methylamyl alcohol	MAA	20	D	D		Α	Yes	1			
Methyl anyl ketone	MAK	18	D	D		Α	Yes	1			
2											



Serial #: C1-1104465 Dated: 07-Dec-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213 Official #: 1226073

Page 6 of 8

Shipyard: Trinity Ashland City

Cargo Identificati	Conditions of Carriage									
								Recovery		1
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	(Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'is of	Insp. Period
Methyl tert-butyl ether	MBE	41 ²	D	C		Α	Yes	1		
Methyl butyl ketone	MBK	18	D	С		Α	Yes	11		
Methyl butyrate	MBU	34	D	С		Α	Yes	1		
Methyl ethyl ketone	MEK	18 ²	D	С		Α	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1		
Methyl isobutyl ketone	MIK	18 ²	D	С		A	Yes	1		
Methyl naphthalene (molten)	MNA	32	D	E		Α	Yes	1		
Mineral spirits	MNS	33	D	D		Α	Yes	1		
Myrcene	MRE	30	D	D		Α	Yes	1		
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1		
Naphtha: Petroleum	PTN	33	D	#		Α	Yes	1		
Naphtha: Solvent	NSV	33	D	D		Α	Yes	1		
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1		
Naphtha: Varnish makers and painters (75%)	NVM	33	D	C		Α	Yes	1		
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1		
Nonene (all isomers)	NON	30	D	D		A	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		Α	Yes	1		
Nonyi phenol	NNP	21	D	E		Α	Yes	1		
Nonyi phenoi poly(4+)ethoxylates	NPE	40	D	E		Α	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		Α	Yes	1		
Octanoic acid (all isomers)	OAY	4	D	E		Α	Yes	1		
Octanol (all isomers)	QCX	20 ²	D	E		Α	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Octene (all isomers)	отх	30	D	С		Α	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 2-D.	OTD	33	D	D		Α	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		Α	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		Α	Yes	1	****	
Oil, misc: Gas, high pour	OGP	33	D	E		Α	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		Α	Yes	1		
Oil, misc: Residual	ORL	33	D	E		Α	Yes	1		
Oil, misc: Turbine	ОТВ	33	D	E		Α	Yes	1		
Pentene (all isomers)	PTX	30	D	Α		Α	Yes	5	· · · · · · · · · · · · · · · · · · ·	
n-Pentyl propionale	PPE	34	D	D		A	Yes	1		
alpha-Pinene	PIO	30	D	D		Α	Yes	1		
beta-Pinene	PIP	30	D	D		Α	Yes	1		
Poly(2-8)aikylene glycol monoaikyl(C1-C5) ether	PAG	40	D	E		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C8) ether acetate	PAF	34	D	E		A	Yes	1		
Polybutene	PLB	30	D	E		A	Yes	1		
Polypropylene glycol	PGC	40	D D	E		Α	Yes			
iso-Propyl acetate	IAC	34	D	-			Yes	1		
n-Propyl acetate	PAT	34	D	c		A	Yes	1		
iso-Propyl alcohol	!PA	20 2	D	c		A	Yes	.		
n-Propyl alcohol	PAL	20 ²	D	c		A	Yes	1		
Propylbenzene (all isomers)	PBY	32	-	<u> </u>			Yes	1		
iso-Propylcyclohexane	IPX	31	D	D		_ <u>^</u>	Yes	1		
				بر)			- 69			



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10213

Official #: 1226073

Page 7 of 8

Shipyard: Trinity Ashland City

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Kuli Type	Tank Group	Vapor I App'd	Recovery VCS	Special Requirements in 46 CFR	Insp. Period
Propylene glycol	PPG	20 ²	D	E		Α	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		Α	Yes	1		
Propylene tetramer	PTT	30	D	D		A	Yes	1		
Sulfolane	SFL	39	D	Ę		Α	Yes	1		
Tetraethylene glycol	ΠG	40	D	E		Α	Yes	1		
Tetrahydronaphthalene	THN	32	D	Ę		Α	Yes	1		
Toluene	TOL	32	D	С		Α	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		Α	Yes	1		
Triethylbenzene	TEB	32	D	E		Α	Yes	1		
Triethylene glycol	TEG	40	D	E		Α	Yes	1	······································	
Triethyl phosphate	TPS	34	D	E		Α	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		A	Yes	1		
Trlxylenyl phosphate	TRP	34	D	E		Α	Yes	. 1		
Undecene	UDC	30	D	D/E		Α	Yes	1	•	
1-Undecyl alcohol	UND	20	D	E		Α	Yes	1		
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1	·	



07-Dec-11



Vessel Name: KIRBY 10213 Official #: 1226073

Page 8 of 8

Shipyard: Trinity Ashland

Hull #: 4732

Explanation of terms & symbols used in the Table:

Cargo Identification

Chem Code

Compatability Group No.

Note 1 Note 2

Subchapter Subchapter D

Subchapter O

Grade

A, B, C D, E

Note 4 NA

Hull Type

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N)

Conditions of Carriage Tank Group Vapor Recover Approved (Y or N)

> VCS Category: Category 1

> > Category 2

Category 3 Category 4 Category 5

Category 6 Category 7

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425.

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart. The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.

Certain mixtures of cargoes may not have a CHRIS Code assigned.

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual.

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.
Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "()" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Flammable liquid cargoes, as defined in 46 CFR 30-10.22

Combustible liquid cargoes, as defined in 45 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classifled as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

The specified cargo's provisional classification for vapor control systems.

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo lank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vesset's owner must develop a method of ensuring all VC\$ safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation

(Highly toxic) VCSs for these loxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3,

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.

The cargo has not been evaluated/classified for use in vapor control systems.