

United States of America Department of Homeland Security **United States Coast Guard**

03 Nov 2022 Certification Date: 03 Nov 2023 **Expiration Date:**

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name

Official Number

IMO Number

KIRBY 10240

1241334

Tank Barge

Hailing Port

Hull Material

Horsepower

Propulsion

WILMINGTON, DE

Steel

UNITED STATES

Place Built

Keel Laid Date

Gross Tons

Net Tons

DWT

Length

ASHLAND CITY, TN

Delivery Date

R-705

R-200 0

R-705

1-

1-0

UNITED STATES

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES

Operator

KIRBY INLAND MARINE LP 18350 MARKET ST Channelview, TX 77530 **UNITED STATES**

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Chief Mates

0 First Class Pilots

0 First Assistant Engineers

0 Second Mates 0 Third Mates

0 Radio Officers 0 Able Seamen

0 Second Assistant Engineers 0 Third Assistant Engineers

0 Master First Class Pilot

0 Ordinary Seamen

0 Licensed Engineers

0 Mate First Class Pilots

0 Deckhands

0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Freeport, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Houston-Galveston certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Zone	A/P/R	Signature
	20110	20110 771711

A ----- I/Daria dia /Da Jana

This certificate issued by:

J. A. COLEMAN CDR, USCG, BY DIRECTION

Officer in Charge, Marine Inspection

Houston-Galveston

Inspection Zone



United States of America Department of Homeland Security **United States Coast Guard**

03 Nov 2022 Certification Date: 03 Nov 2023 **Expiration Date:**

Temporary Certificate of Inspection

Vessel Name: KIRBY 10240

This tank barge is participating in the Eighth & Ninth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

31Aug2032

18Oct2022

31Aug2012

Internal Structure

31Aug2027

18Oct2022

03Oct2017

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

10300

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1	763	13.57
2	703	13.57
3	698	13.57

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
Ш	1551	9ft 6in	11.03	R, LBS
III	1497	9ft 3in	12.08	R, LBS
Ш	1443	9ft 0in	12.91	R, LBS
III	1390	8ft 9in	13.57	R, LBS
II	1443	9ft 0in	9.99	R, LBS
II	1390	8ft 9in	11.66	R, LBS
11	1336	8ft 6in	12.41	R, LBS
II	1283	8ft 3in	12.83	R, LBS
II	1229	8ft 0in	13.33	R, LBS
11	1176	7ft 9in	13.57	R, LBS

Conditions Of Carriage

Only those cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial #C1-1202419, dated May 11, 2021, may be carried, and then only in the tanks indicated. When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C are applied.

Per 46 CFR 150.130, the Person in Charge of the vessel is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the compatibility group numbers from the "Compat Group No" column listed in the vessel's CAA.



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 03 Nov 2022 Expiration Date: 03 Nov 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 10240

The maximum design density of cargo which may be filled to the tank top is 9.99 lbs/gal. Cargoes with higher densities, up to 13.57 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

Per 46 CFR 151.10-15(c)(2) the max tank weights reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter O cargoes at shallower drafts, the barge(s) should always be loaded uniformly.

In accordance with 46 CFR Part 39, excluding part 39.4000, this vessel's vapor collection system (VCS) has been inspected to the plans approved by MSC Letter C1-1202419 dated May 11, 2012 and has been found acceptable for the collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column. The VCS system has been approved with a pressure side of 6 psig P/V valve with Coast Guard Approval 162.017/167/4. The cargo tank top is suitable for a maximum allowable working pressure (MAWP) of 6.5 psig.

--- Inspection Status ---

Fuel Tanks

Internal Examinations

Tank ID	Previous	Last	Next
Forward machinery [Deck -	31Aug2012	

Cargo Tanks

	Internal Exam			External Exam	1	
Tank Id	Previous	Last	Next	Previous	Last	Next
1	31Aug2012	18Oct2022	31Aug2032	03Oct2017	18Oct2022	31Aug2027
2	31Aug2012	18Oct2022	31Aug2032	03Oct2017	18Oct2022	31Aug2027
3	31Aug2012	18Oct2022	31Aug2032	03Oct2017	18Oct2022	31Aug2027
			Hydro Test			
Tank Id	Safety Valves		Previous	Last	Next	
1			3 2	31Aug2012	-	
2			-	31Aug2012	≅	
3	-		o .	31Aug2012		

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity Class Type 2 40-B

END

^{*}Vapor Control Authorization*



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240 Shipyard: Trinity Marine, Ashland

City

Dated:

11-May-12

Official #: 1241334 Hull #: 4842

46 CFR 151 Tank Group Characteristics

Tank Group Information	Cargo I	dentificati	on		C		Tanks		Carg		Enviror Control		Fire	Special Require	ments		
Tnk Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Cargo Seg Tank	-	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp Cont
A #1, #2, #3	13.6	Atmos.	Elev	II	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	.50-70(a), .50-	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

List of Authorized Cargoes

Name Code Group Not Chapter Cargo Code	Cargo Identificatio	Cargo Identification									
Name Code Group Not Chapter Cargo Code								Vapor R	ecovery		
Acetonitritie	Name				Grade						Insp. Period
Acrylonitrile	Authorized Subchapter O Cargoes										
Adjointifile	Acetonitrile	ATN	37	0	С	Ш	Α	Yes	3	No	G
Alkyl(C7-C9) nitrates	Acrylonitrile	ACN	15 ²	0	С	П	Α	Yes	4	.50-70(a), .55-1(e)	G
Ammonity planchage AEE 8 0 E III A No N/A 56-16). (b). (c) Ammonium bisulfite solution (70% or less) ABX 43 2 0 NA III A No N/A 56-16). (b). (c) Ammonium hydroxide (28% or less NH3) AMH 6 0 NA III A No N/A No N/A No Ammonium hydroxide (28% or less NH3) AMH 6 0 NA III A No N/A No N/A Ammonium hydroxide (28% or less NH3) AMH 6 0 NA III A No N/A No N/A Ammonium hydroxide (28% or less NH3) AMH 6 0 NA III A No N/A No No No Benzene oil (Coal tar fraction) AHO 33 0 C III A No N/A No No No No Benzene or hydrocarbon mixtures (having 10% Benzene or more) BHB 32 0 C III A Yes 1 50-60 Benzene of hydrocarbon mixtures (containing Acetylene and 10% BHB 32 0 C III A Yes 1 50-60 Se-16). (d). (f). (g) Benzene of more) BTX 32 0 BIC III A Yes 1 50-60 Se-16). (d). (f). (g) Butyl acrylate (all isomers) BAR 14 0 D III A Yes 1 50-60 Se-16). (d). (f). (g) Butyl adehyde (all isomers) BAR 14 0 D III A Yes 1 50-60 Se-16). (d) (f). (g) Butyl adehyde (all isomers) BAE 19 0 C III A Yes 1 50-60 Se-16). (d) (f). (g) Butyl adehyde (all isomers) BAE 19 0 C III A Yes 1 50-60 Se-16). (d) (f). (g) Carbon tetrachloride CBT 36 0 NA III A No N/A No NO N/A No Caustic potas bolution CPS 5 0 NA III A No N/A No NO N/A No Caustic potas bolution CPS 5 0 NA III A No N/A No N/A No NO N/A No NO NO NO NO NO NO NO	Adiponitrile	ADN	37	0	Е	П	Α	Yes	1	No	G
Ammonium bisulfite solution (70% or less) ABX 43 2 O NA III A NO N/A 50-73, 56-1(a), (b), (c) (c) Ammonium hydroxide (28% or less NH3) AMH 6 O NA III A NO N/A 50-74, 56-1(a), (b), (c), (d), (d), (d), (d), (d), (d), (d), (d	Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	Ш	Α	No	N/A	.50-81, .50-86	G
Ammonium hydroxide (28% or less NH3) AMH 6 0 NA III A NO N/A 56-1(a), (b), (c), (f), (g) Anthracene oil (Coal tar fraction) AHO 33 0 NA II A NO N/A N/A NO N/A	Aminoethylethanolamine	AEE	8	0	Е	Ш	Α	Yes	1	.55-1(b)	G
Anthracene oil (Coal tar fraction) AHO 33 O NA II A No NA No NA No NA Anthracene oil (Coal tar fraction) Benzene BNZ 32 O C III A Yes 1 50-80 Benzene or hydrocarbon mixtures (having 10% Benzene or more) BHB 32 O C III A Yes 1 50-80 Benzene or hydrocarbon mixtures (containing Acetylene and 10% BHA 32 O C III A Yes 1 50-80. 56-1(b), (d), (f), (g) Benzene or more) Benzene, Toluene, Xylene mixtures (10% Benzene or more) Butyl acrylate (all isomers) BAR 14 O D III A Yes 2 50-70(a), 50-81(a), (b) Butyl acrylate (all isomers) BAR 14 O D III A Yes 2 50-70(a), 50-81(a), (b) Butyl methacrylate BMH 14 O D III A Yes 2 50-70(a), 50-81(a), (b) Butyl methacrylate BMH 14 O D III A Yes 2 50-70(a), 50-81(a), (b) Butyl acrylate (all isomers) BAE 19 O C III A Yes 2 50-70(a), 50-81(a), (b) Camphor oil (light) CPO 18 O D III A Yes 1 50-10(b) Carbon tetrachloride CBT 36 O NA III A No N/A No Caustic potash solution CPS 5 O NA III A NO N/A 50-73, 55-1(i) Caustic soda solution CSS 5 O NA III A NO N/A 50-73, 55-1(i) Chemical Oil (refined, containing phenolics) COD 21 O E II A NO N/A 50-73, 55-1(i) Chordoror CRB 36 O NA III A Yes 1 No Chloroform CRF 36 O NA III A Yes 1 No Coal tar naphtha solvent NCT 33 O E III A NO N/A 50-73 Coal tar pitch (molten) CTP 33 O E III A NO N/A 50-73, 55-1(i) Cresols (all isomers) CRS 21 O E III A NO N/A 50-73, 55-1(ib) Cresols (all isomers) CRS 21 O E III A NO N/A 50-73, 55-1(ib) Cresols (all isomers) Cresols (all isomers) CRS 11 O E III A Yes 1 No Cresols (all isomers) Cresols (all isomers) CRS 5 O NA III A NO N/A 50-73, 55-1(ib) Cresolte CCW 21 O E III A NO N/A 50-73, 55-1(ib) Cresolte CCT 1 19 O E III A NO N/A 50-73, 55-1(ib) Cresolte CCT 1 19 O C III A Yes 1 No Cresolte Cresolte CCT 1 19 O C III A Yes 1 No Cresolte Cresolte CCT 1 19 O C III A Yes 1 No Cresolte Cresolte CCT 1 19 O C III A Yes 1 No Cresolte Cresolte CCT 1 19 O C III A Yes 1 No Cresolte Cresolte CCT 1 19 O C III A Yes 1 No Cresolte CCT 1 19 O C III A No Cresolte CCT 1 19 O C III A No C	Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Benzene BNZ 32 0 C III A Yes 1 50-60	Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	Ш	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more) BHB 32 2 0 C III A Yes 1 50-60 Benzene or hydrocarbon mixtures (containing Acetylene and 10% BHA 32 2 0 C III A Yes 1 50-60. 56-1(b). (d). (f). (g) Benzene or more) Benzene, Toluene, Xylene mixtures (10% Benzene or more) BTX 32 0 B/C III A Yes 1 50-60 Benzene, Toluene, Xylene mixtures (10% Benzene or more) BTX 32 0 B/C III A Yes 2 50-70(a). 50-81(a). (b) Butyl arcylate (all isomers) BAR 14 0 D III A Yes 2 50-70(a). 50-81(a). (b) Butyl ardylate (all isomers) BAB 19 0 C III A Yes 2 50-70(a). 50-81(a). (b) Butyraldehyde (all isomers) BAB 19 0 C III A Yes 1 55-1(h) Camphor oil (light) CPO 18 0 D II A No N/A No Caustic potash solution CPS 5 2 O NA III A No N/A 50-73. 55-1(b) Caustic soda solution CSS 5 2 O NA III A No N/A 50-73. 55-1(b) Chemical Oil (refined, containing phenolics) COD 21 0 E II A No N/A 50-73 Chlorobenzene CRB 36 O NA III A Yes 1 No Chloroform CRF 36 O NA III A Yes 1 No Coal tar naphtha solvent Coal tar naphtha solvent Coal tar naphtha solvent Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CCW 21 2 O E III A Yes 4 So-73. 55-1(b) Cresoste CCW 21 2 O C III A Yes 4 55-1(b)	Anthracene oil (Coal tar fraction)	AHO	33	0	NA	Ш	Α	No	N/A	No	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	Benzene	BNZ	32	0	С	Ш	Α	Yes	1	.50-60	G
Benzene or more) Benzene, Toluene, Xylene mixtures (10% Benzene or more) BTX 32 O B/C III A Yes 1 50-60 Butyl acrylate (all isomers) BAR 14 O D III A Yes 2 50-70(a). 50-81(a). (b) Butyl methacrylate BMH 14 O D III A Yes 2 50-70(a). 50-81(a). (b) Butyl adehyde (all isomers) BAE 19 O C III A Yes 1 .50-70(a). 50-81(a). (b) Camphor oil (light) CPO 18 O D III A No N/A No Carbon tetrachloride CBT 36 O NA III A No N/A No Caustic potash solution CPS 5 2 O NA III A No N/A .50-7355-1(i) Caustic potash solution CPS 5 2 O NA III A No N/A	Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 ²	0	С	Ш	Α	Yes	1	.50-60	G
Barriago		ВНА	32 ²	0	С	III	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Butyl methacrylate	Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	Ш	Α	Yes	1	.50-60	G
Sality S	Butyl acrylate (all isomers)	BAR	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Camphor oil (light) CPO 18 O D II A No N/A No Carbon tetrachloride CBT 36 O NA III A No N/A No Caustic potash solution CPS 5 2 O NA III A No N/A .50-73, .55-1() Caustic soda solution CSS 5 2 O NA III A No N/A .50-73, .55-1() Chemical Oil (refined, containing phenolics) COD 21 O E II A No N/A .50-73 Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 1 .50-73 Coal tar naphtha solvent NCTT 33 O E III A No N/A .50-73 Cresoste CCW 21 2 O </td <td>Butyl methacrylate</td> <td>BMH</td> <td>14</td> <td>0</td> <td>D</td> <td>Ш</td> <td>Α</td> <td>Yes</td> <td>2</td> <td>.50-70(a), .50-81(a), (b)</td> <td>G</td>	Butyl methacrylate	BMH	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Carbon tetrachloride CBT 36 O NA III A No N/A No Caustic potash solution CPS 5 2 O NA III A No N/A .50-73, .55-1(j) Caustic soda solution CSS 5 2 O NA III A No N/A .50-73, .55-1(j) Chemical Oil (refined, containing phenolics) COD 21 O E II A No N/A .50-73, .55-1(j) Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 1 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Cresoste CCW 21 2	Butyraldehyde (all isomers)	BAE	19	0	С	Ш	Α	Yes	1	.55-1(h)	G
Caustic potash solution CPS 5 2 O NA III A No N/A .50-73, .55-1(j) Caustic soda solution CSS 5 2 O NA III A No N/A .50-73, .55-1(j) Chemical Oil (refined, containing phenolics) COD 21 O E II A No N/A .50-73 Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 3 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Cresoste CCW 21 2 O E III A Yes 1 No Cresoste CRS 21 O	Camphor oil (light)	CPO	18	0	D	Ш	Α	No	N/A	No	G
Caustic soda solution CSS 5 2 O NA III A No N/A .50-73, .55-1(j) Chemical Oil (refined, containing phenolics) COD 21 O E II A No N/A .50-73 Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 3 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Creosote CCW 21 2 O E III A Yes 1 No Cressols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CRX O E <	Carbon tetrachloride	CBT	36	0	NA	Ш	Α	No	N/A	No	G
Chemical Oil (refined, containing phenolics) COD 21 O E II A No N/A .50-73 Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 3 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Creosote CCW 21 2 O E III A Yes 1 No Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III<	Caustic potash solution	CPS	5 ²	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G
Chlorobenzene CRB 36 O D III A Yes 1 No Chloroform CRF 36 O NA III A Yes 3 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Creosote CCW 21 2 O E III A Yes 1 No Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III A Yes 1 .55-1(b) Crotonaldehyde CTA 19 2 O C III A	Caustic soda solution	CSS	5 ²	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G
Chloroform CRF 36 O NA III A Yes 3 No Coal tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Creosote CCW 21 2 O E III A Yes 1 No Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III A Yes 1 .55-1(f) Crotonaldehyde CTA 19 2 O C III A No N/A .55-1(h)	Chemical Oil (refined, containing phenolics)	COD	21	0	Е	П	Α	No	N/A	.50-73	G
Coll tar naphtha solvent NCT 33 O D III A Yes 1 .50-73 Coal tar pitch (molten) CTP 33 O E III A No N/A .50-73 Creosote CCW 21 2 O E III A Yes 1 No Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III A Yes 1 .55-1(b) Crotonaldehyde CTA 19 2 O C III A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Chlorobenzene	CRB	36	0	D	Ш	Α	Yes	1	No	G
Coal tar hapiting solvent NCT 53 C D III A No N/A .50-73 Creosote CCW 21 ° 2 O E III A Yes 1 No Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III A Yes 1 .55-1(f) Crotonaldehyde CTA 19 ° O C III A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Chloroform	CRF	36	0	NA	Ш	Α	Yes	3	No	G
Creosote CCW 21 ° 2 ° 0 ° E ° III ° A ° No ° N/A ° NO	Coal tar naphtha solvent	NCT	33	0	D	Ш	Α	Yes	1	.50-73	G
Cresols (all isomers) CRS 21 O E III A Yes 1 No Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylic acid tar CRX O E III A Yes 1 .55-1(f) Crotonaldehyde CTA 19 ² O C II A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Coal tar pitch (molten)	CTP	33	0	Ε	Ш	Α	No	N/A	.50-73	G
Cresylate spent caustic CSC 5 O NA III A No N/A .50-73, .55-1(b) Cresylate spent caustic CRX O E III A Yes 1 .55-1(f) Crotonaldehyde CTA 19 ² O C II A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Creosote	CCW	21 ²	0	Е	Ш	Α	Yes	1	No	G
Cresylic acid tar CRX O E III A Yes 1 .55-1(f) Crotonaldehyde CTA 19 2 O C III A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Cresols (all isomers)	CRS	21	0	Е	Ш	Α	Yes	1	No	G
Crotonaldehyde CTA 19 2 O C II A Yes 4 .55-1(h) Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Cresylate spent caustic	CSC	5	0	NA	Ш	Α	No	N/A	.50-73, .55-1(b)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and CHG O C III A No N/A No	Cresylic acid tar	CRX		0	Е	Ш	Α	Yes	1	.55-1(f)	G
	Crotonaldehyde	CTA	19 ²	0	С	Ш	Α	Yes	4	.55-1(h)	G
Litiyipi opyt aci olaliti	Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	III	Α	No	N/A	No	G
Cyclohexanone CCH 18 O D III A Yes 1 .56-1(a), (b)	Cyclohexanone	CCH	18	0	D	Ш	Α	Yes	1	.56-1(a), (b)	G

^{2.} Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

^{3.} Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine, Ashland City

Cargo Identification	Cargo Identification								Conditions of Carriage						
								ecovery							
Name Cyclohexanone, Cyclohexanol mixture	Chem Code CYX	Compat Group No 18 ²	Sub Chapter O	Grade E	Hull Type III	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of .56-1 (b)	Insp. Period G					
Cyclohexylamine	CHA	7	0	D	Ш	Α	Yes	1	.56-1(a), (b), (c), (g)	G					
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	Ш	Α	Yes	1	.50-60, .56-1(b)	G					
iso-Decyl acrylate	IAI	14	0	Е	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G					
Dichlorobenzene (all isomers)	DBX	36	0	Е	Ш	Α	Yes	3	.56-1(a), (b)	G					
1,1-Dichloroethane	DCH	36	0	С	Ш	Α	Yes	1	No	G					
2,2'-Dichloroethyl ether	DEE	41	0	D	Ш	Α	Yes	1	.55-1(f)	G					
Dichloromethane	DCM	36	0	NA	III	Α	Yes	5	No	G					
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	Е	III	Α	No	N/A	.56-1(a), (b), (c), (g)	G					
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2		A	III	Α	No	N/A	.56-1(a), (b), (c), (g)	G					
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 ²	0	E	III	Α	No	N/A	.56-1(a), (b), (c), (g)	G					
1,1-Dichloropropane	DPB	36	0	С	III	A	Yes	3	No	G					
1,2-Dichloropropane	DPP	36	0	С	III	A	Yes	3	No	G					
	DPC	36	0	С	III	Α	Yes	3	No	G					
1,3-Dichloropropage	DPU	15	0	D	 II	A	Yes	4	No	G					
1,3-Dichloropropene	DMX	15	0	C	<u>''</u>	A	Yes	1	No	G					
Dichloropropene, Dichloropropane mixtures	DEA	8	0	E	111	A	Yes	1	.55-1(c)	G					
Diethanolamine Diethanolamine		7	0	C				3	.55-1(c)	G					
Diethylamine Diethylamine	DEN				III	Α	Yes		.55-1(c)	G					
Diethylenetriamine Diethylenetriamine	DET	7 2	0	E	- 111	A	Yes	1		G					
Diisobutylamine	DBU	7	0	D	III	Α	Yes	3	.55-1(c)	G					
Diisopropanolamine	DIP	8	0	E	III	Α	Yes	1	.55-1(c)						
Diisopropylamine	DIA	7	0	С	II	Α	Yes	3	.55-1(c)	G					
N,N-Dimethylacetamide	DAC	10	0	Е	III	Α	Yes	3	.56-1(b)	G					
Dimethylethanolamine	DMB	8	0	D	Ш	Α	Yes	1	.56-1(b), (c)	G					
Dimethylformamide	DMF	10	0	D	Ш	Α	Yes	1	.55-1(e)	G					
Di-n-propylamine	DNA	7	0	С	II	Α	Yes	3	.55-1(c)	G					
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	Е	Ш	Α	No	N/A	.56-1(b)	G					
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	Ш	Α	No	N/A	No	G					
EE Glycol Ether Mixture	EEG	40	0	D	Ш	Α	No	N/A	No	G					
Ethanolamine	MEA	8	0	Е	Ш	Α	Yes	1	.55-1(c)	G					
Ethyl acrylate	EAC	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G					
Ethylamine solution (72% or less)	EAN	7	0	Α	Ш	Α	Yes	6	.55-1(b)	G					
N-Ethylbutylamine	EBA	7	0	D	Ш	Α	Yes	3	.55-1(b)	G					
N-Ethylcyclohexylamine	ECC	7	0	D	Ш	Α	Yes	1	.55-1(b)	G					
Ethylene cyanohydrin	ETC	20	0	Е	Ш	Α	Yes	1	No	G					
Ethylenediamine	EDA	7 ²	0	D	Ш	Α	Yes	1	.55-1(c)	G					
Ethylene dichloride	EDC	36 ²	0	С	Ш	Α	Yes	1	No	G					
Ethylene glycol hexyl ether	EGH	40	0	Е	III	Α	No	N/A	No	G					
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	Ш	Α	Yes	1	No	G					
Ethylene glycol propyl ether	EGP	40	0	Е	Ш	Α	Yes	1	No	G					
2-Ethylhexyl acrylate	EAI	14	0	Е	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G					
Ethyl methacrylate	ETM	14	0	D/E	III	A	Yes	2	.50-70(a)	G					
2-Ethyl-3-propylacrolein	EPA	19 ²	0	E	III	A	Yes	1	No	G					
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E	III	Α	Yes	1	.55-1(h)	G					
Furfural	FFA	19	0	D D	III	A	Yes	1	.55-1(h)	G					
	GTA	19	0	NA	III	A	No	N/A	No	G					
Glutaraldehyde solution (50% or less)									.55-1(c)	G					
Hexamethylenediamine solution	HMC		0	E		Α	Yes	1	.56-1(b), (c)	G					
Hexamethyleneimine	HMI	7	0	С	II	Α	Yes	1	.50-1(0), (0)						



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine,

Ashland City

Cargo Identification)				1		Conditions of Carriage				
	Chem	Compat	Sub		Hull	Tank	Vapor R App'd	VCS	Special Requirements in 46 CFR	Inon	
Name Hydrocarbon 5-9	Code	Group No		Grade C	Type	Group		Category 1	151 General and Mat'ls of .50-70(a), .50-81(a), (b)	Insp. Period G	
Isoprene	IPR	30	0	Α	Ш	Α	Yes	7	.50-70(a), .50-81(a), (b)	G	
Isoprene, Pentadiene mixture	IPN		0	В	Ш	Α	No	N/A	.50-70(a), .55-1(c)	G	
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	KPL	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G	
Mesityl oxide	MSO	18 ²	0	D	Ш	Α	Yes	1	No	G	
Methyl acrylate	MAM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
Methylcyclopentadiene dimer	MCK	30	0	С	Ш	Α	Yes	1	No	G	
Methyl diethanolamine	MDE	8	0	Е	Ш	Α	Yes	1	.56-1(b), (c)	G	
2-Methyl-5-ethylpyridine	MEP	9	0	Е	Ш	Α	Yes	1	.55-1(e)	G	
Methyl methacrylate	MMM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
2-Methylpyridine	MPR	9	0	D	Ш	Α	Yes	3	.55-1(c)	G	
alpha-Methylstyrene	MSR	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
Morpholine	MPL	7 2	0	D	III	Α	Yes	1	.55-1(c)	G	
Nitroethane	NTE	42	0	D	П	Α	No	N/A	.50-81, .56-1(b)	G	
1- or 2-Nitropropane	NPM	42	0	D	III	Α	Yes	1	.50-81	G	
1,3-Pentadiene	PDE	30	0	Α	Ш	Α	Yes	7	.50-70(a), .50-81	G	
Perchloroethylene	PER	36	0	NA	Ш	Α	No	N/A	No	G	
Phthalic anhydride (molten)	PAN	11	0	E	III	Α	Yes	1	No	G	
Polyethylene polyamines	PEB	7 ²	0	E	III	Α	Yes	1	.55-1(e)	G	
iso-Propanolamine	MPA	8	0	E	III	Α	Yes	1	.55-1(c)	G	
Propanolamine (iso-, n-)	PAX	8	0	E	III	A	Yes	1	.56-1(b), (c)	G	
iso-Propylamine	IPP	7	0	Α	II.	A	Yes	5	.55-1(c)	G	
Pyridine	PRD	9	0	C	III	A	Yes	1	.55-1(e)	G	
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0		III	A	No	N/A	.50-73, .55-1(j)	G	
Sodium aluminate solution (45% or less)	SAU	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G	
Sodium chlorate solution (50% or less)	SDD	0 1,2		NA	III	Α	No	N/A	.50-73	G	
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b)	G	
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2		NA	III	Α	Yes	1	.50-73, .55-1(b)	G	
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,2		NA	III	Α	No	N/A	.50-73, .55-1(b)	G	
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	2 0	NA	П	Α	No	N/A	.50-73, .55-1(b)	G	
Styrene (crude)	STX		0	D	Ш	Α	Yes	2	No	G	
Styrene monomer	STY	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
1.1.2.2-Tetrachloroethane	TEC	36	0	NA	Ш	Α	No	N/A	No	G	
Tetraethylenepentamine	TTP	7	0	Е	III	Α	Yes	1	.55-1(c)	G	
Tetrahydrofuran	THF	41	0	С	Ш	Α	Yes	1	.50-70(b)	G	
Toluenediamine	TDA	9	0	E	II	Α	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G	
1,2,4-Trichlorobenzene	TCB	36	0	E	III	Α	Yes	1	No	G	
1,1,2-Trichloroethane	TCM	36	0	NA	III	Α	Yes	1	.50-73, .56-1(a)	G	
Trichloroethylene	TCL	36 ²	0	NA	III	Α	Yes	1	No	G	
1,2,3-Trichloropropane	TCN	36	0	E	II	Α	Yes	3	.50-73, .56-1(a)	G	
Triethanolamine	TEA	8 ²	0	E	III	A	Yes	1	.55-1(b)	G	
Triethylamine	TEN	7	0	С	II.	A	Yes	3	.55-1(e)	G	
Triethylenetetramine	TET	7 2	0	E	III	A	Yes	1	.55-1(b)	G	
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	 	A	No	N/A		G	
Trisodium phosphate solution	TSP	5	0	NA	III	A	No	N/A		G	
modulum priospriate solution	135	J	<u> </u>	INA	111	^	INU	IN/A	- / - · · · · · · · · · · · · · · · · ·	-	



11-May-12

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine,

Conditions of Carriage

Ashland City

Official #: 1241334 Page 4 of 8 Hull #: 4842

Cargo Identification

							Vapor R			
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G
Vinyl acetate	VAM	13	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	0	Е	Ш	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	0	D	III	Α	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (G
Subchapter D Cargoes Authorized for Vapor Contr	ol									
Acetone	ACT	18 ²	D	С		Α	Yes	1		
Acetophenone	ACP	18	D	Е		Α	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	Е		Α	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	Е		Α	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		Α	Yes	1		
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		Α	Yes	1		
Benzyl alcohol	BAL	21	D	Е		Α	Yes	1		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		Α	Yes	1		
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1		
Butyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1		
Butyl alcohol (n-)	BAN	20 ²	D	D		Α	Yes	1		
Butyl alcohol (sec-)	BAS	20 ²	D	С		Α	Yes	1		
Butyl alcohol (tert-)	BAT		D	С		Α	Yes	1		
Butyl benzyl phthalate	BPH	34	D	Е		Α	Yes	1		
Butyl toluene	BUE	32	D	D		Α	Yes	1		
Caprolactam solutions	CLS	22	D	Е		Α	Yes	1		
Cyclohexane	CHX	31	D	С		Α	Yes	1		
Cyclohexanol	CHN	20	D	E		Α	Yes	1		
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		Α	Yes	2		
p-Cymene	CMP	32	D	D		Α	Yes	1		
iso-Decaldehyde	IDA	19	D	Е		Α	Yes	1		
n-Decaldehyde	DAL	19	D	Е		Α	Yes	1		
Decene	DCE	30	D	D		Α	Yes	1		
Decyl alcohol (all isomers)	DAX	20 ²	D	Е		Α	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	Е		Α	Yes	1		
Diacetone alcohol	DAA	20 ²	D	D		Α	Yes	1		
ortho-Dibutyl phthalate	DPA	34	D	Е		Α	Yes	1		
Diethylbenzene	DEB	32	D	D		Α	Yes	1		
Diethylene glycol	DEG	40 ²	D	Е		Α	Yes	1		
Diisobutylene	DBL	30	D	С		Α	Yes	1		
Diisobutyl ketone	DIK	18	D	D		Α	Yes	1		
Diisopropylbenzene (all isomers)	DIX	32	D	E		Α	Yes	1		
Dimethyl phthalate	DTL	34	D	E		Α	Yes	1		
Dioctyl phthalate	DOP	34		E		Α	Yes	1		
Dipentene	DPN	30	D	D		A	Yes	1		
Diphenyl	DIL	32	D	D/E		Α	Yes	1		
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		A	Yes	1		
Diphenyl ether	DPE	41	D	{E}		A	Yes	1		
Dipropylene glycol	DPG	40	D	E		A	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		A	Yes	1		
	DSR	33	D	E		A	Yes	1		
Distillates: Straight run	DON	55	<i>-</i>	_		А	169			



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine, Ashland City

Cargo Identification	Cargo Identification									
							Vapor	Recovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Dodecene (all isomers)	DOZ	30	D	D	1 1 1 1 1 1	A	Yes	1	Tro Concidi and Matio of	renou
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		Α	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		Α	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	Е		Α	Yes	1		
Ethyl acetate	ETA	34	D	С		Α	Yes	1		
Ethyl acetoacetate	EAA	34	D	Е		Α	Yes	1		
Ethyl alcohol	EAL	20 ²	D	С		Α	Yes	1		
Ethylbenzene	ETB	32	D	С		Α	Yes	1		
Ethyl butanol	EBT	20	D	D		Α	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	С		Α	Yes	1		
Ethyl butyrate	EBR	34	D	D		Α	Yes	1		
Ethyl cyclohexane	ECY	31	D	D		Α	Yes	1		
Ethylene glycol	EGL	20 2	D	Е		Α	Yes	1		
Ethylene glycol butyl ether acetate	EMA	34	D	Е		Α	Yes	1		
Ethylene glycol diacetate	EGY	34	D	Е		Α	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	Е		Α	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1		
2-Ethylhexanol	EHX	20	D	Е		Α	Yes	1		
Ethyl propionate	EPR	34	D	С		Α	Yes	1		
Ethyl toluene	ETE	32	D	D		Α	Yes	1		
Formamide	FAM	10		E		A	Yes	1		
Furfuryl alcohol	FAL	20 ²	D	E		Α	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		Α	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		Α	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1		
Glycerine	GCR	20 ²	D	Е		Α	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1		
Heptanoic acid	HEP	4	D	Е		Α	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1		
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2		
Heptyl acetate	HPE	34	D	Е		Α	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1		
Hexanoic acid	НХО	4	D	Е		Α	Yes	1		
Hexanol	HXN	20	D	D		Α	Yes	1		
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2		
Hexylene glycol	HXG	20	D	Е		Α	Yes	1		
Isophorone	IPH	18 ²	D	E		Α	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		Α	Yes	1		
Kerosene	KRS	33	D	D		Α	Yes	1		
Methyl acetate	MTT	34	D	D		Α	Yes	1		
Methyl alcohol	MAL	20 ²	D	С		Α	Yes	1		
Methylamyl acetate	MAC	34	D	D		A	Yes	1		
))										



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine, Ashland City

11-May-12

Cargo Identifica	Cargo Identification									Conditions of Carriage					
						. .		Recovery	0 : 10 : 10 050						
Name	Chem Code	Compat Group No		Grade	Hull Type	Tank Group		VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period					
Methylamyl alcohol	MAA	20	D	D		Α	Yes	1							
Methyl amyl ketone	MAK	18	D	D		Α	Yes	1							
Methyl tert-butyl ether	MBE	41 ²	D	С		Α	Yes	1							
Methyl butyl ketone	MBK	18	D	С		Α	Yes	1							
Methyl butyrate	MBU	34	D	С		Α	Yes	1							
Methyl ethyl ketone	MEK	18 ²	D	С		Α	Yes	1							
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1							
Methyl isobutyl ketone	MIK	18 ²	D	С		Α	Yes	1							
Methyl naphthalene (molten)	MNA	32	D	Е		Α	Yes	1							
Mineral spirits	MNS	33	D	D		Α	Yes	1							
Myrcene	MRE	30	D	D		Α	Yes	1							
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1							
Naphtha: Petroleum	PTN	33	D	#		Α	Yes	1							
Naphtha: Solvent	NSV	33	D	D		Α	Yes	1							
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1							
Naphtha: Varnish makers and painters (75%)	NVM	33	D	С		Α	Yes	1							
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1							
Nonene (all isomers)	NON	30	D	D		Α	Yes	2							
Nonyl alcohol (all isomers)	NNS	20 ²	D	Е		Α	Yes	1							
Nonyl phenol	NNP	21	D	Е		Α	Yes	1							
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	Е		Α	Yes	1							
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		Α	Yes	1							
Octanoic acid (all isomers)	OAY	4	D	Е		Α	Yes	1							
Octanol (all isomers)	OCX	20 ²	D	E		Α	Yes	1							
Octene (all isomers)	OTX	30	D	С		Α	Yes	2							
Oil, fuel: No. 2	OTW	33	D	D/E		Α	Yes	1							
Oil, fuel: No. 2-D	OTD	33	D	D		Α	Yes	1							
Oil, fuel: No. 4	OFR	33	D	D/E		Α	Yes	1							
Oil, fuel: No. 5	OFV	33	D	D/E		Α	Yes	1							
Oil, fuel: No. 6	OSX	33	D	E		Α	Yes	1							
Oil, misc: Crude	OIL	33		C/D		Α	Yes	1							
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1							
Oil, misc: Gas, high pour	OGP	33	D	E		A	Yes	1							
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1							
Oil, misc: Residual	ORL	33		E		A	Yes	1							
Oil, misc: Turbine	OTB	33		E		A	Yes	1							
- 1	PTX	30	D	A		A	Yes	5							
Pentene (all isomers)	PPE	34	D	D		A	Yes	1							
n-Pentyl propionate	PIO	30	D	D		A	Yes	1							
alpha-Pinene	PIP	30	D	D			Yes	1							
beta-Pinene						Α									
Poly(2-8) alkylene glycol monoalkyl(C1-C6) ether	PAG PAF	40	D	E		Α	Yes	1							
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate		34	D	E		Α	Yes	1							
Polybutene	PLB	30	D	E		A	Yes	1							
Polypropylene glycol	PGC	40	D	E		Α	Yes	1							
iso-Propyl acetate	IAC	34	D	С		A	Yes	1							
n-Propyl acetate	PAT	34	D -	С		A	Yes	1							
iso-Propyl alcohol	IPA	20 ²	D	С		Α	Yes	1							
n-Propyl alcohol	PAL	20 ²	D	С		Α	Yes	1							



11-May-12

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240

Shipyard: Trinity Marine,

Ashland City

Official #: 1241334 Page 7 of 8 Hull #: 4842

Cargo Identification						Conditions of Carriage				
Name Propylbenzene (all isomers)	Chem Code PBY	Compat Group No 32	Sub Chapter D	Grade D	Hull Type	Tank Group A	Vapor F App'd (Y or N) Yes	Recovery VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
iso-Propylcyclohexane	IPX	31	D	D		A	Yes	1		
Propylene glycol	PPG	20 ²	D	E		Α	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		Α	Yes	1		
Propylene tetramer	PTT	30	D	D		Α	Yes	1		
Sulfolane	SFL	39	D	Е		Α	Yes	1		
Tetraethylene glycol	TTG	40	D	E		Α	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		Α	Yes	1		
Toluene	TOL	32	D	С		Α	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		Α	Yes	1		
Triethylbenzene	TEB	32	D	E		Α	Yes	1		
Triethylene glycol	TEG	40	D	E		Α	Yes	1		
Triethyl phosphate	TPS	34	D	E		Α	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		Α	Yes	1		
Trixylenyl phosphate	TRP	34	D	E		Α	Yes	1		
Undecene	UDC	30	D	D/E		Α	Yes	1		
1-Undecyl alcohol	UND	20	D	E		Α	Yes	1		
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1		

Serial #: C1-1202419 Dated: 11-May-12

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10240 Shipyard: Trinity Marine, Hull #: 4842 Official #: 1241334

Explanation of terms & symbols used in the Table:

Cargo Identification

Chem Code

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2. The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Note 1 Note 2 Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter

Subchapter D Subchapter O The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

ABC D, E

Note 4

Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Vapor Recovery Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category:

The specified cargo's provisional classification for vapor control systems.

Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3,

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5,

Category 7

The cargo has not been evaluated/classified for use in vapor control systems