



BARGE "KIRBY 10550"

ULLAGE TRIM TABLE

FORMERLY "S/R 101"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 CENTER	- 00-1/2	00-1/2	- 00-7/8	00-7/8	- 01-3/8	01-3/8	- 01-7/8	01-7/8	- 02-1/4	02-1/4	- 02-3/4	02-3/4
2 CENTER	00-1/4	- 00-1/4	00-3/8	- 00-3/8	00-5/8	- 00-5/8	00-3/4	- 00-3/4	01-0/8	- 01-0/8	01-1/8	- 01-1/8
3 CENTER	00-1/8	- 00-1/8	00-1/4	- 00-1/4	00-1/2	- 00-1/2	00-5/8	- 00-5/8	00-3/4	- 00-3/4	00-7/8	- 00-7/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 CENTER IS - 00-3/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 2 CENTER, THE TRIM CORRECTED ULLAGE IS 3'-11 5/8"

LENGTH BETWEEN DRAFT MARKS: 156'-00"

March 14, 2007

PRECISION MEASUREMENT
 & ANALYSIS, INC.

P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>

