

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 22 Jul 2022 Expiration Date: 22 Jul 2023

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name

Official Number

IMO Number

Call Sign

Service

KIRBY 10550

1068374

Tank Barge

Hailing Port

Hull Material

Horsepower

Propulsion

WILMINGTON, DE

Steel

UNITED STATES

Place Built

Delivery Date

Keel Laid Date

Gross Tons

Net Tons

DWT

Length

JEFFERSONVILLE, IN

22Jul1998

17May1998

R-716

R-716

R-195.0

1-0

UNITED STATES

Owner

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES Operator

KIRBY INLAND MARINE, LP 18350 MARKET STREET CHANNELVIEW, TX 77530

UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Oilers

0 Chief Mates 0 Second Mates 0 First Class Pilots0 Radio Officers

0 First Assistant Engineers0 Second Assistant Engineers

0 Third Mates

0 Able Seamen

0 Third Assistant Engineers

0 Master First Class Pilot

0 Mate First Class Pilots

0 Ordinary Seamen 0 Deckhands 0 Licensed Engineers0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge . Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Date	Zone	A/P/R	Signature

This certificate issued by

Officer in Charge, Marine Inspection

B. T. INAGAKI, GS-1

Marine Safety Unit Port Arthur

Inspection Zone

By direction



United States of America Department of Homeland Security **United States Coast Guard**

Certification Date: 22 Jul 2022 **Expiration Date:** 22 Jul 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 10550

---Hull Exams---

Next Exam Exam Type

Last Exam

Prior Exam

DryDock

30Apr2032

22Jul2022

26Apr2012

Internal Structure

31May2027

22Jul2022

19May2017

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated

Part154 Regulated

10667

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Location Description

Max Cargo Weight per Tank (short tons)

Maximum Density (lbs/gal)

595

13.600

2 AND 3

607

13.600

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
	1495	9ft 3in	13.60	
III	1723	10ft 4in	13.60	
II	1495	9ft 3in	13.60	
III	1723	10ft 4in	13.60	

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial ##VN98008448. dated 17 Jul 2000, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Vapor Control Authorization

This vessel's vapor control system (vcs) has been inspected to the plans approved by the Marine Safety Center letter serial #C2-9801873 dated 29MAY98, and found acceptable for the collection of cargo vapors from those specific subchapter "D" cargoes contained in that letter, and those specified hazardous cargoes annotated with either "V" or "T" in the CAA.

The letter "V" in the note column of the CAA signifies approval for vapor control without any additional requirements.

The letter "T" in the note column of the CAA signifies that the cargo is highly toxic and that spill valves or rupture disks are not authorized as the primary means of overfill protection required by 46 CFR 39.20-9. A high level and overfill alarm is required by 46 CFR 39.20-7.



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 22 Jul 2022 Expiration Date: 22 Jul 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 10550

Per 46 CFR 151.10(c)(2), the maximum tank weights listed above reflect uniform(within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

	Internal Exam			External Exam				
Tank Id	Previous Last		Next	Previous	Last	Next		
1	26Apr2012	22Jul2022	30Apr2032		:=	-		
2 AND 3	26Apr2012	22Jul2022	30Apr2032	*	5 **	Œ		
			Hydro Test					
Tank Id	Safety Valves	E	Previous	Last	Next			
1	=		=	=	::=			
2 AND 3	-			10 -	: -			

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

40-B

END

^{*}Stability and Trim*

Department of Transportation
United States Coast Guard

Serial #: VN98008448
COI Ref: 17-Jul-00



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10550 Official #: D1068374

Page 1 of 2

Shipyard: JEFFBOAT

Hull #: 98-2352

L	ist	of	Auti	norize	d Ca	rgoes
---	-----	----	------	--------	------	-------

Cargo Identification						С	Conditions of Carriage		
Name	Chem Code	Group No	Exc	Grade	Hull Type	Note	Special Requirements in 46 CFR 151 General and Mat'is of Construction		
Authorized Subchapter O Cargoes		<u> </u>		!		1			
Acrylonitrile	ACN	15	Y	С	11	Т	.50-70(a), .55-1(e)		
Adiponitrile	ADN	37	N	E	- 11	v	No		
Anthracene oil (Coal tar fraction)	AHO	33	N		11		No		
Alkyl(C7-C9) nitrates	AKN	34	Y	_	111		.50-81, 50-85		
Acetonitrile	ATN	37	N	С	0)	Т	No		
Butyraldehyde (all isomers)	BAE	19	N	C	10	v	.55-1(h)		
Butyl acrylate (all isomers)	BAR	14	N	D	01	V	.50-70(a) .50-81(a), (b)		
Benzene hydrocarbon mixtures (containing Acetylenes)(having 10% Benzene or more)	BHA	- 14	14	U	111	V	.50-60, .56-1(b), (d), (f), (g)		
Benzene hydrocarbon mixtures (baving 10% Benzene ormore)	ВНВ	22	- NI		111	V	.50-60		
Butyl methacrylate	BMH	32 14	N N	D	111	v	.50-70(a), .50-81(a), (b)		
Benzene			_				.50-60		
	BNZ	32	N	C	#11	V	.50-60		
Benzene, Toluene, Xylene mixtures (having 10% Benzeneor more) Carbon tetrachloride	BTX	32	N N	B/C	101	V	No .50-60		
A TABLE OF THE PARTY OF THE PAR	CBT	36	N	- n	- (1)				
Cyclohexanone	CCH	18	N	D	[]]	V	.56-1(a), (b)		
Creosote (all isomers)	CCM	21	Y	E	181	V			
Crude hydrocarbon feedstock (containing Bulyraldehydesand Ethylpropyl acrolein)	CHG	0	N	C	01	V	No		
Camphor oil Chlorobenzene	CPO	18	N	D	0				
	CRB	36	N	D	III		No		
Chloroform	CRF	36	N	E	111		No		
Cresols	CRS	21	N	E	111	V	No		
Cresylic acid tar	CRX	21	N		101	V	.55-1(f)		
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	N	D		V	.50-50, .56-1(b)		
Crotonaldehyde	CTA	19	Υ	С	11	Т	.55-1(h)		
N.N-Dimethylacetamide	DAC	10	N	E	.00	Т	.56-1(b)		
Dichlorobenzenes (all isomers)	DBX	36	N	E	0)	V	.56-1(a), (b)		
1,1-Dichloroethane	DCH	36	N	С	01	V	No		
Dichloromethane	DCM	36	N	NF	111		Na		
2,2'-Dichloroethyl ether	DEE	41	N	D	II	V	.55-1(1)		
Dimethylformamide	DMF	10	N	D	111		.55-1(e)		
Dichloropropene, Dichloropropane mixtures	DMX	15	N		11	V	No		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	N	E	811		.56-1(b)		
1,1-Dichloropropane	DPB	36	N	С	ii)	Т	No		
1,3-Dichloropropane	DPC	36	N	С	m	Т	No		
1,2-Dichloropropane	DPP	36	N	С	10)	Т	No		
1,3-Dichloropropene	DPU	15	N	D	II	Т.,	No		
Ethyl acrylate	EAC	14	N	С	101	V	.50-70(a), .50-81(a), (b)		
2-Ethylhexyl acrylate	EAI	14	N	Е	DI .	V	.50-70(a), .50-81(a), (b)		
Ethylene dichloride	EDC	36	Υ	С	Ш	٧	No		
Ethylene glycol monoalkyl ethers	EGC	40	N	D/E	111	V	No		
Ethylene glycol hexyl ether	EGH	40	N	E	Ш		No		
Ethylene glycol propyl ether	EGP	40	N	E	HI	V	No		
2-Ethyl-3-propylacrolein	EPA	19	Υ	E	III	V	No		
Ethylene cyanohydrin	ETC	20	N	Ε	III	V	No		
Ethyl methacrylate	ETM	14	N	C	40	V	.50-70(m)		
- urfural	FFA	19	N	E	III	V	.55-1(h)		
Formaldehyde solution (37% to 50%)	FMS	19	Υ	D/E	- 01	V	55-1(h)		
Glutara dehyde solution (50% or less)	GTA	19	N	NF	01		No		
Hydrocarbon 5-9	HFN	30	N	Α	III	V	.50-70(a), .50-81(a), (b)		
soprene	IPR	30	N	Α	111		.50-70(a), .50-81(a), (b)		





Serial #: VN98008448 COI Ref 17-Jul-00



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 10550 Official #: D1068374

Page 2 of 2

Shipyard: JEFFBOAT Hull #: 98-2352

Cargo Identification							Conditions of Carriage		
		Compat				ì			
Name	Chem Code	Group No	Exc	Grade	Hull Type	Note	Special Requirements in 48 CFR 151 General and Mat's of Construction		
Methyl acrylate	MAM	14	N	С	181	٧	.50-70(a), .50-81(a), (b)		
Methylcyclopentadiene dimer	MCK	30	N	С	III	V	No		
2-Methyl-5-ethylpyridine	MEP	9	N	E	111	V	.56-1(e)		
Methyl methacrylate	MMM	14	N	С	111	V	.50-70(a), .50-81(a), (b)		
Mesityl oxide	MSO	18	Y	D	101	V	No		
alpha-Methylstyrene	MSR	30	N	D	111	V	.50-70(m), .50-81(m), (b)		
Coal tar naphtha solvent	NCT	33	N	D	Ш	٧	.50-73		
1- or 2-Nitropropane	NPM	42	N	D	111	V	.50-81		
1,3-Pentadiene	PDE	30	N	Α	101	٧	.50-70(a), .50-81		
Polyethylene polyamines	PEB	7	Υ	E	- 0)	٧	.55-1(e)		
Perchloroethylene	PER	36	N	NF	0)		No		
Pyridine	PRD	9	N	С	0)	V	.55-1(e)		
Sodium chlorate solution (50% or less)	SDD	0	Y	NF	0)		.50-73		
Sodium hypochlorite solution (15% or less)	SHP	5	N		0):				
Styrene (crude)	\$TX	30	N	С	III	V	No		
Styrene	STY	30	N	D	01	V	.50-70(a), .50-81(a), (b)		
1,2,4-Trichlorobenzene	TCB	36	N	E	111	V	No		
Trichloroethylene	TCL	36	Υ		111	V	No		
1.1,2-Trichloroethane	TCM	36	N		111	V	.50-73, .56-1(a)		
1,2,3-Trichloropropane	TÇN	36	N	Е	- 11	Т	.50-73, .56-1(a)		
1,1,2,2-Tetrachloroethane	TEC	36	N	NF	111		No		
Triethylamine	TEN	7	Ñ	С	H	Т	.55-1(e)		
Tetrahydrofuran	THF	41	N	С	111	V	.50-70(b)		
Urea, Ammonium nitrate solution (containing more than 2% Ammonia)	UAS	6	N		III		.56-1(b)		
Vinyl acetate	VAM	13	N	С	III	V	.50-70(a), .50-81(a), (b)		

Explanation of terms & symbols used in the Table:

Cargo Identification Chem Code

The proper shipping name as listed in 46 CFR Table 151.05.

Compatability Group No.

Exceptions (Exc)

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Indication of whether or not there are exceptions to the compatibility chart for the given cargo. See Appendix I to 46 CFR Part 150.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for

A.B.C D. E NA, NF Flammable liquid cargoes, as defined in 48 CFR 30-10 22 Combustible liquid cargoes, as defined in 46 CFR 30-10.15

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4)

Conditions of Carriage

See Certificate of Inspection for explaination of symbols used in this column.