

United States of America Department of Homeland Security **United States Coast Guard**

Certification Date: 12 Nov 2020 12 Nov 2025 **Expiration Date:**

Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name

Official Number

IMO Number

Call Sign

Service

KIRBY 11403

1215578

Tank Barge

Hailing Port

NEW ORLEANS, LA

Hull Matedal

Steel

Horsepower

Propulsion

UNITED STATES

Delivery Date

Keel Laid Date

Gross Tons

Net Tons

Length

DWT

22Jan2009 22Nov2008

R-705

R-705

R-200.0

ю

UNITED STATES

JEFFERSONVILLE, IN

KIRBY INLAND MARINE LP 55 WAUGH DRIVE SUITE 1000 HOUSTON, TX 77007 **UNITED STATES**

Operator

KIRBY INLAND MARINE LP **18350 MARKET ST.** CHANNELVIEW, TX 77530

UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates 0 First Class Pilots 0 Chief Engineers

0 Oilers

0 Chief Mates **0 Second Mates**

O Radio Officers

0 Deckhands

0 First Assistant Engineers 0 Second Assistant Engineers

0 Third Mates 0 Master First Class Pilot 0 Able Seamen 0 Ordinary Seamen

0 Third Assistant Engineers

0 Mate First Class Pilots

O Licensed Engineers 0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle,

This vessel has been granted a fresh water service examination interval in accordance with 46 CFR 31.10-21(a) (2). If this vessel is operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change occurs.

This tank barge is participating in the Eighth-Ninth Coast Guard District's Tank Barge Streamlined Inspection

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine Inspection, Sector New Orleans certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	Annual/Periodi	c/Re-in	spection
Date	Zone	A/P/R	Signature
23Jan2023	MSU BatonRge		BRANDT NICHOLAS
12-4-23	Port Arthurt	X ?	Dillon Berry
10-7-24	HOU/GAL	A	DANNY E. MURRAY

This Amended certificate issued by:

L. L. WOODMAN, CDR, USCG, BY

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Nov 2020 Expiration Date: 12 Nov 2025

Certificate of Inspection

Vessel Name: KIRBY 11403

Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan. Inspection issues concerning this barge should be directed to Sector Houston-Galveston.

---Hull Exams---

 Exam Type
 Next Exam
 Last Exam
 Prior Exam

 DryDock
 30Nov2025
 20Nov2015
 22Jan2009

 Internal Structure
 30Nov2025
 12Nov2020
 20Nov2015

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization: FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity Units Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

11066 Barrels A Yes No No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1	628	13.60
2	592	13.60
3	592	13.60

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
•	1420	8ft 9in	13.60	R, LBS
II	1528	9ft 3in	13.60	R, LBS
Ш	1726	10ft 2in	7.40	R, LBS
Ш	1726	10ft 2in	9.60	R, LBS
111	1726	10ft 2in	11.70	R, LBS
111	1726	10ft 2in	13.60	R, LBS

Conditions Of Carriage

Only those cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial C1-1303982, dated 06DEC2013, may be carried, and then only in the tanks indicated.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the Person In Charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Per 46 CFR 150.130, the Person In Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the compatibility group numbers from the "COMPAT GROUP NO" column listed in the vessel's CAA.

In accordance with 46 CFR 39, excluding 46 CFR 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter Serial C1-0803342 dated 13NOV2008, and the list of authorized cargoes on the CAA, Serial C1-1303982, dated 06DEC2013, and found acceptable for collection of bulk liquid cargo vapors annotated

^{*}Vapor Control Authorization*



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Nov 2020 Expiration Date: 12 Nov 2025

Certificate of Inspection

Vessel Name: KIRBY 11403

with "Yes" in the CAA's VCS column.

In accordance with 46 CFR 39.1017 and 39.5000(e), this vessel's VCS has been evaluated and approved for multi-breasted tandem loading with other vessels specifically approved to tandem load with this vessel.

STABILITY AND TRIM

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of cargo in each tank may exceed the uniformly loaded tank cargo weight by at most 5 percent.

The maximum density of cargo which may be filled to the tank top is 7.4 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Fuel Tanks

Internal Examinations

Tank ID Previous Last Next

Machinery Deck - 22Jan2009 -

Cargo Tanks

	Internal Exam			External Exam	1	
Tank Id	Previous	Last	Next	Previous	Last	Next
1	22Jan2009	20Nov2015	30Nov2025	-	*	*
2	22Jan2009	20Nov2015	30Nov2025	-	-	-
3	22Jan2009	20Nov2015	30Nov2025	**	***	**
			Hydro Test			
Tank Id	Safety Valves	;	Previous	Last	Next	
1	-		**	₩	_	
2	-		-	-	-	
3	_			_		

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

40-B

--- Certificate Amendments---

Amending Unit

Amendment Date

Amendment Remark

Marine Safety Unit Baton

23Jan2023

Completed Periodic Inspection.

Rouge

Marine Safety Unit Port Arthur 01Dec2023

CHANGED VESSEL NAME, CHANGED OWNER/OPERATOR, ROUTES AND CONDITIONS AND CONDITIONS OF CARRIAGE.

END



Official #: 1215578

C1-1303982 Dated:

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Shipyard: Jeffboat Hull #: 08-2364

Tank Group Information	Cargo I	dentificat	ion		Cargo	Tanks		Tanks		Cargo Environmental Special Ri Transfer Control Fire							Special Requirements			
Trik Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Seg Tank	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Tem Conf			
A #1-3	13.6	Atmos.	Elev	· I	1 ii 2 ii	Integral Gravity	PV	Closed	11	G-1	NR	NA	Portable	50-70(a), .50-	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	1-B	Yes			

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identificatio	n							Condi	tions of Carriage	
	***************************************						Vapor R	ecovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Authorized Subchapter O Cargoes										
Acetonitrile	ATN	37	0	Ç	111	Α	Yes	3	No	G
Acrylonitrile	ACN	15 ²	0	С	- 11	Α	Yes	4	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	0	E	Ħ	Α	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	111	Α	No	N/A	.50-81, .50-86	G
Aminoethylethanolamine	AÈE	8	0	E	111	Α	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	111	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	II	Α	No	N/A	No	G
Benzene	BNZ	32	0	С	Ш	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 ²	0	Ç	111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 ²	0	С	1)1	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	Ifi	Α	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyl methacrylate	ВМН	14	0	D	111	Α	Yes	2	50-70(a), 50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	0	С	111	Α	Yes	1	.55-1(h)	G
Camphor oil (light)	CPO	18	0	D	11	Α	No	N/A	No	G
Carbon tetrachloride	CBT	36	0	NA	Ш	Α	No	N/A	No	G
Caustic potash solution	CPS	5 ²	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G
Caustic soda solution	CSS	5 ²	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G
Chemical Oil (refined, containing phenolics)	COD	21	0	E	11	Α	No	N/A	.50-73	G
Chlorobenzene	CRB	36	0	D	Ш	Α	Yes	1	No	G
Chloroform	CRF	36	0	NA	III	Α	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	0	D	111	Α	Yes	1	.50-73	G
Coal tar pitch (molten)	CTP	33	Q	E	III	Α	No	N/A	.50-73	G
Creosote	CCV	/ 21 ²	0	Ė	111	Α	Yes	1	No	G
Cresols (all isomers)	CRS	21	0	E	111	Α	Yes	1	No	G
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CRX		0	E	Ш	Α	Yes	1	55-1(f)	G
Crotonaldehyde	CTA	19 ²	Q	С	11	Α	Yes	4	.65-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG	i	0	С	111	Α	No	N/A	No	G
Cyclohexanone	CCH	18	0	D	1	Α	Yes	1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	0	E	111	Α	Yes	1	.56-1 (b)	G



Serial #: C1-1303982 Dated: 06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Official #: 1215578

Page 2 of 8

Cargo Identification	n	'. 1 t. '				Conditions of Carriage						
							Vapor Re	ecovery				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	(Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period		
Cyclohexylamine	CHA	7	0	D	111	Α	Yes	1	.56-1(a), (b), (c), (g)	G		
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	111	Α	Yes	1	.50-60, .56-1(b)	G		
iso-Decyl acrylate	IAI	14	0	Ε	111	Α	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G		
Dichlorobenzene (all isomers)	DBX	36	0	Ε	III	Α	Yes	3	.56-1(a), (b)	G		
1,1-Dichloroethane	DCH	36	0	С	Ш	Α	Yes	1	No	G		
2,2'-Dichloroethyl ether	DEE	41	0	D	ll l	Α	Yes	1	.55-1(f)	G		
Dichloromethane	DCM	36	0	NA	Ш	Α	No	N/A	No	G		
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	Е		Α	No	N/A	.56-1(a), (b), (c), (g)	G		
2.4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 12	2 0	Α	111	Α	No	N/A	.56-1(a), (b), (c), (g)	G		
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 ²	0	Ę	##	Α	No	N/A	.56-1(a), (b), (c), (g)	G		
1,1-Dichloropropane	DPB	36	0	C	III	Α	Yes	3	No	G		
1,2-Dichloropropane	DPP	36	0	Ç	111	Α	Yes	3	No	G		
1,3-Dichloropropane	DPC	36	0	Ç	111	Α	Yes	3	No	G		
1,3-Dichloropropene	DPU	15	0	Đ	Ħ	Α	Yes	4	No	G		
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	11	Α	Yes	1	No	G		
Diethanolamine	DEA	8	0	E	III	Α	Yes	1	.55-1(c)	G		
Diethylamine	DEN	7	0	С		Α	Yes	3	.55-1(c)	G		
Diethylenetriamine	DET	7 2	0	E	H	Α	Yes	1	.55-1(c)	G		
Diisobutylamine	DBU	7	0	D	111	Α	Yes	3	.55-1(c)	G		
Diisopropanolamine	DIP	8	0	Ε		Α	Yes	1	.55-1(c)	G		
Diisopropylamine	DIA	7	0	С		Α	Yes	3	.55-1(c)	G		
N,N-Dimethylacetamide	DAC	10	0	E	111	Α	Yes	3	.56-1(b)	G		
Dimethylethanolamine	DMB	8	0	D	111	Α	Yes	1	.56-1(b), (c)	G		
Dimethylformamide	DMF	10	0	D	111	Α	Yes	1	.55-1(e)	G		
Di-n-propylamine	DNA	7	0	C		Α	Yes	3	.55-1(c)	G		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E		Α	No	N/A	.56-1(b)	G		
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	ll l	A	No	N/A	No	G		
EE Glycol Ether Mixture	EEG	40	0	D	III	Α	No	N/A	No	G		
Ethanolamine	MEA	8	0	Ε	Ш	Α	Yes	1	.55-1(c)	G		
Ethyl acrylate	EAC	14	0	С	111	Α	Yes	2	.50-70(a), .50-61(a), (b)	G		
Ethylamine solution (72% or less)	EAN	7	0	Α		A	No	N/A	.55-1(b)	G		
N-Ethylbutylamine	EBA	7	0	D	— iii	Α	Yes	3	.55-1(b)	G		
N-Ethylcyclohexylamine	ECC	7	0	D	111	A	Yes	1	.55-1(b)	G		
Ethylene cyanohydrin	ETC	20	0	E	III	A	Yes	1	No	G		
Ethylenediamine	EDA	7 ²	0	D	111	A	Yes	1	.55-1(o)	G		
Ethylene dichloride	EDC	36 ²	0	c	111	Α	Yes	1	No	G		
Ethylene glycol hexyl ether	EGH		0	F	111	Α	No	N/A	No	G		
Ethylene glycol monoalkyl ethers	EGC		0	D/E	111	A	Yes	1	No	G		
Ethylene glycol propyl ether	EGP		0	E	111	A	Yes	1	No	G		
2-Ethylhexyl acrylate	EAI	14	0	E	111	A	Yes	2	.50-70(a), .50-81(a), (b)	G		
Ethyl methacrylate	ETM	14	0	D/E	111	A	Yes	2	.50-70(a)	G		
2-Ethyl-3-propylacrolein	EPA	19 2	0	E	111		Yes	1	No	G		
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E		A	Yes	1	.55-1(h)	G		
Furfural	FFA	19	0	D	111	A	Yes	1	.55-1(h)	G		
Glutaraldehyde solution (50% or less)	GTA	19		NA.	111	^	No	N/A	No	- G		
Hexamethylenediamine solution	HMC		0	E	111	A			.55-1(c)	G		
•							Yes	1	.56-1(b), (c)	G		
Hexamethyleneimine	HMI	7	0	C	11	<u>A</u>	Yes	1	.50-70(a), .50-81(a), (b)			
Hydrocarbon 5-9	HFN	~~/	0	· ·		A	Yes	1	-oo-i ofelt 'oo-orfelt (n)			



Serial #: C1-1303982 Dated:

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Official #: 1215578

Page 3 of 8

Cargo Identification							(Condit	ions of Carriage	
		ì	:	1				Recovery		+
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	vcs	Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period
Isoprerie	IPR	30	0	Α	III	Α	No	N/Á	.50-70(a), .50-81(a), (b)	G
Isoprene, Pentadiene mixture	IPN		0	В	111	Α	No	N/A	.50-70(a), .55-1(c)	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	1))	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 ²	0	D	111	À	Yes	1	No	G
Methyl acrylate	MAM	14	0	С	- 111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Methylcyclopentadiene dimer	MCK	30	0	С	111	Α	Yes	1	No	G
Methyl diethanolamine	MDE	8	0	E	Ш	Α	Yes	1	.56-1(b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	0	Е	III	Α	Yes	1	.55-1(e)	G
Methyl methacrylate	MMN	1 14	0	¢	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	0	D	111	Α	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	7 2	0	D	111	Α	Yes	1	.55-1(c)	G
Naphthalene (molten)	NTM	32	0	¢	111	Α	Yes	1	No	G
Nitroethane	NTE	42	О	D	11	Α	No	N/A	.50-81, .56-1(b)	G
1- or 2-Nitropropane	NPM	42	0	D	111	Α	Yes	1	.50-81	G
1,3-Pentadiene	PDE	30	0	Α	111	A	No	N/A	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	111	Α	No	N/A	No	G
Phthalic anhydride (molten)	PAN	11	0	E		Α	Yes	1	Nó	G
Polyethylene polyamines	PEB	7 2	0	Ε	111	Α	Yes	1	.55-1(e)	G
iso-Propanolamine	MPA	8	0	Ε	111	Α	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	0	E		Α	Yes	1	.56-1(b), (c)	G
iso-Propylamine	IPP	7	0	A	11	Α	No	N/A	.55-1(c)	G
Pyridine	PRD	9	0	С	111	Α	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0	***************************************	III	Α	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	O	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDD	Ø 1.	2 0	NA	111	Α	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (b)	G
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,	² O	NA	111	Α	Yes	1	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1.	² O	NA	111	Α	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,	2 0	NA	11	A	No	N/A	.50-73, .55-1(b)	G
Styrene (crude)	STX		0	D	III	A	Yes	2	No	G
Styrene monomer	STY	30	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	III	A	No	N/A	. No	G
Tetraethylenepentamine	TTP	7	0	E	III	A	Yes	1	.55-1(c)	G
Tetrahydrofuran	THF	41	0	С	111	Α	Yes	1	.50-70(b)	G
Toluenediamine	TDA	9	0	E	11	Α	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
1,2,4-Trichlorobenzene	TCB	36	0	E	111	Α	Yes	1	No	G
1,1,2-Trichloroethane	TCM	36	0	NA	Ш	Α	Yes		50-73, 56-1(a)	G
Trichloroethylene	TCL	36 ²	0	NA	111	Α	Yes		No	G
1,2,3-Trichloropropane	TCN		0	Е	#1	Α	Yes		.50-73, .58-1(a)	G
Triethanolamine	TEA	g 2	0	E	111	Α	Yes		.55-1(b)	G
Triethylamine	TEN		0	C	11	A	Yes		.55-1(e)	G
Triethylenetetramine	TET	7 2	0	Ē	<u></u> III	Α	Yes		.55-1(b)	G
Triphenylborane (10% or less), caustic soda solution	TPB		0	NA		A	No	N/A	.56-1(a), (b), (c)	G
Trisodium phosphate solution	TSP	5		NA	111	^A	No	N/A	· · · · · · · · · · · · · · · · · · ·	G
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS		0	NA.	<u>'''</u> III	^_	No	N/A	•	G
oros, removement made solution (containing more than 270 NOS)		······································	<u> </u>	:4/^	F31		IW	14//4	1-4	



Serial #: C1-1303982 Dated:

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Official #: 1215578

Page 4 of 8

Cargo Identification	n						- 1	Condit	ions of Carriage	
		:						ecovery		
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)		Special Requirements in 46 CFR 151 General and Mat'is of	Insp. Period
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G
Vinyl acetate	VAM	13	0	С		Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	0	E	##	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	0	D	11	Α	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (G
Subchapter D Cargoes Authorized for Vapor Contr										
Acetone	ACT	18 ²	D	С		Α	Yes	1		
Acetophenone	ACP	18	D	E		A	Yes	<u>`</u>		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	<u>·</u>		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1		
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D	·	A	Yes	_		
Benzyl alcohol	BAL	21	D	E		A	Yes	<u>-</u>		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E	***	Ä	Yes	1		
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1		
Butyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1		
Butyl alcohol (n-)	BAN	20 ²	D	D		Α	Yes	11		
Butyl alcohol (sec-)	BAS	20 ²	D	C		A	Yes	1		
Butyl alcohol (tert-)	BAT		Đ	C		Α	Yes	1		
Butyl benzyl phthalate	BPH	34	D	E		Α	Yes	1		
Butyl toluene	BUE	32	D	D	·	Α	Yes	1		
Caprolactam solutions	CLS	22	D	Ë		Α	Yes	1		
Cyclohexane	CHX	31	D	С		Α	Yes	11		
Cyclohexanol	CHN	20	D	E		Α	Yes	1		
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		Α	Yes	2	•	
p-Cymene	CMP	32	D	D		Α	Yes	1		
iso-Decaldehyde	IDA	19	D	E		Α	Yes	1		
n-Decaldehyde	DAL	19	D	E		Α	Yes	1		
Decene	DCE	30	D	D		Α	Yes	1		
Decyl alcohol (all isomers)	DAX	20 ²	D	E		Α	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		A	Yes	1		
Diacetone alcohol	DAA	20 ²	D	D		Α	Yes	1		
ortho-Dibutyl phthalate	DPA	34	D	E		Α	Yes	1		
Diethylbenzene	DEB	32	D	D		Α	Yes	1		
Diethylene glycol	DEG	40 ²	D	E		Α	Yes	1		
Diisobutylene	DBL	30	D	С		Α	Yes	1		
Diisobutyi ketone	DIK	18	D	D		Α	Yes	1		
Diisopropylbenzene (all isomers)	DIX	32	D	E		Α	Yes	1		
Dimethyl phthalate	DTL	34	D	E		Α	Yes	1		
Dioctyl phthalate	DOP	34	D	E		Α	Yes	1	····	
Dipentene	DPN	30	D	D		A	Yes	1		-
Diphenyl	DIL	32	D	D/E		Α	Yes	1		
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		A	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Diphenyl ether	DPE	41	D	{E}	••••	Α	Yes	1		
Dipropylene glycol	DPG	40	D	E		Α	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		A	Yes	1		
Distillates: Straight run	DSR	33	D	E		Α	Yes	1		



Serial #: C1-1303982 Dated: 06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Cargo Identificatio	n						1	Condi	tions of Carriage	
	Chem	Compat	Sub		Hull	Tank	Vapor F App'd	Recovery VCS	Second Descriptoments in 46 CER	W
Name	Code	Group No		Grade	Туре	Group		Category	Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period
Dodecene (all isomers)	DOZ	30	D	D		Α	Yes	1	***	
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	Ε		Α	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		Α	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	E		Α	Yes	1		
Ethyl acetate	ETA	34	D	С		Α	Yes	1		
Ethyl acetoacetate	EAA	34	D	Ė		Α	Yes	1		
Ethyl alcohol	EAL	20 ²	D	С		Α	Yes	1		
Ethylbenzene	ETB	32	D	С		Α	Yes	1		
Ethyl butanol	EBT	20	D	D		Α	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	С		Α	Yes	1		
Ethyl butyrate	EBR	34	D	Ď		Α	Yes	1		
Ethyl cyclohexane	ECY	31	D	D	***************************************	Α	Yes	1		
Ethylene glycol	EGL	20 ²	D	Е		Α	Yes	1		***************
Ethylene glycol butyl ether acetate	EMA	34	D	E		Α	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	E	***************************************	Α	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1		
2-Ethylhexanol	EHX	20	D	Ε		Α	Yes	1		
Ethyl propionate	EPR	34	D	С		Α	Yes	1		
Ethyl toluene	ETĖ	32	D	D		Α	Yes	1		
Formamide	FAM	10	D	E		Α	Yes	1		
Furfuryl alcohol	FAL	20 ²	D	Ė		Α	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C	***************************************	Α	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		Α	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1		······································
Glycerine	GCR	20 ²	D	E		Α	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1		
Heptanoic acid	HEP	4	D	E		Α	Yes	1	***************************************	
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1		
Heptene (all isomers)	HPX	30	D	Ç		Α	Yes	2		***************************************
Heptyl acetate	HPE	34	D	E		Α	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1		
Hexanoic acid	НХО		D	E		A	Yes	1		
Hexanol	HXN	20	D	D		Α	Yes	1		
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2		
Hexylene glycol	HXG	20	D	E		Α	Yes	1		
Isophorone	IPH	18 ²	D	E		Α	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1		
JCE IUGI. DF -4	JPV	33	D	D		Α	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JL A						·			
	KRS	33	D	D		Α	Yes	1		
Jet fuel: JP-5 (kerosene, heavy) Kerosene	KRS				· · · · · · · · · · · · · · · · · · ·	A A	Yes Yes			
Jet fuel: JP-5 (kerosene, heavy)		33 34 20 ²	D D	D D		A A A	Yes Yes Yes	1 1		



C1-1303982 Dated:

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Official #: 1215578

Page 6 of 8

Cargo Identifica	tion					 		Condi	tions of Carriage	
		0						Recovery		
Name	Chem Code	Group No	Sub Chapter	Grade	Hull Type	: Tank : Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Methylamyl alcohol	MAA	20	D	D		Α	Yes	1		-t
Methyl amyl ketone	MAK	18	D	D		Α	Yes	1		
Methyl tert-butyl ether	MBE	41 ²	D	C		Α	Yes	1		
Methyl butyl ketone	MBK	18	D	Ç		Α	Yes	1		
Methyl butyrate	MBU	34	D	С		Α	Yes	1		
Methyl ethyl ketone	MEK	18 2	D	C		Α	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1		
Methyl isobutyl ketone	MIK	18 ²	D	С		Α	Yes	1		
Methyl naphthalene (molten)	MNA	32	D	E		Α	Yes	1		
Mineral spirits	MNS	33	D	D		Α	Yes	1		
Myrcene	MRE	30	D	Ð		Α	Yes	1		
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1		
Naphtha: Petroleum	PTN	33	D	#	·······	Α	Yes	1		
Naphtha: Solvent	NSV	33	D	D		Α	Yes	1		
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1		
Naphtha: Vamish makers and painters (75%)	NVM	33	D	С		Α	Yes	1		~~~~
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1		
Nonene (all isomers)	NON	30	D	D	•	Α	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		Α	Yes	1		
Nonyl phenol	NNP	21	D	E		Α	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		A	Yes	1	***************************************	
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		Α	Yes	1		
Octanoic acid (all isomers)	OAY	4	Đ	E		Α	Yes	1		
Octanol (all isomers)	ocx	20 ²	D	E		Α	Yes	1		
Octene (all isomers)	OTX	30	D	С		Α	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		Α	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		Α	Yes	1	~~~~~	
Oil, fuel: No. 5	OFV	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 6	OSX	33	D	E		Α	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		Α	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		Α	Yes	1		***************************************
Oil, misc: Gas, high pour	OGP	33	D	E		Α	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1		
Oil, misc: Residual	ORL	33	D	E		A	Yes	1	······	
Oil, misc: Turbine	OTB	33	D	E		A	Yes	1		
n-Pentyl propionate	PPE	34	D	D		Α	Yes	1		
alpha-Pinene	PIO	30	D	D		Α	Yes	1		
beta-Pinene	PIP	30	D	D		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	Ε		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		Α	Yes	1		
Polybutene	PLB	30	D	E		A	Yes	<u>·</u>		
Polypropylene glycol	PGC	40		E		A	Yes	1		
iso-Propyl acetate	IAC	34	D	C		A	Yes	1		
n-Propyl acetate	PAT	34	D	c		A	Yes	1		
iso-Propyl alcohol	IPA	20 ²	D	c		A	Yes	1		
n-Propyl alcohol	PAL	20 ²	D	c		A	Yes	1		
Propylbenzene (all isomers)	PBY	32		D		A	Yes	<u>'</u>		
· iopyroonacide (difformore)	1 0 1	- VE				т_	162	<u>-</u>		



Serial #: C1-1303982

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Official #: 1215578

Page 7 of 8

Shipyard: Jeffboat

Cargo Identification						Conditions of Carriage				
						Vapor Recover		Recovery	/	
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
iso-Propylcyclohexane	IPX	31	Ď	D		Α	Yes	1	· , ,	
Propylene glycol	PPG	20 ²	D	E		Α	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		Α	Yes	1		
Propylene tetramer	PTT	30	D	D		Α	Yes	1		
Sulfolane	SFL	39	D	E		Α	Yes	1		
Tetraethylene glycol	TTG	40	D	E		Α	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1	,,,,	
Toluene	TOL	32	D	С		Α	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		Α	Yes	1		
Triethylbenzene	TEB	32	D	E		Α	Yes	1		
Triethylene glycol	TEG	40	D	E		Α	Yes	1		
Triethyl phosphate	TPS	34	D	É		Α	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		Α	Yes	1	***************************************	
Trixylenyl phosphate	TRP	34	D	E		Α	Yes	1		
Undecene	UDC	30	D	D/E		Α	Yes	1		
1-Undecyl alcohol	UND	20	D	E		Α	Yes	1	A	
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1		



Department of Homeland Security **United States Coast Guard**

Serial #:

C1-1303982

06-Dec-13

Certificate of Inspection

Cargo Authority Attachment

Shipyard: Jeffboat Hull #: 08-2364

Official #: 1215578

Page 8 of 8

Explanation of terms & symbols used in the Table:

Cargo Identification

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

Chem Code

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual.

Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (2020) 372-1425.

Note 1 Note 2

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter Subchapter D Subchapter O Note 3

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

A, B, C D. E Note 4

mmable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustbility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet,as the necessary flash point/vapor pressure data for such assignments are presently not available.

NA Hull Type

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified, cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Tank Group Vapor Recove Approved (Y or N)

The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category: Category 1

The specified cargo's provisional classification for vapor control systems.

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7 (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.

none

The cargo has not been evaluated/classified for use in vapor control systems.