

United States of America Department of Homeland Security **United States Coast Guard**

02 Nov 2021 Certification Date: 02 Nov 2022 **Expiration Date:**

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name

IMO Number

KIRBY 11506

CG034011

Tank Barge

Hailing Port

Hull Material

Horsepower

Propulsion

Steel

Unknown

Place Built

Delivery Date

Keel Laid Date

Gross Tons

Net Tons

DWT

Length

CARUTHERSVILLE, MO

31Jan1992 23Dec1991

R-705

R-705

R-200.0

1-0

UNITED STATES

KIRBY INLAND MARINE, LP 55 WAUGH DRIVESUITE 1000 HOUSTON, TX 77007 UNITED STATES

KIRBY INLAND MARINE, LP 18350 MARKET ST. CHANNELVIEW, TX 77530 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Oilers

0 Chief Mates

0 First Class Pilots

0 First Assistant Engineers

0 Second Mates

0 Radio Officers

0 Second Assistant Engineers 0 Third Assistant Engineers

0 Third Mates

0 Able Seamen

0 Licensed Engineers

0 Master First Class Pilot 0 Mate First Class Pilots

0 Ordinary Seamen 0 Deckhands

0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI must be notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection A/P/R Signature Zone Date

This certificate issued by:

B. T. INAGAKI, GS-13, USCG, By direction

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



United States of America Department of Homeland Security United States Coast Guard

02 Nov 2021 Certification Date: **Expiration Date:** 02 Nov 2022

Temporary Certificate of Inspection

Vessel Name: KIRBY 11506

---Hull Exams---

Next Exam Exam Type

Last Exam

Prior Exam

DryDock

31May2031

15Sep2021

11May2011

Internal Structure

30Apr2026

15Sep2021

25Apr2016

---Stability---

Type

Issued Date

Office

Book

15Nov1991

Marine Safety Center (MSC)

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units

Highest Grade Type Part151 Regulated

Part153 Regulated Part154 Regulated

10853

Barrels

Yes

No

Hazardous Bulk Solids Authority

Loading Constraints - Structural

| 3 | - 1. (-1 | Maximum Density (lbs/gal) |
|-------------|--|---------------------------|
| Tank Number | Max Cargo Weight per Tank (short tons) | Maximum Bensity (156,94.) |
| 1 C/L | 490 | 13.60 |
| 2 C/L | 507 | 13.60 |
| | 554 | 13.60 |
| 3 C/L | 304 | |

Loading Constraints - Stability

| Hull Type | Maximum Load (short tons) | Maximum Draft (ft/in) | Max Density (lbs/gal) | Route Description | |
|-----------|---------------------------|-----------------------|--------------------------|------------------------|--|
| 1 | 1400 | 8ft 9in | 9 | Lakes, Bays and Sounds | |
| II | 1400 | 8ft 9in | 13.6 | Lakes, Bays and Sounds | |
| III | 1507 | 9ft 5in | 12.7 | Lakes, Bays and Sounds | |
| 1 | 1347 | 8ft 6in | 13.6 | Rivers | |
| 11 | 1400 | 8ft 9in | 13.6 | Rivers | |
| Ш | 1507 | 9ft 5in | 12.7 | Rivers | |
| | | | | | |

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial # C1-1101079 dated 18APR11, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR Part 197, subpart C are applied.

Vapor Control Authorization

Per 46 CFR, Part 39, excluding Part 39.4000, this vessel's vapor control system has been inspected to the plans approved by



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 02 Nov 2021 Expiration Date: 02 Nov 2022

Temporary Certificate of Inspection

Vessel Name: KIRBY 11506

Marine Safety Center letter Serial #M-10829, dated 20NOV92, and extended by MSC letter Serial # C1-1101079 dated 18APR11, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Stability and Trim

Per 46 CFR 151.10(c)(2) the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

| | Internal Exam | 1 | | External Exa | am | |
|---------|---------------|-----------|-----------------|--------------|----------------|--------------|
| Tank ld | Previous | Last | Next | Previous | Last | Next |
| 1 C/L | 13May2019 | 15Sep2021 | 31May2023 | | - | - |
| 2 C/L | 13May2019 | 15Sep2021 | 31May2023 | - | , = | Œ |
| 3 C/L | 13May2019 | 15Sep2021 | 31May2023 | - | - | := |
| | | | Hydro Test | | | |
| Tank ld | Safety Valve | es | Previous | Last | Next | |
| 1 C/L | · = | | (() | • | = 2 | |
| 2 C/L | - | | - : | 3 | Y 2 | |
| 3 C/L | - | | - | - | | |

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

40-B

END





Serial #: C1-1101079

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP. CARUTHERSVILLE

Hull #: 5545

Official #: CG034011

| Tank Group Information | Cargo I | dentificati | on | | Cargo | | Tanks | | Carg | | Enviror Control | nmental | Fire | Special Require | ments | | |
|---------------------------|---------|-------------|-------|-------------|-------------|---------------------|-------|--------|---------------|------|--------------------|-------------------|------------------------|---|--|-------------|------|
| Tnk Grp Tanks in Group | Density | Press. | Temp. | Hull Typ | Seg Tank | Туре | Vent | Gauge | Pipe Class | Cont | Tanks | Handling Space | Protection Provided | General | Materials of Construction | Elec Haz | Temp |
| A #1,#2,#3 | 13.6 | Atmos. | Elev | l | 1ii 2ii | Integral Gravity | PV | Closed | - | G-1 | NR | NA | Portable | 40-1(f)(1), .50-5, .50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50- 81(b), | 55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g), | NR | No |

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks

List of Authorized Cargoes

| Cargo Identificatio | n | | | | | | | Condi | tions of Carriage | |
|--|--------------|--------------------|----------------|-------|--------------|---------------|-------------------|-----------------|---|-----------------|
| | | | | | | | Vapor R | ecovery | | |
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | App'd (Y or N) | VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| Authorized Subchapter O Cargoes | | | | | | | | | | |
| Acetone cyanohydrin | ACY | 0 1,2 | 0 | Ε | 1 | Α | Yes | 3 | .50-5, .50-70(b), .50-73, .50-81 | G |
| Acetonitrile | ATN | 37 | 0 | С | 111 | Α | Yes | 3 | No | G |
| Acrylonitrile | ACN | 15 ² | 0 | С | 11 | Α | Yes | 4 | .50-70(a), .55-1(e) | G |
| Adiponitrile | ADN | 37 | 0 | Ε | 11 | Α | Yes | 1 | No | G |
| Alkyl(C7-C9) nitrates | AKN | 34 2 | 0 | NA | 111 | Α | No | N/A | .50-81, .50-86 | G |
| Allyl alcohol | ALA | 15 ² | 0 | C | 1 | Α | Yes | 3 | .50-5, .50-73 | G |
| Allyl chloride | ALC | 15 | 0 | В | 1 | Α | Yes | 3 | .50-5 | G |
| Aminoethylethanolamine | AEE | 8 | 0 | Е | Ш | Α | Yes | 1 | .55-1(b) | G |
| Ammonium bisulfite solution (70% or less) | ABX | 43 2 | 0 | NA | 111 | Α | No | N/A | .50-73, .56-1(a), (b), (c) | G |
| Ammonium hydroxide (28% or less NH3) | AMH | 6 | 0 | NA | Ш | Α | No | N/A | .56-1(a), (b), (c), (f), (g) | G |
| Aniline | ANL | 9 | 0 | Ε | 1 | Α | Yes | 3 | .50-5, .50-73 | G |
| Anthracene oil (Coal tar fraction) | АНО | 33 | 0 | NA | 11 | Α | No | N/A | No | G |
| Benzene | BNZ | 32 | 0 | С | Ш | Α | Yes | 1 | .50-60 | G |
| Benzene or hydrocarbon mixtures (having 10% Benzene or more) | внв | 32 ² | 0 | С | 111 | Α | Yes | 1 | .50-60 | G |
| Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more) | вна | 32 ² | 0 | С | 111 | Α | Yes | 1 | .50-60, .56-1(b), (d), (f), (g) | G |
| Benzene, Toluene, Xylene mixtures (10% Benzene or more) | BTX | 32 | 0 | B/C | Ш | Α | Yes | 1 | .50-60 | G |
| Butyl acrylate (all isomers) | BAR | 14 | 0 | D | Ш | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| Butyl methacrylate | вмн | 14 | 0 | D | Ш | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| Butyraldehyde (all isomers) | BAE | 19 | 0 | С | Ш | A | Yes | 1 | .55-1(h) | G |
| Camphor oil (light) | СРО | 18 | 0 | D | 11 | Α | No | N/A | No | G |
| Carbolic oil | СВО | 21 | 0 | Ε | ı | Α | Yes | 3 | .50-5, .50-73 | G |
| Carbon tetrachloride | СВТ | 36 | 0 | NA | Ш | Α | No | N/A | No | G |
| Caustic potash solution | CPS | 5 2 | 0 | NA | Ш | Α | No | N/A | .50-73, .55-1(j) | G |
| Caustic soda solution | CSS | 5 2 | 0 | NA | 111 | Α | No | N/A | .50-73, .55-1(j) | G |
| Chemical Oil (refined, containing phenolics) | COD | 21 | 0 | Е | 11 | Α | No | N/A | .50-73 | G |
| Chlorobenzene | CRB | 36 | 0 | D | 111 | Α | Yes | 1 | No | G |
| Chloroform | CRF | 36 | 0 | NA | 111 | Α | Yes | 3 | No | G |
| Chlorohydrins (crude) | CHD | 17 | 0 | D | 1 | Α | Yes | 3 | .50-5 | G |
| o-Chloronitrobenzene | CNC | 42 | 0 | Ε | I | Α | No | N/A | .50-5, .50-73 | G |
| Coal tar crude bases | СТВ | 9 | 0 | D | 1 | Α | No | N/A | .50-5, .50-73, .55-1(e) | G |
| Coal tar naphtha solvent | NCT | 33 | 0 | D | Ш | Α | Yes | 1 | .50-73 | G |
| Coal tar pitch (molten) | СТР | 33 | 0 | Ε | Ш | Α | No | N/A | .50-73 | G |

^{***} This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***

^{2.} Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

^{3.} Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP,

CARUTHERSVILLE

C1-1101079

18-Apr-11

Hull #: 5545

Official #: CG034011

Page 2 of 8

| Cargo Identification | n | | | | | | | | tions of Carriage | |
|--|---------------------|---------------------------------------|---------------------|------------|--------------|--------------------|-------|-----------------|--|----------------------|
| Name | Chem Code CCW | Compat Group No 21 ² | Sub Chapter O | Grade E | Hull Type | Tank Group A | App'd | VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period G |
| Creosote | CRS | 21 | 0 | E | 111 | A | Yes | 1 | No | G |
| Cresols (all isomers) | CSC | 5 | 0 | NA | 111 | A | No | N/A | .50-73, .55-1(b) | G |
| Cresylate spent caustic | CRX | 3 | 0 | E | III | A | Yes | 1 | .55-1(f) | G |
| Cresylic acid tar | CTA | 19 ² | 0 | С | - II | A | Yes | 4 | .55-1(h) | G |
| Crotonaldehyde Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein) | CHG | 19 - | 0 | С | Ш | A | No | N/A | | G |
| Cyclohexanone | ССН | 18 | 0 | D | 111 | Α | Yes | 1 | .56-1(a), (b) | G |
| Cyclohexanone, Cyclohexanol mixture | CYX | 18 ² | 0 | E | Ш | Α | Yes | 1 | .56-1 (b) | G |
| Cyclohexylamine | СНА | 7 | 0 | D | 111 | Α | Yes | 1 | .56-1(a), (b), (c), (g) | G |
| Cyclopentadiene, Styrene, Benzene mixture | CSB | 30 | 0 | D | 111 | Α | Yes | 1 | .50-60, .56-1(b) | G |
| iso-Decyl acrylate | IAI | 14 | 0 | E | 111 | A | Yes | 2 | .50-70(a), .50-81(a), (b), .55-1(c) | G |
| Dichlorobenzene (all isomers) | DBX | 36 | 0 | E | | Α | Yes | 3 | .56-1(a), (b) | G |
| 1,1-Dichloroethane | DCH | 36 | 0 | C | 111 | Α | Yes | 1 | No | G |
| 2,2'-Dichloroethyl ether | DEE | 41 | 0 | D | П | A | Yes | 1 | .55-1(f) | G |
| graduate the state of the state | DCM | | 0 | NA | III | A | No | N/A | No | G |
| Dichloromethane | DDE | 43 | 0 | E | 111 | A | No | N/A | A THE RESIDENCE OF THE PARTY OF | G |
| 2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution | DAD | 0 1,2 | | A | 111 | Ā | No | N/A | | G |
| 2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution | DTI | 43 2 | 0 | E | 111 | Α | No | N/A | | G |
| 2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution | DPB | | 0 | C | 111 | A | Yes | 3 | No | G |
| 1,1-Dichloropropane | | 36 | | С | | | Yes | 3 | No | G |
| 1,2-Dichloropropane | DPP | 36 | 0 | С | 111 | A | Yes | 3 | No | G |
| 1,3-Dichloropropane | DPC | 36 | 0 | | 111 | A | | | No | G |
| 1,3-Dichloropropene | DPU | 15 | 0 | D | 11 | Α . | Yes | 4 | No | G |
| Dichloropropene, Dichloropropane mixtures | DMX | 15 | 0 | C | | A | Yes | 1 | .55-1(c) | G |
| Diethanolamine | DEA | 8 | 0 | E | III | A | Yes | 1 | | G |
| Diethylamine | DEN | 7 | 0 | С | III | A | Yes | 3 | .55-1(c) | G |
| Diethylenetriamine | DET | 7 2 | 0 | E | 111 | A | Yes | 1 | .55-1(c) | G |
| Diisobutylamine | DBU | 7 | 0 | D | - 111 | Α | Yes | 3 | .55-1(c) | |
| Diisopropanolamine | DIP | 8 | 0 | E | 111 | ΑΑ | Yes | 11 | .55-1(c) | G |
| Diisopropylamine | DIA | 7 | 0 | С | 11 | A | Yes | 3 | .55-1(c) | G |
| N,N-Dimethylacetamide | DAC | 10 | 0 | E | 111 | Α | Yes | 3 | .56-1(b) | |
| Dimethylethanolamine | DMB | 8 | 0 | D | 111 | Α | Yes | 1 | .56-1(b), (c) | G |
| Dimethylformamide | DMF | 10 | 0 | D | 111 | Α | Yes | 1 | .55-1(e) | G |
| Di-n-propylamine | DNA | 7 | 0 | С | Ш | Α | Yes | 3 | .55-1(c) | G |
| Dodecyldimethylamine, Tetradecyldimethylamine mixture | DOT | 7 | 0 | E | 111 | Α | No | N/A | | G |
| Dodecyl diphenyl ether disulfonate solution | DOS | 43 | 0 | # | 11 | Α | No | N/A | | G |
| EE Glycol Ether Mixture | EEG | 40 | 0 | D | 111 | Α | No | N/A | | G |
| Epichlorohydrin | EPC | 17 | 0 | D | | A | Yes | 3 | .50-5 | G |
| Ethanolamine | MEA | 8 | 0 | E | Ш | A | Yes | | .55-1(c) | G |
| Ethyl acrylate | EAC | 14 | 0 | С | 111 | Α | Yes | 2 | .50-70(a) .50-81(a), (b) | G |
| Ethylamine solution (72% or less) | EAN | 7 | 0 | Α | 11 | A | Yes | 6 | .55-1(b) | G |
| N-Ethylbutylamine | EBA | 7 | 0 | D | 111 | Α | Yes | 3 | .55-1(b) | G |
| N-Ethylcyclohexylamine | ECC | 7 | 0 | D | 111 | Α | Yes | 1 | .55-1(b) | G |
| Ethylene chlorohydrin | ECH | 20 | 0 | D | i | Α | Yes | 3 | .50-5, .50-73 | G |
| Ethylene cyanohydrin | ETC | 20 | 0 | Ε | Ш | Α | Yes | 1 | No | G |
| Ethylenediamine | EDA | 7 2 | 0 | D | III | А | Yes | 1 | .55-1(c) | G |
| Ethylene dichloride | EDC | 36 ² | 0 | С | 111 | Α | Yes | 1 | No | G |
| Ethylene glycol hexyl ether | EGH | 40 | 0 | E | 111 | Α | No | N/A | No | G |



rial #: C1-1101079 Pated: 18-Apr-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP,

CARUTHERSVILLE

Hull #: 5545

Official #: CG034011

Page 3 of 8

| Cargo Identification | | | | | | | | | tions of Carriage | |
|--|---------------------|--------------------------|---------------------|--------------|---------------------|--------------------|--------------------------|----------------------|---|----------------------|
| | | | | | | - | | ecovery | 0 115 1 10055 | |
| Name Ethylene glycol monoalkyl ethers | Chem Code EGC | Compat Group No 40 | Sub Chapter O | Grade D/E | Hull Type III | Tank Group A | App'd (Y or N) Yes | VCS Category 1 | Special Requirements in 46 CFR 151 General and Mat'ls of No | Insp. Period G |
| Ethylene glycol propyl ether | EGP | 40 | 0 | Ε | 111 | Α | Yes | 1 | No | G |
| 2-Ethylhexyl acrylate | EAI | 14 | 0 | Е | 111 | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| Ethyl methacrylate | ETM | 14 | 0 | D/E | 111 | Α | Yes | 2 | .50-70(a) | G |
| 2-Ethyl-3-propylacrolein | EPA | 19 ² | 0 | Ε | Ш | Α | Yes | 1 | No | G |
| Formaldehyde solution (37% to 50%) | FMS | 19 ² | 0 | D/E | 111 | Α | Yes | 1 | .55-1(h) | G |
| Furfural | FFA | 19 | 0 | D | Ш | Α | Yes | 1 | .55-1(h) | G |
| Glutaraldehyde solution (50% or less) | GTA | 19 | 0 | NA | 111 | Α | No | N/A | No | G |
| Hexamethylenediamine solution | НМС | 7 | 0 | E | 111 | Α | Yes | 1 | .55-1(c) | G |
| Hexamethyleneimine | НМІ | 7 | 0 | С | 11 | Α | Yes | 1 | .56-1(b), (c) | G |
| Hydrocarbon 5-9 | HFN | | 0 | С | 111 | Α | Yes | 1 | .50-70(a), .50-81(a), (b) | G |
| 2-Hydroxyethyl acrylate | HAI | 0 1.2 | 0 | E | ı | Α | Yes | 3 | .50-5, .50-70(a), .50-73, .50-81(a), (| G |
| Isoprene | IPR | 30 | 0 | Α | 111 | A | No | N/A | .50-70(a), .50-81(a), (b) | G |
| Isoprene, Pentadiene mixture | IPN | 1000 | 0 | В | 111 | Α | No | N/A | | G |
| Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor) | KPL | 5 | 0 | NA | Ш | А | No | N/A | .50-73, .56-1(a), (c), (g) | G |
| Mesityl oxide | MSO | 18 ² | 0 | D | Ш | Α | Yes | 1 | No | G |
| Methyl acrylate | MAM | 14 | 0 | С | 111 | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| Methylcyclopentadiene dimer | MCK | 30 | 0 | С | - 111 | Α | Yes | 1 | No | G |
| Methyl diethanolamine | MDE | 8 | 0 | E | 111 | Α | Yes | 1 | .56-1(b), (c) | G |
| 2-Methyl-5-ethylpyridine | MEP | 9 | 0 | Ε | 111 | Α | Yes | 1 | .55-1(e) | G |
| Methyl methacrylate | MMM | | 0 | C | 111 | A | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| 2-Methylpyridine | MPR | 9 | 0 | D | 111 | Α | Yes | 3 | .55-1(c) | G |
| | MSR | 30 | 0 | D | 111 | A | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| alpha-Methylstyrene Morpholine | MPL | 7 2 | 0 | D | 111 | Α | Yes | 1 | .55-1(c) | G |
| | NTB | 42 | 0 | E | 1 | A | Yes | 3 | .50-5, .50-73 | G |
| Nitrobenzene | NTE | 42 | 0 | | <u>i</u> | A | No | N/A | .50-81, .56-1(b) | G |
| Nitroethane | NPM | 42 | 0 | D | | A | Yes | 1 | .50-81 | G |
| 1- or 2-Nitropropane | NIE | 42 | 0 | E | 111 | A | No | N/A | .50-5, .50-73 | G |
| o-Nitrotoluene | PDE | 30 | 0 | A | 111 | ^ | No | N/A | .50-70(a), .50-81 | G |
| 1,3-Pentadiene | PER | 36 | 0 | NA NA | 111 | A | No | N/A | | G |
| Perchloroethylene | | 21 | 0 | E | - 111 | Α | Yes | 3 | .50-5, .50-73 | 2 yr |
| Phenol (or solutions with 5% or more Phenol) | PHN | | | E | 150 | | Yes | 1 | No | G |
| Phthalic anhydride (molten) | PAN | 11 7 ² | 0 | | 111 | A | Yes | 1 | .55-1(e) | G |
| Polyethylene polyamines | PEB | | 0 | E | 111 | Α | | 1 | .55-1(c) | G |
| iso-Propanolamine | MPA | 8 | 0 | E | | A | Yes | | .56-1(b), (c) | G |
| Propanolamine (iso-, n-) | PAX | 8 | 0 | E | 111 | A | Yes | 1 | | G |
| iso-Propylamine | IPP | 7 | 0 | A | 11 | A | No | N/A | .55-1(e) | G |
| Pyridine | PRD | 9 | 0 | С | | A | Yes | 7 | | G |
| Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide) | SAP | | 0 | na e | 111 | Α | No | N/A | | G |
| Sodium aluminate solution (45% or less) | SAU | 5 | 0 | NA | III | Α | No | N/A | | G |
| Sodium chlorate solution (50% or less) | SDD | 0 1.2 | | NA | 111 | A | No | N/A | | G |
| Sodium hypochlorite solution (20% or less) | SHQ | 5 | 0 | NA | 111 | Α . | No | N/A | | G |
| Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less) | SSH | 0 1,2 | | NA | III | Α | Yes | 1 | .50-73, .55-1(b) | |
| Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm) | SSI | 0 1.2 | | NA | 111 | А | No | N/A | | G |
| Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm) | SSJ | 0 1,2 | | NA | Ш | Α | No | N/A | | G |
| Styrene (crude) | STX | | 0 | D | 111 | Α | Yes | 2 | No | G |



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP,

CARUTHERSVILLE

C1-1101079

18-Apr-11

Hull #: 5545

Official #: CG034011

Page 4 of 8

| Cargo Identificatio | n | | | | | | | | A No .55-1(c) .50-70(b) .50-73, .56-1(a), (b), (c), (g) .50-5, .50-73 No .50-73, .56-1(a) No .50-73, .56-1(a) .55-1(b) .55-1(b) .55-1(b) .55-1(a) .56-1(a), (b), (c) .50-73, .56-1(a), (c) .4, .56-1(b) .50-73, .56-1(a), (c) | | | | |
|---|--------|--------------------|----------------|-------|-----------------------|---------------|----------|-----------------|--|-------|--|--|--|
| | | | | | | _ | | Recovery | 2 10 055 | 1. | | | |
| Name | Chem | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | (Y or N) | VCS Category | 151 General and Mat'ls of | Insp. | | | |
| 1,1,2,2-Tetrachloroethane | TEC | 36 | 0 | NA | III | Α | No | N/A | | G | | | |
| Tetraethylenepentamine | TTP | 7 | 0 | E | 111 | A | Yes | 1 | | G | | | |
| Tetrahydrofuran | THF | 41 | 0 | С | 111 | A | Yes | 1 | | G | | | |
| Toluenediamine | TDA | 9 | 0 | E | Н | Α | No | N/A | | G | | | |
| o-Toluidine | TLI | 9 | 0 | E | 11 | Α | Yes | 3 | .50-5, .50-73 | G | | | |
| 1,2,4-Trichlorobenzene | TCB | 36 | 0 | E | 111 | Α | Yes | 1 | No | G | | | |
| 1,1,2-Trichloroethane | TCM | 36 | 0 | NA | 111 | Α | Yes | 1 | .50-73, .56-1(a) | G | | | |
| Trichloroethylene | TCL | 36 ² | 0 | NA | 111 | Α | Yes | 1 | No | G | | | |
| 1,2,3-Trichloropropane | TCN | 36 | 0 | Ε | П | Α | Yes | 3 | .50-73, .56-1(a) | G | | | |
| Triethanolamine | TEA | 8 2 | 0 | Ε | 111 | Α | Yes | 1 | .55-1(b) | G | | | |
| Triethylamine | TEN | 7 | 0 | С | П | Α | Yes | 3 | .55-1(e) | G | | | |
| Triethylenetetramine | TET | 7 2 | 0 | E | 111 | Α | Yes | 1 | .55-1(b) | G | | | |
| Triphenylborane (10% or less), caustic soda solution | TPB | 5 | 0 | NA | 111 | Α | No | N/A | .56-1(a), (b), (c) | G | | | |
| Trisodium phosphate solution | TSP | 5 | 0 | NA | Ш | Α | No | N/A | .50-73, .56-1(a), (c). | G | | | |
| Urea, Ammonium nitrate solution (containing more than 2% NH3) | UAS | 6 | 0 | NA | 111 | Α | No | N/A | .56-1(b) | G | | | |
| Vanillin black liquor (free alkali content, 3% or more). | VBL | 5 | 0 | NA | 111 | Α | No | N/A | .50-73, .56-1(a), (c), (g) | G | | | |
| Vinyl acetate | VAM | 13 | 0 | C | III | A | Yes | 2 | | G | | | |
| | VND | 13 | 0 | E | III | Α | No | N/A | .50-70(a), .50-81(a), (b) | G | | | |
| Vinyl neodecanate | VNT | 13 | 0 | D | 111 | A | Yes | 2 | .50-70(a), .50-81, .56-1(a), (b), (c), (| G | | | |
| Vinyltoluene | V 14 1 | 13 | | | - 10 | | 103 | | | | | | |
| Subchapter D Cargoes Authorized for Vapor Contr | ol | | | | | | | | | | | | |
| Acetone | ACT | 18 ² | D | С | | Α | Yes | 1 | | | | | |
| Acetophenone | ACP | 18 | D | Ε | | Α | Yes | 1 | | | | | |
| Alcohol(C12-C16) poly(1-6)ethoxylates | APU | 20 | D | E | | Α | Yes | 1 | | | | | |
| Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates | AEB | 20 | D | E | | Α | Yes | 1 | | | | | |
| Amyl acetate (all isomers) | AEC | 34 | D | D | | Α | Yes | 1 | | | | | |
| Amyl alcohol (iso-, n-, sec-, primary) | AAI | 20 | D | D | | Α | Yes | 1 | | | | | |
| Benzyl alcohol | BAL | 21 | D | E | | Α | Yes | 1 | | | | | |
| Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters) | BFX | 20 | D | Е | | Α | Yes | 1 | | | | | |
| Butyl acetate (all isomers) | BAX | 34 | D | D | | Α | Yes | 1 | | | | | |
| Butyl alcohol (iso-) | IAL | 20 ² | D | D | | Α | Yes | 1 | | | | | |
| Butyl alcohol (n-) | BAN | 20 ² | D | D | | Α | Yes | 1 | and the second s | | | | |
| Butyl alcohol (sec-) | BAS | 20 ² | D | С | | Α | Yes | 1 | | | | | |
| Butyl alcohol (tert-) | BAT | | D | С | | Α | Yes | 1 | | | | | |
| Butyl benzyl phthalate | ВРН | 34 | D | E | | Α | Yes | 1 | | | | | |
| | BUE | 32 | | | | Α | Yes | 1 | | | | | |
| Butyl toluene | CLS | 22 | D | F | | A | Yes | 1 | The second secon | | | | |
| Caprolactam solutions | CHX | 31 | D | C | | Α | Yes | 1 | Management of the control of the con | | | | |
| Cyclohexane | | | D | E | | A | Yes | 1 | | | | | |
| Cyclohexanol | CHN | 20 | | D/E | | | Yes | 2 | Secretary and a secretary and | | | | |
| 1,3-Cyclopentadiene dimer (molten) | CPD | 30 | D | | and the second second | A | Yes | 1 | | | | | |
| p-Cymene | CMP | 32 | D | D | | A | | | | | | | |
| iso-Decaldehyde | IDA | 19 | D | E | | A | Yes | 1 | | | | | |
| n-Decaldehyde | DAL | 19 | D | E | | A | Yes | 1 | | | | | |
| Decene | DCE | 30 | D | D | | A | Yes | 1 | | | | | |
| Decyl alcohol (all isomers) | DAX | 20 ² | D | E | | A | Yes | 1 | | | | | |
| n-Decylbenzene, see Alkyl(C9+)benzenes | DBZ | 32 | D | E | | Α | Yes | 1 | | | | | |
| Diacetone alcohol | DAA | 20 ² | D | D | | Α | Yes | 1 | | | | | |



C1-1101079

18-Apr-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP, CARUTHERSVILLE

Hull #: 5545

Official #: CG034011

Page 5 of 8

| Cargo Identification | on | | | | | İ | | | tions of Carriage | |
|---|------|--------------------|-----|-------|--------------|---------------|-------------------|-----------------|---|-------|
| | | | | | | | | Recovery | | |
| Name | Chem | Compat Group No | Sub | Grade | Hull Type | Tank Group | App'd (Y or N) | VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. |
| ortho-Dibutyl phthalate | DPA | 34 | D | Е | | Α | Yes | 1 | | |
| Diethylbenzene | DEB | 32 | D | D | | Α | Yes | 1 | | |
| Diethylene glycol | DEG | 40 2 | D | E | | Α | Yes | 1 | | |
| Diisobutylene | DBL | 30 | D | С | | Α | Yes | 1 | | |
| Diisobutyl ketone | DIK | 18 | D | D | | Α | Yes | 1 | | |
| Diisopropylbenzene (all isomers) | DIX | 32 | D | E | | Α | Yes | 1 | | |
| Dimethyl phthalate | DTL | 34 | D | Е | | Α | Yes | 1 | | |
| Dioctyl phthalate | DOP | 34 | D | Е | | Α | Yes | 1 | | |
| Dipentene | DPN | 30 | D | D | | Α | Yes | 1 | | |
| Diphenyl | DIL | 32 | D | D/E | | Α | Yes | 1 | | |
| Diphenyl, Diphenyl ether mixtures | DDO | 33 | D | Ε | | Α | Yes | 1 | | |
| Diphenyl ether | DPE | 41 | D | {E} | | Α | Yes | 1 | | |
| Dipropylene glycol | DPG | 40 | D | E | | Α | Yes | 1 | | |
| Distillates: Flashed feed stocks | DFF | 33 | D | Е | | Α | Yes | 1 | | |
| Distillates: Straight run | DSR | 33 | D | E | | Α | Yes | 1 | | |
| Dodecene (all isomers) | DOZ | 30 | D | D | | A | Yes | 1 | | |
| 2-Ethoxyethyl acetate | EEA | 34 | D | D | | A | Yes | 1 | | |
| Ethoxy triglycol (crude) | ETG | 40 | D | E | | Α | Yes | 1 | | |
| Ethyl acetate | ETA | 34 | D | C | | A | Yes | 1 | | |
| Ethyl acetoacetate | EAA | 34 | D | E | | A | Yes | 1 | | |
| | EAL | 20 ² | D | C | | Α | Yes | 1 | | |
| Ethyl alcohol | ETB | 32 | D | C | | A | Yes | 1 | | |
| Ethylbenzene | EBT | 20 | D | D | | A | Yes | 1 | | |
| Ethyl butanol | | | | | | | | | | |
| Ethyl tert-butyl ether | EBE | 41 | D | С | | A | Yes | 1 | | |
| Ethyl butyrate | EBR | 34 | D | D | | A | Yes | 1 | | |
| Ethyl cyclohexane | ECY | 31 | D | D | | Α | Yes | 1 | | |
| Ethylene glycol | EGL | 20 ² | D | E | | A | Yes | 1 | | |
| Ethylene glycol butyl ether acetate | EMA | 34 | D | Е | | Α | Yes | 1 | | |
| Ethylene glycol diacetate | EGY | 34 | D | E | | Α | Yes | 1 | | |
| Ethylene glycol phenyl ether | EPE | 40 | D | Е | | Α | Yes | 1 | | |
| Ethyl-3-ethoxypropionate | EEP | 34 | D | D | | A | Yes | 1 | | |
| 2-Ethylhexanol | EHX | 20 | D | Е | | Α | Yes | 1 | | |
| Ethyl propionate | EPR | 34 | D | С | | Α | Yes | 1 | | |
| Ethyl toluene | ETE | 32 | D | D | | Α | Yes | 1 | | |
| Formamide | FAM | 10 | D | E | | Α | Yes | 1 | | |
| Furfuryl alcohol | FAL | 20 2 | D | E | | Α | Yes | 1 | | |
| Gasoline blending stocks: Alkylates | GAK | 33 | D | A/C | | Α | Yes | 1 | | |
| Gasoline blending stocks: Reformates | GRF | 33 | D | A/C | | Α | Yes | 1 | | |
| Gasolines: Automotive (containing not over 4.23 grams lead per | GAT | 33 | D | С | | Α | Yes | 1 | | |
| gallon) | | | | | | | | | | |
| Gasolines: Aviation (containing not over 4.86 grams of lead per gallon) | GAV | 33 | D | С | | Α | Yes | 1 | | |
| Gasolines: Casinghead (natural) | GCS | 33 | D | A/C | | Α | Yes | 1 | | |
| Gasolines: Polymer | GPL | 33 | D | A/C | | A. | Yes | 1 | | |
| Gasolines: Straight run | GSR | 33 | D | A/C | | Α | Yes | 1 | | |
| Glycerine | GCR | 20 ² | D | E | | Α | Yes | 1 | | |
| Heptane (all isomers), see Alkanes (C6-C9) (all isomers) | HMX | 31 | D | С | | Α | Yes | 1 | | |
| Heptanoic acid | HEP | 4 | D | E | | Α | Yes | 1 | | |
| Heptanol (all isomers) | HTX | 20 | D | D/E | | Α | Yes | 1 | | |



Serial #: C1-1101079
Dated: 18-Apr-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Shipyard: ST LOUIS SHIP,

CARUTHERSVILLE

Hull #: 5545

Official #: CG034011 Page 6 of 8

| Cargo Identif | ication | | | | | | | Condi | tions of Carriage | |
|--|---------------------|-----------------|---------------------|------------|---|--------------------|--------------------------|----------------------|---|-----------------|
| | | | | | | | - | Recovery | | |
| Name Heptene (all isomers) | Chem Code HPX | Group No 30 | Sub Chapter D | Grade C | Hull Type | Tank Group A | App'd (Y or N) Yes | VCS Category 2 | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| Heptyl acetate | HPE | 34 | D | Е | | Α | Yes | 1 | | |
| Hexane (all isomers), see Alkanes (C6-C9) | HXS | 31 ² | D | В/С | | Α | Yes | 1 | | |
| Hexanoic acid | НХО | 4 | D | E | | Α | Yes | 1 | | |
| Hexanol | HXN | 20 | D | D | | Α | Yes | 1 | | |
| Hexene (all isomers) | HEX | 30 | D | С | | Α | Yes | 2 | | |
| Hexylene glycol | HXG | 20 | D | E | | Α | Yes | 1 | | |
| Isophorone | IPH | 18 ² | D | Е | *************************************** | Α | Yes | 1 | | |
| Jet fuel: JP-4 | JPF | 33 | D | E | | Α | Yes | 1 | | |
| Jet fuel: JP-5 (kerosene, heavy) | JPV | 33 | D | D | | Α | Yes | 1 | | |
| Kerosene | KRS | 33 | D | D | | Α | Yes | 1 | | |
| Methyl acetate | MTT | 34 | D | D | | A | Yes | 1 | | |
| Methyl alcohol | MAL | 20 ² | D | С | | Α | Yes | 1 | | |
| Methylamyl acetate | MAC | 34 | D | D | | Α | Yes | 1 | | |
| Methylamyl alcohol | MAA | 20 | D | D | | Α | Yes | 1 | | |
| Methyl amyl ketone | MAK | 18 | D | D | | Α | Yes | 1 | | |
| Methyl tert-butyl ether | MBE | 41 2 | D | | | Α | Yes | 1 | | |
| Methyl butyl ketone | MBK | 18 | D | С | | Α | Yes | 1 | | |
| Methyl butyrate | MBU | 34 | D | С | | Α | Yes | 1 | | |
| | MEK | 18 ² | D | C | | A | Yes | 1 | | |
| Methyl happyl ketone | MHK | 18 | D | D | | Α | Yes | 1 | | |
| Methyl heptyl ketone | MIK | 18 ² | D | С | | A | Yes | 1 | | |
| Methyl isobutyl ketone | MNA | 32 | D | E | | Α | Yes | 1 | | |
| Methyl naphthalene (molten) | | | | | | | | 1 | | |
| Mineral spirits | MNS | 33 | D | D | | Α | Yes | | | |
| Myrcene | MRE | 30 | D | D | | Α | Yes | 1 | | |
| Naphtha: Petroleum | PTN | 33 | D | # | | Α . | Yes | 11 | | |
| Naphtha: Solvent | NSV | 33 | D | D | | A | Yes | 1 | | |
| Naphtha: Stoddard solvent | NSS | 33 | D | D | | Α | Yes | 1 | | |
| Naphtha: Varnish makers and painters (75%) | N∨M | 33 | D | С | | Α | Yes | 1 | | |
| Nonane (all isomers), see Alkanes (C6-C9) | NAX | 31 | D | D | | Α | Yes | 1 | | |
| Nonene (all isomers) | NON | 30 | D | D | | A | Yes | 2 | | |
| Nonyl alcohol (all isomers) | NNS | 20 ² | D | E | - | А | Yes | 1 | | |
| Nonyl phenol | NNP | 21 | D | E | | Α | Yes | 1 | | |
| Nonyl phenol poly(4+)ethoxylates | NPE | 40 | D | E | | Α | Yes | 1 | | |
| Octane (all isomers), see Alkanes (C6-C9) | OAX | 31 | D | С | | Α | Yes | 1 | | |
| Octanoic acid (all isomers) | OAY | 4 | D | Е | | Α | Yes | 1 | | |
| Octanol (all isomers) | OCX | 20 2 | D | E | | Α | Yes | 1 | | |
| Octene (all isomers) | OTX | 30 | D | С | | Α | Yes | 2 | | |
| Oil, fuel: No. 2 | OTW | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, fuel: No. 2-D | OTD | 33 | D | D | | Α | Yes | 1 | | |
| Oil, fuel: No. 4 | OFR | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, fuel: No. 5 | OFV | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, fuel: No. 6 | OSX | 33 | D | E | | Α | Yes | 1 | | |
| Oil, misc: Crude | OIL | 33 | D | C/D | | Α | Yes | 1 | | |
| Oil, misc: Diesel | ODS | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, misc: Gas, high pour | OGP | 33 | D | E | - | Α | Yes | 1 | | |
| Oil, misc: Lubricating | OLB | 33 | D | E | | Α | Yes | 1 | | |
| Oil, misc: Residual | ORL | 33 | D | E | | Α | Yes | 1 | | |



Serial #: C1-1101079

Dated: 18-Apr-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506

Official #: CG034011

Page 7 of 8

Shipyard: ST LOUIS SHIP, CARUTHERSVILLE

Hull #: 5545

| Cargo Identifica | tion | | | | | Conditions of Carriage | | | | | | |
|--|---------------------|--------------------------|---------------------|------------|--------------|------------------------|--------------------------|----------------------|--|--|--|--|
| Ourgo radiimio | | | | | | | Vapor F | Recovery | | | | |
| Name Dil, misc: Turbine | Chem Code OTB | Compat Group No 33 | Sub Chapter D | Grade E | Hull Type | Tank Group A | App'd (Y or N) Yes | VCS Category 1 | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Perio | | |
| | PPE | 34 | D | D | | Α | Yes | 1 | | | | |
| n-Pentyl propionate | PIO | 30 | D | D | | Α | Yes | 1 | | | | |
| in the second se | PIP | 30 | D | D | | Α | Yes | 1 | | | | |
| peta-Pinene Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether | PAG | 40 | D | E | | Α | Yes | 1 | | | | |
| Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate | PAF | 34 | D | Ε | | Α | Yes | 1 | | | | |
| | PLB | 30 | D | E | | Α | Yes | 1 | | | | |
| Polybutene | PGC | 40 | D | E | | Α | Yes | 1 | | - | | |
| Polypropylene glycol | IAC | 34 | D | С | | Α | Yes | 1 | | | | |
| so-Propyl acetate | PAT | 34 | D | С | | Α | Yes | 1 | | | | |
| n-Propyl acetate | IPA | 20 ² | D | С | | Α | Yes | 1 | | | | |
| so-Propyl alcohol | PAL | 20 ² | D | С | | Α | Yes | 1 | | | | |
| n-Propyl alcohol | PBY | 32 | D | D | | Α | Yes | 1 | | | | |
| Propylbenzene (all isomers) | IPX | 31 | D | D | | Α | Yes | 1 | | | | |
| iso-Propylcyclohexane | PPG | 20 ² | D | E | | Α | Yes | 1 | | | | |
| Propylene glycol | PGN | | D | D | | Α | Yes | 1 | | | | |
| Propylene glycol methyl ether acetate | PTT | 30 | D | D | | Α | Yes | 1 | | | | |
| Propylene tetramer | SFL | 39 | D | E | | Α | Yes | 1 | | | | |
| Sulfolane | TTG | 40 | D | E | | Α | Yes | 1 | | | | |
| Tetraethylene glycol | THN | | D | E | | Α | Yes | 1 | | | | |
| Tetrahydronaphthalene | TOL | 32 | D | C | | A | Yes | 1 | The second secon | | | |
| Toluene | TCP | | D | E | | A | Yes | 1 | | | | |
| Tricresyl phosphate (less than 1% of the ortho isomer) | | | D | E | | A | Yes | | | | | |
| Triethylbenzene | TEB | | D | E | | A | Yes | | | | | |
| Triethylene glycol | TEG | | | E | | A | Yes | | The second secon | | | |
| Triethyl phosphate | TPS | | D | | | A | Yes | | | | | |
| Trimethylbenzene (all isomers) | TRE | | D | {D} | | A | Yes | | | ACCRECATION OF THE PARTY OF THE | | |
| Trixylenyl phosphate | TRP | | D | E | | | Yes | | | | | |
| Undecene | UDC | | D | D/E | | A | Yes | | | | | |
| 1-Undecyl alcohol | UND | | D | E | | A | | | | | | |
| Xylenes (ortho-, meta-, para-) | XLX | 32 | D | D | | A | Yes | i I | | | | |



Department of Homeland Security United States Coast Guard

Serial #: C1-1101079

18-Apr-11

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 11506 Official #: CG034011

Page 8 of 8

Shipyard: ST LOUIS SHI

Hull #: 5545

Explanation of terms & symbols used in the Table:

Cargo Identification

Chem Code

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2 The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Note 1

Subchapter O Note 3

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility problems. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425

Note 2

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those harmfable and confidential instead in 40 CFR Table 30.25-1.
Those hazardous cargoes listed in 46 CFR Part 450 Ad 46 CFR Part 153 Table 2.
Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges

Grade

Subchapter Subchapter D

> The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
> Flammable liquid cargoes, as defined in 46 CFR 30-10.22

A, B, C D. E Note 4

Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the

cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No. The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category: Category 1

The specified cargo's provisional classification for vapor control systems

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of passing all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems