



BARGE "KIRBY 11518"

ULLAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 CENTER	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 CENTER	00-1/8	- 00-1/8	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-5/8	- 00-5/8	00-3/4	- 00-3/4	01-0/8	- 01-0/8
3 CENTER	00-1/8	- 00-1/8	00-3/8	- 00-3/8	00-1/2	- 00-1/2	00-5/8	- 00-5/8	00-7/8	- 00-7/8	01-0/8	- 01-0/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 2 CENTER IS - 00-3/8"
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 2 CENTER, THE TRIM CORRECTED ULLAGE IS 3'-11 5/8"

LENGTH BETWEEN DRAFT MARKS: 162'-09"

July 14, 2005

PRECISION MEASUREMENT
 & ANALYSIS, INC.
 P.O. Box 2092
 Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "KIRBY 11518"

3 CENTER ULLAGE TABLE

CAPACITIES GIVEN IN WHOLE BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 17'-10 1/4"

Table with columns for depth (0 FT. to 9 FT.) and gauge height (IN 0, 1/4, 1/2, 3/4). Rows list capacity values for each depth and gauge height combination.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7. CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL. CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK. CAPACITY TABLE ONLY APPLIES TO ULLAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE. GAUGE POINT: (HERMETIC) LOCATED 1'-00" OFF CENTERLINE AND 29'-01" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT & ANALYSIS, INC. P.O. Box 2092 Pearland, Texas 77588 http://www.pmacorp.net

Handwritten signature of Precision Measurement & Analysis, Inc.

