



**United States of America  
Department of Homeland Security  
United States Coast Guard**

Certification Date: 13 Mar 2023  
Expiration Date: 13 Mar 2024

# Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name	Official Number	IMO Number	Call Sign	Service
KIRBY 16806	980959			Tank Barge

Hailing Port	Hull Material	Horsepower	Propulsion
HOUSTON, TX	Steel		
UNITED STATES			

Place Built	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
BEAUMONT, TX	31Dec1991	27Nov1991	R-1179	R-1179		R-260.0
UNITED STATES						

Owner	Operator
KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES	KIRBY INLAND MARINE, LP 18350 MARKET STREET CHANNELVIEW, TX 77530 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers	
0 Second Mates	0 Radio Officers	0 Second Assistant Engineers	
0 Third Mates	0 Able Seamen	0 Third Assistant Engineers	
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers	
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer	

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

**Route Permitted And Conditions Of Operation:**  
**---Lakes, Bays, and Sounds plus Limited Coastwise---**

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth & Ninth Coast Guard District's Tank Barge Streamlined Inspection

**\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\***

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection				This certificate issued by: K. A. Hantal, CDR, USCG, By direction Officer in Charge, Marine Inspection Marine Safety Unit Port Arthur Inspection Zone
Date	Zone	A/P/R	Signature	



# Temporary Certificate of Inspection

Vessel Name: KIRBY 16806

Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

### ---Hull Exams---

Exam Type	Next Exam	Last Exam	Prior Exam
DryDock	30Apr2028	12Apr2018	10Nov2008
Internal Structure	31Mar2028	13Mar2023	12Apr2018

### --- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization: FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity	Units	Highest Grade Type	Part151 Regulated	Part153 Regulated	Part154 Regulated
16253	Barrels	LFG	Yes	No	No

### \*Hazardous Bulk Solids Authority\*

Not Authorized

### \*Loading Constraints - Structural\*

Tank Location Description	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1S	835	7.400
2P	835	7.400

### \*Conditions Of Carriage\*

Hull Type	Max Load (S/T)	Max Draft (ft/in)	Max Density (lbs/gal)	Route
II (BDI)	1671	8'5"	5.2	LBS, R, LC (0-12)
II (BUT)	1535	8'1"	4.8	LBS, R, LC (0-12)
II (IBT)	1478	7'11"	4.7	LBS, R, LC (0-12)
II (BTN)	1578	8'2"	4.96	LBS, R, LC (0-12)
II (IBL)	1595	8'3"	5.0	LBS, R, LC (0-12)
II (PRP)	1279	7'4"	4.2	LBS, R, LC (0-12)
II (PPL)	1326	7'6"	4.3	LBS, R, LC (0-12)
II (BHB)	1671	8'5"	7.4	LBS, R, LC (0-12)

Only those cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #VN91010899 dated 14 Feb 01 and LFG cargoes may be carried.

Inspected and approved for the carriage of specified liquefied flammable gases at a pressure not to exceed 260 PSIG relief valve setting and at temperatures not less than ambient (0-115 degrees F).

Mixtures of the subchapter "D" LFG cargoes Butane, Isobutane, Butylene, Propane and Propylene are also authorized for carriage subject to the loading and stability constraints of the least dense gas cargo in the mixture specified above.

Mixtures of subchapter "O" and "D" LFG cargoes not specified above must be approved by Commandant (MTH) prior to being authorized for carriage.

PPM is the only "O" and "D" LFG mixture presently authorized. No other cargoes may be carried when PPM is carried unless the PPM piping system is separated from the other cargo piping systems.

Vessel authorized special seasonal loading constraints for the carriage of propylene (PPL) not to exceed 89% of cargo tank capacity and in accordance with operating procedures approved by MSO New Orleans letter serial #16711 dated 02MAY96.

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of cargo in each tank may exceed the uniformly loaded tank cargo weight by at most 5 percent.



# Temporary Certificate of Inspection

Vessel Name: KIRBY 16806

### --- Inspection Status ---

#### \*Cargo Tanks\*

Tank Id	Internal Exam			External Exam		
	Previous	Last	Next	Previous	Last	Next
1S	10Nov2008	12Apr2018	30Apr2028	12Mar2021	13Mar2023	31Mar2028
2P	10Nov2008	12Apr2018	30Apr2028	12Mar2021	13Mar2023	31Mar2028

#### Hydro Test

Tank Id	Safety Valves	Previous	Last	Next
1S	04Mar2023	-	-	-
2P	04Mar2023	-	-	-

### ---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

### --- Fire Fighting Equipment ---

#### \*Fire Extinguishers - Hand portable and semi-portable\*

Quantity	Class Type
1	B-II

\*\*\*END\*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name **KIRBY 16806**

Shipyard **NEWPARK SHPBLDG**

Official # **D980959**

Page 1 of 1

Hull # **1281**

### List of Authorized Cargoes

Cargo Identification						Conditions of Carriage	
Name	Chem Code	Compat		Grade	Hull Type	Note	Special Requirements in 46 CFR 151 General and Mats of Construction
		Group No	Exc				
<b>Authorized Subchapter O Cargoes</b>							
Butadiene	BDI	30	N	LFG	II		50-70(a), 50-73
Benzene hydrocarbon mixtures (having 10% Benzene or more)	BHB	32	N		III		50-60
Benzene Toluene Xylene mixtures (having 10% Benzene or more)	BTX	32	N	B/C	III		50-60
Propylene Propane, MAPP gas mixture (containing 12% or less MAPP gas)	PPM	30	Y	LFG	III		50-79 (c) only

### Explanation of terms & symbols used in the Table:

#### Cargo Identification

Name	The proper shipping name as listed in 46 CFR Table 151.05
Chem Code	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual
Compatibility Group No	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Exceptions (Exc)	Indication of whether or not there are exceptions to the compatibility chart for the given cargo. See Appendix I to 46 CFR Part 150.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "( )" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. <ul style="list-style-type: none"> <li>A, B, C Flammable liquid cargoes as defined in 46 CFR 30-10.22</li> <li>D, E Combustible liquid cargoes as defined in 46 CFR 30-10.15</li> <li>NA, NF Those subchapter O cargoes which are not classified as a flammable or combustible liquid</li> <li># No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.</li> </ul>
Hull Type	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo. see 46 CFR 151.10-1. <ul style="list-style-type: none"> <li>I Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1)</li> <li>II Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3)</li> <li>III Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4)</li> </ul>

#### Conditions of Carriage

Note	See Certificate of Inspection for explanation of symbols used in this column.
------	---

# Law Valve of Texas

## Pressure Barge Checklist

Barge Number KIRBY 16806 Bobby Davis  
 Product \_\_\_\_\_  
 Date 2/15/2023  
 Official # \_\_\_\_\_

Emergency Shutdown System		Valves	
New or old?	<u>NEW</u>	Headers	Qty <u>SEE BELOW</u>
Manufacturer	<u>ERL</u>	Valves on pipeline	Qty <u>SEE BELOW</u>
Size		Valves per tank	Qty <u>2 EA</u>
Settings	<u>90 PSI &amp; 55 PSI</u>	Spew tubes	Qty <u>2</u>
ESD Pull Boxes	Qty <u>4 - 2-L, 2-R</u>	Sample stations	Qty <u>N/A</u>
ESD Master Box	Qty <u>1</u>		
Versa-quick exhaust	Qty <u>12</u> Size <u>1/4</u>		

### NOTES

4EA 6x8 Consolidate RV 1910Q SET-260PSI  
 4EA 1x1 AQUATROL RV SET-480PSI

Gauges			
Pressure gauges	Qty _____	Size _____	Rating _____
Pressure gauges	Qty _____	Size _____	Rating _____
Pressure gauges	Qty _____	Size _____	Rating _____
Pressure gauges on pi	Qty _____	Size _____	Rating _____
Temp gauges	Qty _____	Size _____	Length _____ Rating _____
Gauge manifold	Qty _____		
Needle valve	Qty _____	Size _____	

### NOTES

10EA 8" 300 Butterfly - 10EA - 6 AIR ; 4 GEAR  
 4EA 10" 300 Butterfly - 4EA - AIR  
 2EA 6" 300 Butterfly - 2EA GEAR  
 1EA 8" 300 WARREN BV - Q4000 GEAR

### INTERNAL STICKS:

QUOTE 3 STICKS EACH FOR SPANS

2-HIGH DWG 249AC 094B  
 2-MID DWG 249AC 091B  
 2-LOW DWG 249AC 093B  
 2-COAXIAL OUTER DWG 249AC 096B  
 2- " " INNER DWG 249AC 097B

Bottom sticks 249AC 093B (T# 21 B# 90)  
 MID BOW " " 249AC 091B 68-140  
 High " " 249AC 094B (T# 134 B# 180)  
 COAXIAL Short 249AC 096B 145-197  
 Long 249AC 097B 0-

