

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 06 Feb 2023 Expiration Date: 06 Feb 2024

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel	Name

Official Number

IMO Number

Call Sign

Service

KIRBY 18700

1204652

Tank Barge

Hailing Port

WILMINGTON, DE

Hull Material

Steel

Horsepower

Propulsion

UNITED STATES

Place Built

Delivery Date

Keel Laid Date

Gross Tons

Net Tons

DWT

Length

ASHLAND CITY, TN

21Nov2007 18Oct2007

R-1197

R-1197

R-220.0

UNITED STATES

Owner

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES Operator

KIRBY INLAND MARINE, LP 18350 MARKET STREET CHANNELVIEW, TX 77530

UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Oilers

0 Chief Mates

0 First Class Pilots

0 First Assistant Engineers

0 Second Mates

0 Radio Officers

0 Second Assistant Engineers0 Third Assistant Engineers

0 Third Mates

0 Able Seamen

0 Licensed Engineers

Master First Class Pilot
 Mate First Class Pilots

Ordinary Seamen
 Deckhands

0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

--- Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth Coast Guard District's Tank Barge Streamlined Inspection Program

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Date	Zone	A/P/R	Signature

This certificate issued by:

K. A. Hantal, CDR, USCG, By direction

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 06 Feb 2023 **Expiration Date:** 06 Feb 2024

Temporary Certificate of Inspection

Vessel Name: KIRBY 18700

(TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

30Nov2027

20Nov2017

21Nov2007

Internal Structure

30Nov2027

06Feb2023

20Nov2017

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

18900

Barrel

Yes

No

Hazardous Bulk Solids Authority

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	620	13.6
2 P/S	626	13.6
3 P/S	494	13.6

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
H	2502	9ft 6in	13.6	R
II	2502	9ft 6in	13.6	LBS
Ш	3328	11ft 6in	13.6	R
Ш	3328	11ft 6in	13.6	LBS

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #C1-0703266, dated October 22, 2007, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

Benzene Prohibition

Vessels is not covered by a benzene monitoring program IAW 46 CFR 197, Subpart C. Vessel is not authorized to carry Benzene or Benzene containing cargoes with a Benzene concentration of 0.5% or more.

Per 46 CFR 151.10(c) (2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

^{*}Stability and Trim*



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 06 Feb 2023 Expiration Date: 06 Feb 2024

Temporary Certificate of Inspection

Vessel Name: KIRBY 18700

Thermal fluid heater may only be operated when carrying Grade "E" cargoes.

Thermal fluid heater may only be operated when carrying Grade "E" cargoes. The vessel is inspected and approved for the carriage of Grade "E" combustible liquids when transported in molten form at elevated temperatures.

--- Inspection Status ---

Cargo Tanks

	Internal Exam			External Exa	m	
Tank Id	Previous	Last	Next	Previous	Last	Next
1 P/S	21Nov2007	20Nov2017	30Nov2027	. .	2	-
2 P/S	21Nov2007	20Nov2017	30Nov2027	=	*	=:
3 P/S	21Nov2007	20Nov2017	30Nov2027	•)	≅.	-
			Hydro Test			
Tank Id	Safety Valves		Previous	Last	Next	
1 P/S	-		•	=:		
2 P/S	= 2		4	-	-	
3 P/S	8		-	: - :	÷	

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

3

40-B

END

^{*}Thermal Fluid Heater Restriction*



C1-0703266

22-Oct-07

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 18700

Official #: 1204652

Shipyard Trinity Marine Products

Tank Group Information	Cargo I	dentifica	lion		Cargo		Tanks		Carg Tran		Enviror		Fire	Special Requin	ements		П
Trill Grp Tanks in Group	Density	Press.	Temp	Huti Typ	Seg	1000	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec	Temp
A #1P,#1S,#2P,#2S,#3P, #3S	13 6	Atmos	Elev	#	1ii 2ii	Integral Gravity	Open	Restr	П	G-1	NR	NA	Portable	40-1(f)(1), 50- 70(a), 50-70(b),	55-1(h), (j), 56-1(a), (c), (d), (e), (f), (g),	NR	Yes

Notes 1 Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks

- 2 Under Environmental Control, Handling Space NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3 Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location

List of Authorized Cargoes

Cargo Identification						Conditions of Carriage					
							Vapor R		1	-	
Name	Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank	App d (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	FR Insp Pence	
Authorized Subchapter O Cargoes											
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	100	Α	No	N/A	.50-81 50-86	0	
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	11	Α	No	N/A		G	
Camphor oil (light)	CPO	18	0	D	Н	Α	No	N/A		G	
Caustic potash solution	CPS	5 2	0	NA	111	Α	No	N/A	.50-73, 55-1(j)	G	
Caustic soda solution	CSS	5 2	0	NA	HI	Α	No	N/A	.50-73, 55-1(j)	G	
Chloroform	CRF	36	0	NA	01	Α	No	N/A	No	G	
Creosote	CCW	21 2	0	Е	11)	Α	No	N/A	No	G	
Cresols (all isomers)	CRS	21	0	Ę	III	Α	No	N/A	No	G	
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#		A	No	N/A	No	G	
Ethylene cyanohydrin	ETC	20	0	E	HI	A	No	N/A	No	G	
Ethylene glycol hexyl ether	EGH	40	0	Е	(II	Α	No	N/A	No	G	
Ethylene glycol propyl ether	EGP	40	0	Ε	10	Α	No	N/A	No	G	
2-Ethylhexyl acrylate	EAI	14	0	Ε	111	Α	No	N/A	50-70(a), 50-81(a), (b)	G	
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	III	Α	No	N/A	No	G	
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G	
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0		Ш	Α	No	N/A	.50-73 ₋ 55-1(j)	G	
Sodium chlorate solution (50% or less)	SDD	0 1.2	0	NA	111	Α	No	N/A	50-73	G	
Styrene monomer	STY	30	0	D	- (1)	Α	No	N/A	.50-70(a) .50-81(a) (b)	G	
Trisodium phosphate solution	TSP	5	0	NA	H	Α	No	N/A	50-73, 56-1(a), (c).	G	
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	101	Α	No	N/A	.50-73, 56-1(a), (c), (g)	G	
Vinyl neodecanate	VND	13	0	E	III	A	No	N/A	50-70(a), 50-81(a), (b)	G	





Dated

Serial #: C1-0703266

22-Oct-07

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 18700 Official #: 1204652

Page 2 of 2

Shipyard Trinity Marine

4603

Explanation of terms & symbols used in the Table:

Cargo	Identif	ication
-------	---------	---------

Name Chem Code

The proper shipping name as listed in 46 CFR Table 30 25-1, 46 CFR Table 151 05, and 46 CFR Part 153 Table 2

The three fetter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual Certain mixtures of cargoes may not have a CHRIS Code assigned

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II In accordance with 46 CFR 150 130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 45 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carnage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility.

Note 1 Note 2

Subchapter D

Subchapter O

Compatability Group No

For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second. Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425

Subchapter

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Those flammable and combustible liquids listed in 46 CFR Table 30 25-1

Those hazardous cargoes listed in 46 CFR Table 151 05 and 46 CFR Part 153 Table 2

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of

A. B. C DE Note 4

Flammable liquid cargoes, as defined in 46 CFR 30-10 22 Combustible liquid cargoes, as defined in 46 CFR 30-10 15

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the

cargo grade based on Manufacturers data and ensure that the barge is authorized for carnage of that grade of cargo

Those subchapter O cargoes which are not classified as a flammable or combustible fluud

No flammablity/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available

Hull Type 101

NΑ

The required barge hull classification for carnage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1) Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151 10-1(b)(3).

Designed to carry products of sufficent hazard to require a moderate degree of control. See 46 CFR 151 10-1(b)(4).

Not applicable to barges certificated under Subchapter D

Conditions of Carriane

Tank Group Vapor Recovery Approved (Y or N)

The vessel's tank group (as defined in Section 4) which is authorized for carnage of the named cargo

Yes. The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No. The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N)

The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

Yes. The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No. The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category Category 1

The specified cargo's provisional classification for vapor control systems

must use appropriate friction factors, vapor densities and vapor growth rates

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155 750, 33 CFR 156 120, 33 CFR 156 170, 46 CFR 35 35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39 20-11) and the pressure drop calculations (46 CFR 39 30-1(b))

Category 2

(Polymerizes) Polymenzation and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurzation. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge. Manne Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39 20-9 This requirement is in addition to the requirements of Category 1

Category 4

(Polymerzes and highly toxic) Must comply with requirements of Categories 1, 2 and 3

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1

Category 6 Category 7

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5 (High vapor pressure and polymenzes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems