

United States of America Department of Homeland Security United States Coast Guard

24 Oct 2024 Certification Date: 24 Oct 2025 **Expiration Date:**

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT. This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

For ships on internation remporary Certificate of Inspection is is receipt on board sali	at voyages this certificate fulfills the sued under the provision of Title 46 it vessel of the original certificate of	IMO Numi	ber	Call Sign		70
Name	Official Number	****			Tank Bar	ge
	1217132					
BY 27759		500 (1904)			Company of the Compan	
				Propulsion		
ng Port	Hull Mate	erial Hor	sepawer			
LMINGTON, DE	Steel					
LIVINIO	0.000					
NITED STATES				10 × 70 × 10 × 10 × 10 × 10 × 10 × 10 ×	and the state of t	
411 me			C - Tone	Net Tons	DWT	Length
	Delivery Da	te Keel Laid Date	Gross Tons R-1632	R-1632		R-300.0
ce Built	20Feb2		B 1-	1-		1-0
SHLAND CITY, TN	201 602		14"			
NITED STATES						may be defined problem. The first contribution are completely and contribute to the contribution of the co
1 41 5 mm m.	2000	The second secon	orator	e periodical description and a deficiency control and a description and a description and a second and a second		100
CONTRACTOR OF CO		V	erator IRBY INLANI	MARINE LP		
IRBY INLAND MARINE	P	4.0	COTO MARTIO	STREET		
E MALIGH DRIVE, SOIT	E 1000		MANNELVIE	W, 1X //300		
IOLICTON IX //UU/			NITED STAT			
INITED STATES			15-1000	nel Included in	which there	must be
	and with the following lice	censed and unlice	nsed Person	DSS Operator	S.	
INITED STATES This vessel must be mann Certified Lifeboatmen, (Certified Tankermen,	0 HSC Type Rati	ny, and o on	n Oilers		
Centiled Elleboation	0 Licensed Mates	0 Chief Engineers		o ono.		
0 Masters	0 First Class Pilots	0 First Assistant En	gineers			
0 Chief Mates	0 Radio Officers	0 Second Assistant	Engineers			
0 Second Mates	0 Able Seamen	0 Third Assistant E	ngineers			
0 Third Mates		0 Licensed Engine	ers			
0 Master First Class Pilot	n Deckhands	0 Qualified Member	r Engineer	ersons in addition	on to crew, ar	nd no Others. Total
0 Mate First Class Pilots	av carry n Passengers	, 0 Other Persons	in crew, UP	C130(13 11 40 3 m)		
0 Master First Class Pilot 0 Mate First Class Pilots In addition, this vessel m	ay carry or association				Control of the Contro	
Persons allowed.	Marian Control of the	ion:				
Route Permitted AndLakes, Bays, a	Conditions of Operation	imited Coas	twise			- whollo
Lakes, Bays, a	nd Sounds plus i	and it is a second	iles from st	ore between S	t. Marks an	d Carrapelle,
	aniu, not more and				01-20	() (2) If this
Also, in fair weathe Florida. This vessel has been vessel is operated it is operated in the control of the con		EL WINNE MINISTER	ination into	erval per 46 (FR 31.10-21	be inspected using
This vessel has been vessel is operated is salt water intervals	granted a fresh wat	er service exam	any 12 mont	n period, the	in writing	as soon as this
This vessel has been uessel is operated i	n salt water more th	(a) (1) and the	cognizant	COST NOTE TO		PA
salt water intervals change in status occ	per an C. R			's Tank Bard	e Streamlin	ed Inspection Progr
change in	- ninating in the	Eighth Coast G	dard Discret			
This tank barge is	76.L C. A. P. M. C.	OFDIEICATE I	NEORMATIC	N***	The second second second second second second second second	Servin Charge Marin
***SEF NEXT PAGE	FOR ADDITIONAL	CERTIFICATE	Port Arthur	TX, UNITED ST	ATES, the O	olicable vessel inspec
Latin this Inspection for	FOR ADDITIONAL r Certification having be fety Unit Port Arthur ce t regulations prescribed	een completed at	in all respects	s, is in conformi	ty with the ap	Direction
With this inspection to	fety Unit Port Arthur ce	rtified the vesser,		and the state of t	h	1
HISPECTION, MAN	1 -aculations prescribed	Hieround	This ce	1	nv.	2 1 4 2 1 mg 1 m
Anni	Jairi Citotii			B. T. INAGA	(1, GS-13, US	SCG, By direction
Date Z	one A/P/R	Signature	Officer in	The same of the sa	co	
Date		NAME OF THE OWNER, OF THE OWNER, WHEN THE OWNE		Marine	Safety Unit I	OIL MILL
1				The second secon	Special management of the special spec	
			Inspection	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TRANSPORT OF THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TR		OMB Approved No. 1625



United States of America Department of Homeland Security **United States Coast Guard**

24 Oct 2024 Certification Date: 24 Oct 2025 **Expiration Date:**

Temporary Certificate of Inspection

(TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to CCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

28Feb2029

16May2019

20Feb2009

16May2019

Internal Structure

31Oct2029

24Oct2024

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

COMBUSTIBLE LIQUIDS

Total Capacity

Highest Grade Type

Part151 Regulated

Part153 Regulated

Part154 Regulated

27800

Barrels

D

No

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number

Max Cargo Weight per Tank (short tons)

Maximum Density (lbs/gal)

855

8.74

1 P/S

860

8.74

2 P/S 3 P/S

732

8.74

Loading Constraints - Stability

Loading Co	onstraints - Stability	2.4	Max Density	Route Description
Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	(lbs/gal) 13.6	LBS
4444	3784	10ft 0in	13.6	R
11	3784	10ft 0in	13.6	LBS
111	4662	11ft 9in	13.6	R
111	4662	11ft 9in	13.0	

Vessels is not covered by a benzene monitoring program per 46 CFR 197, Subpart C. Vessel is not authorized to carry Benzene or Benzene containing cargoes with a Benzene concentration of 0.5% or more.

Thermal fluid heater may only be operated when carrying grade "E" cargoes.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to *Stability and Trim* 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Fuel Tanks

Internal Examinations

Tank ID

Previous

Last

Next

Aft main deck

20Feb2009



United States of America Department of Homeland Security United States Coast Guard

24 Oct 2024 Certification Date: 24 Oct 2025 **Expiration Date:**

Temporary Certificate of Inspection

Vessel Name: KIRBY 27759

Cargo Tanks*	Internal Exam		Next	External Exam Previous	Last	Next
Tank Id	Previous	Last	31Oct2034	-		-
1 P/S	16May2019	24Oct2024	31Oct2034	_		•
2 P/S	16May2019	24Oct2024	310ct2034	-	-	-
3 P/S	16May2019	24Oct2024	Hydro Test			
Tank Id	Safety Valves	5	Previous	Last 20Feb2009	Next -	
1 P/S 2 P/S	•		-	20Feb2009 20Feb2009	F	
3 P/S	-		~			
Boilers/Steam Piping Maximum Steam Pressure	Allowed: 150			Mountings I	nspection	
Boiler/Piping ID	Hydro Inspe Previous	ction Last 20Feb2009	Next	Opened -	Removed -	
800SB-0811-1430	Fireside Ins	pection		Waterside	Inspection Last	Nex
Boiler/Piping ID 800SB-0811-1430	Previous	Last 20Feb2009	Next -	Previous -	-	-

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

B-II

END



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: Kirby 27759 Official #: 1217132

Shipyard: Trinity Ashland City

Hull #: 4639

Tank Group Information Cargo Identification				Tanks	inks Cargo Transfer		Environmental Control		Fire	Special Requirements							
Tnk Grp Tanks in Group	Density	Press	Temp.	Hull Typ	Cargo Seg Tank	-	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction		Temp Cont
A #1P/S, #2P/S, #3P/S	13.6	Atmos	Elev	11	1 ii 2 ii	Integral Gravity	PV	Open	11	G-1	NR	NA	Portable	40-1(f)(1), 50- 70(a), 50-70(b), 50-73, 50-81(b),	55-1(h), (j), 56-1(a), (c), (d), (e), (f), (g),	NR	Yes

- Notes 1 Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks
 - 2 Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied
 - 3 Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical

List of Authorized Cargoes

Cargo Identification								Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Ri App'd (Y or N)	VCS	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp Period		
Authorized Subchapter O Cargoes			L									
Adiponitrile	ADN	37	0	E	II	Α	No	N/A	No	G		
Alkyl(C7-C9) nitrates	AKN	342	0	NA	111	Α	No	N/A	50-81, 50-86	G		
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	11	Α	No	N/A	No	G		
Butyraldehyde (all isomers)	BAE	19	0	С	III	Α	No	N/A	55-1(h)	G		
Camphor oil (light)	CPO	18	0	D	11	A	No	N/A	No	G		
Carbon tetrachloride	CBT	36	0	NA	111	Α	No	N/A	No	G		
Caustic potash solution	CPS	52	0	NA	111	Α	No	N/A	50-73, 55-1(j)	G		
Caustic soda solution	CSS	5 ²	0	NA	111	Α	No	N/A	50-73, 55-1(j)	G		
Chlorobenzene	CRB	36	0	D	111	Α	No	N/A	No	G		
Chloroform	CRF	36	0	NA	111	A	No	N/A	No	G		
Creosate	CCM	212	0	E	111	Α	No	N/A	No	G		
Cresols (all isomers)	CRS	21	0	E	111	Α	No	N/A	No	G		
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	11	Α	No	N/A	No	G		
Ethylene cyanohydrin	ETC	20	0	E	III	A	No	N/A	No	G		
Ethylene glycol hexyl ether	EGH	40	0	E	III	A	No	N/A	No	G		
Ethylene glycol propyl ether	EGP	40	0	E	111	Α	No	N/A	No	G		
2-Ethylhexyl acrylate	EAI	14	0	E	111	Α	No	N/A	50-70(a), 50-81(a) (b)	G		
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	!!!	Α	No	N/A	No	G		
Isoprene	IPR	30	0	Α	111	A	No	N/A	50-70(a), .50-81(a), (b)	G		
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	, KPL	5	0	NA	111	Α	No	N/A	50-73, 56-1(a), (c), (g)	G		
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxic	le) SAP		0		111	Α	No	N/A	50-73, .55-1(j)	G		
Sodium chlorate solution (50% or less)	SDD	0 1.2	0	NA	111	A	No	N/A	50-73	G		
Styrene monomer	STY	30	0	D	111	A	No	N/A	50-70(a), 50-81(a), (b)	G		
Trisodium phosphate solution	TSP	5	0	NA	111	Α	No	N/A	50-73 56-1(a). (c)	G		
Vanillin black liquor (free alkali content, 3% or more)	VBL	5	0	NA	111	A	No	N/A	50-73, 56-1(a), (c) (g)	G		
Vinyl acetate	VAM	13	0	Ç	III	Α	No	N/A	50-70(a), 50-81(a), (b)	G		
Vinyl neodecanate	VND	13	0	E	III	Α	No	N/A	50-70(a), 50-81(a), (b)	G		

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: Kirby 27759 Official #: 1217132

Page 2 of 2

Shipyard: Trinity Ashland

C1-0900094

25-Mar-10

Hull #: 4639

Serial #:

Explanation of terms & symbols used in the Table:

Cargo Identification

Name

Chem Code

Compatability Group No.

Note 1

Note 2

Subchapter

Subchapter D Note 3

A, B, C D, E

Hull Type

NA

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2 The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual

Certain mixtures of cargoes may not have a CHRIS Code assigned.

The cargo reactive group number assigned for compatibility determinations in 48 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

(202) 372-1425 See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.

e subchapter in Title 40 Coue or Federal Regulations under what the Sergo has both recently.

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those hazardous cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for camage of that grade of cargo.

Flammable liquid cargoes, as defined in 46 CFR 30-10.22.

Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for camage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

Conditions of Carriage

Vapor Recovery Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 155.120, 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 and 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. The specified cargo's provisional classification for vapor control systems.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Calegory 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7 (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5 (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems.