United States of America Department of Homeland Security United States Coast Guard Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT. This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection.

Vessel Name	receipt on board si		fficial Number		lumber	Call Sign	Service	
			158899				Tank B	arge
KIRBY 28065			10099					
3								
Hailing Port						Dronulsion		
WILMINGTON	I. DE		Hull Material	н	lorsepower	Propulsion		
	10.5. Jane Lengt		Steel			ж. <u>1</u>		
UNITED STAT	TES							
Place Built			Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
AHSLAND CI	TY, TN		101-10004	27 102004	R-1632	R-1632	1632	R-300.0
			13Jul2004	27Jul2004	I-	ŀ	1032	I-0
UNITED STAT	TES							
Owner					erator			
KIRBY INLAN		P				MARINE, LP		
55 WAUGH D					3350 Market S hannelview, T			
HOUSTON, T					NITED STAT			
UNITED SIA	120							
This vessel m	ust be manned	d with the fol	lowing license	ed and unlicer	nsed Personne	el. Included in	which there m	nust be
0 Certified Life	eboatmen, 0 C	Certified Tan	kermen, 0 HS	C Type Ratir	ng, and 0 GME	OSS Operators	•	
0 Masters		0 Licensed Ma	tes 0 Ch	ief Engineers	0	Oilers	3	
0 Chief Mates	j	0 First Class P	Pilots 0 First	st Assistant Eng	ineers			
0 Second Mat		0 Radio Office		cond Assistant E	Ingineers			
0 Third Mates		0 Able Seame		ird Assistant Eng	-			
0 Master First		0 Ordinary Sea	amen 0 Lic	ensed Engineers	5			
0 Mate First C		0 Deckhands		alified Member B				
		carry 0 Pass	engers, 0 Oth	ner Persons ir	n crew, 0 Pers	ons in addition	to crew, and	no Others. Total
Persons allow								
Route Perm	itted And Co	nditions Of	Operation:					
1	Bays, and							
						12) milos fro	m chora hat	toon St Marks and
Also, in fai Carrabelle,		ly, limited	i coastwise,	not more th	nan tweive ()	12) Miles Iro	m snore betv	ween St. Marks and
		wheed a factor	h	wice evamin	ation interv	al in accorda	nce with 46	CFR 31.10-21(a)
(2) If this	vessel is c	poperated in	salt water	more than 6	months in an	ny 12 month p	eriod, the t	vessel must be
inspected us	ing salt wat	er interval	ls per 46 CE	'R 31.10-21(a	a)(1) and the	e cognizant 0	CMI must be	notified in
writing as s	soon as this	change in s	status occur	·s.				
	KT PAGE FO					**		
							the Officer !	n Charge Marine
With this Insp	ection for Cer	tification hav	ing been com	pleted at Fre	eport, TX, UN	ty with the ann	icable vessel	n Charge, Marine inspection laws and
the rules and	regulations pr	escribed the	reunder.	an respects,	io in comonnii			
		eriodic/Re-Ins			This certific	ate issued by:	DA	
Date	Zone	A/P/R	Signa	ature	E. M.	CARRENO	DP, USCG, E	BY DIRECTION
			3		Officer in Charge,	, Marine Inspection		
							ton-Galvestor	1
					Inspection Zone			
	T							

		United Sta	ates of America	Certification	n Date: 05 Dec 2019
25-22		Department of	Homeland Security	Expiration	Date: 05 Dec 2020
			tes Coast Guard		
	Тетро	rary Cert	ificate of I	Inspection	1
Vessel Name: KIRBY 28	065				
Program (TBSIP). Inspection acti	in the Eighth & Nint vities aboard this ba sues concerning this	arge shall be conduc	ted in accordance w	reamlined Inspection with its Tank Barge con-Galveston.
Hull Exam	IS				
Exam Type	Next	Exam	Last Exam	Prior Exa	ım
DryDock	30Nc	v2024	06Nov2014		
Internal Structur	e 30No	ov2024	05Dec2019	06Nov20	14
Liquid/Ga	as/Solid Cargo	Authority/Conditi	ons		
Authorization:	Grade A (max. 25	psia Reid) and Lower F azardous Cargoes.		ble Liquids Identified in	1 46 CFR Table 30.25
Total Capacity	Units	Highest Grade Type	Part151 Regulated	Part153 Regulated	Part154 Regulated
28281	Barrels	А	Yes	No	No
*Hazardous Bu	Ik Solids Authority	•			
Not Authorized					
***	tusinta Ctructural*				
•	traints - Structural*	Max Cargo Weight p	or Tank (short tans)	Maximum Densi	ity (lbs/aal)
Tank Number		828	Sel Tarik (Short toris)	13.6	ty (iba/gai)
1S		829		13.6	
1P		825		13.6	
2S				13.6	
2P		825		13.6	
3S		764			
3P		764		13.6	
Loading Cons	straints - Stability				
Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density R (lbs/gal)	loute Description	
	3608	9ft 6in	13.6		
П	3608	9ft 6in	13.6		
111	4604	11ft 6in	13.6		
111	4604	11ft 6in	13.6		
Conditions O	f Carriage				
Only those care 2004, may be o	goes named in the ve carried, and then only	essel's Cargo Authority A r in the tanks indicated. sponsible for ensuring th	When the vessel is ca	rrying cargoes contain	ing greater than 0.5%
Per 46 CFR 15 CFR 150 are m	0.130; the Person in net. Cargoes must b	Charge of the vessel is e checked for compatib	responsible for ensurin ility using the figures, to	ables, and appendices	s of 46 CFR 150 in

CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR conjunction with the compatibility group numbers from the "Compat Group No" column listed in the vessel's CAA.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.



United States of America Department of Homeland Security United States Coast Guard Certification Date:05 Dec 2019Expiration Date:05 Dec 2020

Temporary Certificate of Inspection

Vessel Name: KIRBY 28065

Per 46 CFR 151.10-15(c) the max tank weights reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter O cargoes at shallower drafts, the barge(s) should always be loaded uniformly.

In accordance with 46 CFR part 39.1017 and 39.5001(e) this vessel's VCS has been evaluated and approved for multibreasted tandem loading with this vessel.

Vapor Control Authorization

In accordance with 46 CFR Part 39, excluding part 39.4000, this vessel's vapor collection system has been inspected to the plans approved by MSC Letter C2-0400740 dated April 12, 2004, and has been found acceptable for the collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column. The VCS system has been approved with a pressure side of 3.0 psig P/V valve. The cargo tank top is suitable for a maximum allowable working pressure (MAWP) of 3.5 psig.

---- Inspection Status ----

Cargo Tanks						
	Internal Exam			External Exam	i	
Tank Id	Previous	Last	Next	Previous	Last	Next
1S	-	06Nov2014	06Nov2024	-	-	-
1P	-	06Nov2014	06Nov2024	-	-	-
2S	-	06Nov2014	06Nov2024	-	-	-
2P	-	06Nov2014	06Nov2024	-	-	-
3S	-	06Nov2014	06Nov2024	- ,	-	-
3P	-	06Nov2014	06Nov2024	-	-	-
			Hydro Test			
Tank Id	Safety Valves	;	Previous	Last	Next	
1S	-		-	10Sep2004	- '	
1P	-		-	10Sep2004	-	
2S	-		-	10Sep2004	-	
2P	-		-	10Sep2004	-	
3S	-		-	10Sep2004	-	
3P	-		-	10Sep2004	-	
Conditional Portat		nguisher R				

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity	Class Type
2	40-B

END



Department of Homeland Security **United States Coast Guard**

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28065

Official #: 1158899

Shipyard: Trinity Ashland City Huli #: 4470

.56-1(a), (b), (c), (g)

Tank Group Information	Cargo I	dentificatio	ол		Cargo		Tanks		Caro Tran		Environ Control	mental	Fire	Special Requirer	nents	T	Т
Tni Grr Tanks in Group	Density	Press.	Temp.	Hull Typ	Seg Tank	T	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	T∈ P
a #1P/s, #2P/s, #3P/s	13.6	Atmos.	Amb.	II	1ii 2ii	Integrat Gravity	PV	Closed	п	G-1	NR	NA	Portable	.50-81(a), .50- 81(b), .50-86,	55-1(b), (c), (e), (f), (h), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	1

Notes: 1. Under Environmental Control. Tanks, NR means that the tank aroup is suitable only for those carooes which require no environmental control in the caroo tanks.

2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

L

2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution

Cargo Identification							Co	nditio	ns of Carriage
							Vapor R	есоvегу	
Name	Chem Code	Compat Group	Sub Chapter	Grade	Huli Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 15 General and Mat'ls of Construction
Authorized Subchapter O Cargoes									
Acetonitrile	ATN	37	0	С	111	A	Yes	3	No
Acrytonitrile	ACN	15 ²	0	С	11	Α	Yes	4	.50-70(a), .55-1(e)
Adiponítrile	ADN	37	0	E	П	A	Yes	1	No
Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	111	A	No	N/A	.50-81, .50-86
Aminoethylethanolamine	AEE	8	0	E	111	A	Yes	1	.55-1(b)
Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	111	А	No	N/A	.50-73, .56-1(a), (b), (c)
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	[]]	A	No	N/A	.56-1(a). (b), (c), (f), (g)
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	11	A	No	N/A	No
Benzene	BNZ	32	0	C	m	A	Yes	1	.50-60
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 2	0	NA	111	A	Yes	1	.50-60
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	BHA	32 2	0	NA		А	Yes	1	.50-60, .56-1(b), (d), (1), (g)
Senzene, Toluene, Xylene mixtures (10% Benzene or more)	ΒΤΧ	32	0	B/C	- III	A	Yes	1	.50-60
Butyl acrylate (all isomers)	BAR	14	0	D		A	Yes	2	.50-70(a), .50-81(a), (b)
Butyl methacrylate	BMH	14	0	D		A	Yes	2	.50-70(a), .50-81(a), (b)
Butyraldehyde (all isomers)	BAE	19	0	c	111	A	Yes	1	.55-1(h)
Camphor oil (light)	CPO	18	0	D	11	A	No	N/A	No
Carbon tetrachloride	CBT	36	0	NA	111	A	No	N/A	No
Chemical Oil (refined, containing phenolics)	COD	21	0	E	11	A	No	N/A	.50-73
Chlorobenzene	CRB	36	ō	D	111	A	Yes	1	No
Chloroform	CRF	36	0	E	111	A	Yes	3	No
Coal tar naphtha solvent	NCT	33	0	D	111	A	Yes	1	.50-73
Creosote	CCV	V 21 ²	0	E	ni	A	Yes		No
Cresols (all isomers)	CRS	21	0	Ë	111	A	Yes	1	No
Cresylate spent caustic	CSC		0	NA	111	A	No		.50-73, .55-1(b)
Cresylic acid tar	CRX		0		ni -	A	Yes	1	.55-1(1)
Crotonaldehyde	CTA	19 ⁻²		c		A	Yes	4	.55-1(h)
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropy acrolein)	/I CHO		0		I	A	No	N/A	No
Cyclohexanone	CCH	18	0	D	111	A	Yes	1	.56-1(a), (b)
Cyclohexanone, Cyclohexanol mixture	CYX	18 2	0	E	[1]	A	Yes	1	.56-1 (b)
Cyclohexylamine	CHA	. 7	0	 D	111	A	Yes		.56-1(a), (b), (c), (g)
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	111	A	Yes		.50-60, .56-1(b)
so-Decyl acrylate	IAI	14	ō	E		A	Yes		.50-70(a), .50-81(a), (b), .55-1(c)
Dichiorobenzene (all isomers)	DBX		0	 E	 111	A	Yes	3	.56-1(a), (b)
1.1-Dichloroethane	DCH		ŏ	C	111	A	Yes		No
2.2'-Dichloroethyl ether	DEE	41	0	D	<u> </u>	A	Yes		.55-1(f)
Dichloromethane	DCN		ŏ	NA		A	No	N/A	No
			<u> </u>					34763	

43 This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. *** ***

0

NA

111

А

No

N/A

DDE



Vessel Name: KIRBY 28065 Official #: 1158899

Page 2 of 7

Shipyard: Trinity Ashland City Hull #: 4470

Cargo Identification							Со	nditio	ns of Carriage
	1		[1 1			Vapor Re		
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1.		NA	Ш	A	No	N/A	.56-1(a), (b), (c), (g)
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution (70% or les			0			A	No	N/A	.55-1(b)
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 2	0	NA		Α	No	N/A	.56-1(a), (b), (c), (g)
1,1-Dichloropropane	DPB	36	<u> </u>	<u> </u>		A	Yes	3	No
1,2-Dichloropropane	DPP	36	0	С		A	Yes	3	No
1,3-Dichloropropane	DPC	36	0	C	111	Α	Yes	3	No
1,3-Dichloropropene	DPU	15	0	D	11	A	Yes	4	No
Dichloropropene, Dichloropropane mixtures	DMX	15	0	NA	11	A	Yes	1	No
Diethanolamine	DEA	8	0	E	111	A	Yes	1	.55-1(c)
Diethylamine Diethylamine	DEN	7	0	С	111	A	Yes	3	.55-1(c)
Diethylenetriamine	DET	7 2	0	E		A	Yes	1	.56-1(c)
Diisobutylamine	DBU	7	0	D		A	Yes	3	.55-1(c)
Diisopropanolamine	DIP	8	0	E		A	Yes	1	.55-1(c)
Diisopropylamine	DIA	7	0	С		A	Yes	3	.55-1(c)
N,N-Dimethylacetamide	DAC	10	0	E	111	Α	Yes	3	.56-1(b)
Dimethylethanolamine	DMB	8	0	D	111	A	Yes	1	.56-1(b), (c)
Dimethylformamide	DMF	10	0	D	111	Α	Yes	1	.55-1(e)
Di-n-propylamine	DNA	7	<u> </u>	С	11	Α	Yes	3	.55-1(c)
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	<u> </u>	E		<u>A</u>	No	N/A	.56-1(b)
Ethanolamine	MEA	8	0	E	111	A	Yes	1	.55-1(c)
Ethyl acrylate	EAC	14	0	C	111	A	Yes	2	.50-70(a), .50-81(a), (b)
Ethylamine solution (72% or less)	EAN	7	0	A	11	A	No	N/A	.55-1(b)
N-Ethyibutylamine	EBA	7	0	D	III	A	Yes	3	.55-1(b)
N-Ethylcyclohexylamine	ECC	7	0	D	111	А	Yes	1	.55-1(b)
Ethylene cyanohydrin	ETC	20	0	E	111	A	Yes	1	No
Ethylenediamine	EDA	7 2	0	D		A	Yes	1	.55-1(c)
Ethylene dichloride	EDC	36 2	0	C	Ш	A	Yes	1	No
Ethylene glycol hexyl ether	EGH	40	0	Ę		A	No	N/A	No
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	111	A	Yes	1	No
Ethylene glycol propyl ether	EGP	40	0	Ë		A	Yes	1	No
2-Ethylhexyl acrylate	EAI	14	0	Ε		A	Yes	2	.50-70(a), .50-81(a), (b)
Ethyl methacrylate	ETM	14	0	D/E	Ш	A	Yes	2	.50-70(a)
2-Ethyl-3-propylacrolein	EPA	19 2	0	E	111	A	Yes	1	No
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E	111	A	Yes	1	.55-1(h)
Furfural	FFA	19	0	E	111	Α	Yes	1	.55-1(h)
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	111	А	No	N/A	No
Hexamethylenediamine solution	HMC	7	0	Ë	111	А	Yes	1	.55-1(c)
Hexamethyleneimine	HMI	7	0	С	11	А	Yes	1	.56-1(b), (c)
Hydrocarbon 5-9	HFN		0		111	А	Yes	1	.50-70(a), .50-81(a), (b)
Isoprene	IPR	30	0	Α	111	A	No	N/A	.50-70(a), .50-81(a), (b)
Isoprene, Pentadiene mixture	IPN		0		111	A	No	N/A	.50-70(a), .55-1(c)
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (c), (g)
Mesityl oxide	MSO	18 2	0	D	111	A	Yes	1	No
Methyl acrylate	MAM	14	0	С	111	A	Yes	2	.50-70(a), .50-81(a), (b)
Methylcyclopentadiene dimer	MCK	30	0	С	111	A	Yes	1	No
Methyl diethanolamine	MDE	8	0	E	10	А	Yes	1	.56-1(b), (c)
2-Methyl-5-ethylpyridine	MEP	9	0	Е	111	A	Yes	1	.55-1(e)
Methyl methacrylate	MMM	14	0	С	111	A	Yes	2	.50-70(a), .50-81(a), (b)
2-Methylpyridine	MPR	9	0	D	111	A	Yes	3	.55-1(c)
aipha-Methylstyrene	MSR	30	0	D	111	A	Yes	2	.50-70(a), .50-81(a), (b)
Morpholine	MPL	7 2	ō	 D	111	A	Yes	1	.55-1(c)
1- or 2-Nitropropane	NPM		ō	D	111	A	Yes	1	.50-81
						· · · · ·		•	



Vessel Name: KIRBY 28065 Official #: 1158899

Page 3 of 7

Shipyard: Trinity Ashland City Hull #: 4470

	••••••••••••••••••••••••••••••••••••••		~~~~	New York Consideration of the					
Cargo Identification							Co	nditio	ns of Carriage
							Vapor Re	ecovery	
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
		•• •			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		(Constant Maris of Constantion
1,3-Pentadiene	PDE	30	о	٨	111	٨	N .	b) /6	.50-70(a), .50-81
Perchloroethylene	PER	30		A NA	 111	A 	No No	<u>N/A</u>	No
Polyethylene polyamines	PEB	7 2		E		A	Yes	<u>N/A</u>	.55-1(e)
iso-Propanoiamine	MPA	8	ō	 E		<u>A</u>	Yes	1	.55-1(c)
Propanolamine (iso-, n-)	PAX	8	0	Ē		A	Yes	, 1	.56-1(b), (c)
iso-Propylamine	IPP	7	0	A	11	A	Yes	5	.55-1(c)
Pyridine	PRD	9	0	C	HI	A	Yes	1	.55-1(e)
Sodium aluminate solution (45% or less)	SAU	5	0	NA	111	А	No	N/A	.50-73, .56-1(a), (b), (c)
Sodium chlorate solution (50% or less)	SDD	0 1,2	2 0	NA	111	А	No	N/A	.50-73
Sodium hypochlorite solution (20% or less)	SHQ		0	NA	111	А	No	N/A	.50-73, .56-1(a), (b)
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2		NA	111	A	Yes	1	.50-73, .55-1(b)
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,2	° 0	NA	111	A	No	N/A	.50-73, .55-1(b)
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2	2 0	NA	11	A	No	N/A	.50-73, .55-1(b)
Styrene (crude)	STX		0	D	 111	A	Yes	2	Na
Styrene monomer	STY	30	0	D	111	A	Yes	2	.50-70(a), .50-81(a), (b)
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	A	No	N/A	No
Tetraethylenepentamine	TTP	7	0	E	111	A	Yes	1	.55-1(c)
Tetrahydrofuran	THF	41	0	С	111	A	Yes	1	.50-70(b)
Toluenediamine	TDA	9	Ö	E		A	No	N/A	.50-73, .56-1(a), (b), (c), (g)
1,2,4-Trichlorobenzene	TCB	36	0	E	111	A	Yes	1	No
1,1,2-Trichloroethane	TCM		0	NA	111	A	Yes	1	.50-73, .56-1(a)
Trichloroethylene	TCL	36 2	0	NA		A	Yes	1	No
1,2,3-Trichloropropane Triethanolamine	TCN	36 8 ²		<u> </u>		<u>A</u>	Yes	3	.50-73, .56-1(a) .55-1(b)
Triethylamine	TEA TEN	7	 0	E		<u>A</u>	Yes	1	.55-1(e)
Triethylenetetramine	TET	7 2	0	E	[1 	<u>A</u> A	Yes Yes	3	.55-1(b)
Triphenylborane (10% or less), caustic soda solution	TPB	5		NA	 []]	A	No	 N/A	.56-1(a), (b), (c)
Trisodium phosphate solution	TSP	5		NA		A	No	N/A	.50-73, .56-1(a), (c).
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA		A	No	N/A	.56-1(b)
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA		A	No	N/A	.50-73, .56-1(a), (c), (g)
Vinyi acetate	VAM	13	0	С	111	A	Yes	2	.50-70(a)50-81(a), (b)
Vinyl neodecanate	VND	13	0	E	111	A	No	N/A	.50-70(a), .50-81(a), (b)
Vinyltoluene	VNT	13	0	D	111	A	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (g)
Subchapter D Cargoes Authorized for Vapor Control		an a							
Acetone	ACT	18 ²	D	С		A	Yes	1	
Acetophenone	ACP	18	D	E		A	Yes	1	
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1	
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1	
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1	·····
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		A	Yes	1	
Benzyl alcohol	BAL.	21	D	E		А	Yes	1	
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		A	Yes	1	
Butyl acetate (all isomers)	BAX	34	D	D		A	Yes	1	
Butyl alcohol (iso-)	IAL	20 ²	D	. <u> </u>		A	Yes	1	
Butyl alcohol (n-)	BAN		D	D		A	Yes	1	
Butyi alcohol (sec-)	BAS		D	c		A	Yes	1	
Butyl alcohol (tert-)	BAT		D	С		A	Yes	1	
Butyi benzyl phthalate	BPH	34	D	E.		A	Yes	1	
Butyl toluene	BUË	32	D	D		A	Yes	1	



Vessel Name: KIRBY 28065 Official #: 1158899

Page 4 of 7

Shipyard: Trinity Ashland City Hull #: 4470

Cargo Identification							Co	nditio	ns of Carriage
			1				Vapor Re	ecovery	Г — Г
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Caprolactam solutions	CLS	22	D	Ë		A	Yes	1	
Cyclohexane	СНХ	31	D	С		A	Yes	1	
Cyclohexanoi	CHN	20	D	Е		A	Yes	1	
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2	
p-Cymene	CMP	32	D	D		A	Yes	1	
iso-Decaldehyde	IDA	19	D	E		A	Yes	1	
n-Decaldehyde	DAL	19	D	E		A	Yes	1	······································
Decene	DCE	30	D	D		A	Yes	1	
Decyl alcohol (all isomers)	DAX	20 ²	D	Ε		A	Yes	1	
n-Decylbenzene, see Alkyi(C9+)benzenes	DBZ	32	D	E		A	Yes	1	
Diacetone alcohoi	DAA	20 ²	D	E		A	Yes	1	
ortho-Dibutyl phthalate	DPA	34	D	E		A	Yes	1	
Diethylbenzene	DEB	32	D	D		A	Yes	1	· · · · · · · · · · · · · · · · · · ·
Diethylene glycol	DEG	40 2	D	E		A	Yes	1	
Diisobutylene	DBL	30	D	C		A	Yes	1	
Diisobutyl ketone	DIK	18	D	D		A	Yes	1	
Dilsopropylbenzene (all isomers)	DIX	32	D	E	• •	A	Yes	1	
Dimethyl phthalate	DTL	34	 D	<u>-</u>		A	Yes	1	
Dioctyl phthalate	DOP	34	D	E		A	Yes	1	
Dipentene	DPN	30	 D			A	Yes	1	
Diphenyl	DIL	32		D/E		<u></u>	Yes	1	
Diphenyl, Diphenyl ether mixtures	DDC		D	E		A	Yes	1	
Diphenyl ether	DPE	41				<u>A</u>	Yes	1	
Dipropylene glycol	DPG	40	D	<u>_/</u> E		A	Yes	1	· · · · · · · · · · · · · · · · · · ·
Distillates: Flashed feed stocks	DFF	33	D	E		<u>A</u>	Yes	1	
Distillates: Straight run	DSR		D	E		A	Yes	1	
Dodecene (all isomers)	DOZ	30	D	 D		A	Yes	1	
Dodecylbenzene, see Aikyi(C9+)benzenes	DDB	32	D	E		A	Yes	1	
2-Ethoxyethyl acetate	EEA	34		 D		A	Yes	1	
Ethoxy trigiycol (crude)	ETG	40	. <u>D</u>	Ē		A	Yes	1	
Ethyl acetate	ETA	34	D	<u>E</u>					
						A	Yes	1	
Ethyl acetoacetate	EAA	34	D	E		A	Yes	1	
	EAL	20 2		<u> </u>		A	Yes	1	
Ethylbenzene	ETB	32	<u>D</u>	<u> </u>		A	Yes	1	
Ethyl butanol	EBT	20	D	D		<u> </u>	Yes	1	
Ethyl tert-butyl ether	EBE	41	<u>D</u>	<u> </u>		A	Yes	1	
Ethyl butyrate	EBR	34	D	D		A	Yes	1	
Ethyl cyclohexane	ECY	31	D	D		Α	Yes	1	
Ethylene glycol	EGL	20 2		Е		A	Yes	1	
Ethylene glycol butyl ether acetate	EMA	34	D	E		A	Yes	1	
Ethylene glycol diacetate	EGY	34	<u>D</u>	E		A	Yes	1	
Ethylene glycol phenyl ether	EPE	40	D	E		A	Yes	1	
Ethyl-3-ethoxypropionate	EEP	34	D	E		A	Yes	1	
2-Ethylhexanol	EHX		<u>D</u>	E		<u>A</u>	Yes	1	
Ethyl propionate	EPR		D	С		A	Yes	1	
Ethyi toluene	ETE	32	D	E		A	Yes	1	
Formamide	FAM		D	E		A	Yes	1	
Furfuryl alcohol	FAL	20 2	D	Ë		A	Yes	1	
Gasoline blending stocks: Alkylates	GAK		D	A/C		A	Yes	1	
Gasoline blending stocks: Reformates	GRF	33	D	A/C		А	Yes	1	
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		A	Yes	1	
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		A	Yes	1	



Vessel Name: KIRBY 28065 Official #: 1158899

Page 5 of 7

Shipyard: Trinity Ashland City Hull #: 4470

Ourcial #. 11288888	·····	rage	e 5 of /	t marytes 33 the such to / th					Huli #: 4470
Cargo Identification						1		nditio	ns of Carriage
ou go raonanouton			T			 			ils of carriage
Name	Chem Code	Compat Group	Sub Chapter	Grade	Huli Type	Tank Group	Vapor R App'd (Y or N)	ecovery VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Gasolines: Casinghead (natura!)	GCS	33	D	A/C		A	Yes	1	
Gasolines: Polymer	GPL	33	D	A/C		A	Yes	1	
Gasolines: Straight run	GSR		D	A/C		A	Yes	1	
Glycerine	GCF			E		A	Yes	1	
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX					A	Yes	1	
Heptanoic acid	HEP		 D	Ē		A	Yes	1	
Heptanol (all isomers)	HTX	20	 D	D/É		<u>A</u>	Yes	1	
Heptene (all isomers)	HPX	30	D	С		A	Yes	2	
Heptyl acetate	HPE	34	D	D		A	Yes	1	
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		A	Yes	1	· · · · · · · · · · · · · · · · · · ·
Hexanoic acid	НХО	4	D	Е		A	Yes	1	
Hexanol	HXN	20	D	D		A	Yes	1	
Hexene (all isomers)	HEX	30	D	С		A	Yes	2	·····
Hexylene glycol	HXG	20	D	E		A	Yes	1	
Isophorone	IPH	18 2	D	E		A	Yes	1	
Jet fuel: JP-4	JPF	33	D	E		A	Yes	1	
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1	
Kerosene	KRS	33	D	D		A	Yes	1	
Methyl acetate	MIT	34	D	D		A	Yes	1	
Methyl alcohol	MAL,	20 2	D	С		A	Yes	1	······································
Methylamyl acetate	MAC	34	D	D		A	Yes	1	
Methylamyl alcohol	MAA	. 20	D	D		A	Yes	1	······································
Methyl amyl ketone	MAK	18	D	Đ		A	Yes	1	
Methyl tert-butyl ether	MBE	41 2	D	С		A	Yes	1	······································
Methyl butyl ketone	MBK	18	D	С		A	Yes	1	
Methyl butyrate	MBL	34	D	C		A	Yes	1	
Methyl ethyl ketone	MEK	18 ²	D	С		A	Yes	1	
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1	
Methyl isobutyl ketone	MIK	18 ²	D	С		A	Yes	1	
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1	
Mineral spirits	MNS	33	D	D		A	Yes	1	
Мугсепе	MRE	30	D	D		A	Yes	1	
Naphtha: Heavy	NAG	33	D	#		A	Yes	1	
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1	
Naphtha: Solvent	NSV	33	D	D		A	Yes	1	
Naphtha: Stoddard solvent	NSS	33	D	D		A	Yes	1	
Naphtha: Varnish makers and painters (75%)	NVN	1 33	D	С		A	Yes	1	
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A	Yes	1	
Nonene (all isomers)	NON	1 30	D	D		A	Yes	2	
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		A	Yes	1	
Nonyl phenol	NNP	21	D	E		A	Yes	1	
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		A	Yes	1	
Octane (all isomers), see Alkanes (C6-C9)	OAX		D	С		A	Yes	1	
Octanoic acid (all isomers)	ÖAY		D	E		A	Yes	1	
Octanol (all isomers)	OC>		D	Е		A	Yes	1	
Octene (all isomers)	ΟΤΧ	30	D	С		А	Yes	2	
Oil, fuel: No. 2	ОТИ	/ 33	D	D/E		А	Yes	1	
Oil, fuel: No. 2-D	OTD	33	D	D		А	Yes	1	
Oil, fuel: No. 4	OFF		D	D/E		А	Yes	1	
Oil, fuel: No. 5	OFV	′ 33	D	D/E		A	Yes	1	
Oil, fuel: No. 6	osx	33	D	Ε		A	Yes	1	
Oll, misc: Crude	OIL	33	D	C/D	1	Α	Yes	1	



Vessel Name: KIRBY 28065 Official #: 1158899

Page 6 of 7

Shipyard: Trinity Ashland City Hull #: 4470

Cargo Identification						1	Co	nditio	ns of Carriage
	1		1			 	Vapor R		
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1	
Oil, mise: Lubricating	OLB	33	D	E		А	Yes	1	
Oil, misc: Residual	ORL	33	D	E		А	Yes	1	
Oil, misc: Turbine	OTB	33	D	Ē		А	Yes	1	
Pentane (all isomers)	PTY	31	D	А		А	Yes	5	
Pentene (ali isomers)	PTX	30	D	Α		А	Yes	5	
alpha-Pinene	PIO	30	D	D		А	Yes	1	
beta-Pinene	PIP	30	D	D		A	Yes	1	
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	Е		A	Yes	1	
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A	Yes	1	
Polybutene	PLB	30	D	E		A	Yes	1	
Polypropylene glycol	PGC	40	D	E		A	Yes	1	
iso-Propyl acetate	IAC	34	D	С		A	Yes	1	
n-Propyl acetate	PAT	34	D	С		A	Yes	1	
iso-Propyl alcohol	IPA	20 2	D	С		A	Yes	1	
n-Propyl alcohol	PAL	20 2	D	С		A	Yes	1	
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1	
iso-Propylcyclohexane	IPX	31	D	D		A	Yes	1	
Propylene glycol	PPG	20 2	D	Ē		A	Yes	1	
Propylene glycol methyl ether acetate	PGN	34	D	D	•	A	Yes	1	
Propylene tetramer	PIT	30	D	D		A	Yes	1	
Sulfolane	SFL	39	D	E		A	Yes	1	
Tetraethylene glycol	ΠG	40	D	E		A	Yes	1	
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1	······································
Toluene	TOL	32	D	С		A	Yes	1	······································
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		A	Yes	1	
Triethylbenzene	TEB	32	D	E		A	Yes	1	
Triethylene glycol	TEG	40	D	E		A	Yes	1	······································
Triethyl phosphate	TPS	34	D	E		A	Yes	1	
Trimethylbenzene (all isomers)	TRE	32	Ð	{D}		A	Yes	1	· · · · · · · · · · · · · · · · · · ·
Trixylenyl phosphate	TRP	34	D	E		A	Yes		
Undecene	UDC		 D	 D/E		A	Yes		
1-Undecyl alcohol	UNE		 D	E		A	Yes		
Xylenes (ortho-, meta-, para-)	XLX	32		 D		A	Yes	· · · · · ·	
				<u></u>			100		




Vessel Name: KIRBY 28065 Official #: 1158899

Page 7 of 7

Shipyard: Trinity Ashland Huli #: 4470

Explanation of terms & symbols used in the Table:

Cargo Identificatio	
Name Chem Code	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2. The three fetter decording assigned to the come in the Charged Manager Property Revenue of Concerns and the come
none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatability Group No.	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. in accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (G-MSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001.
Note 2	Telephone (202) 267-1217. See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.
Subchapter Subchapter D	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Subchapter O Note 3	Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2. Those hazardous cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which
	were not ventiled by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
A, B, C D, E	Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.
Note 4	The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the
NA	cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classified as a flammable or combustible liquid.
#	No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151,10-1,
l Il	Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1), Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).
III NA	Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.
Conditions of Carriag	9
Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo,
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Conditions of Carriag	1
Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo,
Tank Group Vapor Recovery	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo. Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Tank Group Vapor Recovery Approved (Y or N) VCS Category:	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems.
Tank Group Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Tank Group Vapor Recovery Approved (Y or N) VCS Category:	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CCFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouting safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be accentable to the local Officer to Chargo
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouting safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe controliton due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20.9
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuing all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be accepitable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannol use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank ovepressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. (Polymerizes and highly toxic) Must comply with requirements of Category 1. 2 and 3. (High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vap
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4 Category 5	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densitites and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuing all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. (Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3. (High vapor pressure) VCS pressure drop calculations for cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. Th
Tank Group Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4 Category 5 Category 6	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oll) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densitites and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly taxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. (Polymetizes and highly toxic) Must comply with requirements of category 1. and 3. (High vapor pressure) VCS pressure drop calculations for cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in additio



16917 Market St, Channelview, TX 77530 (713)453-0413

LVT Sales Order	LV-4773-SO	
Barge Name	K 28065	
Work Order #		

Shop Order & Test Report

Customer:	Kirby Inland	Marine		Order #	RDJ 670353	·
Make	Midland		Size	4"	Model #	A 843
Serial #	G766T		nlet	4" 150	Outlet	NA
Constrution:	P/V				Cap:	N/A
Set Pressure:	3.0 psi pressure	e/0.5 psi va	cuum			
Tag:				Orifice:	N/A	
Work Require	d: Ci	omplete Ov	verhaul		Те	st Air
Condition Rec		Need R	epair	-		
Inlet	Dirty	e-repair		Spring	Good Cond.	
Seats	Dirty			Work	ST	
				Repairs	Lapped Seat	
	Dirty			nepairs	Lapped Sea	LS
Guide Outlet	Dirty Dirty			Repairs	Lapped Sea	
Guide	manufacture construction of the design of the second second second second second second second second second se		Installed	viton quad ri		.5
Guide Outlet	manufacture construction of the design of the second second second second second second second second second se	-	Installed	•		

Final Test Report

Date	11/27/2019		
Set Pressure	3.0 psi pressure/0.5 psi vacuum		
Nozzle Ring Se	etting N/A		
Back Pressure	N/A		
Tested By: C	Lundo A pering	Witness/Assy By	
U.S. Coast Gu	ard Witness		



. 1

16917 Market St, Channelview, TX 77530 (713)453-0413

LVT Sales Order	LV-4773-SO	
Barge Name	K 28065	
Work Order #		

Shop Order & Test Report

Customer:	Kirby Inland Marine		Order #	RDJ 670353
Make	Tank Tech	Size	6"	Model # KSPA/KSPV6
Serial #	KLPH-80083105	Inlet	6" 150	Outlet NA
Constrution:	P/V			Cap: N/A
Set Pressure:	3.0 psi pressure/0.5 psi	vacuum	-	
Tag:			Orifice:	N/A
Work Require	d: Complete	Overhaul		Test Air
Condition Rec	eived: Need	d Repair	_	
		ir		
General	Condition Pre-repa	11	3	
Inlet	Dirty		Spring	
Seats	Dirty		Work	ST
Guide	Dirty		Repairs	Lapped Seats Replaced gaskets
Outlet	Dirty			
Parts replace	d and other work:	See attach	ned parts list	
	Fi	nal T	est R	eport
Date	11/27/2019			
Set Pressure	3.0 psi pressure/0.5 ps	i vacuum	И	
Nozzle Ring S				
Back Pressure			E.	
	CI A r	2000 /		Witness/Assy By:
Tested By:	Commedo A f	som -		
U.S. Coast Gu	uard Witness			



16917 Market St, Channelview, TX 77530 (713)453-0413

LVT Sales Order	LV-4773-SO	
Barge Name	K 28065	
Work Order #		

Shop Order & Test Report

Customer:	Kirby Inland Ma	rine	Order #	RDJ 670353	
Make	Farris	Size	6" x 8"	Model #	26QA10L-120
Serial #	825746-33-A14	Inlet	6"150	Outlet	8"150
Constrution:	Conventional RV			Cap:	Plain
Set Pressure:	125 psi pressure		_		
Tag:			Orifice:	٩	
Work Require	d: Com	plete Overhaul		Test A	Air
Condition Rec	eived:	Need Repair	_		
General C	Condition Pre-r	epair			
Inlet	Dirty		Spring	Good Cond.	
Seats	Dirty		Work	ST	
Guide	Dirty		Repairs	Lapped Seats	Installed gaskets
Outlet	Dirty			2	
Parts replaced	and other work:				
		· • • •			

Final Test Report

Date	11/27/2019		
Set Pressure	125 psi pressure		
Nozzle Ring Sett	ing 5 Down	_	
Back Pressure	30 PSI	_	
Tested By: E.J.	urchen A purch	Witness/Assy By	
U.S. Coast Guard	d Witness		
-			