

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 11 Feb 2020 Expiration Date: 11 Feb 2025

Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name

Official Number

IMO Number

Call Sign

Service

KIRBY 28068

1158902

Tank Barge

Hailing Port

WILMINGTON, DE

Hull Material

Steel

Delivery Date

Horsepower

Propulsion

UNITED STATES

Place Built

ASHLAND CITY, TN

-- ----

Keel Laid Date

Gross Tons

Net Tons

DWT

Length

22Oct2004 02Sep2004

R-1632

R-1632

1632

R-300.0

1-0

UNITED STATES

Owner

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES Operator

KIRBY INLAND MARINE LP 18350 Market Street Channelview, TX 77530 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Oilers

0 Chief Mates

O First Class Pilots

O First Assistant Engineers

0 Second Mates

0 Radio Officers

0 Second Assistant Engineers

0 Third Mates

0 Able Seamen

0 Ordinary Seamen

O Third Assistant Engineers
O Licensed Engineers

0 Master First Class Pilot
0 Mate First Class Pilots

0 Deckhands

0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

--- Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth Coast Guard District's Tank Barge Streamlined Inspection Program

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at PORT ARTHUR, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection

Date Zone A/P/R Signature

2-3-21 Hou/GAL A DANNY MYRRAY

11-16-21 BRLA A Murphy MAKES

12-13-22 Hou P Kuban Montes

12-13-23 BTR, LA A Daylan Lacouste

This certificate issued by: Infrace, core

J.J. ANDREW, CDR, USCG, By direction

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



United States of America **Department of Homeland Security United States Coast Guard**

Certification Date: 11 Feb 2020 **Expiration Date:** 11 Feb 2025

Certificate of Inspection

Vessel Name: KIRBY 28068

(TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

30Dec2024

30Dec2014

22Oct2004

Internal Structure

31Dec2024

11Feb2020

30Dec2014

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

Flammable/Combustible Liquids and Specified Hazardous Cargoes

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

28484

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Location Description	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	828	13.60
2 P/S	825	13.60
3 P/S	764	13.60

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
II	3608	9ft 6in	13.60	
11	3608	9ft 6in	13.60	
III	4604	11ft 6in	13.60	
Ш	4604	11ft 6in	13.60	

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment(CAA), Serial # C2-0402521, dated September 27, 2004, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Per 46 CFR 39, excluding Part 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter serial Marine Safety Center letters Serial # C2-0402332 dated August 25, 2004, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Per 46 CFR 39.1017 and 39.5000(e), this vessel's VCS has been evaluated and approved for multi-breasted tandem loading with other vessels specifically approved to tandem load with this vessel.

^{*}Vapor Control Authorization*



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 11 Feb 2020 Expiration Date: 11 Feb 2025

Certificate of Inspection

Vessel Name: KIRBY 28068

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

		Internal Exam			External Exam		
	Tank Id	Previous	Last	Next	Previous	Last	Next
	1 P/S	22Oct2004	30Dec2014	30Dec2024	-	-	-
	2 P/S	22Oct2004	30Dec2014	30Dec2024	-	-	-
ı	3 P/S	22Oct2004	30Dec2014	30Dec2024	-	-	-
				Hydro Test			
	Tank Id	Safety Valves		Previous	Last	Next	
	1 P/S	-		-	-	-	
	2 P/S	-		-	-	·-	
	3 P/S	-		_	-	-	

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Number of Fireman Outfits - 0

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

B-II

END

^{*}Stability and Trim*



Serial #: C2-0402521

Generated: 27-Sep-04

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068 Official #: 1158902

Shipyard: Trinity Ashland City

Hull #: 4473

46 CFR 151 Tank Group Characteristics

Tank Group Information	Cargo Identification			Cargo	Tanks Cargo							Fire	Special Requirements				
Tnk Grp Tanks in Group	Density	Press.	Temp.	Hull	Seg Tank	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Tem
A #1P/S, #2P/S, #3P/S	13.6	Atmos.	Amb.	11	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	.50-81(a), .50- 81(b), .50-86,	55-1(b), (c), (e), (f), (h), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

List of Authorized Cargoes

Cargo Identification						Conditions of Carriage						
		1200					Vapor R					
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction			
Authorized Subchapter O Cargoes												
Acetonitrile	ATN	37	0	С	Ш	Α	Yes	3	No			
Acrylonitrile	ACN	15 ²	0	С	Ш	Α	Yes	4	.50-70(a), .55-1(e)			
Adiponitrile	ADN	37	0	E	11	Α	Yes	1	No			
Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	111	Α	No	N/A	.50-81, .50-86			
Aminoethylethanolamine	AEE	8	0	E	Ш	Α	Yes	1	.55-1(b)			
Ammonium bisulfite solution (70% or less)	ABX	43 2	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)			
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	111	Α	No	N/A	.56-1(a), (b), (c), (f), (g)			
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	- 11	Α	No	N/A	No			
Benzene	BNZ	32	0	С	111	Α	Yes	1	.50-60			
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 ²	0	NA	111	Α	Yes	1	.50-60			
Senzene or hydrocarbon mixtures (containing Acetylene and 10% Senzene or more)	ВНА	32 2	0	NA	III	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)			
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	111	Α	Yes	1	.50-60			
Butyl acrylate (all isomers)	BAR	14	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)			
Butyl methacrylate	вмн	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)			
Butyraldehyde (all isomers)	BAE	19	0	С	111	Α	Yes	1	.55-1(h)			
Camphor oil (light)	СРО	18	0	D	П	Α	No	N/A	No			
Carbon tetrachloride	CBT	36	0	NA	111	Α	No	N/A	. No			
Chemical Oil (refined, containing phenolics)	COD	21	0	E	11	Α	No	N/A	.50-73			
Chlorobenzene	CRB	36	0	D	111	Α	Yes	1	No			
Chloroform	CRF	36	0	E	III	Α	Yes	3	No			
Coal tar naphtha solvent	NCT	33	0	D	111	Α	Yes	1	.50-73			
Creosote	CCM	/ 21 ²	0	E	111	Α	Yes	1	No			
Cresols (all isomers)	CRS	21	0	E	111	Α	Yes	1	No			
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)			
Cresylic acid tar	CRX		0		111	Α	Yes	1	.55-1(f)			
Crotonaldehyde	CTA	19 ²	0	С	11	Α	Yes	4	.55-1(h)			
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropy icrolein)			0		Ш	Α	No	N/A	No			
Cyclohexanone	ССН	18	0	D	111	Α	Yes	1	.56-1(a), (b)			
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	0	Е	111	Α	Yes	1	.56-1 (b)			
Cyclohexylamine	CHA	7	0	D	III	Α	Yes	1	.56-1(a), (b), (c), (g)			
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	III	Α	Yes	1	.50-60, .56-1(b)			
so-Decyl acrylate	IAI	14	0	E	111	Α	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)			
Dichlorobenzene (all isomers)	DBX	36	0	Е	III	Α	Yes	3	.56-1(a), (b)			
1,1-Dichloroethane	DCH	36	0	С	ill	Α	Yes	1	No			
2,2'-Dichloroethyl ether	DEE	41	0	D	11	Α	Yes	1	.55-1(f)			
Dichloromethane	DCM	36	0	NA	111	Α	No	N/A	No			
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE		0	NA	111	Α	No	N/A	.56-1(a), (b), (c), (g)			

^{2.} Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

^{3.} Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068

Official #: 1158902

Page 2 of 7

Shipyard: Trinity Ashland City

Name									ns of Carriage		
Name											
	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction		
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1.	2 0	NA	Ш	Α	No	N/A	.56-1(a), (b), (c), (g)		
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution (70% or less	DDA		0		Ш	Α	No	N/A	.55-1(b)		
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 ²	0	NA	111	Α	No	N/A	.56-1(a), (b), (c), (g)		
,1-Dichloropropane	DPB	36	0	С	111	Α	Yes	3	No		
,2-Dichloropropane	DPP	36	0	С	111	Α	Yes	3	No		
,3-Dichloropropane	DPC	36	0	С	111	Α	Yes	3	No		
,3-Dichloropropene	DPU	15	0	D	- 11	Α	Yes	4	No		
Dichloropropene, Dichloropropane mixtures	DMX		0	NA	11	Α	Yes	1	No		
Diethanolamine	DEA	8	0	E	111	Α	Yes	1	.55-1(c)		
Diethylamine	DEN	7	0	С	111	Α	Yes	3	.55-1(c)		
Diethylenetriamine	DET	7 2	0	E	III	Α	Yes	1	.55-1(c)		
Diisobutylamine	DBU	7	0	D	111	Α	Yes	3	.55-1(c)		
Diisopropanolamine	DIP	8	0	Ε	111	Α	Yes	1	.55-1(c)		
Diisopropylamine	DIA	7	0	С	- 11	Α	Yes	3	.55-1(c)		
N,N-Dimethylacetamide	DAC	10	0	Ε	111	Α	Yes	3	.56-1(b)		
Dimethylethanolamine	DMB	8	0	D	111	Α	Yes	1	.56-1(b), (c)		
Dimethylformamide	DMF	10	0	D	Ш	Α	Yes	1	.55-1(e)		
Di-n-propylamine	DNA	7	0	С	- 11	Α	Yes	3	.55-1(c)		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	111	Α	No	N/A	.56-1(b)		
Ethanolamine	MEA	8	0	E	111	Α	Yes	1	.55-1(c)		
Ethyl acrylate	EAC	14	0	С	111	Α	Yes	2	.50-70(a), .50-81(a), (b)		
Ethylamine solution (72% or less)	EAN	7	0	Α	11	Α	No	N/A	.55-1(b)		
N-Ethylbutylamine	EBA	7	0	D	111	Α	Yes	3	.55-1(b)		
N-Ethylcyclohexylamine	ECC	7	0	D	111	Α	Yes	1	.55-1(b)		
Ethylene cyanohydrin	ETC	20	0	E	111	Α	Yes	1	No		
thylenediamine	EDA	7 2	0	D	111	Α	Yes	1	.55-1(c)		
thylene dichloride	EDC	36 ²	0	С	111	Α	Yes	1	No		
Ethylene glycol hexyl ether	EGH	40	0	E	111	Α	No	N/A	No		
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	111	Α	Yes	1	No		
Ethylene glycol propyl ether	EGP	40	0	E	111	Α	Yes	1	No		
2-Ethylhexyl acrylate	EAI	14	0	E	111	Α	Yes	2	.50-70(a), .50-81(a), (b)		
Ethyl methacrylate	ETM	14	0	D/E	Ш	Α	Yes	2	.50-70(a)		
2-Ethyl-3-propylacrolein	EPA	19 ²	0	E	111	Α	Yes	1	No		
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E	111	Α	Yes	1	.55-1(h)		
Furfural	FFA	19	0	E	111	Α	Yes	1	.55-1(h)		
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	111	Α	No	N/A	No		
Hexamethylenediamine solution	HMC	7	0	E	111	Α	Yes	1	.55-1(c)		
Hexamethyleneimine	HMI	7	0	С	- 11	Α	Yes	1	.56-1(b), (c)		
Hydrocarbon 5-9	HFN		0		111	Α	Yes	1	.50-70(a), .50-81(a), (b)		
soprene	IPR	30	0	Α	111	Α	No	N/A	.50-70(a), .50-81(a), (b)		
soprene, Pentadiene mixture	IPN		0		111	Α	No	N/A	.50-70(a), .55-1(c)		
Craft pulping liquors (free alkali content 3% or more)(including: Black,	KPL	5	0	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (c), (g)		
Green, or White liquor)	MSO	18 ²	0	D	III	Α	Yes	1	No		
Mesityl oxide	MAM		0	C	111	A	Yes	2	.50-70(a), .50-81(a), (b)		
Methyl acrylate	MCK		-0		111		Yes	1	No		
Methylcyclopentadiene dimer	MDE		0	E	111	A	Yes	1	.56-1(b), (c)		
Methyl diethanolamine	MEP		0	E	111	A	Yes	1	.55-1(e)		
2-Methyl-5-ethylpyridine	MMN		0	C	111	A	Yes	2	.50-70(a), .50-81(a), (b)		
Methyl methacrylate	MPR		-0	D	III	A	Yes	3	.55-1(c)		
2-Methylpyridine	MSR		0	D	111	A	Yes	2	.50-70(a), .50-81(a), (b)		
alpha-Methylstyrene	MPL	7 2		D	111	A	Yes	1	.55-1(c)		
Morpholine	NPM		- 0	D	111	A	Yes	1	.50-81		



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068
Official #: 1158902

8902 Page 3 of 7

Shipyard: Trinity Ashland City

Cargo Identification		Co	nditio	ns of Carriage							
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction		
1,3-Pentadiene	PDE	30	0	Α	Ш	Α	No	N/A	.50-70(a), .50-81		
Perchloroethylene	PER	36	0	NA	111	Α	No	N/A	No		
Polyethylene polyamines	PEB	7 2	0	E	Ш	Α	Yes	1	.55-1(e)		
iso-Propanolamine	MPA	8	0	Ε	111	Α	Yes	1	.55-1(c)		
Propanolamine (iso-, n-)	PAX	8	0	E	111	Α	Yes	1	.56-1(b), (c)		
iso-Propylamine	IPP	7	0	Α	11	Α	Yes	5	.55-1(c)		
Pyridine	PRD	9	0	С	111	Α	Yes	1	.55-1(e)		
Sodium aluminate solution (45% or less)	SAU	5	0	NA	Ш	Α	No	N/A	.50-73, .56-1(a), (b), (c)		
Sodium chlorate solution (50% or less)	SDD	0 1.	2 0	NA	111	Α	No	N/A	.50-73		
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b)		
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1.		NA	111	Α	Yes	1	.50-73, .55-1(b)		
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1.		NA	111	Α	No	N/A	.50-73, .55-1(b)		
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1.	2 0	NA	11	A	No	N/A	.50-73, .55-1(b)		
Styrene (crude)	STX		0	D	111	Α	Yes	2	No		
Styrene monomer	STY	30	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)		
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	Α	No	N/A	No		
Tetraethylenepentamine	TTP	7	0	E	- 111	Α	Yes	1	.55-1(c)		
Tetrahydrofuran	THF	41	0	С	111	Α	Yes	1	.50-70(b)		
Toluenediamine	TDA	9	0	E	- 11	Α	No	N/A	.50-73, .56-1(a), (b), (c), (g)		
1,2,4-Trichlorobenzene	TCB	36	0	E	111	Α	Yes	1	No		
1,1,2-Trichloroethane	TCM	36	0	NA	111	Α	Yes	1	.50-73, .56-1(a)		
Trichloroethylene	TCL	36 ²	0	NA	111	Α	Yes	1	No		
1,2,3-Trichloropropane	TCN	36	0	E	11	Α	Yes	3	.50-73, .56-1(a)		
Triethanolamine	TEA	8 ²	0	E	III	Α	Yes	1	.55-1(b)		
Triethylamine	TEN	7	0	С	11	Α	Yes	3	.55-1(e)		
Triethylenetetramine	TET	7 2	0	E	111	Α	Yes	1	.55-1(b)		
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	111	Α	No	N/A	.56-1(a), (b), (c)		
Trisodium phosphate solution	TSP	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (c).		
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	111	Α	No	N/A	.56-1(b)		
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (c), (g)		
Vinyl acetate	VAM	13	0	С	111	Α	Yes	2	.50-70(a), .50-81(a), (b)		
Vinyl neodecanate	VND	13	0	E	111	Α	No	N/A	.50-70(a), .50-81(a), (b)		
vinyltoluene	VNT	13	0	D	Ш	Α	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (g)		
ubchapter D Cargoes Authorized for Vapor Control											
Acetone	ACT	18 ²	D	С		Α	Yes	1			
Acetophenone	ACP	18	D	Ε		Α	Yes	1			
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E	7.	Α	Yes	1			
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1			
Amyl acetate (all isomers)	AEC	34	D	D		Α	Yes	1			
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		Α	Yes	1			
Benzyl alcohol	BAL	21	D	E		Α	Yes	1			
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		Α	Yes	1			
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1			
Butyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1			
Butyl alcohol (n-)	BAN		D	D		Α	Yes	1			
	2.0		D	С		Α	Yes	1			
	BAS		U	C			103				
Butyl alcohol (sec-)	BAS		D	c		A	Yes	1			
Butyl alcohol (sec-) Butyl alcohol (tert-) Butyl benzyl phthalate		34									



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068

Official #: 1158902

Page 4 of 7

Shipyard: Trinity Ashland City

Cargo Identification							Co	nditio	ns of Carriage
			T	Т			Vapor R	ecovery	
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Haire	0000		G		.,,,,,	5.04	(, ,,,		
Caprolactam solutions	CLS	22	D	E		Α	Yes	1	
Cyclohexane	CHX		D	С		Α	Yes	1	
Cyclohexanol	CHN		D	E		Α	Yes	1	
1,3-Cyclopentadiene dimer (molten)	CPD		D	D/E		Α	Yes	2	
p-Cymene	CMP		D	D		Α	Yes	1	
iso-Decaldehyde	IDA	19	D	E		Α	Yes	1	
n-Decaldehyde	DAL	19	D	E		Α	Yes	1	
Decene	DCE	30	D	D		Α	Yes	1	
Decyl alcohol (all isomers)	DAX	20	2 D	E		Α	Yes	1	
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		Α	Yes	1	
Diacetone alcohol	DAA		2 D	E		Α	Yes	1	
ortho-Dibutyl phthalate	DPA		D	E		Α	Yes	1	
Diethylbenzene	DEB		D	D		Α	Yes	1	
Diethylene glycol	DEG		2 D	E		Α	Yes	1	
Diisobutylene	DBL	30	D	С		Α	Yes	1	
Diisobutyl ketone	DIK	18	D	D		Α	Yes	1	
Diisopropylbenzene (all isomers)	DIX	32	D	E		A	Yes	1	
Dimethyl phthalate	DTL	34	D	E		A	Yes	1	
Dioctyl phthalate	DOP		D	E		A	Yes	1	
Dipentene	DPN	17000	D	D		A	Yes	1	
Diphenyl	DIL	32	D	D/E		A	Yes	1	
Diphenyl, Diphenyl ether mixtures	DDC		D	E		A	Yes	1	
	DPE		D	{E}		A	Yes	1	
Diphenyl ether	DPG		D	E		A	Yes	1	
Dipropylene glycol	DFF	33	D	E		A	Yes	1	
Distillates: Flashed feed stocks	DSR		D	E		A	Yes	1	
Distillates: Straight run	DOZ		D	D		A	Yes	1	
Dodecene (all isomers)	DDB		D	E			Yes	1	
Dodecylbenzene, see Alkyl(C9+)benzenes	EEA	34	D	D		A	Yes	1	
2-Ethoxyethyl acetate	ETG	40	D	E		A	Yes	1	
Ethoxy triglycol (crude)	ETA	34	D	C		A	Yes	1	
Ethyl acetate	EAA	34	D	E		A	Yes	1	
Ethyl acetoacetate	EAL	20		C		A	Yes	1	
Ethyl alcohol	ETB	32	D	C		A	Yes	1	
Ethylbenzene	EBT	20	D	D			Yes	1	
Ethyl butanol	EBE	41	D	C		A	Yes	1	
Ethyl tert-butyl ether	EBR		D	D			Yes	1	
Ethyl butyrate	ECY		D	D			Yes	1	
Ethyl cyclohexane	EGL	20		E		A	Yes	1	
Ethylene glycol				E			Yes	1	
Ethylene glycol butyl ether acetate	EMA EGY		D D	E		A	Yes	1	
Ethylene glycol diacetate			D	E			Yes	1	
Ethylene glycol phenyl ether	EPE		D	E		A	Yes	1	
Ethyl-3-ethoxypropionate	EEP		D	E		A	Yes	1	
2-Ethylhexanol	EHX		D	C		A	Yes	1	
Ethyl propionate			D	E		A	Yes	1	
Ethyl toluene	ETE		D	E		A	Yes	1	
Formamide	FAM	20		E		A	Yes	1	
Furfuryl alcohol	FAL		D	A/C		A	Yes	1	
Gasoline blending stocks: Alkylates	GAK		D	A/C		A	Yes	1	_
Gasoline blending stocks: Reformates			D	c		A	Yes	1	
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT GAV		D	- C		A	Yes		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	აა	U	<u> </u>			168		



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068

Official #: 1158902

Page 5 of 7

Shipyard: Trinity Ashland City

Cargo Identification							Co	nditio	ns of Carriage
							Vapor R	ecovery	
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1	
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1	
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1	
Glycerine	GCR	20 2	D	E		Α	Yes	1	
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1	
Heptanoic acid	HEP	4	D	E		Α	Yes	1	
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1	
Heptene (all isomers)	HPX	30	D	С	.,	Α	Yes	2	
Heptyl acetate	HPE	34	D	D		Α	Yes	1	
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1	
Hexanoic acid	HXO	4	D	Е		Α	Yes	1	
Hexanol	HXN	20	D	D		Α	Yes	1	
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2	
Hexylene glycol	HXG	20	D	E		Α	Yes	1	
Isophorone	IPH	18 ²		E		Α	Yes	1	
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1	
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D			A	Yes	1	
Kerosene	KRS	33	D	D		A	Yes	1	
Methyl acetate	MTT	34	D	D	-	A	Yes	1	
Methyl alcohol	MAL	20 2		c		A	Yes	1	
Methylamyl acetate	MAC	34	D	D		A	Yes	1	
Methylamyl alcohol	MAA	20	D			A	Yes	1	
	MAK	18	D			A	Yes	1	
Methyl tert-butyl ether	MBE	41 2		C		A	Yes	1	
	MBK	18	D	c		A	Yes	1	
Methyl butyl ketone	MBU	34	D	- C		A	Yes	1	
Methyl butyrate	MEK	18 2		c		A	Yes	1	
Methyl books ketone	MHK	18	D			A	Yes	1	
Methyl heptyl ketone	MIK	18 2		C		A	Yes	1	
Methyl isobutyl ketone	MNA	32	D	E		A	Yes	1	
Methyl naphthalene (molten)	MNS	33	D	D		A	Yes	1	
Mineral spirits				D					
Myrcene	MRE	30	D D	#		A	Yes	1	
Naphtha: Heavy									
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1	
Naphtha: Solvent	NSV	33	D	D		Α.	Yes	11	
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1	
Naphtha: Varnish makers and painters (75%)	NVM	33	D	<u>C</u>		Α	Yes	1	
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A .	Yes	1	
Nonene (all isomers)	NON	2	D	D		Α.	Yes	2	
Nonyl alcohol (all isomers)	NNS			E		A	Yes	1	
Nonyl phenoi	NNP		D	E		Α.	Yes	1	
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		Α_	Yes	1	
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	C		A	Yes	11	
Octanoic acid (all isomers)	OAY		D	E		A	Yes	1	
Octanol (all isomers)	OCX			E		A	Yes		
Octene (all isomers)	OTX		D	C		A	Yes	2	
Oil, fuel: No. 2	OTW		D	D/E		A	Yes	1	
Oil, fuel: No. 2-D	OTD	33	D	D C		A	Yes	1	
Oil, fuel: No. 4	OFR		D	D/E		A	Yes	1	
Oil, fuel: No. 5	OFV		D	D/E		A	Yes	11	
Oil, fuel: No. 6	OSX		D	E		A	Yes	1	
Oil, misc: Crude	OIL	33	D	C/D		Α	Yes	1	



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068

Official #: 1158902

Page 6 of 7

Shipyard: Trinity Ashland City

Cargo Identification		Co	nditio	ns of Carriage					
Name	Chem Code	Compat Group	Sub Chapter	Grade	Hull Type	Tank Group	Vapor R App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of Construction
Oil, misc: Diesel	ODS	33	D	D/E		Α	Yes	1	
Oil, misc: Lubricating	OLB	33	D	E		Α	Yes	1	
Oil, misc: Residual	ORL	33	D	E		Α	Yes	1	
Oil, misc: Turbine	OTB	33	D	E		Α	Yes	1	
Pentane (all isomers)	PTY	31	D	Α		Α	Yes	5	
Pentene (all isomers)	PTX	30	D	Α		Α	Yes	5	
alpha-Pinene	PIO	30	D	D		Α	Yes	1	
beta-Pinene	PIP	30	D	D		Α	Yes	1	
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	Ε		Α	Yes	1	
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		Α	Yes	1	
Polybutene	PLB	30	D	E		Α	Yes	1	
Polypropylene glycol	PGC	40	D	E		Α	Yes	1	
iso-Propyl acetate	IAC	34	D	С		Α	Yes	1	
n-Propyl acetate	PAT	34	D	С		Α	Yes	1	
iso-Propyl alcohol	IPA	20 ²	D	С		Α	Yes	1	
n-Propyl alcohol	PAL	20 ²	D	С		Α	Yes	1	
Propylbenzene (all isomers)	PBY	32	D	D		Α	Yes	1	
iso-Propylcyclohexane	IPX	31	D	D		Α	Yes	1	
Propylene glycol	PPG	20 2	D	E		Α	Yes	1	
Propylene glycol methyl ether acetate	PGN	34	D	D		Α	Yes	1	
Propylene tetramer	PTT	30	D	D		Α	Yes	1	
Sulfolane	SFL	39	D	E		Α	Yes	1	
Tetraethylene glycol	TTG	40	D	E		Α	Yes	1	
Tetrahydronaphthalene	THN	32	D	E		Α	Yes	1	
Toluene	TOL	32	D	С		Α	Yes	1	
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	Е		Α	Yes	1	
Triethylbenzene	TEB	32	D	Е		Α	Yes	1	
Triethylene glycol	TEG	40	D	Ε		Α	Yes	1	
Triethyl phosphate	TPS	34	D	Е		Α	Yes	1	
Trimethylbenzene (all isomers)	TRE	32	D	{D}		Α	Yes	1	
Trixylenyl phosphate	TRP	34	D	E		Α	Yes	1	
Undecene	UDC	30	D	D/E		Α	Yes	1	
1-Undecyl alcohol	UND	20	D	Е	7	Α	Yes	1	
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1	



Serial #: C2-0402521

Generated: 27-Sep-04

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28068 Official #: 1158902

Page 7 of 7

Shipyard: Trinity Ashland

Hull #: 4473

Explanation of terms & symbols used in the Table:

Cargo Identification

Compatability Group No.

Note 1

Note 2

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2. Name The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual Chem Code

Certain mixtures of cargoes may not have a CHRIS Code assigned.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and III. In accordance with 46 CFR 150.130, the Person-in-Charge

of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables

and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (G-MSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001.

Telephone (202) 267-1217

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Subchapter

Subchapter D Subchapter O

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which Grade were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for

carriage of that grade of cargo.
Flammable liquid cargoes, as defined in 46 CFR 30-10.22.

A, B, C Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the Note 4

cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

NA No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Hull Type

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

Conditions of Carriag

Tank Group

The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Vapor Recover

Approved (Y or N)

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriag

Vapor Recover

Tank Group

The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Approved (Y or N)

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category Category 1

The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles

Category 2

33 and 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1). 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could

lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7 (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5 (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems