



# BARGE "KIRBY 28112"

## ULLAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-1/2	- 00-1/2	00-7/8	- 00-7/8	01-3/8	- 01-3/8	01-3/4	- 01-3/4	02-1/4	- 02-1/4	02-3/4	- 02-3/4
1 STBD	00-1/2	- 00-1/2	00-7/8	- 00-7/8	01-3/8	- 01-3/8	01-3/4	- 01-3/4	02-1/4	- 02-1/4	02-3/4	- 02-3/4
2 PORT	00-1/2	- 00-1/2	00-7/8	- 00-7/8	01-3/8	- 01-3/8	01-3/4	- 01-3/4	02-1/4	- 02-1/4	02-5/8	- 02-5/8
2 STBD	00-1/2	- 00-1/2	00-7/8	- 00-7/8	01-3/8	- 01-3/8	01-3/4	- 01-3/4	02-1/4	- 02-1/4	02-5/8	- 02-5/8
3 PORT	00-3/8	- 00-3/8	00-7/8	- 00-7/8	01-1/4	- 01-1/4	01-3/4	- 01-3/4	02-1/8	- 02-1/8	02-5/8	- 02-5/8
3 STBD	00-3/8	- 00-3/8	00-7/8	- 00-7/8	01-1/4	- 01-1/4	01-3/4	- 01-3/4	02-1/8	- 02-1/8	02-1/2	- 02-1/2

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

### EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD DRAFT = 2'-00"  
 AFT DRAFT = 4'-00"  
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 1 PORT IS - 00-7/8"  
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 1 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11 1/8"

LENGTH BETWEEN DRAFT MARKS: 241'-03"

July 30, 2009

PRECISION MEASUREMENT  
 & ANALYSIS, INC.  
 P.O. Box 2092  
 Pearland, Texas 77588

<http://www.pmacorp.net>



















BARGE "KIRBY 28112"

2 STBD  
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

Table with columns for GAUGE HEIGHT 16'-06 3/4" and 19 FT., and rows for capacities from 0 to 2,026.20. Each row contains 18 columns of data representing different gauge heights from 0 to 19 feet.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 07/30/2009 CL - SW  
CALCULATED: 07/30/2009 CL  
PRINTED: 07/30/2009 CL

CANCELS AND SUPERCEDES  
ALL PRIOR TO 07/2009

PRECISION MEASUREMENT  
& ANALYSIS, INC.  
P.O. Box 2092  
Pearland, Texas 77588  
http://www.pmacorp.net



BARGE "KIRBY 28112"

3 PORT ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

GAUGE HEIGHT 16'-05 1/4"

Table with 21 columns (IN 0 FT., 1 FT., 2 FT., 3 FT., 4 FT., 5 FT., 6 FT., 7 FT., 8 FT., 9 FT.) and 34 rows of capacity data.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7. CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL. CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK. CAPACITY TABLE ONLY APPLIES TO ULLAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE. GAUGE POINT: (HERMETIC) LOCATED 12'-08" OFF CENTERLINE AND 52'-03" FORWARD OF AFT BULKHEAD.

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

PRECISION MEASUREMENT & ANALYSIS, INC. P.O. Box 2092 Pearland, Texas 77588 http://www.pmacorp.net

Handwritten signature





