

UNITED STATES

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 18 Nov 2019 Expiration Date: 18 Nov 2020

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name	Official Number	IMO Num		Call Sign	Service		
KIRBY 28114	1220961				10.20	Barge	
Hailing Port WILMINGTON, DE	Hull Material Steel	Horse	power	Propulsion			
UNITED STATES							
Place Built ASHLAND CITY, TN	Delivery Date 31Aug2009	Keel Laid Date 31May2009	Gross Tons R-1632	Net Tons R-1632	DWT	Length R-300.0	
UNITED STATES	_		 -	ŀ		10	
Owner KIRBY INLAND MARINE, LP 55 WAUGH DRIVE SUITE 1000 HOUSTON, TX 77007	1	1835	Y INLAND 0 MARKET	MARINE, LP STREET		1	

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters 0 Licensed Mates 0 Chief Engineers 0 Oilers 0 Chief Mates 0 First Class Pilots 0 First Assistant Engineers 0 Second Mates 0 Radio Officers 0 Second Assistant Engineers 0 Third Mates 0 Able Seamen 0 Third Assistant Engineers 0 Master First Class Pilot 0 Ordinary Seamen 0 Licensed Engineers 0 Mate First Class Pilots 0 Deckhands 0 Qualified Member Engineer

UNITED STATES

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

--- Lakes, Bays, and Sounds---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	Annual/Peri	odic/Re-Inspe	ction	This certificate issued by:
Date	Zone	A/P/R	Signature	J.J. ANDREW, CDR, USCG, By direction
				Officer in Charge, Marine Inspection Marine Safety Unit Port Arthur
				Inspection Zone



United States of America Department of Homeland Security **United States Coast Guard**

Certification Date: 18 Nov 2019 18 Nov 2020 **Expiration Date:**

Temporary Certificate of Inspection

Vessel Name: KIRRY 28114

Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

31Aug2029

18Nov2019

15Aug2009

Internal Structure

31Aug2024

18Nov2019

24Oct2014

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

CERTIFIED FOR CARRIAGE OF 46 CFR SUBCHAPTER D, GRADE "A" AND LOWER, AND SPECIFIED

46 CFR SUBCHAPTER O DANGEROUS CARGOES.

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

28500

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	838	13.6
2 P/S	843	13.6
3 P/S	777	13.6

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
11	3804	10ft 0in	13.6	LBS
II	3804	10ft 0in	13.6	R
III	4680	11ft 9in	13.6	R
Ш	4680	11ft 9in	13.6	LBS

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial #C1-0901515, dated May 15, 2009, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR Part 197, subpart C are applied.

Vapor Control Authorization

Per 46 CFR, Part 39, excluding Part 39.40, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letters serial Marine Safety Center letters Serial #C1-0901515, dated May 15, 2009, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Per 46 CFR 151.10(c)(2) the maximum tank weights listed above reflect uniform(within 5%) loading at the deepest draft

^{*}Stability and Trim*



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 18 Nov 2019 Expiration Date: 18 Nov 2020

Temporary Certificate of Inspection

Vessel Name: KIRBY 28114

allowed. When carrying subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

Next

--- Inspection Status ---

Fuel Tanks

Internal Examinations

Tank ID Previous Last
Aft main deck - 31Aug2009

Cargo Tanks

	Tank Id	Internal Exam			External Exan	n	
		Previous	Last	Next	Previous	Last	Next
I	1 P/S	31Aug2009	18Nov2019	31Aug2029	. .		1
	2 P/S	31Aug2009	18Nov2019	31Aug2029		2	-
	3 P/S	31Aug2009	18Nov2019	31Aug2029	÷.	¥:	_
				Hydro Test			
	Tank ld 1 P/S	Safety Valves		Previous	Last	Next	
	2 P/S			-	31Aug2009	9	
	3 P/S			~	31Aug2009	·	
	3 7/3	##:		-	31Aug2009	-	

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

B-II

END





Serial #: C1-0901515 Dated:

15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Shipyard: TRINITY ASHLAND

CITY

Hull #: 4655

Official #: 1220961

ank Group Information Cargo Identification		dentification					Tanks		Cargo Transfer		Environmental Control		Fire	Special Requirements			
Ink Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Cargo Seg Tank	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp Cont
4 #1P/S, #2P/S, #3P/S	13.6	Almos.	Amb.	II	1ii 2ii	Integral Gravity	PV	Closed	it	G-1	NR	NA	Portable	.50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50- 81(b),	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

- Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.
 - 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
 - 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identificatio	n				!	Conditions of Carriage					
			:			!	Vapor Re	covery			
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period	
Authorized Subchapter O Cargoes											
Acetonitrile	ATN	37	0	C	111	Ą	Yes	3	No	G	
Acrylonitrile	ACN	15 ²	0	С	11	Α	Yes	4	50-70(a), .55-1(o)		
Adiponitrile	ADN	37	0	E	()	Α	Yes	1	No	G	
Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	131	Α	No	N/A	.50-81, .50-86	G	
Aminoethylethanolamine	AEE	8	0	Ε	111	Α	Yes	1	.55-1(b)	G	
Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	H	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G	
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	111	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G	
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	II	Α	No	N/A	No	G	
Benzene	BNZ	32	0	С	111	A	Yes	1	.50-60	G	
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 ²	0	С	III	Α	Yes	1	.50-60	G	
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 ²	0	С	Ш	À	Yes	1	.50-80, .56-1(b), (d), (f), (g)	G	
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	втх	32	0	B/C	111	Α	Yes	1	.50-60	G	
Butyl acrylate (all isomers)	BAR	14	0	D	III	Α	Yes	2	50-70(a), .50-81(a), (b)	G	
Butyl methacrylate	вмн	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	
Butyraldehyde (ail isomers)	BAE	19	0	С	III	A	Yes	1	.55-1(h)	G	
Camphor oil (light)	CPO	18	0	D	- 11	Α	No	N/A	No	G	
Carbon tetrachloride	CBT	36	0	NA	III	Α	No	N/A	No	G	
Caustic potash solution	CPS	5 ²	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G	
Caustic soda solution	CSS	5 ²	0	NA	III	Α	No	N/A	.50-73, .55-1(j)	G	
Chemical Oil (refined, containing phenolics)	COD	21	ō	Ε	II	Α	No	N/A	.50-73	G	
Chlorobenzene	CRB	36	0	D	III	Α	Yes	1	No	G	
Chloroform	CRF	36	0	NA	III	A	Yes	3	No .	G	
Coal tar naphtha solvent	NCT	33	0	D	111	Α	Yes	1	.50-73	G	
Creosote	CCW	21 2	0	E	III	Α	Yes	1	No	G	
Cresols (all isomers)	CRS	21	0	E	111	Α	Yes	1	No	G	
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)	G	
Cresylic acid tar	CRX		0	Ε	111	Α	Yes	1	.55-1(f)	G	
Crotonaldehyde	CTA	19 ²	0	С	11	Α	Yes	4	55-1(h)	G	
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	III	Α	No	N/A	No	G	
Cyclohexanone	ССН	18	0	D	111	Α	Yes	1	.56-1(a), (b)	G	
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	0	E	III	Α	Yes	1	.56-1 (b)	G	
Cyclohexylamine	CHA	7	0	D	111	A	Yes	1	.56-1(a), (b), (c), (g)	G	
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	111	A	Yes	1	.50-80, 56-1(b)	G	

Department of Homeland Security
United States Coast Guard



Serial #: C1-0901515 Dated: 15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Shipyard: TRINITY ASHLAND

CITY

Official #: 1220961

Page 2 of 8

Hull #: 4655

Cargo Identification						Conditions of Carriage						
							Vapor R	ecovery				
Name	Chem Code	Compat Group No	Sub Chapter	Grade		Tank Group		VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of .50-70(a), .50-81(a), (b), .55-1(c)	Insp. Perio		
iso-Decyl acrylate	IAI	14	0	E		<u>A</u>	Yes	2 2	.56-1(a), (b)	G		
Dichlorobenzene (all isomers)	DBX	36	0			<u>A</u> _	Yes	3	No No	G		
1,1-Dichloroethane	DCH	36	0	С	- 111	A	Yes	1	.55-1(f)	G		
2,2'-Dichloroethyl ether	DEE	41	0	D		A	Yes		No No	G		
Dichloromethane	DCM	36	0	NA	111	A	Yes	5				
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0_	<u>E</u>	111	Α	No	N/A	.56-1(a), (b), (c), (g)			
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2		Α	- 111	A	No	N/A	.56-1(a), (b), (c), (g)			
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 2	_ 0_	E		A	No	N/A				
1,1-Dichloropropane	DPB	36	_	С	111	Α	Yes	3	No	G		
1,2-Dichloropropane	DPP	36	0	С	111	Α	Yes	3	No	- G		
1,3-Dichloropropane	DPC	36	0	С	III	Α	Yes	3	No	G		
1,3-Dichloropropene	DPU	15	0	D	11	Α	Yes	4	No			
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	11	Α	Yes	1	No	G		
Diethanolamine	DEA	8	0	E	Ш	A	Yes	1	.55-1(c)	G		
Diethylamine	DEN	7	0	С	111	Α	Yes	3	.55-1(c)	G		
Diethylenetriamine	DET	7 2	0	E	III	Α	Yes	1	.55-1(c)	G		
Diisobutylamine	DBU	7	0	D	111	Α	Yes	3	.55-1(c)	G		
Diisopropanolamine	DIP	8	0	E	HI	Α	Yes	1	.55-1(c)	G		
Diisopropylamine	DIA	7	0	С	Ħ	A	Yes	3	.55-1(c)	G		
N,N-Dimethylacetamide	DAC	10	0	Ε	111	Α	Yes	3	.56-1(b)	G		
Dimethylethanolamine	DMB	8	0	D	Ш	Α	Yes	1	.56-1(b), (c)	G		
Dimethylformamide	DMF	10	0	D	III	Α	Yes	1	55-1(e)	G		
Di-n-propylamine	DNA	7	0	С	Ħ	Α	Yes	3	.55-1(c)	G		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	E	111	A	No	N/A	.56-1(b)	G		
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	- 11	Α	No	N/A	No	G		
EE Glycol Ether Mixture	EEG	40	0	Õ	H	Α	No	N/A	No	G		
Ethanolamine	MEA	8	0	E	(1)	A	Yes	1	55-1(c)	G		
Ethyl acrylate	EAC	14	0	С	111	Α	Yes	2	50-70(a), 50-81(a), (b)	G		
Ethylamine solution (72% or less)	EAN	7	0	Α	11	Α	Yes	6	.55-1(b)	G		
N-Ethylbutylamine	EBA	7	0	D	111	A	Yes	3	.55-1(b)	G		
N-Ethylcyclohexylamine	ECC	 7	0	D	101	A	Yes	1	.55-1(b)	G		
Ethylene cyanohydrin	ETC	20	0	E	<u>;;;</u>	A	Yes	1	No	G		
Ethylenediamine	EDA	7 2			111		Yes	1	.55-1(c)	G		
Ethylene dichloride	EDC	36 ²	-	c	111	A	Yes	1	No	G		
	EGH	40	-	Ē	111	A	No	N/A	No	G		
Ethylene glycol hexyl ether	EGC	40	-	D/E			Yes	1	No No	G		
Ethylene glycol monoalkyl ethers	EGP	40	0	E	111	 A	Yes	1	No	G		
Ethylene glycol propyl ether	EAI	14	0	E	- 111	— `	Yes		.50-70(a), .50-81(a), (b)	G		
2-Ethylhexyl acrylate	ETM	14		D/E	- 111	<u>^</u>	Yes	2	50-70(a)	G		
Ethyl methacrylate	EPA	19 ²	-0	E	- 111	<u>^</u> _	Yes	1	No	G		
2-Ethyl-3-propylacrolein							Yes	1	.55-1(h)	G		
Formaldehyde solution (37% to 50%)	FMS	19 ²	0	D/E	111	A			.55-1(h)	G		
Furfural	FFA	19	0_	D		A	Yes	1		G		
Glutaraldehyde solution (50% or less)	GTA	19	0_	NA_	- 111	A	No	N/A	.55-1(c)	G		
Hexamethylenediamine solution	HMC		0	E	. 111	A	Yes	1	.56-1(b), (c)	G		
Hexamethyleneimine	HMI	7	0	<u> </u>		A	Yes	1				
Hydrocarbon 5-9	HFN		0	С	101	A	Yes	1	.50-70(a), .50-81(a), (b)			
Isoprene	IPR	30	0	Α	111	A_	Yes	7	.50-70(a), .50-81(a), (b)	G		
Isoprene, Pentadiene mixture	IPN		0	В	- 111	Α Δ	No No	N/A N/A		G		
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	III	Α	INO	INIA				
Mesityl oxide	MSO	18 ²	0	D	III	Α	Yes	1	No	G		



C1-0901515

15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Shipyard: TRINITY ASHLAND

CITY

Official #: 1220961

Page 3 of 8

Hull #: 4655

Cargo Identification	1					Conditions of Carriage					
Name	Chem Code	Compat Group No	Sub Chapter O	Grade C	Hull Tvoe III	Tank Group A	App'd (Y or N) Yes	vcs	Special Requirements in 46 CFR 151 General and Mat'ls of .50-70(a), .50-81(a), (b)	Insp. Period G	
Methyl acrylate	MAM	14							No	G	
Methylcyclopentadiene dimer	MCK	30	0	<u> </u>		A	Yes		.56-1(b), (c)	G	
Methyl diethanolamine	MDE	8		<u>E</u>	111	A	Yes		.55-1(0)	G	
2-Methyl-5-ethylpyridine	MEP	9	0	E	111	A	Yes	1	.50-70(a), .50-81(a), (b)	- 6	
Methyl methacrylate	MMM		0	С		A	Yes	2	.55-1(c)	_	
2-Methylpyridine	MPR	9	0	D	- 111	<u> </u>	Yes	3		G	
alpha-Methylstyrene	MSR	30	0	D	111	A	Yes	2	.50-70(a), .50-81(a), (b)		
Morpholine	MPL	7 ²	0	D	III	A	Yes	1	.55-1(c)		
1- or 2-Nitropropane	NPM	42	0	D		A	Yes	1	.50-81	G	
1,3-Pentadiene	PDE	30	0	Α	111	A	Yes	7	.50-70(a), .50-81	G	
Perchloroethylene	PER	36	0	NA	- 111	Α	No	N/A	No	G	
Polyethylene polyamines	PEB	7 2	0	E	HII	Α_	Yes	1	.55-1(e)	G	
iso-Propanolamine	MPA	8	0	E	III	Α	Yes	. 1	.55-1(c)	G	
Propanolamine (iso-, n-)	PAX	8	0	E	111	Α	Yes	1	.56-1(b), (c)	G	
iso-Propylamine	IPP	7	0	A	- 11	Α	Yes	5	.55-1(c)	G	
Pyridine	PRD	9	0	С	111	Α	Yes	1	.55-1(e)	G	
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0		111	Α	No	N/A	.50-73, .55-1(j)	G	
Sodium aluminate solution (45% or less)	SAU	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G	
Sodium chlorate solution (50% or less)	SDD	0 1,2	0	NA	- 111	Α	No	N/A	.50-73	G	
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b)	G	
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2	0	NA	III	Α	Yes	1	.50-73, .55-1(b)	G	
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,2	0	NA	111	Ā	No	N/A	.50-73, .55-1(b)	G	
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1.2	0	NA	11	Α	No	N/A	.50-73, .55-1(b)	G	
Styrene (crude)	STX		0	D	Ш	Α	Yes	2	No	G	
Styrene monomer	STY	30	0	D	HI	Α	Yes	2	.50-70(a), 50-81(a), (b)	G	
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	A	No	N/A	No	G	
Tetraethylenepentamine	TTP	7	0	E	411	A	Yes	1	.55-1(c)	G	
	THF	41	-		111	A	Yes	1	.50-70(b)	G	
Tetrahydrofuran	TDA	9	0	E	11	A	No	N/A	.50-73, .58-1(a), (b), (c), (g)	G	
Toluenediamine	TCB	36	0	_ <u>_</u> _	111	A	Yes	1	No	G	
1,2,4-Trichlorobenzene	TCM	36	-	NA NA	111	$\frac{1}{A}$	Yes	1	.50-73, .56-1(a)	G	
1,1,2-Trichloroethane	TCL	36 ²		NA.	''' -	<u></u>	Yes	<u>-</u>	No	G	
Trichloroethylene					-''' -	<u>A</u>	Yes	3	.50-73, .56-1(a)	G	
1,2,3-Trichloropropane	TCN	36	0	_ <u>E</u> _		A	Yes	1	.55-1(b)	G	
Triethanolamine	TEA	8 ²		E		<u>^</u>	Yes	3	.55-1(e)	G	
Triethylamine	TEN	7	0	<u>C</u>	- 11			3 1	.55-1(b)		
Triethylenetetramine	TET	7 2		E		A	Yes		.56-1(a), (b), (c)	G	
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA		A	No	N/A	.50-73, .56-1(a), (c).	G	
Trisodium phosphate solution	TSP	5	0	NA	111	A	No	N/A		G	
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	111	A	No	N/A		-	
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	HI	A	No	N/A		<u> </u>	
Vinyl acetate	VAM	13	0	C	111		Yes	2	.50-70(a), .50-81(a), (b)	G	
Vinyl neodecanate	VND	13	0	E	111	Α	No	N/A		G	
Vinyltoluene	VNT	13	0	D	- 111	Α	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (
Subchapter D Cargoes Authorized for Vapor Contr		40.2					Yes				
Acetone	ACT	18 ²	<u> D</u>	<u> </u>		A					
Acetophenone	ACP	18	_ <u>D</u>	<u> </u>		<u>A</u> _	Yes	1			
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	<u>E</u>		A	Yes	1			
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1			



Department of Homeland Security **United States Coast Guard**

Serial #: C1-0901515

15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114 Official #: 1220961

Shipyard: TRINITY ASHLAND

CITY

			Page 4	018		CITY Hull #: 4655					
Cargo Identification	n										
	T	T			_			Condi	tions of Carriage		
Amyl acetate (all isomers)	Chem Code AEC	Compat Group No 34	Sub Chapte D		Hull Type	Tank Gmun	Vapor I App'd	Recovery VCS	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp.	
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		<u> </u>	Yes	1	· · · · · · · · · · · · · · · · · · ·	Perio	
Benzyl alcohol	BAL	21	D	D E		_ <u>A</u>	Yes	1			
Brake fluid base mixtures (containing Poly(2-8)aikylene(C2-C3)	BFX	20	_	<u> </u>		A	Yes	1			
their borate esters)		20	b	-		Α	Yes	1			
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1			
Butyl alcohol (iso-)	IAL	20 2	D	Ď		A	Yes	1			
Butyl alcohol (n-)	BAN	20 ²	D	D		A	Yes	1			
Butyl alcohol (sec-)	BAS	20 ²	D	С		A	Yes	1	······································		
Butyl alcohol (tert-)	BAT		D	С		Α	Yes	1			
Butyl benzyl phthalate	ВРН	34	D	E		A	Yes	1			
Butyl toluene	BUE	32	D	D		A	Yes	1			
Caprolactam solutions	CLS	22	D	E		A	Yes	1			
Cyclohexane	CHX	31	D	-		A	Yes	1			
Cyclohexanol	CHN	20	D	E		A	Yes	1			
.3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2			
dinas citiza a ama ama a a como como a como a como a como como	CMP	32	D	D		A	Yes	1		-	
-Cymene	IDA	19	D	E		Α	Yes	1			
so-Decaldehyde	DAL	19	D	E		Α	Yes	1			
-Decaldehyde	DCE	30	D	D		A	Yes	1			
Decene	DAX	20 ²	D	E		Α	Yes	1			
Decyl alcohol (all isomers)	DBZ	32	D	E		Α	Yes	1			
n-Decylbenzene, see Alkyl(C9+)benzenes	DAA	20 ²	D	D		Α	Yes	1			
Diacetone alcohol	DPA	34	D	E		Α	Yes	11			
ortho-Dibutyl phthalate	DEB	32	D	D		Α	Yes	1			
Diethylbenzene	DEG	40 ²	D	E	-	A	Yes	1			
Diethylene glycol	DBL	30	D	С		Α	Yes	1			
Diisobutylene	DIK	18	D	D		Α	Yes	1			
Diisobutyl ketone	DIX	32	D	E		Α	Yes	1			
Diisopropylbenzene (all isomers)	DTL	34	D	E		Α	Yes	1			
Dimethyl phthalate	DOP	34	D	E		Α	Yes	1			
Dioctyl phthalate	DPN	30	D	D		Α	Yes	1			
Dipentene	DIL	32	D	D/E		Α	Yes	1			
Diphenyl	DDO	33	D	E		Α	Yes	1			
Diphenyl, Diphenyl ether mixtures	DPE	41	D	{E}		Α	Yes	1_			
Diphenyl ether	DPG	40	D	E		Α	Yes				
Dipropylene glycol	DFF	33	D	E		Α_	Yes				
Distillates: Flashed feed stocks	DSR	33	D	E		Α	Yes	1			
Distillates: Straight run	DOZ	30	D	D		A	Yes				
Dodecene (all isomers)	DDB	32	D	E		A_	Yes				
Dodecylbenzene, see Alkyl(C9+)benzenes	EEA	34	D	D		A	Yes				
2-Ethoxyethyl acetate	ETG	40	D	E		<u>A</u>	Yes				
Ethoxy triglycol (crude)	ETA	34	D	С		A	Yes				
Ethyl acetate	EAA	34	D	E		. <u> </u>	Yes				
Ethyl acetoacetate	EAL	20 ²	D	С		<u>A</u>	Yes				
Ethyl alcohol	ETB		D	С		A	Yes				
Ethylbenzene	EBT		D	D		A	Yes		a water to the control of the contro		
Ethyl butanol	EBE		D	С		A	Ye				
Ethyl tert-butyl ether	EBF	34	D	D		A	Ye				
Ethyl butyrate	EC	/ 31	D	D		Α	Ye	<u> </u>	of Inspection. ***		



Serial #: C1-0901515 Dated:

15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Shipyard: TRINITY ASHLAND

CITY Hull #: 4655

Official #: 1220961

Page 5 of 8

					T					
Cargo Identification	n	,		Conditions of Carriage						
Name Ethylene glycol	Chem Code EGL	Compat Group No 20 ²	Sub Chaoter D	Grade E	Hull TvDe	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Ethylene glycol butyl ether acetate	EMA	34	D	E		Α	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	E		Α	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1		
2-Ethylhexanol	EHX	20	D	E		Α	Yes	1		
Ethyl propionate	EPR	34	D	С		Α	Yes	1		
Ethyl toluene	ETE	32	D	D		Α	Yes	1		
Formamide	FAM	10	D	E		Α	Yes	1		
Furfuryl alcohol	FAL	20 ²	D	E		Α	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		Α	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		Α	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gailon)	GAV	33	D	С		Α	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		Α	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	11		
Glycerine	GCR	20 ²	D	E		Α	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	НМХ	31	D	С		Α	Yes	1		
Heptanoic acid	HEP	4	D	Е		Α	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		Α	Yes	1		
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2		
Heptyl acetate	HPE	34	D	E		Α	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1		
Hexanoic acid	НХО	4	D	E		Α	Yes	1		
Hexanol	HXN	20	D	D		Α	Yes	1		
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2		
Hexylene glycol	HXG	20	D	E		Α	Yes	1		
Isophorone	IPН	18 ²	D	E		Α	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		Α	Yes	1		
Kerosene	KRS	33	D	D		Α	Yes	1		
Methyl acetate	MTT	34	D	D		Α	Yes	1		
Methyl alcohol	MAL	20 ²	D	С		Α	Yes	1		
Methylamyl acetate	MAC	34	D	D		Α	Yes	1		
Methylamyl alcohol	MAA	20	D	D		Α	Yes	1		
Methyl amyl ketone	MAK	18	D	D		Α	Yes	· 1		
Methyl tert-butyl ether	MBE	41 ²	D	С		Α	Yes	1		
Methyl butyl ketone	MBK	18	D	c		A	Yes	1		
Methyl butyrate	MBU	34		c		A	Yes	1		
Methyl ethyl ketone	MEK	18 ²	D	С		A	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		Α	Yes	1		
Methyl isobutyl ketone	MIK	18 ²	D	С		Α	Yes	1		
Methyl raphthalene (molten)	MNA	32	. D	E		A	Yes	1	W	
Mineral spirits	MNS	33	D	D		A	Yes	1		
Myrcene	MRE	30		_ _		A	Yes	1		
Naphtha: Heavy	NAG	33	. D	#		Α	Yes	1		
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1		
Naphtha: Solvent	NSV	33					Yes	1		
riapiniia. Joivent	.,,,,,									



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Official #: 1220961

Shipyard: TRINITY ASHLAND

Serial #: C1-0901515


15-May-09

CITY

Hull #: 4655

Page 6 of 8

Cargo Identifica		Conditions of Carriage								
04.90				1			Vapor	Recovery		1.
	Chem	Compat	Sub	Grade	Hull	Tank Groun	App'd (Y or N)	VCS	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp.
Name	l Code NSS	Group No	Chapte:	D	: IVDe	A	Yes	1		
Naphtha: Stoddard solvent	NVM	33	D	C		Α	Yes	1		
Naphtha: Varnish makers and painters (75%)	NAX	31	D	D		Α	Yes	1		
Nonane (all isomers), see Alkanes (C6-C9)	NON	30	D	<u> </u>		A	Yes	2		
Nonene (all isomers)	NNS	20 ²	D	E		A	Yes	1		
Nonyl alcohol (all isomers)	NNP	21	. – D	Ε.		Ā	Yes	1	·	
Nonyl phenol	NPE	40	D	E		A	Yes	1		
Nonyl phenol poly(4+)ethoxylates	OAX	31	D	Ċ		Α	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAY	4	D	E		A	Yes	1		
Octanoic acid (all isomers)	OCX	20 2	D	Ē		A	Yes	1		
Octanol (all isomers)	OTX	30	D	c		A	Yes	2		
Octene (all isomers)	OTW	33	D_	D/E		A	Yes	1		
Oil, fuel: No. 2	OTD	33	<u> </u>	D		- <u>A</u>	Yes	1		
Oil, fuel: No. 2-D	OFR		D	D/E		. <u>- 2</u>	Yes	:: 1		
Oil, fuel: No. 4		33	D	D/E		- 	Yes			* "
Oil, fuel: No. 5	OFV	33		E		$\frac{1}{A}$	Yes	<u> </u>		
Oil, fuel: No. 6	OSX	33	<u>D</u>					1		
Oil, misc: Crude	OIL	33	D	C/D		<u> </u>	Yes			
Oll, misc: Diesel	ODS	33	D	D/E		<u> </u>	Yes	1		
Oil, misc: Gas, high pour	OGP	33	D	E		<u> </u>	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1		
Oil, misc: Residual	ORL	33	D	E.		. A	Yes	1		
Oil, misc: Turbine	ОТВ	33	D	E		<u> </u>	Yes	1		
Pentane (all isomers)	PTY	31	D	Α		Α	Yes	5		
Pentene (all isomers)	PTX	30	D	Α		Α	Yes	5		
alpha-Pinene	PIO	30	D	D		Α	Yes	1		
beta-Pinene	PIP	30	D	D		Α	Yes	1		
Poly(2-8)aikylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		Α	Yes	1		
Poly(2-8)aikylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		Α	Yes	1		
Polybutene	PLB	30	D	Е		Α	Yes	1		
Polypropylene glycol	PGC	40	D	E		Α	Yes	1		
iso-Propyl acetate	IAC	34	D	С		Α	Yes	1		
n-Propyl acetate	PAT	34	D	С		Α	Yes	1		
iso-Propyl alcohol	IPA	20 ²	D	С		Α	Yes	1		
n-Propyl alcohol	PAL	20 ²	D	С		Α	Yes	1		
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1		
iso-Propylcyclohexane	IPX	31	D	D		Α	Yes	1		
Propylene glycol	PPG	20 ²	D	E		Α	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		A	Yes	1		
Propylene tetramer	PTT	30	<u> </u>	D		A	Yes	1		
Sulfolane	SFL	39	D	E		A	Yes	1		
Tetraethylene glycol	ΠG	40	D	E		Ā	Yes	1		
Tetrahydronaphthalene	THN	32		E		—	Yes	<u>-</u>		
Toluene	TOL	32	D	C		- <u>^</u>	Yes	.		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D D	E		- ^	Yes	<u>-</u>		
Triethylbenzene	TEB	32	D	Ē		Â	Yes	<u>.</u>		
Triethylene glycol	TEG	40	<u>D</u>	E		- <u>A</u> -	Yes			
Triethyl phosphate	TPS	34	D	E		<u>A</u>	Yes			
Trimethylbenzene (all isomers)			D					1		
Trixylenyl phosphate	TRE	32		(D)		A	Yes			
	TRP	34	D	E		Α.	Yes	. 1		
Undecene	UDC	30	D	D/E		A	Yes	1		





Serial #: C1-0901515 Dated: 15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114

Shipyard: TRINITY ASHLAND


CITY

Official #: 1220961

Page 7 of 8

Hull #: 4655

Cargo Identification					Conditions of Carriage					
Nama 1-Undecyl alcohol	Chem Code UND	Compat Group No 20	Sub Chapter D	Grade E	Hull Type	Tank Group A	Aco'd	Recovery VCS Category 1	Special Requirements in 48 CFR	insp. Period
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1		



Serial #: C1-0901515 Dated:

15-May-09

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 28114 Official #: 1220961

Page 8 of 8

Shipyard: TRINITY ASHL

Hull #: 4655

Explanation of terms & symbols used in the Table:

Cargo Identification

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

Chem Code

Name

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

Note 1

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart

Subchapter Subchapter D Subchapter O

Note 2

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1. Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo Flammable liquid cargoes, as defined in 46 CFR 30-10,22

A, B, C

Note 4

Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the

cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

NA

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo.

No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Vapor Recovery Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category:

The specified cargo's provisional classification for vapor control systems.

Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems.