

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 13 Jan 2023 Expiration Date: 13 Jan 2024

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the

receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection. Vessel Name Official Number IMO Number KIRBY 28713 1265777 Tank Barge Hailing Port Hull Material Horsepower Propulsion WILMINGTON, DE Steel UNITED STATES Place Built Delivery Date Keel Laid Date Gross Tons Net Tons Length GALVESTON, TX R-1632 R-1632 R-300.0 07Mar2016 30Sep2015 1-0 UNITED STATES Owner Operator

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES KIRBY INLAND MARINE LP 18350 MARKET ST. CHANNELVIEW, TX 77530 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters 0 Licensed Mates 0 Chief Engineers 0 Chief Mates 0 First Class Pilots 0 First Assistant Engineers 0 Second Mates 0 Radio Officers 0 Second Assistant Engineers 0 Third Mates 0 Able Seamen 0 Third Assistant Engineers 0 Master First Class Pilot 0 Ordinary Seamen 0 Licensed Engineers 0 Mate First Class Pilots 0 Deckhands 0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

--- Lakes, Bays, and Sounds---

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Date	Zone	A/P/R	Signature

This certificate issued by:

K. A. Hantal, CDR, USCG, By direction

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



United States of America Department of Homeland Security **United States Coast Guard**

Certification Date: 13 Jan 2023 **Expiration Date:** 13 Jan 2024

Temporary Certificate of Inspection

Vessel Name: KIRBY 28713

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

31Jan2033

13Jan2023

07Mar2016

Internal Structure

31Jan2028

13Jan2023

07Mar2016

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

25711

Barrels

Units

D

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number

Max Cargo Weight per Tank (short tons)

Maximum Density (lbs/gal)

1 P/S

759

13.6

2 P/S

885

13.6

3 P/S

618

13.6

Loading Constraints - Stability

Hull Type

Maximum Load (short tons)

Maximum Draft

Max Density

Route Description

11

2334

(ft/in) 7ft Oin (lbs/gal) 13.6

R, LBS

111

4309

11ft Oin

13.6

R, LBS

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial # C1-2300134, dated 12 Jan 2023, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

Vessels is not covered by a benzene monitoring program IAW 46 CFR 197, Subpart C. Vessel is not authorized to carry Benzene or Benzene containing cargoes with a Benzene concentration of 0.5% or more.

Thermal fluid heater may only be operated when carrying Grade "E" cargoes. The vessel is inspected and approved for the carriage of Grade "E" combustible liquids when transported in molten form at elevated temperatures.

Stability and Trim

Per 46 CFR 151.10(c) (2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 13 Jan 2023 Expiration Date: 13 Jan 2024

Temporary Certificate of Inspection

Vessel Name: KIRBY 28713

Fuel	Tan	ks

Internal Examinations

Tank ID

Previous

Next

FWD Machinery Deck

27

23Nov2022

Aft Machinery Deck

07Mar2016

Last

Cargo Tanks

	Internal Exam			External Exam	E.	
Tank Id	Previous	Last	Next	Previous	Last	Next
1 P/S	07Mar2016	13Jan2023	31Jan2033	-	-	÷
2 P/S	07Mar2016	13Jan2023	31Jan2033	-	*	: -
3 P/S	07Mar2016	13Jan2023	31Jan2033	=	-	н
			Hydro Test			
Tank Id	Safety Valves		Previous	Last	Next	
1 P/S	-		·	78	:: =	
2 P/S	~		=	æ	7 2	
3 P/S	2		¥	4	-	

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

4

40-B

END



C1-2300134

Dated: 12-Jan-23



Certificate of Inspection

Cargo Authority Attachment

Official #: 1265777

Shipyard: WEST GULF MARINE

Hull #: 253

Tank Group Information	Cargo I	dentificat	ion		Caraa		Tanks		Carg		Environ		Fire	Special Require	ments		
Tnk Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Cargo Seg Tank	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp Cont
A #1 P/S, #2 P/S, #3 P/S	13.6	Atmos	Elev	11	1ii 2ii	Integral Gravity	Open	Restr.	11:	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50-73,	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

List of Authorized Cargoes

Cargo Identification	Conditions of Carriage									
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor R App'd (Y or N)	ecovery VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Authorized Subchapter O Cargoes										
Olefins (C13+, all isomers)	OFZ	30	D/O	E	III	Α	No	N/A		G
Alkyl (C7-C9) nitrates	AKN	34 2	0	NA	111	Α	No	N/A	,50-81, .50-86	G
Aminoethyl ethanolamine	AEE	8	0	E	111	Α	No	N/A	55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	432	0	NA	.111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	-11	Α	No	N/A	No	G
Benzene, C10-16 alkyl derivatives	BEND	32	0	D	Ш	Α	No	N/A		G
Camphor oil (light)	CPO	18	0	D	.11	Α	No	N/A	No	G
Caustic potash solution	CPS	52	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G
Caustic soda solution	CSS	5 ²	0	NA	Ш	Α	No	N/A	.50-73, .55-1(j)	G
Chloroform	CRF	36	0	NA	111	Α	No	N/A	No	G
Creosote	ccw	212	0	E	III	Α	No	N/A	No	G
Cresols (all isomers)	CRS	21	0	E	111	А	No	N/A	No	G
Cresylic acid tar	CRX	21	0	E	Ш	Α	No	N/A	.55-1(f)	G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	111	Α	No	N/A	.50-60, .56-1(b)	G
iso-Decyl acrylate	IAI	14	0	E	111	Α	No	N/A	.50-70(a), .50-81(a), (b), .55-1(c)	G
2.4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	111	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2.4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	432	0	E	111	Α	No	N/A	.56-1(a), (b), (c), (g)	G
Diethanolamine	DEA	8	0	Е	Ш	Α	No	N/A	.55-1(c)	G
Diethylenetriamine	DET	72	0	E	111	Α	No	N/A	.55-1(c)	G
Diisopropanolamine	DIP	8	0	E	III	Α	No	N/A	.55-1(c)	G
1-Dodecene	DDC	30	0	E	Ш	Α	No	N/A	No	G
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	Е	III	Α	No	N/A		G
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	П	Α	No	N/A	No	G
Ethanolamine	MEA	8	0	E	Ш	Α	No	N/A	.55-1(c)	G
Ethylene cyanohydrin	ETG	20	0	E	111	A	No	NA	No	a i
Ethylene glycol hexyl ether	EGH	40	0	E	III	Α	No	N/A	No	G
Ethylene glycol propyl ether	EGP	40	0	E	HI	Α	No	N/A	No	G
2-Ethylhexyl acrylate	EAI	14	0	E	111	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Glutaraldehyde solutions (50% or less)	GTA	19	0	NA	111	Α	No	N/A	No	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	KPL	5	0	NA	10	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G
Methyl diethanolamine	MDE	8	0	E	Ш	Α	No	N/A	.56-1(b), (c)	G
2-Methyl-5-ethyl pyridine	MEP	9	0	E	H	Α	No	N/A	.55-1(e)	G
Morpholine	MPL	72	0	D	111	Α	No	N/A	.55-1(c)	G

^{2.} Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

^{3.} Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.





Serial #: C1-2300134

12-Jan-23

Certificate of Inspection

Cargo Authority Attachment

Shipyard: WEST GULF MARINE

Hull #: 253

Official #: 1265777

Page 2 of 3

Cargo Identification							Conditions of Carriage							
		Compat					Vapor Recovery		Special Requirements in 46 CFR	1				
Name	Chem Code	Group	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	151 General and Mat'ls of	Insp. Period				
Polyethylene polyamines	PEB	72	0	Ε	Ш	Α	No	N/A	.55-1(e)	G				
Potassium chloride solution (brine)	PCSB	0	0	NA	111	Α	No	N/A		G				
iso-Propanolamine	MPA	8	0	E	111	Α	No	N/A	.55-1(c)	G				
Propanolamine (iso-, n-)	PAX	8	0	E	Ш	Α	No	N/A	,56-1(b), (c)	G				
Sodium aluminate solution (45% or less)	SAU	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (b), (c)	G				
Sodium chlorate solution (50% or less)	SDD	0 1.2	0	NA	111	A	No	N/A	.50-73	G				
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1.2	0	NA	111	Α	No	N/A	,50-73, .55-1(b)	G				
Styrene monomer	STY	30	0	D	Ш	А	No	N/A	.50-70(a), .50-81(a), (b)	G				
Tetraethylene pentamine	TTP	7	0	E	III	A	No	N/A	.55-1(c)	G				
Triethanolamine	TEA	82	0	Ε	111	Α	No	N/A	.55-1(b)	G				
Triethylenetetramine	TET	72	0	Ε	111	Α	No	N/A	.55-1(b)	G				
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	H	Α	No	N/A	.56-1(a), (b), (c)	G				
Trisodium phosphate solution	TSP	5	0	NA	111	Α	No	N/A	50-73, 56-1(a), (c)	G				
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	HI	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G				
Vinyl neodecanoate	VND	13	0	E	111	A	No	N/A	.50-70(a), 50-81(a), (b)	G				



Serial #: C1-2300134

12-Jan-23

Certificate of Inspection

Cargo Authority Attachment

Shipyard: WEST GULF MAR

Hull #: 253

Official #: 1265777

Page 3 of 3

Explanation of terms & symbols used in the Table:

Cargo Identification

Chem Code

The propper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual

Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

Note 1

Note 2

Subchapter O

Note 3

Note 4

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-ENG-5), 2703 Martin Luther King Jr. Ave SE Stop 7509, Washington DC 20593-7509. Email:

hazmatstandards@uscg.mil See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Subchapter D

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2 Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "()" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

A, B, C Flammable liquid cargoes, as defined in 46 CFR 30-10.22 D.F

Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the

cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo. Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4) Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category Category 1

The specified cargo's provisional classification for vapor control systems

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.2011) and the pressure drop calculations (46 CFR 39.3001) must use appropriate friction factors, vapor densities and vapor growth rates

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.2009. This requirement is in addition to the requirements of Category 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This

Category 6 Category 7

requirement is in addition to the requirements of Category 1. (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems