Sacras and a second	CODD.			ed States o			Certification D	ate:	02 Jun 2022
			Departm	ent of Home	eland Secur	rity	Expiration Dat	te:	02 Jun 2023
	T	<i>émpor</i> a		d States Co PrtífíC		- Insp	ection		
This Terrore	For ships on inte	mational voyages this ce	rtificate fulfills the rec	quirements of SOLAS	374 as amended, re	egulation V/14, for	a SAFE MANNING DOC	UMENT.	
This Temporary	receipt on boa	on is issued under the pr ard said vessel of the orig	ovision of Title 46 Uni jinal certificate of insp	ited States Code, Se pection, this certifica	ction 399, in lieu of te in no case to be v	the regular certific valid after one year	ate of inspection, and shi r from the date of inspecti	all be in fo ion.	rce only until the
Vessel Name			ficial Number	IMO NU		Call Sign	Service		
KIRBY 287	37	1.	239860				Tank E	3arge	
Hailing Port									
GIBSON, L	A		Hull Material	Но	rsepower	Propulsion	n		
UNITED ST	TATES		Steel						
Place Built						14			
Madisonville	e, LA		Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Leng	Jth
	,		27Sep2012	20Aug2012	R-1619	R-1619		R-29)7.5
UNITED ST	ATES				l-	l-		1-0	
				183 CH/	^{tor} y Inland Mar 50 MARKET ANNELVIEW TED STATE	' ST /, TX 77530			
This vessel n 0 Certified Li	nust be manne ifeboatmen, 0	ed with the follow Certified Tanke	ving licensed rmen, 0 HSC	and unlicense Type Rating,	ed Personnel and 0 GMDS	. Included i SS Operato	n which there mi	ust be	
0 Masters		0 Licensed Mates		Engineers		ilers			
0 Chief Mate	es	0 First Class Pilot		ssistant Engine					
0 Second Ma	ates	0 Radio Officers		d Assistant Eng					
0 Third Mate	es	0 Able Seamen		Assistant Engine					
0 Master First	st Class Pilot	0 Ordinary Seame		ed Engineers					
0 Mate First	Class Pilots	0 Deckhands	0 Qualifi	ed Member Eng	ineer				
In addition, the Persons allow	nis vessel may wed: 0	carry 0 Passen	gers, 0 Other	Persons in cr	ew, 0 Persor	ns in additio	n to crew, and n	o Othe	ers. Total
Route Perm	nitted And Co	nditions Of Op	eration:						
Lakes,	Bays, and	Sounds plu	s Limited	Coastwis	e				
Also, in fai Florida.	ir weather or	nly, not more	than twelve	(12) miles	from shore 3	between St	. Marks and Ca	rrabel	.le,
salt water i	perated in sa	alt water more : 46 CFR 31.10-	than 6 mont	hs in anv 13	2 month per	iod. the v	R 31.10-21(a)(essel must be writing as so	inspec	rtad using
This tank ba	arge is parti	cipating in th	ne Eighth Co	ast Guard D:	istrict's Ta	ank Barge :	Streamlined In	specti	on Program
		R ADDITIONAL							-
Inspection, Ma	arine Safety U	ification having nit Port Arthur c lations prescribe	ertified the ve	ssel, in all res	thur, TX, UN spects, is in c	ITED STAT	ES, the Officer i	in Char le vess	ge, Marine el inspection
		riodic/Re-Inspec	and the second		his certificate	issued by:	RATI	(-).	
Date	Zone	A/P/R	Signature				5-13, USCG, B	y direc	USCC5
				Of	ficer in Charge, Mar	27	ety Unit Port Art	thur	
				Ins	pection Zone	Manne Oa	cty offict of All	nui	

ſ



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 02 Jun 2022 Expiration Date: 02 Jun 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 28737

(TBSIP). Inspe Inspection iss	ction activities al ues concerning this	poard this barge sh s barge should be d	all be conducted print irected to OCMI Ho	per its buston-	Tank Barge Acti Galveston.	on Plan (TAP).
Hull Exam	50					
Exam Type	Next	Exam	Last Exam		Prior Exa	ım
DryDock	30Jur	12032	02Jun2022		27Sep20	12
Internal Structur	e 31Ma	r2027	02Jun2022		31Mar20	17
Liquid/Ga	as/Solid Cargo /	Authority/Condit	tions			
Authorization:	FLAMMABLE/COM	BUSTIBLE LIQUIDS	AND SPECIFIED H	IAZARD	OUS CARGOES	
Total Capacity	Units	Highest Grade Type	e Part151 Regulate	ed Pa	rt153 Regulated	Part154 Regulated
28400	Barrels	А	Yes	No		No
Hazardous Bu	lk Solids Authority					
Loading Const	traints - Structural	2				
Tank Number		Max Cargo Weight	per Tank (short tons)	Maximum Densit	y (lbs/gal)
1 P/S		863			13.6	
2 P/S		876			13.6	
3 P/S		702			13.6	
Loading Const	raints - Stability					
Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route	Description	
II	3776	10ft 0in	13.6	R, LBS	3	
111	4648	11ft 9in	13.6	R, LBS	3	

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial # C1-1202856, dates 05 Jun 2012, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Vapor Control Authorization

Per 46 CFR 39, excluding Part 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter serial # C1-1202856, dated 05 Jun 2012, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Per 46 CFR 39.1017 and 39.5000(e), this vessel's VCS has been evaluated and approved for multi-breasted tandem loading with other vessels specifically approved to tandem load with this vessel.

Stability and Trim

Per 46 CFR 151.10(c) (2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 10.00 lbs/gal. Cargoes with higher densities, up to 13.57 lbs/gal. may be carried as slack loads, but shall not exceed the tank weight limits as listed above.



United States of America Department of Homeland Security United States Coast Guard

Certification Date:	02 Jun 2022
Expiration Date:	02 Jun 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 28737

Thermal Fluid Heater Restriction Thermal fluid heater may only be operated when carrying Grade "E" cargoes.

--- Inspection Status ---

Cargo Tanks

	Internal Exam	1		External Exar	n	
Tank Id	Previous	Last	Next	Previous	Last	Next
1 P/S	27Sep2012	02Jun2022	30Jun2032	Ξ.	-	-
2 P/S	27Sep2012	02Jun2022	30Jun2032	-	-	-
3 P/S	27Sep2012	02Jun2022	30Jun2032	-	-	-
			Hydro Test			
Tank Id	Safety Valves	1	Previous	Last	Next	
1 P/S	-	4	-	-	-	
2 P/S	-		-	-	-	
3 P/S	x=		-	-	-	

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity	Class Typ	e
2	40-B	

END



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: SMI 30038

Shipyard: Trinity Marine Madisonville Hull #: 2203-5

Official #: 1239860

Tank Group Information		Cargo Identification			Cover	Tanks			Cargo Transfer		Environmental Control		Fire	Special Requirements				
Tnk Grg		Density	Press.	Temp.	Hull Typ			Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec	Temp Cont
A	#1P/S, #2P/S, #3P/S	13.6	Atmos.	Amb.	11	111 211	Integral Gravity	PV	Closed	1	G-1	NR	NA	Portabie	,50-60, .50-70(a), ,50-70(b), .50-73, ,50-81(a), .50- 81(b),	55-1(h), (j), 56-1(a), (c), (d), (e), (f), (g),	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identificatio	n					Conditions of Carriage					
							Vapor R				
Name	Chem Code	Compat Group No	Sub Chapter	Gradə	Hull Type	Tank Group	App'd (Y or N)	VCS Calegory	Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period	
Authorized Subchapter O Cargoes											
Acetonitrite	ATN	37	0	С	111	А	Yes	3	Νο	G	
Adiponitrile	ADN	37	0	E	11	A	Yes	1	No	G	
Alkyl(C7-C9) nitrates	AKN	34 ²	0	NA	111	Α	No	N/A		G	
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	11	A	No	N/A		G	
Benzene	BNZ	32	0	С	Ift	Α	Yes	1	.50-60	G	
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 ²	0	С	IH	Α	Yes	1	.50-60	G	
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	lti	Α	Yes	1	,50-60	G	
Butyl acrylate (all isomers)	BAR	14	0	D	111	А	Yes	2	.50-70(a), .50-81(a), (b)	G	
Butyl methacrylate	BMH	14	0	D	111	А	Yes	2	.50-70(a), .50-81(a), (b)	G	
Butyraldehyde (all isomers)	BAE	19	0	С	[[]	A	Yes	1	.55-1(h)	G	
Camphor oil (light)	CPO	18	0	D	ll	Α	No	N/A	No	G	
Carbon tetrachloride	CBT	36	0	NA	11	А	No	N/A	No	G	
Caustic potash solution	CPS	5 ²	0	NA	111	А	No	N/A	.50-73, .55-1(j)	G	
Caustic soda solution	CSS	52	0	NA	111	А	No	N/A	.50-73, .55-1(j)	G	
Chemical Oil (refined, containing phenolics)	COD	21	0	E	II	А	No	N/A	.50-73	G	
Chlorobenzene	CRB	36	0	D	111	А	Yes	1	No	G	
Chloroform	CRF	36	0	NA	111	A	Yes	3	No	G	
Coal tar naphtha solvent	NCT	33	0	D	111	Α	Yes	1	.50-73	G	
Creosote	CCV	/ 21 2	0	ε	111	A	Yes	1	No	G	
Cresols (all isomers)	CRS	21	0	Е	Ш	А	Yes	1	No	G	
Crotonaldehyde	СТА	19 ²	0	С	11	A	Yes	4	.55-1(h)	G	
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	с	111	A	No	N/A	No	G	
1,1-Dichloroethane	DCH	36	0	С	11	A	Yes	1	No	G	
Dichloromethane	DCN	36	0	NA	111	Α	Yes	5	No	G	
1,1-Dichloropropane	DPB	36	0	С	111	A	Yes	3	No	G	
1,2-Dichloropropane	DPP	36	0	С	11	А	Yes	3	No	G	
1,3-Dichloropropane	DPC	36	0	С	111	А	Yes	3	No	G	
1,3-Dichloropropene	DPU	15	0	D	П	Α	Yes	4	No	G	
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С		Α	Yes	1	No	G	
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	lł	Α	No	N/A	No	G	
EE Glycol Ether Mixture	EEG	40	о	D	111	А	No	N/A	No	G	
Ethyl acrylate	EAC		0	C	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G	



C1-1202856 Serial #: Dated: 05-Jun-12

Madisonville

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038

Shipyard: Trinity Marine Hull #: 2203-5

Official #: 1239860		F	Page 2	of 7					Hull #: 2203-5	
Cargo Identification	 1						(Condi	tions of Carriage	
Name Ethylene cyanohydrin	Chem Code ETC	Compat Group No 20	Sub Chapter O	Grade	Hull Type III	Tank Group A	Vapor R App'd (Y or N) Yes	ecovery VCS	Special Requirements in 46 CFR 151 General and Mat'ls of No	Insp. Period G
Ethylene dichloride	EDC	36 ²	0	С	11	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	0	E	111	A	No	N/A	No	G
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E		A	Yes	1	No	G
Ethylene glycol propyl ether	EGP	40	0	ε	111	A	Yes	1	No	G
2-Ethylhexyl acrylate	EAI	14	0	ε	111	А	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethyl methacrylate	ETM	14	0	D/E	111	А	Yes	2	.50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 ²	0	E	111	A	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 ²	о	D/E	111	А	Yes	1	.55-1(h)	G
Furfural	FFA	19	0	D	111	A	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	111	A	No	N/A	No	G
Hydrocarbon 5-9	HFN		0	С	111	Α	Yes	1	.50-70(a), .50-81(a), (b)	G
Isoprene	IPR	30	0	А	111	А	Yes	7	.50-70(a), .50-81(a), (b)	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	, KPL	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 ²	0	D	11	А	Yes	1	No	G
Methyl acrylate	MAM	14	0	С	H	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Methylcyclopentadiene dimer	MCK	30	0	С	111	Α	Yes	1	No	G
Methyl methacrylate	MMN	1 14	0	С	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
alpha-Methylstyrene	MSR	30	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
1- or 2-Nitropropane	NPM	42	0	D	111	A	Yes	1	,50-81	G
1,3-Pentadiene	PDE	30	0	Α	111	Α	Yes	7	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	111	А	No	N/A	No	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxic	le) SAP		0		111	А	No	N/A	,50-73, .55-1(j)	G
Sodium chlorate solution (50% or less)	SDD	0 1,	2 O	NA		Α	No	N/A	.50-73	G
Styrene (crude)	STX		0	D		Α	Yes	2	No	G
Styrene monomer	STY	30	0	D	111	A	Yes	2	.50-70(a), .50-81(a), (b)	G
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	111	Α	No	N/A	No	G
Tetrahydrofuran	THF	41	0	С	Ш	А	Yes	1	.50-70(b)	G
1,2,4-Trichlorobenzene	TCB	36	0	E	111	Α	Yes	1	No	G
1,1,2-Trichloroethane	тсм	36	0	NA	11	Α	Yes	1	.50-73, .56-1(a)	G
Trichloroethylene	TCL	36 ²	0	NA	111	Α	Yes	1	No	G
1,2,3-Trichloropropane	TCN	36	0	E	1	Α	Yes	3	.50-73, .56-1(a)	G
Trisodium phosphate solution	TSP	5	0	NA	111	А	No	N/A	.50-73, .56-1(a), (c).	G
Vanillin black liquor (free alkali content, 3% or more).	V8L	5	0	NA	111	А	No	N/A	.50-73, .56-1(a), (c), (g)	G
Vinyl acetate	VAM	13	0	С	[[]	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	0	E	111	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Subchapter D Cargoes Authorized for Vapor Contro	ol									
Acetone	ACT	18 ²	D	С		А	Yes	1		
Acetophenone	ACP	18	D	E		А	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		А	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1		
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		А	Yes	1		
Benzyl alcohol	BAL	21	D	Ε		А	Yes	1		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		А	Yes	1		

their borate esters)



Serial #: C1-1202856 Dated: 05-Jun-12

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038 Official #: 1239860

Page 3 of 7

Shipyard: Trinity Marine Madisonville Hull #: 2203-5

Cargo Identificatio	n							Condi	tions of Carriage	
							Vapor I	Recovery		
	Chem	Compat	Sub Chapter	Grade	Huli Type	Tank Group	App'd (Y or N)	VCS	Special Requirements in 46 CFR 151 General and Mat'is of	Insp. Period
Name Butyl acetate (all isomers)	I Code BAX	Group No 34	D	D	I VDe I	A	Yes	1	101 General and Mads of) Penon (
Butyl alcohol (iso-)	IAL	20 ²	D	D		А	Yes	1		
Butyl alcohol (n-)	BAN	20 ²	D	Ð		A	Yes	1		
Butyl alcohol (sec-)	BAS	20 ²	D	С		Α	Yes	1		
Butyl alcohoi (tert-)	BAT		D	С		A	Yes	1		
Butyl benzyl phthalate	BPH	34	D	Е		A	Yes	1		
Butyl toluene	BUE	32	D	D		А	Yes	1		
Caprolactam solutions	CLS	22	D	Ε		A	Yes	1		
Cyclohexane	СНХ	31	D	с		А	Yes	1		
Cyclohexanol	CHN	20	D	E		A	Yes	1		
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2		
p-Cymene	CMP	32	D	D		A	Yes	1		
iso-Decaldehyde	IDA	19	D	E		A	Yes	1		
n-Decaldehyde	DAL	19	D	E		A	Yes	1		
Decene	DCE	30		D		A	Yes	1	Anarr	
Decene Decyl alcohol (all isomers)	DAX	20 2		<u>Е</u>		A	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		A	Yes	1		
Diacetone alcohol	DAA	20 2	 D	D		A	Yes	1		
AMANYANINI	DPA	34	 D	E		A	Yes	1		
ortho-Dibutyl phthalate	DEB	32	D	D		A	Yes	1		
Diethylbenzene	DEG	40 2	D	E		A	Yes	1		
Diethylene glycol	DBL	30	D	C		A	Yes	, 1		
Diisobutylene	DIK	18		 D		A	Yes	1		
Diisobutyl ketone	DIX	32	D	E		 A	Yes	1		
Diisopropylbenzene (all isomers)	DIA	34				 A	Yes	1		
Dimethyl phthalate	DOP	34		<u>е</u> Е		 A	Yes	1		
Dioctyl phthalate		34	D	<u>е</u> D		A	Yes	1		
Dipentene	DPN			D/E	•	A	Yes	1		
Diphenyl		32		E						
Diphenyl, Diphenyl ether mixtures	DDO	33	D			A	Yes	1		
Diphenyl ether	DPE	41	D	(E)		A	Yes	1		
Dipropylene glycol	DPG	40	D	E		A	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		<u>A</u>	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Distillates: Straight run	DSR	33		<u>Е</u>		<u>A</u>	Yes	1		
Dodecene (all isomers)	DOZ	30	D	0		<u>A</u>	Yes	1		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		<u>A</u>	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		<u>A</u>	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	E		<u>A</u>	Yes	1		
Ethyl acetate	ETA	34		<u>c</u>		A	Yes	1		
Ethyl acetoacetate	EAA	34	D	E		<u>A</u>	Yes	1		
Ethyl alcohol	EAL	20 ²	D	C		A	Yes	1		
Ethylbenzene	ETB	32	D	c		<u>A</u>	Yes	1		
Ethyl butanol	EBT	20	D	D		A	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	C		A	Yes			
Ethyl butyrate	EBR	34	D	D		<u>A</u>	Yes	· · ·		
Ethyi cyclohexane	ECY	31	D	D		A	Yes			
Ethylene glycol	EGL	20 2	D	E		A	Yes			
Ethylene glycol butyl ether acetate	EMA	34	D	E		A	Yes			
Ethylene glycol diacetate	EGY	34	D	E		A	Yes	1		



Serial #: C1-1202856 Dated: 05-Jun-12

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038 Official #: 1239860

Page 4 of 7

Shipyard: Trinity Marine Madisonville Hull #: 2203-5

Cargo Identificatio	n					Conditions of Carriage						
		Τ	I				Vapor I	Recovery	1			
	Chem	Compat	Sub	Quede	Hull	Tank	App'd	VCS	Special Requirements in 46 CFR	insp.		
l Name Ethylene glycol phenyl ether	l Code EPE	Group No 40	Chapter D	E	Type	Group A	(Y or N) Yes	Catedory 1	151 General and Mat'ls of	I Period I		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1				
	EHX	20	D	<u>Е</u>		A	Yes	1				
2-Ethylhexanol	EPR	34	D	C		A	Yes	1		· · ·		
Ethyl propionate	ETE	32	D			A	Yes	1				
Ethyl toluene	FAM	10	D	E		A	Yes	1				
Formamide		20 2		E		A	Yes	1	· · · · · · · · · · · · · · · · · · ·			
Furfuryl alcohol	FAL		D		÷			1				
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		A	Yes					
Gasoline blending stocks: Reformates	GRF	33	D	A/C		A	Yes	1				
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	с		A	Yes	1				
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	с		A	Yes	1				
Gasolines: Casinghead (natural)	GCS	33	D	A/C		A	Yes	1	·····			
Gasolines: Polymer	GPL	33	D	A/C		Α	Yes	1				
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1				
Glycerine	GCR	20 ²	D	E		Α	Yes	1				
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	нмх	31	D	С		Α	Yes	1				
Heptanoic acid	HEP	4	D	Е		А	Yes	1				
Heptanol (all isomers)	HTX	20	D	D/E	•••	А	Yes	1				
Heptene (all isomers)	HPX	30	D	С		А	Yes	2				
Heptyl acetate	HPE	34	D	Е		Α	Yes	1				
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 2	D	B/C		Α	Yes	1				
Hexanoic acid	нхо	4	D	Е		A	Yes	1				
Hexanol	HXN	20	D	D		A	Yes	1				
Hexene (all isomers)	HEX	30	D	С		A	Yes	2		•		
• • • • • • • • • • • • • • • • •	HXG	20	 D	E		A	Yes	1				
Hexylene glycol Isophorone	IPH	18 2	 D	<u>–</u> Е		A	Yes	1				
	JPF	33	D	E		A	Yes	1				
Jet fuel: JP-4	JPV	33		D		A	Yes	1				
Jet fuei: JP-5 (kerosene, heavy)	KRS	33	<u> </u>	D		A	Yes	1				
Kerosene		34	 D	D		A	Yes	1				
Methyl acetate	MTT	20 2	 D	c		A	Yes	1				
Methyl alcohol	MAL			D			Yes	1				
Methylamyl acetate	MAC	34	0									
Methylamyi alcohol	MAA	20	D	D		A	Yes	1				
Methyl amyl ketone	MAK	18		D		<u> </u>	Yes	1				
Methyl tert-butyl ether	MBE	41 2	D	C		A	Yes	1				
Methyl butyl ketone	MBK	18	D	C		A	Yes	1				
Methyl butyrate	MBU	34	D	С		A	Yes	1				
Methyl ethyl ketone	MEK		D	С		A	Yes	1		-		
Methyl heptyl ketone	мнк		D	D		A	Yes	1				
Methyl isobutyl ketone	MIK	18 ²	D	С		A	Yes	1				
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1	Lanut Lanut Lanut			
Mineral spirits	MNS	33	D	D		Α	Yes	1				
Myrcene	MRE	30	D	D		А	Yes	1				
Naphtha: Heavy	NAG	33	D	#		Α	Yes	1				
Naphtha: Petroleum	PTN	33	D	#		А	Yes	1				
Naphtha: Solvent	NSV	33	D	D		А	Yes	1				
Naphtha: Stoddard solvent	NSS	33	D	D		A	Yes	1				



Serial #: C1-1202856 Dated: 05-Jun-12

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038

Official #: 1239860

Page 5 of 7

Shipyard: Trinity Marine Madisonville Hull #: 2203-5

Cargo Identificatio								Condi	tions of Carriage	
				1				Recovery	aons of Carnage	
Name Naphtha: Varnish makers and painters (75%)	Chem Code NVM	Compat Group No 33	Sub Chaoter D	Grade	Hull Type	Tank Grouo A	App'd	VCS	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Periori
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A	Yes	1		
Nonene (all isomers)	NON	30	D	D		A	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 2	 D	<u>Е</u>		A	Yes	1		
Nonyl phenol	NNP	21	 D	E		A	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D D	E		A	Yes	1	1. <u>1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1</u>	
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	 D	c		A	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Octanoic acid (all isomers)	OAY	4	D	Ē		A	Yes	1		
Octanol (all isomers)	ocx	20 ²	D	E		А	Yes	1		
Octene (all isomers)	OTX	30	D	c		A	Yes	2	min	
Oil, fuel: No. 2	OTW	33	 D	D/E		A	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		A	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		A	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		A	Yes	1		
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1	AAAAAAAA	
Oil, misc: Crude	OIL	33	D	C/D		A	Yes	1		
Oil, misc. Olde	ODS	33	D	D/E		A	Yes	1		
Oil, misc. Gas, high pour	OGP	33	 D	E		A	Yes	1		
Oil, misc: Lubricating	OL8	33	 D	 Е		A	Yes	1		
Oil, misc. Residual	ORL	33	 D	 E		A	Yes	1		
Oil, misc. Turbine	OTB	33	 D	 Е		A	Yes	1		
	PTY	31	 D	A		A	Yes	5		
Pentane (all isomers) Pentene (all isomers)	PTX	30	D	A		A	Yes	5		
	PPE	34	 D	D		A	Yes	1		
n-Pentyl propionate alpha-Pinene	PIO	30	D	D		A	Yes	1		
beta-Pinene	PIP	30	 D	D		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	- D	E		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34		 E		A	Yes	1		
	PLB	30		 E		A	Yes	1		
Polybutene Polypropylene glycol	PGC	40	 D	<u>—</u> Е		A	Yes	1		
iso-Propyl acetate	IAC	34		c		A	Yes	1		
n-Propyl acetate	PAT	34	D	c		A	Yes	1		
iso-Propyl alcohol	IPA	20 2	 D	c		A	Yes	1		
n-Propyl alcohol	PAL	20 2		c		A	Yes	1		
Propylenzene (all isomers)	PBY	32	 D	D		A	Yes	1		
iso-Propylcyclohexane	IPX	31	 D	D		A	Yes	1		
Propylene glycol	PPG	20 ²		Ē		A	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Propylene glycol methyl ether acetate	PGN	34	D	D		A	Yes	1		
Propylene tetramer	PTT	30	 D			A	Yes	1		
Sulfolane	SFL	39		<u>Е</u>		A	Yes	1	· · · · · · · · · · · · · · · · · · ·	
Tetraethylene glycol	TTG	40	 D	E		A	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1		
Toluene	TOL	32	 D			A	Yes			
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	<u>Е</u>		A	Yes		· · · · ·	
Triethylbenzene	TEB	32	D	E		A	Yes			
Triethylene glycol	TEG	40	D	E		A	Yes			
Triethyl phosphate	TPS	34	D	E	•	A	Yes			
	TRE	32	D	{D}		A	Yes		·····	
Trimethylbenzene (all isomers)	1110	~~~	<u> </u>	(0)						



Serial #: C1-1202856 Dated: 05-Jun-12

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038

Page 6 of 7

Shipyard: Trinity Marine Madisonville Hull #: 2203-5

Official #: 1239860		Page 6 of 7							Hull #: 2203-5						
Cargo	dentification							Condi	tions of Carriage						
Name Trixylenyl phosphate Undecene	Chem Cade TRP UDC	Compat Group No 34 30		Grade E D/E	Huli Tvoe	Tank Group A A	App'd	Recovery VCS Category 1 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period					
1-Undecyl alcohol Xylenes (ortho-, meta-, para-)	UND XLX	20 32	D D	E D		A A	Yes Yes	1							



Serial #: C1-1202856 Dated: 05-Jun-12

Certificate of Inspection Cargo Authority Attachment

Vessel Name: SMI 30038 Official #: 1239860

Page 7 of 7

Shipyard: Trinity Marine Hull #: 2203-5

Explanation of terms & symbols used in the Table:

Cargo Identification	
Name	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.
Chem Code none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatability Group No.	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and according so of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-
Note 2	0001. Telephone (202) 372-1425. See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.
Subchapter	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Subchapter D Subchapter O Note 3	Those harmmable and combustide in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2. Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for
	carriage of that grade of cargo.
A, B, C D, E	Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.
Note 4	The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
NA #	Those subchapter O cargoes which are not classified as a flammable or combustible liquid. No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.
1	Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).
	Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).
NA	Not applicable to barges certificated under Subchapter D.
Conditions of Carriage	
Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes; The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Conditions of Carriage	
Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Tank Group Vapor Recovery Approved (Y or N)	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo. Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Vapor Recovery	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
Vapor Recovery Approved (Y or N) VCS Category:	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 158.120, 33 CFR 155.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-
Vapor Recovery Approved (Y or N) VCS Category: Category 1	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could tead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge,
Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 158.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuing all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9.
Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156,170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. 2 and 3. (Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3. (High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased
Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4 Category 5	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. (Polymerizes and highly toxic) Must comply with requirements of Category 1. (High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densilies and vapor growth rates as compared to
Vapor Recovery Approved (Y or N) VCS Category: Category 1 Category 2 Category 3 Category 4 Category 5 Category 6	 Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo. The specified cargo's provisional classification for vapor control systems. (No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30- 1(b)) must use appropriate friction factors, vapor densities and vapor growth rates. (Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation (Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 48 CFR 39.20-9. This requirement is in addition to the requirements of Category 1. (Polymerizes and highly toxic) Must comply with requirements of Category 1. 2000 (High vapor pressure) VCS pressure drop calculations for cargoes consuit the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1. (High vapor pressure) VCS pressure drop calculations for cargoes. Consuit the Marine Safety Center's VCS Guidelines f