

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 10 Apr 2024 Expiration Date: 10 Apr 2029

Certificate of Inspection

For ships on International voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT

Vessel Name		- 100 A TO	Official Number	IMO	Number	Call Sign	Service	
KIRBY 30006	5		1109337				Tank B	arge
Hailing Port			Hull Material	****	Horsepower	Propulsion		
HOUSTON, TX			Steel			None		
UNITED STA	ATES							
Place Built	N. W. I. S. IN. I.		Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
JEFFERSON	IVILLE, IN		07Jun2001	11Feb20	01 R-1754	R-1754		R-297.5
UNITED STA	ATES							
				1 1	Persion KIRBY INLAND 8350 MARKET CHANNELVIEW JNITED STATE	ST. /, TX 77530		
					nsed Personne	I. Included in wh SS Operators.	hich there m	ust be
0 Masters		0 Licensed Ma	ates 0 Chie	f Engineers	0.0	ilers		
0 Chief Mates	s	0 First Class Pilots 0 First Assistant Engineers						
0 Second Ma	ites	0 Radio Officers 0 Second Assistant Engineers						
0 Third Mates	s	0 Able Seame	en O Thire	d Assistant En	gineers			
0 Master Firs	t Class Pilot	0 Ordinary Se	amen 0 Lice	nsed Engineer	S			
0 Mate First (Class Pilots	0 Deckhands	0 Qua	lified Member	Engineer			
In addition, th Persons allov		carry 0 Pass	sengers, 0 Othe	er Persons i	n crew, 0 Perso	ons in addition to	crew, and	no Others. Total
This vessel vessel is op salt water is change in st This tank ba (TBSIP). Instruction is	perated in sa- intervals per tatus occurs. arge is parti- spection acti- issues concer	Sounds- nted a fre lt water m 46 CFR 31 cipating i vities abo ning this	sh water servore than 6 mo .10-21(a)(1) n the Eighth ard this barg barge should	nths in an and the co Coast Guar e shall be be directe	y 12 month pe gnizant OCMI: d District's conducted pe	notified in wr Tank Barge Str r its Tank Bar ston-Galveston	el must be iting as s eamlined I ge Action	inspected using oon as this named in the section Programme of the secti
With this Insp	ection for Cert	ification hav	ring been comp	leted at Por	t Arthur, TX, U	NITED STATES	, the Office	in Charge, Mari
Inspection, M laws and the	arine Safety Urules and requi	nit Port Arth	our certified the cribed thereund	vessel, in a ler.	II respects, is in	conformity with	the applica	ble vessel inspec
		riodic/Re-In:			This certifica	te issued by:	tad	Woodma
Date	Zone	A/P/R	Signat	ure		WOODMAN, CI	DR, USCG,	By direction
		100	Principal Transport		Officer in Charge, M	larine inspection	(7)	11000
			100			Marine Safety	/ Unit Port A	rthur

Inspection Zone



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 10 Apr 2024 Expiration Date: 10 Apr 2029

Certificate of Inspection

Vessel Name: KIRBY 30006

---Hull Exams---

Exam Type Next Exam

Last Exam

Prior Exam

DryDock

30Sep2028

17Sep2018

17Aug2006

Internal Structure

30Apr2029

10Apr2024

17Sep2018

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units High

Highest Grade Type Part151 Regulated

Part153 Regulated

Part154 Regulated

31120

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	884	13.60
2 P/S	835	13.60
3 P/S	771	13.60

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
III	4744	12ft 0in	13.60	RIVERS; LAKES, BAYS & SOUNDS
.11	4002	10ft 6in	13.60	RIVERS; LAKES, BAYS & SOUNDS

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #VN01003176, dated 07JUN01, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

Vapor Control Authorization

Per 46 CFR 39, excluding Part 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter serial #T2-0003386 dated 30NOV00, and found acceptable for collection of bulk liquid cargo vapors from those specific Subchapter "D" cargoes contained in the that letter, and those specified hazardous cargoes annotated a "V" or "T" in the CAA.

The letter "V" in the note column of the CAA signifies approval for vapor control without any additional requirements.

The letter "T" in the note column of the CAA signifies that the cargo is highly toxic and that spill valves or rupture disks are not authorized as the primary means of overfill protection required by 46 CFR 39.20-9. A high level and overfill alarm is required by 46 CFR 39.20-7.

Stability and Trim



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 10 Apr 2024 Expiration Date: 10 Apr 2029

Certificate of Inspection

Vessel Name: KIRBY 30006

Per 46 CFR 151.10(c)(2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.7 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

33.	Internal Exam			External Exam						
Tank Id	Previous	Last	Next	Previous	Last	Next				
1 P/S	17Aug2006	17Sep2018	30Sep2028	-	-					
2 P/S	17Aug2006	17Sep2018	30Sep2028	-		-				
3 P/S	17Aug2006	17Sep2018	30Sep2028		-	-				
			Hydro Test							
Tank ld	Safety Valves		Previous	Last	Next					
1 P/S	-		-	-	-					
2 P/S										
3 P/S				120	12					

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity Class Type

40-B

END

Dept. of Home Sec., USCG, CG-841 (Rev 4-2000)(v2)

07-Jun-01



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 30006

Dichloropropene, Dichloropropane mixtures

Shipyard: JEFFBOAT LLC

Official #: D1109337 Pa	ge 1 of 3						Hull #: 002158
ist of Authorized Cargoes							
Cargo Identification	A. 9	93			3524	С	onditions of Carriage
	1	Comp	at				
Name	Code	Group No	Exc	Grade	Hull Type	Note	Special Requirements in 46 CFR 151 General and Mat'ts of Construction
Authorized Subchapter O Cargoes							
Ammonium bisulfite solution (70% or less)	ABX	43	Y		III		.50-73, .56-1(a), (b), (c)
Acrylonitrile	ACN	15	Y	С	11	T	.50-70(a), .55-1(a)
Adiponitrile	ADN	37	N	E	Ш	V	No
Aminoethylethanolamine	AEE	8	N	E	III	V	.55-1(b)
N-Aminoethylpiperazine	AEP	7	N	E			
Anthracene oil (Coal tar fraction)	AHO	33	N	1,5	II .		No
Alkyl(C7-C9) nitrates	AKN	34	Y	444	141		.50-81, .50-88
Ammonium hydroxide (28% or less NH3)	AMH	6	N		M		.56-1(a), (b), (c), (f), (g)
Acetonitrile	ATN	37	N	С	111	Т	No
Butyraldehyde (all isomers)	BAE	19	N	С	III	V	.55-1(h)
Butyl acrylate (all Isomers)	BAR	14	N	D	Ш	V	.50-70(a), .50-81(a), (b)
Benzene hydrocarbon mixtures (containing Acetylenes)(having 10% Benzene or more)	BHA				III	V	.50-60, .58-1(b), (d), (f), (g)
Benzene hydrocarbon mixtures (having 10% Benzene ormore)	BHB	32	N		00	V	50-60
Butyl methacrylate	BMH	14	N	D	- 80	V	.50-70(a), .50-81(a), (b)
Benzene	BNZ	32	N	С	III	V	.50-80
Benzene, Toluene, Xylene mixtures (having 10% Benzeneor more)	BTX	32	N	B/C	III	V	.50-80
Carbon tetrachloride	CBT	36	N		113		No
Cyclohexanone	CCH	18	N	D	01	V	.56-1(a), (b)
Creosote (all isomers)	CCW	21	Y	E	H H	V	No
Cyclohexylamine	CHA	7	N	D	311	V	.56-1(a), (b), (c), (g)
Crude hydrocarbon feedstock (containing Butyraldehydesand Ethylpropyl acrolein)	CHG	0	N	С	111		No
Camphor oil	CPO	18	N	Ð	<u>II</u>		No
Caustic potash solution	CPS	5	Y		111		.50-73, .55-1(j)
Chlorobenzene	CRB	36	N	D		V	No
Chloroform	CRF	36	N	E	III		No
Cresols	CRS	21	N	E	10	V	No
Cresylic acid tar	CRX	21	N		10	V	.55-1(f)
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	N	D		V	.50-60, .56-1(b)
Cresylate spent caustic	CSC	5	N		III		.50-73, .55-1(b)
Caustic soda solution	CSS	5	Y		111		.50-73, .55-1(j)
Crotonaldehyde	CTA	19	Y	С	ll_	Т	.55+1(h)
Cyclohexanone, Cyclohexanol mixture	CYX	18	Y		111	V	.56-1 (b)
N,N-Dimethylacetamide	DAC	10	N	Е	- 111	т.	.56-1(b)
2,4-Dichlorophenoxyacetic acid, dimethylamine saltsolution	DAD	0	Y		III		.56-1(a), (b), (c), (g)
Disobutylamine	DBU	7	N	D	118	T	.56-1(c)
Dichlorobenzenes (all isomers)	DBX	36	N	Ε	li)	T	.50-1(a), (b)
1,1-Dichloroethane	DCH	36	N	С	111	V	No
Dichloromethane	DCM	36	N		10		No
2,4-Dichlorophenoxyacetic acid, dimethylamine saltsolution (70% or less)	DDA	0	Y	NF	Ш		.55-1(b)
2,4-Dichlorophenoxyacetic acid, diethanolamine saltsolution	DDE	43	N			20000	.58-1(a), (b), (c), (g)
Diethanolamine	DEA	8	N	_	III	V	.55-1(c)
2,2'-Dichloroethyl ether	DEE	41	N	_		V	.55-1(f)
Diethylamine	DEN	7	N		111	Т	.55-1(c)
Diethylenetriamine	DET	7		E	III	V	.55-1(c)
Diisopropylamine	DIA	7	N		B	T	.55-1(c)
Diisopropanolamine	DIP	8	N	E	III	V	.56-1(c)
Dimethylethanolamine	DMB	8	N	D	III	V	.50-1(b), (c)
Dimethylformamide	DMF	10	N	D	111	V	.55-1(e)
DI-M	CHAN	4=			- 0	14	The state of the s

DMX

15 N

United States Coast Guard

Department of Transportation

VN01003176 07-Jun-01



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 30006 Official #: D1109337

Page 2 of 3

Shipyard: JEFFBOAT LLC

Hull #: 002158

Cargo Identification							onditions of Carriage	
		Comp	at	1 -				
Name	Chem Code	Group No	Exc	Grade	Huli Type	Note	Special Requirements in 46 CFR 151 General and Mat'ls of Construction	
Di-n-propylamine	DNA	7	N	С	11	T	.55-1(c)	
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	N	E	141		56-1(b)	
1,1-Dichioropropane	DPB	36	N	С	101	Т	No	
1,3-Dichloropropane	DPC	36	N	Ç	111	Т	No	
1,2-Dichloropropane	DPP	36	N	С	III	Т	No	
1,3-Dichloropropena	DPU	15	N	D	11	Т	No	
2,4-Dichlorophenoxyacetic acid, triisopropanolaminesatt solution	DTI	43	Y		111		.56-1(a), (b), (c), (g)	
Ethyl acrylate	EAC	14	N	С	III	٧	50-70(a), .50-61(a), (b)	
2-Ethylhexyl acrylate	EAI	14	N	E	111	٧	50-70(a), .50-81(a), (b)	
Ethylamine solution (72% or less)	EAN	7	N	Α	II	Т	.55-1(b)	
N-Ethylbutylamine	EBA	7	N	С	10	T	55-1(b)	
N-Ethylcyclohexylamine	ECC	7	N	Đ	III	V	55-1(b)	
Ethylenedlamine	EDA	7	Υ	D	(1)	٧	55-1(c)	
Ethylene dichloride	EDC	36	Y	С	(1)	V	No	
Ethylene glycol monoalkyl ethers	EGC	40	N	D/E	- (1)	٧	No	
Ethylene glycol hexyl ether	EGH	40	N	E	181		No	
Ethylene glycol propyl ether	EGP	40	N	E	10	V	No	
2-Ethyl-3-propylacrolein	EPA	19	Y	E	III	V	No	
Ethylene cyanohydrin	ETC	20	N	E	Įti –	V	No	
Ethyl methacrylate	ETM	14	N	С		V	50-70(a)	
Ethylene dichloride, 1,1,2-Trichloroethane mixture	ETX							
Furfural	FFA	19	N	E	III	V	.55-1(h)	
Formaldehyde solution (37% to 50%)	FMS	19	Y	D/E	- III	V	55-1(h)	
Glutaraldehyde solution (50% or less)	GTA	19	N	NF	III	WAS LOVE	No	
Hydrocarbon 5-9	HFN	30	N	A	10	V	.50-70(a), 50-81(a), (b)	
Hexamethylenediamine solution	HMC	7	N	E	III	V	55-1(c)	
Hexamethyleneimine	НМІ	7	N	С	11	٧	56-1(b). (c)	
Isodecyl acrylate	tAI	14	N	E	101		.50-70(a), 50-81(a), (b), 55-1(c)	
Isoprene, Pentadiene mixture	IPN	30	N	Α	101		50-70(a), 55-1(c)	
iso-Propylamine *	IPP	7	N	Α	H		55-1(c)	
Isoprene	IPR	30	N	Α	111		.50-70(a), 50-61(a), (b)	
Kraft pulping liquors (free alkali content 3% or more)	KPL	5	N		110		.50-73, 56-1(a), (c), (g)	
Methyl acrylate	MAM	14	N	C	111	V	.50-70(a), 50-81(a), (b)	
Methylcyclopentadiene dimer	MCK	30	N	С	01	V	Na	
Methyl diethanolamine	MDE	8	N	E	01	V	.56-1(b), (c)	
Ethanolamine	MEA	8	N	E	111	V	.55-1(c)	
2-Methyl-5-ethylpyridine	MEP	9	N	Е	181	V	55-1(e)	
Methyl methacrylate	MMM	14	N	С	111	V	.50-70(a), 50-81(a), (b)	
Iso-Propanolamine	MPA	8	N	E	111	٧	55-1(c)	
Morpholine Morpholine	MPL	7	Υ	D	141	V	.55-1(c)	
2-Methylpyridine	MPR	9	N	D	181	T	.55-1(c)	
Mesityl oxide	MSO	18	Υ	D	III	V	No	
alpha-Methylstyrene	MSR	30	N	D	141	V	50-70(a), 50-81(a), (b)	
Coal tar naphtha solvent	NCT	33	N	D	101	V	50-73	
1- or 2-Nitropropane	NPM	42	N	D	10	V	50-81	
Propanolamine (iso-, n-)	PAX	8	N	E	10	V	56-1(b), (c)	
1,3-Pentadiene	PDE	30	N	Α	S III	V	50-70(a), :50-81	
Polyuthylene polyamines	PEB	7	Υ	E	ill	V	.55-1(e)	
Perchloroethylene	PER	36	N	NF	- UI		No	
Polyglycerine, Sodium salts solution (containing 3% ormore Sodium hydroxide)	PGS			11/1/2	2 6			
Pyridine	PRD	9		С	HI	V	55-1(e)	



Serial #: VN01003176 COI Ref. 07-Jun-01



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 30006

Official #: D1109337

Page 3 of 3

Shipyard: JEFFBOAT LLC

Hull #: 002158

Cargo Identification	Conditions of Carriage						
Name	Chem Code	Group No		Grade	Hull Type	Note	Special Requirements in 46 CFR 151 General and Mat's of Construction
Sodium acetate, Glycol, Water mixture (3% or moreSodium hydroxide)	SAP	5	N		01		
Sodium aluminate solution (45% or less)	SAU	5	N		101		.50-73, .58-1(a), (b), (c)
Sodium chlorate solution (50% or less)	SDD	0	Y	NF	00		.50-73
Sodium sulfide	SDS					- 82	
Sodium hypochlorite solution (15% or less)	SHP	5	N		10		
Sodium sulfide, hydrosulfide solution (H2S 15 ppm orless)	SSH	0	Y		UI	V	.50-7355-1(b)
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0	Y		00	200 200	.50-73, .55-1(b)
Sodium sulfide, hydrosulfide solution (H2S greater than200 ppm)	SSJ	0	Y		0		.50-73, .55-1(b)
Styrene tar	STT	33	N	Е			
Styrene (crude)	STX	30	N	С	- 01	V	No
Styrene	STY	30	N	Ð	- 01	V	.50-70(a), .50-81(a), (b)
Sewage, raw	SWR						
1,2,4-Trichlorobenzene	TCB	36	N	E	III	V	No
richloroethylene	TCL	36	Υ	_	111	V	No
1,1,2-Trichloroethane	TCM	36	N		111	٧	.50-73, .56-1(a)
1,2,3-Trichloropropane	TCN	36	N	E	0	T	.50-73, .56-1(a)
riethanolamine	TEA	8	Y	E	III	V	.55-1(b)
1,1,2,2-Tetrachloroethane	TEC	36	N	NF	111		No
Friethylamine	TEN	7	N	С	- 11	T	.55-1(e)
Friethylenetetramine	TET	7	Y	Ε	III	V	.55-1(b)
Tetrahydrofuran etrahydrofuran	THE	41	N	С		V	.50-70(b)
Friphenylborane (10% or less), caustic soda solution	TPB	5	N		III		.56-1(a), (b), (c)
risodium phosphate solution	TSP	5	N	NF	H		.50-73, .56-1(a), (c).
etraethylenepentamine	TTP	7	N	E	111	V	.55-1(c)
Irea, Ammonium nitrate solution (containing more than2% Ammonia)	UAS	6	N		III		.56-1(b)
/inyl acetate	VAM	13	N	С	OH .	V	.50-70(a), .50-61(a), (b)
/anillin black liquor (free alkali content 3% or more)	VBL	5	N		III		.50-73, .56-1(a), (c), (g)
/inyttoluene	VNT	13	N	D	101	V	.50-70(a), .50-81, .56-1(a), (b), (c), (g)

Explanation of terms & symbols used in the Table:

Cargo identification

The proper shipping name as listed in 46 CFR Table 151.05.

Chem Code The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number. Compatability Group No.

Exceptions (Exc) Indication of whether or not there are exceptions to the compatibility chart for the given cargo. See Appendix I to 46 CFR Part 150.

Grade The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for

carriage of that grade of cargo. A, B, C Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

NA, NF

Those subchapter O cargoes which are not classified as a flammable or combustible tiquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Conditions of Carriage

Hull Type

See Certificate of Inspection for explaination of symbols used in this column