

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 31 May 2022 Expiration Date: 31 May 2023

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name Official Number **IMO Number** Call Sign **KIRBY 30040B** 1194273 Tank Barge Hailing Port Hull Material Horsepower Propulsion WILMINGTON, DE Steel UNITED STATES Place Built Delivery Date Keel Laid Date Gross Tons Net Tons DWT Length ASHLAND CITY, TN R-1632 R-1632 R-300.0 13Apr2007 01Mar2007 **UNITED STATES**

KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 HOUSTON, TX 77007 UNITED STATES Operator

KIRBY INLAND MARINE, LP 18350 MARKET ST CHANNELVIEW, TX 77530 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters 0 Licensed Mates 0 Chief Engineers 0 Chief Mates 0 First Class Pilots 0 First Assistant Engineers 0 Second Mates 0 Radio Officers 0 Second Assistant Engineers 0 Third Mates 0 Able Seamen 0 Third Assistant Engineers 0 Master First Class Pilot 0 Ordinary Seamen 0 Licensed Engineers 0 Mate First Class Pilots 0 Deckhands 0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth and Ninth Coast Guard District's Tank Barge Streamlined Inspection Program (TBSIP). Inspection activities aboard this barge shall be conducted in accordance with its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

Annual/Periodic/Po Inspecti

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	, tillidai/i Cil	odic/ite-iiispet	Suori	This certificate issued by
Date	Zone	A/P/R	Signature	K. A. Hantal, CDR, USCG, By direction
				Officer in Charge, Marine Inspection
		+		Marine Safety Unit Port Arthur
				Inspection Zone
				100-100



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 31 May 2022 **Expiration Date:** 31 May 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 30040B

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

30Apr2027

14Jun2017

13Apr2007

Internal Structure

31May2027

Α

31May2022

14Jun2017

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

31000

Barrels

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Location Description	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	891	13.58
2 P/S	887	13.58
3 P/S	816	13.58

SLOP TANK

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
11	4055	10ft 0in	13.58	
II	4055	10ft 0in	13.58	
III	4942	11ft 9in	13.58	
III	4942	11ft 9in	13.58	

Conditions Of Carriage

Only those cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #C2-0700595, dated 27FEB07, may be carried and then only in the tanks indicated.

Per 46 CFR 150.130, the Person In Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "Compat Group No" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing greater than 0.5% Benzene, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

46 CFR 151.45-2(b) contains restrictions on operating box and square end barges as the lead barges of tows.

Vapor Control Authorization

Per 46 CFR, 39, excluding Part 39,4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter #C2-0700595, dated 27FEB07, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

Per 46 CFR 39 1017 and 39 5000(e), this vessel's VCS has been evaluated and approved for multi-breasted tandem loading

Dept. Of Home Sec., USCG = GG-854 (Rev. 06-04)

Page 2 of 3

OMB Approved No. 1625-0057



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 31 May 2022 Expiration Date: 31 May 2023

Temporary Certificate of Inspection

Vessel Name: KIRBY 30040B

with other vessels specifically approved to tandem load with this vessel.a

Stability and Trim

The maximum design density of cargo which may be filled to the tank top is 8.745 lbs/gal. Cargoes with higher densities, up to 13.58 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

Per 46 CFR 151.10-15(c)(2), the maximum tank weights listed below reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter O cargoes at shallower drafts, the barge should always be loaded uniformly.

--- Inspection Status ---

Cargo Tanks

	Internal Exam	l		External Exa	m	
Tank Id	Previous	Last	Next	Previous	Last	Next
1 P/S	13Apr2007	14Jun2017	30Apr2027	-	-	_
2 P/S	13Apr2007	14Jun2017	30Apr2027	-		_
3 P/S	13Apr2007	14Jun2017	30Apr2027	•	-	_
SLOP TANK	13Apr2007	14Jun2017	30Apr2027	-	-	-
			Hydro Test			
Tank Id	Safety Valves		Previous	Last	Next	
1 P/S	-		-	13Apr2007	•	
2 P/S	-		-	13Apr2007	_	
3 P/S	-		_	13Apr2007		
SLOP TANK	-		-	13Apr2007	-	

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

2

40-B

END



Serial #: C2-0700595 Dated:

27-Feb-07

Certificate of Inspection

Cargo Authority Attachment

Shipyard: Trinity Marine, Ashland

Hull #: 4550

Tar	nk Group Information	Cargo I	dentificati	on	T. TOP TAIK 31		Carg Tran	argo Environmental ransfer Control		Fire	Special Requirements							
Tnk Grp	Tanks in Group	Density	Press.	Temp.	100000000	Seg		Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction	Elec Haz	Temp
A i	#1P/S,#2P/S,#3P/S	13.6	Atmos.	Amb.	II	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	.50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50- 81(b),	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	I-A	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Vessel Name: KIRBY 30040B

Official #: 1194273

Cargo Identification	n							Condi	tions of Carriage	
	T						Vapor Re			14
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Perio
Authorized Subchapter O Cargoes										
EE Glycol Ether Mixture	EEG	40)/O	D	Ш	Α	No	N/A	No	G
Acetonitrile	ATN	37	0	С	111	Α	Yes	3	No	G
Acrylonitrile	ACN	15 ²	0	С	11	A	Yes	4	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	0	E	11	Α	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	Ш	Α	No	N/A	.50-81, .50-86	G
Aminoethylethanolamine	AEE	8	0	E	111	Α	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 ²	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	Ш	Α	No	N/A		G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	11	Α	No	N/A		G
Benzene	BNZ	32	0	С	111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 ²	0	С	111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 ²	0	С	111	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	111	Α	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyl methacrylate	BMH	14	0	D	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	0	С	111	Α	Yes	1	.55-1(h)	G
Camphor oil (light)	CPC	18	0	D	11	Α	No	N/A	No	G
Carbon tetrachloride	CBT	36	0	NA	111	Α	No	N/A	No	G
Caustic potash solution	CPS	5 ²	0	NA	111	Α	No	N/A	.50-73, .55-1(j)	G
Caustic soda solution	CSS	5 ²	0	NA	111	Α	No	N/A	.50-73, .55-1(j)	G
Chemical Oil (refined, containing phenolics)	COL	21	0	E	11	Α	No	N/A	.50-73	G
Chlorobenzene	CRE	36	0	D	111	Α	Yes	1	No	G
Chloroform	CRF	36	0	NA	111	Α	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	0	D	111	Α	Yes	1	.50-73	G
Creosote	CCV	V 21 ²	0	E	111	Α	Yes	1	No	G
Cresols (all isomers)	CRS	3 21	0	E	111	Α	Yes	1	No	G
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CR)	<	0	E	111	Α	Yes	1	.55-1(f)	G
Crotonaldehyde	CTA	19 2	0	С	Н	Α	Yes	4	.55-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHO	3	0	С	111	Α	No	N/A		G
Cyclohexanone	CC	1 18	0	D	111	Α	Yes	3 1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	(18 ²	0	Е	111	Α	Yes	s 1	.56-1 (b)	G
Cyclohexylamine	CHA		0	D	111	Α	Yes	5 1	.56-1(a), (b), (c), (g)	G
Cyclopentadiene, Styrene, Benzene mixture	CSE		0	D	III	Α	Yes	s 1	.50-60, .56-1(b)	G



Serial #: C2-0700595 Dated: 27-Feb-07

Certificate of Inspection

Čargo Authority Attachment

Vessel Name: KIRBY 30040B Official #: 1194273

Shipyard: Trinity Marine,

Ashland

Hull #: 4550 Page 2 of 7

Cargo Identification						Conditions of Carriage						
	0.							Recovery	0			
Name iso-Decyl acrylate	Chem Code IAI	Group No	Sub Chapter O	Grade E	Hull Type III	Tank Group A	App'd (Y or N) Yes	VCS Category 2	Special Requirements in 46 CFR 151 General and Mat'ls of .50-70(a), .50-81(a), (b), .55-1(c)	Insp. Period G		
Dichlorobenzene (all isomers)	DBX	36	0	E	III	Α	Yes	3	.56-1(a), (b)	G		
1.1-Dichloroethane	DCH	36	0		III	A	Yes	1	No	G		
2,2'-Dichloroethyl ether	DEE	41	0	D	 	A	Yes	1	.55-1(f)	G		
Dichloromethane	DCM		0	NA	III	A	Yes	5	No	G		
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	Ш	A	No	N/A	.56-1(a), (b), (c), (g)	G		
	DAD	0 1,2		A	111	A	No	N/A		G		
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DTI	43 2	0	E	111	A	No	N/A		G		
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DPB	36	0	C	111		Yes	3	No			
1,1-Dichloropropane	DPP	36	0	c	111	A	Yes	3	No	G		
1,2-Dichloropropane			0		111	A	Yes	3	No	G		
1,3-Dichloropropane	DPC	36		C				4	No	G		
1,3-Dichloropropene	DPU	15	0	D	11	A	Yes		No	G		
Dichloropropene, Dichloropropane mixtures	DMX		0	C	11	A	Yes	1	.55-1(c)	G		
Diethanolamine	DEA	8	0	E	111	Α	Yes	1	.55-1(c)	G		
Diethylamine	DEN	7	0	C	- 111	A	Yes	3		G		
Diethylenetriamine	DET	7 2	0	E		Α	Yes	1	.55-1(c)	G		
Diisobutylamine	DBU	7	0	D	111	Α	Yes	3	.55-1(c)			
Diisopropanolamine	DIP	8	0	E	111	Α_	Yes		.55-1(c)	G		
Diisopropylamine	DIA	7	0	С	Н	Α	Yes	3	.55-1(c)	G		
N,N-Dimethylacetamide	DAC	10	0	E	111	Α	Yes	3	.56-1(b)	G		
Dimethylethanolamine	DMB	8	0	D	111	Α	Yes	1	.56-1(b), (c)	G		
Dimethylformamide	DMF	10	0	D	111	Α	Yes	1	.55-1(e)	G		
Di-n-propylamine	DNA	7	0	С	11	Α	Yes	3	.55-1(c)	G		
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	Е	III	Α	No	N/A	.56-1(b)	G		
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	II	Α	No	N/A	No	G		
Ethanolamine	MEA	. 8	0	E	III	Α	Yes	1	.55-1(c)	G		
Ethyl acrylate	EAC	14	0	С	111	Α	Yes	2	.50-70(a), .50-81(a), (b)	G		
Ethylamine solution (72% or less)	EAN	7	0	Α	II	Α	Yes	6	.55-1(b)	G		
N-Ethylbutylamine	EBA	7	0	D	111	Α	Yes	3	.55-1(b)	G		
N-Ethylcyclohexylamine	ECC	7	0	D	111	Α	Yes	1	.55-1(b)	G		
	ETC	20	0	E	111	Α	Yes	1	No	G		
Ethylene cyanohydrin	EDA	72	0	D	111	A	Yes		.55-1(c)	Ġ		
Ethylenediamine 5th does dishlarida	EDC		0	C	III	A	Yes		No	G		
Ethylene dichloride	EGH		0	E	111	A	No	N/A	No	G		
Ethylene glycol hexyl ether	EGC		-0	D/E	111	A	Yes		No	G		
Ethylene glycol monoalkyl ethers	EGP		0	E	111	A	Yes		No	G		
Ethylene glycol propyl ether			0	E	111	A	Yes		.50-70(a), .50-81(a), (b)	G		
2-Ethylhexyl acrylate	EAI	14					Yes		.50-70(a)	G		
Ethyl methacrylate	ETM		0	D/E	111	A			No	G		
2-Ethyl-3-propylacrolein	EPA		0	E =	111	A	Yes		.55-1(h)	G		
Formaldehyde solution (37% to 50%)	FMS		0	D/E	111	A	Yes		.55-1(h)	G		
Furfural	FFA		0	D	111	A	Yes			G		
Glutaraldehyde solution (50% or less)	GTA		0	NA	111	A	No	N/A		G		
Hexamethylenediamine solution	HMC		0	E	111	Α.	Yes		.55-1(c)	G		
Hexamethyleneimine	HMI	7	0	С	11	Α	Yes		.56-1(b), (c)			
Hydrocarbon 5-9	HFN		0	С	111	Α	Yes	-	.50-70(a), .50-81(a), (b)	G		
Isoprene	IPR	30	0	Α	111	Α	Yes		.50-70(a), .50-81(a), (b)	G		
Isoprene, Pentadiene mixture	IPN		0	В	Ш	Α	No	N/A		G		
Kraft pulping liquors (free alkali content 3% or more)(including: Black Green, or White liquor)	, KPL	5	0	NA	III	Α	No	N/A		G		
Mesityl oxide	MSC) 18 ²	0	D	111	Α	Yes	3 1	No	G		
Methyl acrylate	MAN	И 14	0	С	111	Α	Yes	3 2	.50-70(a), .50-81(a), (b)	G		



Serial #: C2-0700595 Dated:

27-Feb-07

Certificate of Inspection

Čargo Authority Attachment

Vessel Name: KIRBY 30040B Official #: 1194273

Shipyard: Trinity Marine,

Ashland

Page 3 of 7

Hull #: 4550

Cargo Identification	1								tions of Carriage	
		_						ecovery	0	
Name	Chem	Compat Group No	Sub	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp.
Methylcyclopentadiene dimer	MCK	30	0	С	111	Α	Yes	1	No	G
Methyl diethanolamine	MDE	8	0	E	Ш	Α	Yes	1	.56-1(b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	0	E	111	Α	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	0	С	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	0	D	111	Α	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	0	D	Ш	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	7 2	0	D	111	Α	Yes	1	.55-1(c)	G
1- or 2-Nitropropane	NPM	42	0	D	III	Α	Yes	1	.50-81	G
1.3-Pentadiene	PDE	30	0	Α	111	Α	Yes	7	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	111	Α	No	N/A	No	G
Polyethylene polyamines	PEB	7 2	0	E	III	Α	Yes	1	.55-1(e)	G
iso-Propanolamine	MPA	8	0	E	III	Α	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	0	E	111	Α	Yes	1	.56-1(b), (c)	G
iso-Propylamine	IPP	7	0	Α	11	A	Yes	5	.55-1(c)	G
Pyridine	PRD	9	0	C	111	Α	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		0		111	Α	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (40 % or less)	SDD	0 1,		NA	111	Α	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ		0	NA	111	A	No	N/A		G
Sodium rypochionic solution (20% of ress) Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,3		NA	III	A	Yes		.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1,		NA	III	Α	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,	2 0	NA	11	Α	No	N/A	.50-73, .55-1(b)	G
	STX		0	D	111	A	Yes	2	No	G
Styrene (crude)	STY	30	0	D	111	Α	Yes		.50-70(a), .50-81(a), (b)	G
Styrene monomer	TEC	36	0	NA		Α	No	N/A	No	G
1,1,2,2-Tetrachloroethane	TTP	7	0	E	111	A	Yes		.55-1(c)	G
Tetraethylenepentamine	THF	41	0	C		A	Yes		.50-70(b)	G
Tetrahydrofuran	TDA	9	0	E		A	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
Toluenediamine	TCB	36	0	E	111	A	Yes		No	G
1,2,4-Trichlorobenzene	100000000		0	NA.	111	A	Yes		.50-73, .56-1(a)	G
1,1,2-Trichloroethane	TCM				III	A	Yes		No	G
Trichloroethylene	TCL	36 ²	0	NA_		A	Yes		.50-73, .56-1(a)	G
1,2,3-Trichloropropane	TCN		0	E	11		Yes		.55-1(b)	3
Triethanolamine	TEA		0	E	111	A			.55-1(e)	G
Triethylamine	TEN		0	С	- 11	A	Yes		.55-1(b)	G
Triethylenetetramine	TET	7 2	0	E	111	A	Yes			G
Triphenylborane (10% or less), caustic soda solution	TPB		0	NA		A	No	N/A		G
Trisodium phosphate solution	TSP		0	NA	111	A	No	N/A		G
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS		0	NA	111	A	No	N/A		- G
Vanillin black liquor (free alkali content, 3% or more).	VBL		0	NA	111	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyl acetate	VAN		0	С	111	A	Yes			G
Vinyl neodecanate	VND		0	E	111		No	N//	.50-70(a), .50-81(a), (b) .50-70(a), .50-81, .56-1(a), (b), (c), (G
Vinyltoluene	VNT	13	0	D	111	A	Yes	3 2	.00-10(a), .00 01, .00-1(a), (b), (c), (
Subchapter D Cargoes Authorized for Vapor Cont		45.0				_	V	4		
Acetone	ACT	18 ²	D	C		A	Yes	11		
Acetophenone	ACP	18	D	E		A	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1		
	AEC	34	D	D		Α	Yes	1		



omeland Security Serial #:

Coast Guard Dated:

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 30040B

Shipyard: Trinity Marine,

Ashland Hull #: 4550 C2-0700595

27-Feb-07

Official #: 1194273

Page 4 of 7

Cargo Identification	n					Conditions of Carriage						
								Recovery				
Name Amyl alcohol (iso-, n-, sec-, primary)	Chem Code AAI	Group No 20	Sub Chapter D	Grade D	Hull Type	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Benzyl alcohol	BAL	21	D	E		Α	Yes	1				
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		Α	Yes	1				
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1				
Butyl alcohol (iso-)	IAL	20 ²	D	D		Α	Yes	1				
Butyl alcohol (n-)	BAN		D	D		Α	Yes	1				
Butyl alcohol (sec-)	BAS		D	С		Α	Yes	1				
Butyl alcohol (tert-)	BAT		D	С		Α	Yes	1				
Butyl benzyl phthalate	BPH	34	D	E		Α	Yes	1				
Butyl toluene	BUE	32	D	D		Α	Yes	1				
Caprolactam solutions	CLS	22	D	E		Α	Yes	1				
Cyclohexane	CHX	31	D	С		Α	Yes	1				
Cyclohexanol	CHN	20	D	E		Α	Yes	1				
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		Α	Yes	2				
p-Cymene	CMP	32	D	D		Α	Yes	1				
iso-Decaldehyde	IDA	19	D	E		Α	Yes	1				
n-Decaldehyde	DAL	19	D	E		Α	Yes	1				
Decene	DCE	30	D	D		A	Yes	1				
Decyl alcohol (all isomers)	DAX	20 ²	D	E		A	Yes	1				
	DBZ	32	D	E		Α	Yes	1				
n-Decylbenzene, see Alkyl(C9+)benzenes	DAA	20 ²	D	D		A	Yes	1				
Diacetone alcohol	DPA	34	D	E		A	Yes	1				
ortho-Dibutyl phthalate	DEB	32		D		A	Yes	1				
Diethylbenzene	DEG	40 ²	D	E		- A	Yes	1				
Diethylene glycol	DBL	30	D	C		A	Yes	1				
Diisobutylene				D		A	Yes	1				
Diisobutyl ketone	DIK	18	D				Yes	1				
Diisopropylbenzene (all isomers)	DIX	32	D	E		A						
Dimethyl phthalate	DTL	34	D	E		A	Yes	1				
Dioctyl phthalate	DOP	34	D	E		A	Yes	1				
Dipentene	DPN	30	D	D		A	Yes	1				
Diphenyl	DIL	32	D	D/E		Α	Yes	1				
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		Α	Yes	1				
Diphenyl ether	DPE	41	D	{E}		A	Yes	1				
Dipropylene glycol	DPG	40	D	E		A	Yes	11				
Distillates: Flashed feed stocks	DFF	33	D	E		Α	Yes	1				
Distillates: Straight run	DSR	33	D	E		A	Yes	1				
Dodecene (all isomers)	DOZ	30	D	D		Α	Yes	11				
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		Α	Yes	1				
2-Ethoxyethyl acetate	EEA	34	D	D		Α	Yes	1				
Ethoxy triglycol (crude)	ETG	40	D	Е		Α	Yes	1				
Ethyl acetate	ETA	34	D	С		Α	Yes	1				
Ethyl acetoacetate	EAA	34	D	Ε		Α	Yes	1				
Ethyl alcohol	EAL	20 ²	D	С		Α	Yes	1				
Ethylbenzene	ETB	32	D	С		Α	Yes	1				
Ethyl butanol	EBT	20	D	D		Α	Yes	1				
Ethyl tert-butyl ether	EBE	41	D	С		Α	Yes	1				
Ethyl butyrate	EBR		D	D		Α	Yes					
	ECY	31	D	D		Α	Yes					
Ethyl cyclohexane Ethylene glycol	EGL	20 ²	D	E		Α	Yes					



Dated: 27-Feb-07

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 30040B

Official #: 1194273

Page 5 of 7

Shipyard: Trinity Marine, Ashland

Hull #: 4550

Cargo Identification	on							Condi	tions of Carriage	
							Vapor I	Recovery		
Name Ethylene glycol butyl ether acetate	Chem Code EMA	Compat Group No 34	Sub Chapter D	Grade E	Hull Type	Tank Group A	App'd (Y or N) Yes	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Perio
Ethylene glycol diacetate	EGY	34	_ D	E		Α	Yes	1		
Ethylene glycol diacetate Ethylene glycol phenyl ether	EPE	40		E		A	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1		
2-Ethylhexanol	EHX	20		E		A	Yes	1		
	EPR	34	D	C		A	Yes	1		
Ethyl propionate	ETE	32	D	D		A	Yes	1		
Ethyl toluene Formamide	FAM	10	D	E		A	Yes	1		
	FAL	20 ²	D	 E		A	Yes	1		
Furfuryl alcohol	GAK	33	D	A/C		A	Yes	1		
Gasoline blending stocks: Alkylates	GRF	33	D	A/C		A	Yes	1		
Gasoline blending stocks: Reformates		33	D	C		A	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT									
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		A	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		A	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		A	Yes	1		
Glycerine	GCR	20 ²	D	E		Α	Yes	11		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С		Α	Yes	1		
Heptanoic acid	HEP	4	D	E		Α	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		A	Yes	1		
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2		
Heptyl acetate	HPE	34	D	Ε		Α	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		Α	Yes	1		
Hexanoic acid	НХО	4	D	Е		Α	Yes	1		
Hexanol	HXN	20	D	D		Α	Yes	1		
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2		
Hexylene glycol	HXG	20	D	E		Α	Yes	1		
Isophorone	IPH	18 ²	D	E		Α	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		Α	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D	77-918	Α	Yes	1		
Kerosene	KRS	33	D	D		Α	Yes	1		
	MTT	34	D	D		Α	Yes	1		-
Methyl acetate	MAL	20 ²	D	С		Α	Yes	1		
Methyl alcohol	MAC		D	D		A	Yes	1		
Methylamyl acetate	MAA		D	D		A	Yes	1		
Methylamyl alcohol	MAK		D	D		A	Yes	1		
Methyl amyl ketone	MBE		D	C		A	Yes	1		
Methyl tert-butyl ether	MBK		D	C		A	Yes	1		
Methyl butyl ketone			D	C		A	Yes	1		
Methyl butyrate	MBU		D	C		A	Yes			
Methyl ethyl ketone	MEK			D		A	Yes	1		
Methyl heptyl ketone	MHK	18 18 ²	D			A	Yes			
Methyl isobutyl ketone	MIK		D	С		A	Yes			
Methyl naphthalene (molten)	MNA		D	E						
Mineral spirits	MNS		D	D		A	Yes			
Myrcene	MRE		D	D #		A	Yes			
Naphtha: Heavy	NAG	-	D	#		A	Yes			
Naphtha: Petroleum	PTN		D	#		A	Yes			
Naphtha: Solvent	NSV		D	D		A	Yes			
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1		



Serial #: C2-0700595 Dated: 27-Feb-07

Certificate of Inspection Cargo Authority Attachment

Official #: 1194273

Shipyard: Trinity Marine,

Ashland

Hull #: 4550

Vessel Name: KIRBY 30040B

Page 6 of 7

Cargo Identifica	tion								tions of Carriage	
							-	Recovery		
Name Naphtha: Varnish makers and painters (75%)	Chem Code NVM	Group No 33	Sub Chapter D	Grade C	Hull Tvoe	Tank Group A	App'd (Y or N) Yes	VCS Category 1	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		Α	Yes	1		
Nonene (all isomers)	NON	30	D	D		Α	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		Α	Yes	1		
Nonyl phenol	NNP	21	D	E		Α	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		Α	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	С		Α	Yes	1		
Octanoic acid (all isomers)	OAY	4	D	Е		Α	Yes	1		
Octanol (all isomers)	OCX	20 ²	D	Е		Α	Yes	1		
Octene (all isomers)	OTX	30	D	С		Α	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		Α	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		Α	Yes	1		
Oil, fuel: No. 6	osx	33	D	E		Α	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		Α	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		Α	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		Α	Yes	11		
Oil, misc: Residual	ORL	33	D	E		Α	Yes	1		
Oil, misc: Turbine	OTB	33	D	E		Α	Yes	1		
Pentane (all isomers)	PTY	31	D	Α		Α	Yes	5		
Pentene (all isomers)	PTX	30	D	Α		Α	Yes	5		
alpha-Pinene	PIO	30	D	D		Α	Yes	1		
beta-Pinene	PIP	30	D	D		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	Ε		Α	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		Α	Yes	1		
Polybutene	PLB	30	D	E		Α	Yes	1		
Polypropylene glycol	PGC	40	D	E		Α	Yes	1		
iso-Propyl acetate	IAC	34	D	С		Α	Yes	1		
n-Propyl acetate	PAT	34	D	С		Α	Yes	1		
iso-Propyl alcohol	IPA	20 2	D	С		Α	Yes	1		
n-Propyl alcohol	PAL	20 2	D	С		Α	Yes	1		
Propylbenzene (all isomers)	PBY	32	D	D		Α	Yes	1		
iso-Propylcyclohexane	IPX	31	D	D		Α	Yes	1		
Propylene glycol	PPG	20 2	D	Ε		Α	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		Α	Yes	1		
Propylene tetramer	PTT	30	D	D		Α	Yes	1		
Sulfolane	SFL	39	D	E		Α	Yes	1		
Tetraethylene glycol	TTG	40	D	E		Α	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		Α	Yes	1		
Toluene	TOL	32	D	С		Α	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		Α	Yes			
Triethylbenzene	TEB	32	D	E		Α	Yes			
Triethylene glycol	TEG	40	D	Ε	4	Α	Yes			
Triethyl phosphate	TPS	34	D	E		Α	Yes			
Trimethylbenzene (all isomers)	TRE	32	D	{D}		Α	Yes			
Trixylenyl phosphate	TRP	34	D	E		Α	Yes			
Undecene	UDC	30	D	D/E		Α	Yes			
1-Undecyl alcohol	UND	20	D	E		Α	Yes			
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		Α	Yes	1		



Serial #: C2-0700595

27-Fen-07



Vessel Name: KIRBY 30040B Official #: 1194273

Page 7 of 7

Shipyard: Trinity Marine,

Hull #: 4550

Explanation of terms & symbols used in the Table:

Cargo Identification

The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

Chem Code

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No.

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Note 1 Note 2

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter Subchapter D Subchapter O Note 3

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Path 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

A, B, C D. E Note 4 Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

NA

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group Vapor Recovery Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Tank Group Vapor Recove Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category

The specified cargo's provisional classification for vapor control systems.

Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.

Category 6 Category 7 (High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.

none

The cargo has not been evaluated/classified for use in vapor control systems.