

United States of America Department of Homeland Security United States Coast Guard

Certification Date: 20 Apr 2023 Expiration Date: 20 Apr 2024

Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Official Number IMO Number Call Sign Vessel Name Tank Barge MMI 3046 1166417 Hailing Port Hull Material Propulsion Horsepower HOUSTON, TX Steel UNITED STATES Delivery Date Keel Laid Date Gross Tons Net Tons DWT Length MADISONVILLE, LA R-1619 R-1619 R-297.5 22Mar2005 14Feb2005 1-0 UNITED STATES HIGMAN BARGE LINES INC KIRBY INLAND MARINE LP 55 WAUGH DR STE 1000 18350 Market Street HOUSTON, TX 77007 Channelview, TX 77530 **UNITED STATES** UNITED STATES This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators. 0 Masters 0 Licensed Mates 0 Chief Engineers 0 Chief Mates 0 First Class Pilots 0 First Assistant Engineers 0 Second Mates 0 Radio Officers 0 Second Assistant Engineers 0 Third Mates 0 Able Seamen 0 Third Assistant Engineers 0 Master First Class Pilot 0 Ordinary Seamen 0 Licensed Engineers 0 Mate First Class Pilots 0 Deckhands 0 Qualified Member Engineer

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a) (2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a) (1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

This tank barge is participating in the Eighth Coast Guard District's Tank Barge Streamlined Inspection Program

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

| | Annual/Peri | odic/Re-Inspe | ction | This certificate issued |
|------|-------------|---------------|-----------|--|
| Date | Zone | A/P/R | Signature | B. T. INAGAKI, GS-13, USOG, By direction |
| | | | | Officer in Charge, Marine Inspection Marine Safety Unit Port Arthur |
| | | | | Inspection Zone |



United States of America **Department of Homeland Security United States Coast Guard**

Certification Date: 20 Apr 2023 **Expiration Date:** 20 Apr 2024

Temporary Certificate of Inspection

Vessel Name: MMt 3046

(TBSIP). Inspection activities aboard this barge shall be conducted per its Tank Barge Action Plan (TAP). Inspection issues concerning this barge should be directed to OCMI Houston-Galveston.

---Hull Exams---

Exam Type

Next Exam

Last Exam

Prior Exam

DryDock

14Apr2025

14Apr2015

22Mar2005

Internal Structure

30Apr2028

18Apr2023

27Feb2018

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization:

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES.

Total Capacity

Units

Highest Grade Type Part151 Regulated Part153 Regulated Part154 Regulated

29500

Barrels

Α

Yes

No

No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

| Tank Location Description | Max Cargo Weight per Tank (short tons) | Maximum Density (ibs/gal) |
|---------------------------|--|---------------------------|
| 1 P/S | 841 | 13.6 |
| 2 P/S | 793 | 13.6 |
| 3 P/S | 781 | 13.6 |

Loading Constraints - Stability

| Hull Type | Maximum Load (short tons) | Maximum Draft (ft/in) | Max Density (lbs/gal) | Route Description |
|-----------|---------------------------|--------------------------|--------------------------|--------------------------------|
| II | 3614 | 9ft 6in | 13.6 | Rivers, Lakes, Bays and Sounds |
| III | 4603 | 11ft 6in | 13.6 | Rivers, Lakes, Bays and Sounds |

Conditions Of Carriage

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial C1-2000602, dated 19FEB20, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 CFR Part 197, Subpart C, are applied.

Vapor Control Authorization

Per 46 CFR, Part 39, excluding Part 39.4000 and 39.5000, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letter serial # C1-2000348, dated 30JAN20, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

The VCS system has been approved with a pressure side 3 psig P/V valve with Coast Guard approval 162.017/167/4. The cargo tank top is suitable for a MAWP of 3.5 psi.

Per 46 CFR Part 39,1017 and 39,5000(e) this vessel's VCS has been evaluated and approved for multi-breasted tandem loading with other vessels specifically approved to tandem load with this vessel.



United States of America Department of Homeland Security United States Coast Guard

Certification Date: 20 Apr 2023 Expiration Date: 20 Apr 2024

Temporary Certificate of Inspection

Vessel Name: MMI 3046

Stability and Trim

Per 46 CFR 151.10-15(c)(2) the maximum tank weights listed above reflect uniform(within 5%) loading at the deepest draft allowed. When carrying subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.7 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

--- Inspection Status ---

Cargo Tanks

| | Internal Exam | 1 | | External Exar | m | |
|---------|---------------|-----------|------------|---------------|------|------|
| Tank id | Previous | Last | Next | Previous | Last | Next |
| 1 P/S | 14Apr2015 | 27Feb2018 | 29Feb2028 | - | - | - |
| 2 P/S | 14Apr2015 | 27Feb2018 | 29Feb2028 | - | - | - |
| 3 P/S | 14Apr2015 | 27Feb2018 | 29Feb2028 | - | - | - |
| | | | Hydro Test | | | |
| Tank ld | Safety Valves | 5 | Previous | Last | Next | |
| 1 P/S | - | | - | - | - | |
| 2 P/S | - | | - | - | - | |
| 3 P/S | - | | - | • | - | |

--- Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity

Class Type

B-II

END



Serial #: C1-2000602 Dated:

19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine Madisonville

Hull #: 2137-1

Official #: 1166417

| Tank Group Information | <u>-</u> | | Cargo | 1 | Tanks | | | Cargo Transfer | | Environmental Control | | Special Requirements | | | | | |
|---------------------------|----------|--------|-------|-------------|-------------|---------------------|------|-------------------|---------------|--------------------------|-------|----------------------|------------------------|---|--|-------------|--------------|
| Tnk Grp Tanks in Group | Density | Press. | Temp. | Hull Typ | Seg Tank | | Vent | Gauge | Pipe Class | Cont | Tanks | Handling Space | Protection Provided | General | Materials of Construction | Elec Haz | Temp Cont |
| A #1 - #3 P/S | 13.6 | Atmos. | Amb. | Ħ | 1ii 2ii | Integral Gravity | PV | Closed | II | G-1 | NR | NA | Portable | .50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50- 81(b), | 55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g), | NR | No |

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.

3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

| Cargo Identification | Conditions of Carriage | | | | | | | | | |
|--|------------------------|-----------------|----------------|-------|--------------|--|-------------------|-----------------|---|------------------|
| | | Compat | | | | | | Recovery | | |
| Name | Chem Code | Group No | Sub Chapter | Grade | Hull Type | Tank Group | App'd (Y or N) | VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of | Insp. Period |
| Authorized Subchapter O Cargoes | | | _ | | | | | | | ' |
| Sodium acetate solution | SAN | 34 | D/Q 3 | # | | A | No | N/A | | |
| Acetonitrile | ATN | 37 | 0 | С | Ш | Α | Yes | 3 | No | G |
| Acrylonitrile | ACN | 15 ² | 0 | С | П | Α | Yes | 4 | 50-70(a). :55-1(e) | G |
| Adiponitrile | ADN | 37 | 0 | Ε | Ш | Α | Yes | 1 | No | G |
| Alkyl (C7-C9) nitrates | AKN | 34 2 | - 0 | NA | 101 | Α | No | N/A | .50-81, .50-86 | G |
| Aminoethyl ethanolamine | AEE | 8 | 0 | Ε | Ш | Α | Yes | 1 | .55-1(b) | G |
| Ammonium bisuffite solution (70% or less) | ABX | 43 ² | 0 | NA | [§] | Α | No | N/A | 50-73, 56-1(a), (b), (c) | G |
| Ammonium hydroxide (28% or less NH3) | AMH | 6 | 0 | NA | 111 | Α | No | N/A | .56-1(a), (b), (c), (f), (g) | G |
| Anthracene oil (Coal tar fraction) | AHO | 33 | 0 | NA | Ш | Α | No | N/A | No | G |
| Benzene | BNZ | 32 | 0 | С | III | Α | Yes | 1 | .50-60 | G |
| Benzene or hydrocarbon mixtures (having 10% Benzene or more) | внв | 32 ² | 0 | С | Ш | Α | Yes | 1 | .50-60 | G |
| Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more) | ВНА | 32 ² | 0 | С | Ш | Α | Yes | 1 | .50-60, .56-1(b), (d), (f), (g) | G |
| Benzene, Toluene, Xylene mixtures (10% Benzene or more) | BTX | 32 | 0 | B/C | 111 | Α | Yes | 1 | .50-60 | G |
| Butyl acrylate (all isomers) | BAR | 14 | _ | D | III | A | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| Butyl methacrylate | ВМН | 14 | 0 | D . | Ш | Α | Yes | | .50-70(a), .50-81(a), (b) | - · G |
| Butyraldehyde (all isomers) | BAE | 19 | 0 | С | Ш | Α | Yes | 1 | .55-1(h) | G |
| Camphor oil (light) | CPO | 18 | 0 | D | II | Α | No | N/A | No | G |
| Carbon tetrachloride | CBT | 36 | 0 | NA | JII | Α | Yes | 3 | No | G |
| Caustic potash solution | CPS | 5 ² | 0 | NA | [2] | Α | No | N/A | .50-73, .55-1(j) | G |
| Caustic soda solution | CSS | 5 ² | 0 | NA | 10 | A | No | N/A | .50-73, .55-1(j) | G |
| Chlorobenzene | CRB | 36 | 0 | D | 11) | Α | Yes | 1 | No | G |
| Chloroform | CRF | 36 | 0 | NA | IJ | A | Yes | 3 | No | G |
| Coal tar naphtha solvent | NCT | 33 | 0 | D | 111 | A | Yes | _ _ | 50-73 | G |
| Creosote | CCW | 21 2 | 0 | E | | | Yes | - <u>-</u> | No | |
| Cresols (all isomers) | CRS | 21 | 0 | `_ | III | —————————————————————————————————————— | Yes | <u>`</u> | No | G |
| Cresylate spent caustic | CSC | 5 | 0 | NA | 01 | | No | N/A | .50-73, .55-1(b) | G |
| Cresylic acid tar | CRX | 21 | 0 | E | 161 | A | Yes | 1 | 55-1(f) | G |
| Crotonaldehyde | CTA | 19 2 | ō | c | 11 | A | Yes | 4 | .55-1(h) | G |
| Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein) | CHG | 19 ² | 0 | C | HI | A | Yes | 1 | No | G |
| Cyclohexanone | ССН | 18 | 0 | D | 111 | Α | Yes | 1 | .56-1(a), (b) | G |
| Cyclohexanone, Cyclohexanol mixture | CYX | 18 ² | 0 | E | III | A | Yes | 1 | .56-1 (b) | G |

This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine Madisonville

19-Feb-20

Hull #: 2137-1

Official #: 1166417

Page 2 of 9

| Cargo Identification | Conditions of Carriage | | | | | | | | | |
|---|------------------------|-------------|------------------|--|--------------|---------------|-------------------|-----------------|--|---|
| - | | Compat | | | | ! | | Recovery | Special Requirements in 46 CFR | \top |
| Name | Chem Code | Group No | Sub Chapter | Grade | Huli Type | Tank Group | App'd (Y or N) | VCS Category | 151 General and Mat'ls of Construction | Insp. Period |
| - | | | | <u>: </u> | | | | | | |
| | | _ | _ | _ | | 4 | | _ | 56 1(a) (b) (c) (a) | G |
| Cyclohexylamine | CHA | 7 | 0 | D | III | A | Yes | 1 | .56-1(a). (b). (c). (g) .50-60, .\$6-1(b) | G |
| Cyclopentadiene, Styrene, Benzene mixture | CSB | 30 | 0 | D | #[[| A | Yes | 1 | .50-70(a), 50-81(a), (b), 55-1(c) | G |
| iso-Decyl acrylate | IAI | 14 | 0 | E | III | Α | Yes | 2 | ** | G |
| Dichlorobenzene (all isomers) | DBX | 36 | 0 | E | III | Α | Yes | | .56-1(a), (b) | G |
| 1,1-Dichloroethane | DCH | 36 | 0 | С | III | Α | Yes | | No | |
| 2,2'-Dichloroethyl ether | DEE | 41 | 0 | D | il | Α | Yes | | 55-1(f) | G |
| Dichloromethane | DCM | 36 | 0 | NA | Ш | Α | Yes | 5 | No | G |
| 2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution | DDE | 43 | 0 | E | Ш | Α | No | N/A | | G |
| 2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution | DAD | 0 | 1,2 O | Α | Ħ | Α | No | N/A | | G |
| 2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution | DΤΙ | 43 | 2 0 | Ε | Ш | Α | No | N/A | .56-1(a), (b), (c), (g) | G |
| 1,1-Dichloropropane | DPB | 36 | 0 | С | III | Α | Yes | 3 | No | G |
| 1,2-Dichloropropane | DPP | 36 | 0 | С | III | Α | Yes | 3 | No | G |
| 1,3-Dichloropropane | DPC | 36 | 0 | С | 111 | Α | Yes | 3 | Na | G |
| 1,3-Dichloropropene | DPU | 15 | 0 | Đ | II | Α | Yes | 4 | No | G |
| Dichloropropene, Dichloropropane mixtures | DMX | 15 | 0 | С | Ð | Α | Yes | 1 | No | G |
| Diethanolamine | DEA | . 8 | 0 | Ε | III | Α | Yes | 1 | 55-1(c) | G |
| Diethylamine | DEN | 7 | 0 | С | 101 | Α | Yes | 3 | \$5-1(c) | G |
| Diethylenetriamine | DET | 7 | 2 0 | E | BI | Α | Yes | 1 | .55-1(c) | G |
| | DBU | 7 | Ó | D | 111 | Α | Yes | 3 | 55-1(c) | G |
| Diisobutylamine | DIP | 8 | 0 | Ε | Ш | Α | Yes | . 1 | 55-1(c) | G |
| Diisopropanolamine | DIA | 7 | 0 | C | 11 | Α | Yes | 3 | .55-1(c) | G |
| Diisopropylamine | DAC | | | E | 111 | | Yes | | 56-1(b) | G |
| N,N-Dimethylacetamide | DME | | | — _ | JII | | Yes | | 56-1(b), (c) | G |
| Dimethylethanolamine | DMF | | | | | | Yes | | 55-1(e) | G |
| Dimethylformamide | DNA | | | c | | A | Yes | | 55-1(c) | G |
| Di-n-propylamine | DOT | | | — E | | | No | N// | Δ 56-1(b) | - · · · · · · · · · · · · · · · · · · · |
| Dodecyldimethylamine, Tetradecyldimethylamine mixture | | | _ | | 11 | A | No | N/A | • | G |
| Dodecyl diphenyl ether disulfonate solution | DOS | | | | 111 | | No | N/A | • | G |
| EE Glycol Ether Mixture | EEG | | | D | | | Yes | | .55-1(c) | G |
| Ethanolamine | ME/ | | | | 111 | | | | .50-70(a), .50-81(a), (b) | G |
| Ethyl acrylate | EAC | . — | | | | | Yes | | .55-1(b) | G |
| Ethylamine solutions (72% or less) | EAN | | | | 11 | A | Ye: | | .55-1(b) | |
| N-Ethylbutylamine | EBA | | | | | | Ye | | 55-1(b) | G |
| N-Ethylcyclohexylamine | ECC | | | | 111 | | Yes | | No | G |
| Ethylene cyanohydrin | ETC | | | _ E | | | Ye: | | | G |
| Ethylenediamine | EDA | | ² C | D | U | | Ye | | 55-1(c) | G |
| Ethylene dichloride | EDO | 36 | 5 ² C | | H | | Ye | | No | G |
| Ethylene glycol hexyl ether | EGI | H 40 |) (|) E | II | 1 A | No | | | G |
| Ethylene glycol monoalkyl ethers | EG | C 40 | | | | | Ye | | | |
| Ethylene glycol propyl ether | EGI | P 40 |) (| | II | I A | Ye | | No | G |
| 2-Ethylhexyl acrylate | EAI | 14 | 4 C |) E | H | ı A | Ye | | .50-70(a), .50-81(a), (b) | G |
| Ethyl methacrylate | ETM | VI _14 | 4 |) D/ | E 11 | I A | Ye | s 2 | .50-70(a) | <u> </u> |
| 2-Ethyl-3-propylacrolein | €P/ | A 19 | 9 ² C |) E | Ī. II | I A | Ye | s 1 | | <u> </u> |
| Formaldehyde solution (37% to 50%) | FM | S 19 | 9 ² | D/ | E !! | ı A | Ye | s 1 | .55-1(h) | G |
| Furfural | FF. | A 19 | 9 (| Q (| İl | i A | Ye | | .55-1(h) | G |
| Glutaraldehyde solutions (50% or less) | GT. | A 1 | 9 (|) N | A 11 | II A | No | N/ | /A No | G |



19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine Madisonville

Hull #: 2137-1

Official #: 1166417

Page 3 of 9

| Official #. 100417 | | | Page 3 | or 9 | | Hull #: 2137-1 | | | | | | |
|---|---------------|-----------------|----------------|-------|--------------|------------------------|-------------------|-----------------|--|-----------------|--|--|
| Cargo Identification | 1 | | | | | Conditions of Carriage | | | | | | |
| | | Compat | | | | | Vapor F | Recovery | Special Requirements in 46 CFR | | | |
| Name | Chem Code | Group No | Sub Chapter | Grade | Hull Type | Tank Group | App'd (Y or N) | VCS Category | 151 General and Mat'ls of Construction | Insp. Period | | |
| | | | | | | | | | | | | |
| Hexamethylenediamine solution | НМС | 7 | 0 | E | Ш | Α | Yes | 1 | .55-1(c) | G | | |
| Hexamethyleneimine | НМІ | 7 | 0 | С | li | Α | Yes | 1 | .56-1(b), (c) | G | | |
| Isoprene | IPR | 30 | 0 | Α | 10 | Α | Yes | 7 | .50-70(a), .50-81(a), (b) | G | | |
| Isoprene, Pentadiene mixture | IPN | 30 | 0 | В | II(| Α | No | N/A | .50-70(a), .55-1(c) | G | | |
| Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor) | KPL | 5 | 0 | NA | Ш | Α | No | N/A | 50-73, .56-1(a), (c), (g) | G | | |
| Mesityl oxide | MSO | 18 ² | 0 | D | H | A | Yes | 1 | No | G | | |
| Methyl acrylate | MAM | 14 | 0 | C | 181 | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G | | |
| Methylcyclopentadiene dimer | MCK | 30 | 0 | С | Ш | Α | Yes | 1 | Na | G | | |
| Methyl diethanolamine | MDE | 8 | O | E | Ш | Α | Yes | 1 | .56-1(b), (c) | G | | |
| 2-Methyl-5-ethyl pyridine | MEP | 9 | 0 | E | IIt | A | Yes | 1 | .55-1(e) | G | | |
| Methyl methacrylate | MMM | 1 14 | 0 | С | #11 | Α | Yes | 2 | 50-70(a), 50-81(a), (b) | G | | |
| 2-Methylpyridine | MPR | 9 | 0 | D | 01 | Α | Yes | 3 | 55-1(c) | G | | |
| alpha-Methylstyrene | MSR | 30 | 0 | D | Ш | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G | | |
| Morpholine | MPL | 7 2 | 0 | D | Ш | Α | Yes | 1 | .55-1(c) | G | | |
| Nitroethane | NTE | 42 | 0 | D | П | Α | No | N/A | .50-81 .56-1(b) | G | | |
| 1- or 2-Nitropropane | NPM | 42 | 0 | D | III | A | Yes | 1 | .50-81 | G | | |
| 1,3-Pentadiene | PDE | 30 | o | Α | Ш | Α | Yes | 7 | .50-70(a), .50-81 | G | | |
| Perchloroethylene | PER | 36 | 0 | NA | III | A | No | N/A | No | G | | |
| Polyethylene polyamines | PEB | 7 2 | 0 | Ε | 411 | A | Yes | 1 | .55-1(e) | G | | |
| iso-Propanolamine | MPA | 8 | 0 | E | £11 | A | Yes | 1 | .55-1(c) | G | | |
| Propanolamine (iso-, n-) | PAX | 8 | | E | DI. | A | Yes | <u>·</u> | .56-1(b), (c) | | | |
| Isopropylamine | IPP | 7 | ō | Ā | li. | A | Yes | 5 | .55-1(c) | G | | |
| Pyridine | PRD | 9 | 0 | C C | 10 | <u>A</u> | Yes | 1 | .55-1(e) | G | | |
| Pyrolysis Gasoline (containing benzene) | PYG | 32 | 0 | c | 11 | | No | , N/A | .50-60 | G | | |
| Sodium acetate, Glycol, Water mixture (3% or more Sodium | SAP | 5 | 0 | | III | A | No | N/A | .50-73, 55-1(j) | G | | |
| Hydroxide) | 2 , ,, | Ŭ | J | | | ^ | 140 | 1307 | . 4, | | | |
| Sodium aluminate solution (45% or less) | SAU | 5 | 0 | NA | 411 | Α | No | N/A | 50-73, 56-1(a), (b), (c) | G | | |
| Sodium chlorate solution (50% or less) | SDD | 0 1,2 | 0 | NA | 111 | Α | No | N/A | .50-73 | G | | |
| Sodium hypochlorite solution (20% or less) | SHQ | 5 | 0 | NA | (III | Α | No | N/A | 50-73, .56-1(a), (b) | G | | |
| Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less) | SSH | 0 1.2 | 0 | NA | III | A | Yes | 1 | 50-73, .55-1(b) | G | | |
| Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm) | SSI | 0 1.2 | 0 | NA | HI | A | No | N/A | .50-73, 55-1(b) | G | | |
| Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm) | SSJ | 0 1.2 | 0 | NA | П | Α | No | N/A | .50-73, .55-1(b) | G | | |
| Styrene monomer | STY | 30 | 0 | D | | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G | | |
| 1,1,2,2-Tetrachloroethane | TEC | 36 | 0 | NA | Ш | Α | No | N/A | No | G | | |
| Tetraethylene pentamine | TTP | 7 | 0 | E | Ш | Α | Yes | 1 | .55-1(c) | G | | |
| Tetrahydrofuran | THF | 41 | 0 | c | 111 | A - | Yes | <u>·</u> | 50-70(b) | G | | |
| 1,2,4-Trichlorobenzene | тсв | 36 | ō | E | IH | A | Yes | 1 | No | G | | |
| 1,1,1-Trichloroethane | TCE | 36 ² | 0 3 | NA | 11 | :: A | No | N/A | .50-73, 56-1(a) | G | | |
| 1,1,2-Trichloroethane | TCM | 36 | - - | NA | | - :- <u>:::</u> A | Yes | 1 | .50-73, .56-1(a) | G | | |
| Trichloroethylene | TCL | 36 ² | _ | NA | | A | Yes | <u>;</u> | No | G | | |
| 1,2,3-Trichloropropane | TCN | 36 | 0 | E | | — <u>:</u> : | Yes | 3 | .50-73, 56-1(a) | G | | |
| Triethanolamine | TEA | 8 2 | | E | 10 | | Yes | 1 | .55-1(b) | | | |
| Triethylamine | TEN | 7 | - <u>-</u> | c | 11 | A | Yes | 3 | .55-1(e) | G | | |
| Triethylenetetramine | TET | 7 2 | ō | E | III | A | Yes | 1 | .55-1(b) | G | | |
| | | | - | _ | | . • | | • | The state of the s | | | |

This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



C1-2000602 Dated:

19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine

Madisonville

Official #: 1166417

Page 4 of 9

Hull #: 2137-1

| Cargo Identification | | Conditions of Carriage | | | | | | | | |
|---|--------------|------------------------|-----------------|-------|--------------|---------------|-------------------------------|-----|---|--------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | Vapor Ri App'd (Y or N) | vcs | Special Requirements in 46 CFR 151 General and Mat'ls of Construction | Insp Peri |
| | | | | | | | | | | |
| Friphenylborane (10% or less), caustic soda solution | ТРВ | 5 | 0 | NA | 111 | Α | No | N/A | .56-1(a), (b), (c) | G |
| Frisodium phosphate solution | TSP | 5 | 0 | NA | ill | Α | No | N/A | .50-73 .56-1(a), (c). | G |
| Urea, Ammonium nitrate solution (containing more than 2% NH3) | UAS | 6 | 0 | NA | Ш | Α | No | N/A | .56-1(b) | G |
| /anillin black liquor (free alkali content, 3% or more). | VBL | 5 | 0 | NA | Ш | Α | No | N/A | 50-73, 56-1(a), (c), (g) | G |
| /inyl acetate | VAM | 13 | 0 | С | Bl | Α | Yes | 2 | .50-70(a), .50-81(a), (b) | G |
| /inyl neodecanoate | VND | 13 | 0 | E | III | Α | No | N/A | .50-70(a), 50-81(a), (b) | G |
| Vinyltoluene | VNT | 13 | 0 | D | III | Α | Yes | 2 | .50-70(a), .50-81, .56-1(a), (b), (c), (| G |
| ubchapter D Cargoes Authorized for Vapor Contr | ol | | | | | | | | | |
| Acetone | ACT | 18 | · D | C | | <u>A</u> | Yes | 1 | | |
| Acetophenone | ACP | 18 | D | Ε | | Α | Yes | 1 | | |
| Alcohol (C12-C16) poly(20+) ethoxylates | APV | / 20 | D | Ε | | _A_ | Yes | 1 | <u> </u> | |
| Alcohol (C6-C17) (secondary) poly(3-6) ethoxylates | AEA | 20 | D | E | | Α | Yes | 1 | | |
| Alcohol (C6-C17) (secondary) poly(7-12) ethoxylates | AEB | 20 | D | E | | Α | Yes | 1 | | |
| Amyl acetate (all isomers) | AEC | 34 | D | D | | Α | Yes | 1 | | |
| Amyl alcohol (iso-, n-, sec-, primary) | AAI | 20 | D | D | | Α | Yes | 1 | | |
| Benzyl acetate | BZE | 34 | D | Е | | Α | Yes | 1 | | |
| Benzyl alcohol | BAL | 21 | – <u>–</u> D | E | | A | Yes | 1 | | |
| Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters) | BFY | | =_ D | E | | Α | Yes | 1 | <u> </u> | |
| Butyl acetate (all isomers) | BAX | 34 | D | D | | Α | Yes | 1 | | |
| Isobutyl alcohol | IAL | 20 | 2 D | D | | А | Yes | i | | |
| Butyl alcohol (n-) | BAN | | | | | A | Yes | 1 | | |
| | BAS | | | c | | A | Yes | 1 | | |
| Butyl alcohol (sec-) | BAT | | | | | A | Yes | 1 | | |
| Butyl alcohol (tert-) | BPH | | D | | | ^ | Yes | 1 | <u> </u> | |
| Butyl benzyl phthalate | | | | | | | | | ME/ | |
| Butyl toluene | BUE | | D - | | | A | Yes | | | |
| Caprolactam solutions | CLS | | D | | | A | Yes | 1 | | |
| Cycloheptane | CYE | 31 | D | | | A | Yes | 1 | | |
| Cyclohexane | CH | 31 | D | С | | Α | Yes | 1 | | |
| Cyclohexanol | CHI | N 20 | D | E | | Α | Yes | 1 | | |
| Cyclohexyl acetate | CYC | 34 | ַם | D | | A | Yes | 1 | | |
| 1,3-Cyclopentadiene dimer (molten) | CPC | 30 | D | D/E | Ė | Α | Yes | 2 | | |
| Cyclopentane | CYF | 31 | | В | | Α | Yes | 1 | | |
| p-Cymene | CMI | P 32 | D | D | | Α | Yes | 1 | | |
| iso-Decaldehyde | IDA | 19 | D | Е | | Α | Yes | 1 | | |
| n-Decaldehyde | DAI | | D | Е | | Α | Yes | 1 | | |
| Decanoic acid | DC | | D | | | А | Yes | | | |
| Decarroic acid | | E 30 | | | | | | 1 | | |



Serial #: C1-2000602 Dated:

19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine

Madisonville

Official #: 1166417

Page 5 of 9

Hull #: 2137-1

| Cargo Ider | Cargo Identification | | | | | | | | Conditions of Carriage | | | | | | | | |
|---|----------------------|-----------------|---------|--------------|-----------|----------|------------------|-----------------|--|-----------------|--|--|--|--|--|--|--|
| | Chem | Compat Group | Sub | | : Hull | Tank | Vapor F App'd | Recovery VCS | Special Requirements in 46 CFR 151 General and Mat'ls of | Inco | | | | | | | |
| Name | Code | No | Chapter | Grade | Туре | Group | (Y or N) | Category | Construction | Insp. Period | | | | | | | |
| Don't stocket (all icomore) | DAY | 20. | , 5 | _ | | | V | á | | | | | | | | | |
| Decyl alcohol (all isomers) n-Decylberizene, see Alkyl(C9+)benzenes | DBZ | | | E | | <u>A</u> | Yes | 1_ 1 | | | | | | | | | |
| Diacetone alcohol | | | , D | | | Α . | Yes | | | | | | | | | | |
| | DAA | | | D | | A | Yes | 1 | | | | | | | | | |
| Dibutyl phthalate | DPA | | D | E | | A | Yes | 1 | | | | | | | | | |
| Diethylbenzene | DEB | | . D | | | A | Yes | 1 | | | | | | | | | |
| Diethylene glycol | DEG | | | . <u>E</u> | - | <u>A</u> | Yes | | | | | | | | | | |
| Diisobutylene | DBL | 30 | D | C | | Α . | Yes | 1 | | | | | | | | | |
| Diisobutyl ketone | DIK | 18 | D_ | D | | <u>A</u> | Yes | 1 | | | | | | | | | |
| Diisopropylbenzene (all isomers) | DIX | 32 | D | E | | A | Yes | 1 | | | | | | | | | |
| Dimethyl phthalate | DTL | 34 | D_ | <u>E</u> | | A | Yes | | | | | | | | | | |
| Dioctyl phthalate | DOP | | D | Е | | Α | Yes | 1 | | | | | | | | | |
| Dipentene | DPN | 30 | D | D | | Α | Yes | 1 | | | | | | | | | |
| Diphenyt | DIL | 32 | D | D/E | | A | Yes | 1 | | | | | | | | | |
| Diphenyl, Diphenyl ether mixtures | DDO | 33 | D | E | | Α | Yes | 1 | | | | | | | | | |
| Diphenyl ether | DPE | 41 | D | { E } | | Α | Yes | 1 | | | | | | | | | |
| Dipropylene glycol | DPG | 40 | Đ | E | | Α | Yes | 1 | | | | | | | | | |
| Distillates: Flashed feed stocks | DFF | 33 | D | E | | Α | Yes | 1 | | | | | | | | | |
| Distillates: Straight run | DSR | 33 | D | Ε | | Α | Yes | 1 | | | | | | | | | |
| Dodecene (all isomers) | DOZ | 30 | Ď | D | | Α | Yes | 1 | | | | | | | | | |
| Dodecylbenzene, see Alkyl(C9+)benzenes | DDB | 32 | D | E | | Α | Yes | 1 | | | | | | | | | |
| 2-Ethoxyethyl acetate | EEA | 34 | , D | D | | Α | Yes | . 1 | | | | | | | | | |
| Ethoxy triglycol (crude) | ETG | 40 | D | E | | Α | Yes | 1 | | | | | | | | | |
| Ethyl acetate | ETA | 34 | D | С | | Α | Yes | 1 | | | | | | | | | |
| Ethyl acetoacetate | EAA | 34 | D | E | | Α | Yes | 1 | | | | | | | | | |
| Ethyl alcohol | EAL | 20 2 | D | С | | Α | Yes | 1 | | | | | | | | | |
| Ethylbenzene | ETB | 32 | D | Ç | | Α | Yes | 1 | | | | | | | | | |
| Ethyl butanol | EBT | 20 | D | D | | Α | Yes | 1 | | | | | | | | | |
| Ethyl tert-butyl ether | EBE | 41 | D | С | | Α | Yes | 1 | | | | | | | | | |
| Ethyl butyrate | EBR | 34 | D | D | | Α | Yes | 1 | | | | | | | | | |
| Ethyl cyclohexane | ECY | 31 | D | D | | Α | Yes | 1 | | | | | | | | | |
| Ethylene glycol | EGL | 20 2 | | E | | Α | Yes | 1 | | | | | | | | | |
| Ethylene glycol butyl ether acetate | EMA | | D | E | | Α | Yes | 1 | | | | | | | | | |
| Ethylene glycol diacetate | EGY | | D | E | | A | Yes | 1 | | | | | | | | | |
| Ethylene glycol phenyl ether | EPE | 40 | D | Ę | | : A | Yes | 1 | | | | | | | | | |
| Ethyl-3-ethoxypropionate | EEP | 34 | | <u>-</u> | | A | Yes | <u>`</u> 1 | | | | | | | | | |
| 2-Ethylhexanol | EHX | 20 | D | E | | ≘ A | Yes | 1 | | | | | | | | | |
| Ethyl propionate | EPR | | D | c | | A | Yes | 1 | 34 | | | | | | | | |
| Ethyl toluene | ETE | 32 | D | D | | A | | <u>'</u> | | | | | | | | | |
| - | | JŁ | | | | | Yes | <u>_</u> | · | | | | | | | | |



Dated:

19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine Madisonville

Hull #: 2137-1

Official #: 1166417

Page 6 of 9

| Cargo Identification | i | Conditions of Carriage | | | | | | | | |
|---|--------------|------------------------|----------------|---------|--------------|---------------|-------|-----------------------------|---|-----------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade · | Hull Type | Tank Group | App'd | Recovery VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of Construction | Insp. Period |
| | | | | | | | | | | |
| Formamide | FAM | 10 | D | Ë | | Α | Yes | 1 | | |
| Furfuryl alcohol | FAL | 20 | 2 D | E | | Α | Yes | 1 | | |
| Gasoline blending stocks: Alkylates | GAK | 33 | D | A/C | | Α | Yes | 1 | | |
| Gasoline blending stocks: Reformates | GRF | 33 | D | A/C | | Α | Yes | 1 | | |
| Gasolines: Automotive (containing not over 4.23 grams lead per | GAT | 33 | . D | _C | | Α | Yes | 1 | | |
| Gasolines: Aviation (containing not over 4.86 grams of lead per gallo | n) GAV | 33 | D | С | | Α | Yes | _ 1 | | |
| Gasolines: Casinghead (natural) | GCS | 33 | Đ | A/C | | Α | Yes | 1 | | |
| Gasolines: Polymer | GPL | 33 | D | A/C | | A | Yes | 1 | | |
| Gasolines: Straight run | GSR | 33 | D | A/C | | Α. | Yes | 1 | | |
| Glycerine | GCR | 20 | 2 D | E | | Α | Yes | 1 | | |
| Heptane (all isomers), see Alkanes (C6-C9) (all isomers) | НМХ | 31 | D | С | | Α | Yes | 1 | | |
| n-Heptanoic acid | HEN | 4 | D | E | | Α | Yes | 1 | | |
| Heptanol (all isomers) | нтх | 20 | D | D/E | | Α | Yes | 1 | | |
| Heptene (all isomers) | HPX | 30 | D | С | | Α | Yes | 2 | | |
| Heptyl acetate | HPE | 34 | D | E | | Α | Yes | 1 | | |
| Hexane (all isomers), see Alkanes (C6-C9) | HXS | 31 | 2 D | B/C | | Α | Yes | 1 | | |
| Hexanoic acid | нхо | 4 | D | E | | Α | Yes | 1 | | |
| Hexanol | HXN | 20 | D | D | | Α | Yes | 1 | | |
| Hexene (all isomers) | HEX | 30 | D | С | | Α | Yes | 2 | | |
| Hexylene glycol | HXG | 20 | D | E | | Α | Yes | 1 | | |
| Isophorone | IPH | 18 | 2 D | E | | Α | Yes | 1 | | |
| Jet fuel: JP-4 | JPF | 33 | D | E | | A | Yes | 1 | | |
| Jet fuel: JP-5 (kerosene, heavy) | JPV | 33 | D | D | | Α | Yes | 1 | | |
| Kerosene | KRS | 33 | D | D | | Α | Yes | 1 | | |
| Methyl acetate | MTT | 34 | D | D | | Α | Yes | 1 | | |
| Methyl alcohol | MAL | 20 | 2 D | С | | А | Yes | 1 | | |
| Methylamyl acetate | MAC | 34 | D | D | | Α | Yes | 1 | | |
| Methylamyl alcohol | MAA | 20 | D | D | | Α | Yes | . 1 | | |
| Methyl amyl ketone | MAK | 18 | D | D | | Α | Yes | . 1 | | |
| Methyl tert-butyl ether | MBE | 41 | 2 D | С | | Α | Yes | 1 | | |
| Methyl butyl ketone | мвк | 18 | D | С | | Α | Yes | 1 | | |
| Methyl butyrate | MB. | J 34 | D | С | | Α | Yes | 1 | | |
| Methylcyclohexane | MCY | 7 31 | D | С | | Α | Yes | 1 | | |
| Methyl ethyl ketone | MEK | | 2 D | С | | A | Yes | 1 | | |
| Methyl heptyl ketone | мни | | D | D | | Α | Yes | 1 | | |
| Methyl isobutyl ketone | MIK | | | Ç | | Α | Yes | | | |
| Mineral spirits | MNS | | D | D | | Α | Yes | . 1 | | |
| Myrcene | MRE | | D | D | | Α | Yes | 1 | | |



Serial #: C1-2000602 Dated:

19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine

Madisonville

Official #: 1166417

Page 7 of 9

Hull #: 2137-1

| Cargo Identification | n | | | | | | (| Condi | tions of Carriage | |
|--|--------------|-----------------------|----------------|------------|--------------|---------------|-------|-----------------|---|-----------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | App'd | VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of Construction | Insp. Period |
| | | | | <u>! i</u> | | | | | | ; |
| Naphtha: Heavy | NAG | 33 | D | # | | Α | Yes | 1 | | |
| Naphtha: Petroleum | PTN | 33 | D | # | | Α | Yes | 1 | | |
| Naphtha: Solvent | N\$V | 33 | D | D | | Α | Yes | 1 | | |
| Naphtha: Stoddard solvent | NSS | 33 | D | D | | Α | Yes | 1 | | |
| Naphtha: Varnish makers and painters (75%) | NVM | 33 | D | С | | Α | Yes | 1 | | |
| Nonane (all isomers), see Alkanes (C6-C9) | NAX | 31 | D | D | | Α | Yes | 1 | | |
| Nonene (all isomers) | NON | 30 | D | D | | Α | Yes | 2 | | |
| Nonyl alcohol (all isomers) | NNS | 20 ² | . D | E | | Α | Yes | 1 | | |
| Nonyl phenoi | NNP | 21 | D | E | | Α | Yes | 1 | | |
| Nonyl phenol poly(4+)ethoxylates | NPE | 40 | D | E | | Α | Yes | 1 | | |
| Octane (all isomers), see Alkanes (C6-C9) | OAX | 31 | D | С | | Α | Yes | 1 | | |
| Octanoic acid (all isomers) | OAY | 4 | D. | Е | | Α | Yes | 1 | | |
| Octanol (all isomers) | осх | 20 ² | . D | Е | | Α | Yes | 1 | | |
| Octene (all isomers) | OTX | 30 | D | С | | Α. | Yes | 2 | | |
| Oit, fuel: No. 2 | OTW | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, fuel: No. 2-D | OTD | 33 | D | D | | Α | Yes | 1 | | |
| Oil, fuel: No. 4 | OFR | 33 | D | D/E | | Α | Yes | 1 | | |
| Oil, fuel: No. 6 | OSX | 33 | D | E | | A | Yes | 1 | | |
| Oil, misc: Crude | OIL | 33 | D | A/D | _ | Α | Yes | 1 | | |
| Oil, misc: Diesel | ODS | 33 | ۵ | D/E | | Α | Yes | 1 | | |
| Oil, misc: Gas, high pour | QGP | 33 | D | Е | | Α | Yes | 1 | | |
| Oil, misc: Lubricating | OLB | 33 | D | E | | Α | Yes | 1 | | |
| Oil, misc: Residual | ORL | 33 | D | E | | Α | Yes | 1 | · · · | |
| Oil, misc: Turbine | ОТВ | 33 | D | E | | Α | Yes | 1 | | |
| alpha-Olefins (C6-C18) mixtures | QAM | 30 | D | E | | Α | Yes | 1 | | |
| Olefins (C13+, all isomers) | OFZ | 30 | D | E | | Α | Yes | 1 | | |
| Pentane (all isomers) | PTY | 31 | D | Α | | Α | Yes | 5 | | |
| Pentene (all isomers) | PTX | 30 | D | Α | | Α | Yes | 5 | | |
| n-Pentyl propionate | PPE | 34 | D | D | | Α | Yes | 1 | | |
| alpha-Pinene | PIO | 30 | D | D | | A | Yes | 1 | | |
| beta-Pinene | PIP | 30 | D | D | | Α | Yes | 1 | | |
| Poly(2-8)alkylene glycol monoalkyl (C1-C6) ether | PAG | 40 | D | Е | | Α | Yes | 1 | | |
| Poly(2-8)alkylene glycol monoalkyl (C1-C6) ether acetate | PAF | 34 | Đ | E | | A | Yes | 1 | | |
| Polybutene | PLB | 30 | D D | É | | A | Yes | 1 | | |
| Polypropylene glycol | PGC | 40 | D | E | | Α | Yes | <u>-</u> 1 | | _ |
| Isopropyl acetate | IAC | 34 | D | С | | Α | Yes | 1 | | |
| n-Propyl acetate | PAT | 34 | D | c | | A | Yes | 1 | | |
| Isopropyl alcohol | !PA | 20 2 | .3 D | С | | A | Yes | 1 | | _ |



19-Feb-20

Certificate of Inspection

Cargo Authority Attachment

Vessel Name: KIRBY 29326

Shipyard: Trinity Marine Madisonville

Hull #: 2137-1

Official #: 1166417

Page 8 of 9

| Cargo Identification | | | | | | Conditions of Carriage | | | | |
|--|--------------|-----------------------|----------------|-------|--------------|------------------------|-------|-----------------------------|---|-----------------|
| Name | Chem Code | Compat Group No | Sub Chapter | Grade | Hull Type | Tank Group | App'd | Recovery VCS Category | Special Requirements in 46 CFR 151 General and Mat'ls of Construction | Insp. Period |
| | | | | | | | | | | |
| n-Propyl alcohol | PAL | 20 ² | D | С | | Α | Yes | 1 | | |
| Propylbenzene (all isomers) | PBY | 32 | D | D | | Α | Yes | 1 | | |
| Isopropylcyclohexane | IPX | 31 | D | D | | Α | Yes | 1 | | |
| Propylene glycol | PPG | 20 ² | D | E | | Α | Yes | 1 | | |
| Propylene glycol methyl ether acetate | PGN | 34 | D | D | | Α_ | Yes | 1 | · | |
| Propylene tetramer | PTT | 30 | 0 | D | | A | Yes | 1 | | |
| Sulfolane | SFL | 39 | D | Е | | Α | Yes | 1 | | |
| Tetraethylene głycol | TTG | 40 | D | E | | A | Yes | 1 | | |
| Tetrahydronaphthalene | THN | 32 | D | E | | <u>A</u> | Yes | 1_ | <u>-</u> . | |
| Toluene | TOL | 32 | D | С | | . <u>A</u> | Yes | 1 | | |
| Tricresyl phosphate (containing less than 1% ortho isomer) | TCP | 34 | D | Ε | | Α | Yes | 1 | | |
| Triethylbenzene | TEB | 32 | D | E | | Α | Yes | 1 | | |
| Triethylene glycol | TEG | 40 | D | E | | A | Yes | 1 | | |
| Triethyl phosphate | TPS | 34 | D | Ε | | Α | Yes | 1 | | |
| Trimethylbenzene (all isomers) | TRE | 32 | D | {D} | | Α | Yes | 1 | | |
| Trixylyl phosphate | TRP | 34 | D | E | | Α | Yes | 1 | | |
| 1-Undecene | UDC. | 30 | D | D/E | | Α_ | Yes | 1 | | |
| 1-Undecyl alcohol | UND | 20 | D | . E | | Α | Yes | 1 | | |
| Xylenes (ortho-, meta-, para-) | XLX | 32 | D | D | | Α | Yes | 1 | | |



19-Feb-20

Dated:

Certificate of Inspection Cargo Authority Attachment

Vessel Name: KIRBY 29326 Official #: 1166417

Page 9 of 9

Shipyard: Trinity Marine

Hull #: 2137-1

Explanation of terms & symbols used in the Table:

Cargo Identification

The propper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

Chem Code

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No

The cargo reactive group number assigned for compatibility determinations in 48 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Note 1

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

Note 2

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart

Subchapter Subchapter D Note 3

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.

Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "()" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

A. B. C Note 4

Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficeint hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).

Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category:

The specified cargo's provisional classification for vapor control systems.

Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

Category 2

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1

Category 4

(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.

Category 5

(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1

Category 6 Category 7

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.

The cargo has not been evaluated/classified for use in vapor control systems.